

IS 29500:2008 Defect Report Log

Rex Jaeschke (project editor)

(rex@RexJaeschke.com)

2009-05-27

DRs 08-0001 through 08-0015

DRs 09-0001 through 09-0230

Introduction	1
Revision History.....	3
DR Status at a Glance	5
1. DR 08-0001 — DML, Framework: Removal of ST_PercentageDecimal from the strict schema	6
2. DR 08-0002 — Primer: Format of ST_PositivePercentage values in strict mode examples.....	9
3. DR 08-0003 — DML, Main: Format of ST_PositivePercentage values in strict mode examples	12
4. DR 08-0004 — DML, Diagrams: Type for prSet attributes	14
5. DR 08-0005 — PML, Animation: Description of hsl attributes Lightness and Saturation	20
6. DR 08-0006 — PML, Animation: Description of rgb attributes Blue, Green and Red	22
7. DR 08-0007 — DML, Main: Format of ST_TextBulletSizePercent percentage.....	24
8. DR 08-0008 — DML, Main: Format of buSzPct percentage values in strict mode example	28
9. DR 08-0009 — WML, Fields: Inconsistency between FILESIZE behaviour and example	31
10. DR 08-0010 — WML: Use of transitional attribute in tblLook strict mode examples	33
11. DR 08-0011 — WML: Use of transitional attribute in cnfStyle strict mode example	37
12. DR 08-0012 — Schemas: Supposedly incorrect schema namespace names	39
13. DR 08-0013 — Shared MLs, Shared Simple Types: ST_String allowed characters and max length.....	47
14. DR 08-0014 — Shared MLs, Shared Simple Types: ST_String example description error.....	49
15. DR 08-0015 — General: Differences between ISO/IEC 29500:2008 and ECMA-376:2006, SpreadsheetML.....	53
16. DR 09-0001 — SML, Charts, Trend lines: Incorrect range restriction in backward and forward.....	55
17. DR 09-0002 — SML, Charts: Incorrect range restriction in ST_HoleSize	58
18. DR 09-0003 — SML, Charts, Trend lines: Incorrect data type and range restriction in ST_Period	60
19. DR 09-0004 — SML, Charts: Incomplete enumeration definition for ST_MarkerStyle.....	63
20. DR 09-0005 — SML, Charts: Incorrect measurement unit/range restriction in ST_Perspective	66
21. DR 09-0006 — SML, Charts: Incorrect data type in ST_Skip	68
22. DR 09-0007 — SML: Incorrect range for Precision value space	70
23. DR 09-0008 — WML, Mail Merge: Incorrect definition of uniqueTag.....	72
24. DR 09-0009 — SML, Pivot Tables: Incorrect description of calculatedMember	75
25. DR 09-0010 — SML, Workbook: Extensibility broken for externalLink.....	78
26. DR 09-0011 — Shared MLs, Math: Incomplete list of valid child elements for Math objects	81
27. DR 09-0012 — Parts, Font Part: Incomplete definition for Font Part.....	89
28. DR 09-0013 — SML: Incorrect restriction on externalData.....	91
29. DR 09-0014 — SML: Incorrect restriction on the Name Representation	93

30.	DR 09-0015 — SML: Incomplete list of error value constants and valid expression error values.....	97
31.	DR 09-0016 — SML, Formulas: Incorrect attribute name in Array Formulas	100
32.	DR 09-0017 — WML, Annotations: Inserted math control character missing valid child.....	103
33.	DR 09-0018 — Shared MLs, Math: Invalid child Previous Run Properties	106
34.	DR 09-0019 — Shared MLs, Math: Invalid Child Previous Run Properties	109
35.	DR 09-0020 — SML: Incorrect restriction on scenario	111
36.	DR 09-0021 — SML, Pivot Tables: Incorrect restriction on item	113
37.	DR 09-0022 — SML: Incomplete set of format symbols for numFmts	115
38.	DR 09-0023 — SML, Parts: Incorrect naming of Root Element for certain parts	118
39.	DR 09-0024 — SML, Parts: Incomplete set of implicit relationships for Worksheet Part	121
40.	DR 09-0025 — SML, Parts: Incorrect Root Namespace for the Styles Part	123
41.	DR 09-0026 — SML: xml:space attribute note declared in SpreadsheetML.....	125
42.	DR 09-0027 — Shared Simple Types: Unnecessary text in description of ST_String	128
43.	DR 09-0028 — WML, Custom XML and Smart Tags: Tighten data types.....	130
44.	DR 09-0029 — WML, Custom XML and Smart Tags: Specification for Validation Lacking	132
45.	DR 09-0030 — OPC: Placement of package RelationshipReference elements	136
46.	DR 09-0031 — General: Request for support of Unicode 5.1.0	138
47.	DR 09-0032 — General: Inappropriate use of "content type"	140
48.	DR 09-0033 — DML, Charts, Simple Types: Lack of support for percent sign	144
49.	DR 09-0034 — General: Numerous media types should be registered at IANA.....	151
50.	DR 09-0035 — WML, Parts: Incorrect media types for Alternative Format Import Part	165
51.	DR 09-0036 — Shared, Parts, Font Part: Inappropriate media types.....	167
52.	DR 09-0037 — PML, Presentation: Clarify description of properties in embeddedFontLst.....	169
53.	DR 09-0038 — WML/PML/DML: Panose-1 Typeface Classification	171
54.	DR 09-0039 — Shared, Parts, Font Part: File format for "bitmapped font" is missing	173
55.	DR 09-0040 — WML/DML: Complex scripts.....	175
56.	DR 09-0041 — WML, Fonts: Font resource search	177
57.	DR 09-0042 — WML, Fonts: notTrueType attribute missing from list	179
58.	DR 09-0043 — WML, Fonts: notTrueType attribute and bitmap fonts	181
59.	DR 09-0044 — WML, Fonts: Support for commas in font family/subfamily/full names	182
60.	DR 09-0045 — WML, Fonts: Character encodings of font names	184
61.	DR 09-0046 — WML, Fonts: Misleading example	186

62.	DR 09-0047 — WML, Fonts: Identifying a face in an embedded font file	188
63.	DR 09-0048 — WML, Fonts: Panose-1 classification mechanism missing	190
64.	DR 09-0049 — WML, Fields: SYMBOL switch proper charset name usage	192
65.	DR 09-0050 — SML, Worksheets: comma delimiter between font name and type	193
66.	DR 09-0051 — SML, Shared String Table: charset value duplicate	195
67.	DR 09-0052 — SML, Styles: family attribute range issue.....	197
68.	DR 09-0053 — PML, Presentation: Attribute name pitchFamily is misleading	198
69.	DR 09-0054 — DML, run formatting: Attribute name pitchFamily is misleading	199
70.	DR 09-0055 — PML, Presentation: Type of the attribute pitchFamily is too loose	201
71.	DR 09-0056 — DML, Main: Type of the attribute pitchFamily is too loose.....	203
72.	DR 09-0057 — PML, Presentation: Allow aliases as values for attribute typeface	205
73.	DR 09-0058 — DML, Main: Possible values of attribute script are unclear.....	206
74.	DR 09-0059 — DML, Main: Relationship between the symbol font and Symbol character set.....	208
75.	DR 09-0060 — WML, Fonts: Names should be registered at IANA	210
76.	DR 09-0061 — Shared MLs, Shared Simple Types: Constrain ST_Panose value set	212
77.	DR 09-0062 — WML, Settings: Semantics of short file names.....	214
78.	DR 09-0063 — WML, Fields: Form Field Properties length.....	217
79.	DR 09-0064 — WML, Simple Types: ST_FFFHelpTextVal length	218
80.	DR 09-0065 — WML, Simple Types: ST_FFName length.....	219
81.	DR 09-0066 — WML, Simple Types: ST_MacroName length	220
82.	DR 09-0067 — SML, Workbook: Semantics of short file names	221
83.	DR 09-0068 — SML, Styles: name attribute length	223
84.	DR 09-0069 — SML, Pivot Tables: longText attribute length.....	225
85.	DR 09-0070 — PML, Presentation: modifyVerifier password length	227
86.	DR 09-0071 — WML, Simple Types: Katakana enumeration examples	230
87.	DR 09-0072 — WML, Simple Types: ST_BrClear terminology usage	232
88.	DR 09-0073 — WML, Simple Types: ST_BrClear extraneous text	235
89.	DR 09-0074 — WML, Simple Types: ST_TextDirection direction of rotation	237
90.	DR 09-0075 — WML, Simple Types: ST_TextDirection conflict between attribute values	238
91.	DR 09-0076 — Part 1: Trivial Editorial Defects	239
92.	DR 09-0077 — Schemas, RELAX NG: Error in Theme Override Part	241
93.	DR 09-0078 — Schemas, RELAX NG: Schema missing.....	243

94.	DR 09-0079 — Schemas, RELAX NG: Error in PML.....	246
95.	DR 09-0080 — General: Unintended underscore characters in text	248
96.	DR 09-0081 — General: Inter-word space missing.....	254
97.	DR 09-0082 — General: Unsatisfactory attribute name example.....	256
98.	DR 09-0083 — DML chart element ‘userShapes’ lacking Parent Element box	258
99.	DR 09-0084 — WML: Ecma Response 261 not fully implemented.....	260
100.	DR 09-0085 — WML: Incorrect style name in ‘w:val’ attributes in Examples	265
101.	DR 09-0086 — Primer: Duplicate mathematical expressions in Primer	268
102.	DR 09-0087 — Strict Part Normative References to transitional features	270
103.	DR 09-0088 — Shared MLs: Incorrect citation of Normative Reference	273
104.	DR 09-0089 — WML: DATE Field switch names incorrectly styled	275
105.	DR 09-0090 — WML: Incorrect case used for ISO country code in ‘en-ca’	277
106.	DR 09-0091 — WML: Inconsistent citation of Normative Reference ‘XSLT’	279
107.	DR 09-0092 — WML: Identical definitions for ST_NumberFormat enumeration values.....	282
108.	DR 09-0093 — WML: Incorrect simple type name in example of ‘ST_UcharHexNumber’	284
109.	DR 09-0094 — WML: Ecma Response 71 not fully implemented in definition of ‘ST_Shade’	286
110.	DR 09-0095 — SML: References to non-existent attribute ‘paperUnits’	288
111.	DR 09-0096 — DML: Error in definition of attribute ‘paperSize’	290
112.	DR 09-0097 — General: Miscellaneous mis-spellings.....	292
113.	DR 09-0098 — SML: Duplicate mathematical expressions in function definitions.....	294
114.	DR 09-0099 — SML: No Normative References or Definitions for “MDX” and “OLAP”	297
115.	DR 09-0100 — Part 1: Unnecessary annex	299
116.	DR 09-0101 — WML, Fields: Grammar Production letter.....	301
117.	DR 09-0102 — SML, Formulas: Grammar Production letter	303
118.	DR 09-0103 — WML: Error in WML schema.....	305
119.	DR 09-0104 — DML: Contradiction between text and dml-wordProcessingDrawing schema	306
120.	DR 09-0105 — WML: Errors in examples	308
121.	DR 09-0106 — PML: Errors in examples.....	311
122.	DR 09-0107 — WML: Errors in examples	313
123.	DR 09-0108 — WML: Errors in examples	318
124.	DR 09-0109 — WML: Errors in examples	326
125.	DR 09-0110 — WML: Errors in examples	328

126.	DR 09-0111 — WML: Errors in examples	330
127.	DR 09-0112 — WML: Errors in examples	334
128.	DR 09-0113 — WML: Errors in examples	336
129.	DR 09-0114 — WML: Errors in examples	338
130.	DR 09-0115 — WML: Errors in examples	341
131.	DR 09-0116 — WML: Errors in examples	345
132.	DR 09-0117 — WML: Errors in examples	347
133.	DR 09-0118 — PML: Errors in examples.....	349
134.	DR 09-0119 — WML: Errors in examples	351
135.	DR 09-0120 — PML: Errors in examples.....	353
136.	DR 09-0121 — WML: Errors in examples	355
137.	DR 09-0122 — WML: Errors in examples	358
138.	DR 09-0123 — WML: Errors in examples	364
139.	DR 09-0124 — SML: Errors in examples	369
140.	DR 09-0125 — WML: Errors in examples	371
141.	DR 09-0126 — WML: Errors in examples	373
142.	DR 09-0127 — WML: Errors in examples	375
143.	DR 09-0128 — WML: Errors in examples	377
144.	DR 09-0129 — WML: Errors in examples	379
145.	DR 09-0130 — WML: Errors in examples	381
146.	DR 09-0131 — PML: Errors in examples.....	383
147.	DR 09-0132 — WML: Errors in examples	385
148.	DR 09-0133 — WML: Errors in examples	387
149.	DR 09-0134 — WML: Errors in examples	389
150.	DR 09-0135 — SML: Errors in examples	391
151.	DR 09-0136 — WML: Errors in examples	393
152.	DR 09-0137 — WML: Errors in examples	395
153.	DR 09-0138 — WML: Errors in examples	397
154.	DR 09-0139 — WML: Errors in examples	399
155.	DR 09-0140 — PML: Errors in examples.....	401
156.	DR 09-0141 — PML: Errors in examples.....	403
157.	DR 09-0142 — PML: Errors in examples.....	405

158.	DR 09-0143 — SML, Formulas: TIMEVALUE, return value and terminology	407
159.	DR 09-0144 — SML, Formulas: Various functions, iterative search technique	409
160.	DR 09-0145 — SML, Formulas: Various functions, duplicate mathematical expressions.....	411
161.	DR 09-0146 — SML, Formulas: MATCH, inconsistent use of return value #NUM!	414
162.	DR 09-0147 — Shared MLS: incorrect attribute value format	415
163.	DR 09-0148 — Shared MLS: Inter-word space missing	417
164.	DR 09-0149 — Shared MLs: Bad page break in Parent Elements table.....	419
165.	DR 09-0150 — Shared MLs: Attribute value in incorrect style.....	420
166.	DR 09-0151 — Shared MLs: Incorrect abbreviation of ‘points’ to ‘pts.’	425
167.	DR 09-0152 — Shared MLs: Unneeded blank in math formula	427
168.	DR 09-0153 — Shared MLs: XML III-formed example of sepChr	429
169.	DR 09-0154 — Shared MLs: placeholders that should be visible in matrix are not.....	431
170.	DR 09-0155 — WML: Error in Example	433
171.	DR 09-0156 — WML: XSLT Transformation error in Example.....	436
172.	DR 09-0157 — WML: restriction on ordering of run properties	439
173.	DR 09-0158 — WML: Error in unit definition for ST_UniversalMeasure.....	440
174.	DR 09-0159 — General: Unintended incompatibilities between Transitional schema and Ecma-376	442
175.	DR 09-0160 — SML and Shared ML: Lack of Specialized Media Types.....	444
176.	DR 09-0161 — Shared ML: Digital Signature Origin Part Media Type.....	446
177.	DR 09-0162 — Shared ML: Printer Settings Part Media Types	447
178.	DR 09-0163 — VML: Drawing Part Media Type.....	449
179.	DR 09-0164 — WML: Alternative Format Import Part Media Type	450
180.	DR 09-0165 — SML and PML: Lack of Media Types.....	451
181.	DR 09-0166 — SML: Custom Property Part Media Type.....	452
182.	DR 09-0167 — SML: Embedded Control Persistence Part Media Type	453
183.	DR 09-0168 — OPC: No mechanism to distinguish ECMA-376:2006 from IS 29500	454
184.	DR 09-0169 — Normative Reference to XML 1.1	455
185.	DR 09-0170 — Normative Reference to Namespaces in XML 1.1	456
186.	DR 09-0171 — WML and SML: Space-related errors in grammar productions	457
187.	DR 09-0172 — WML: Filename-to-IRI mapping.....	459
188.	DR 09-0173 — WML: shapeID attribute semantics missing	461
189.	DR 09-0174 — WML: Header cell identifier resolution	462

190.	DR 09-0175 — WML: Imprecise forward reference.....	463
191.	DR 09-0176 — General: ST_String instance value set and length constraints.....	465
192.	DR 09-0177 — WML: Embedded control name length and content constraints.....	467
193.	DR 09-0178 — WML: Syntax for, and handling of, fieldCodes values	468
194.	DR 09-0179 — WML: progID length and content constraints.....	470
195.	DR 09-0180 — WML: Table cell id length and content constraints	472
196.	DR 09-0181 — WML: Handling of invalid name values	473
197.	DR 09-0182 — WML: Handling of invalid uri values	474
198.	DR 09-0183 — WML: Handling of invalid customXML element name values	476
199.	DR 09-0184 — WML: Alias val length and content constraints	478
200.	DR 09-0185 — WML: Programmatic Tag val length and content constraints	479
201.	DR 09-0186 — WML: Style Definition styleId length and content constraints.....	480
202.	DR 09-0187 — WML: Font Properties name length and content constraints	481
203.	DR 09-0188 — WML: Paragraph Style's Associated Numbering Level val length and content constraints	482
204.	DR 09-0189 — WML: Font Character Set reference to non-existent attribute	484
205.	DR 09-0190 — WML: Error in examples.....	485
206.	DR 09-0191 — Custom XML Schema: Allowed attribute values	487
207.	DR 09-0192 — BRM Resolution not implemented (Transitional Migration Features)	488
208.	DR 09-0193 — WML: Move hMerge from strict to transitional.....	490
209.	DR 09-0194 — WML: Use of terminology "id" and "unique identifier"	491
210.	DR 09-0195 — WML: numbering definition instance description	493
211.	DR 09-0196 — General: Conventions for element long names	494
212.	DR 09-0197 — General: dotted line rendering problem.....	496
213.	DR 09-0198 — saveInvalidXml, clarification of text	497
214.	DR 09-0199 — WML: ST_BrClear, description vs. intended behavior	499
215.	DR 09-0200 — WML: mirrorMargins.....	501
216.	DR 09-0201 — WML: error in ST_Jc example	502
217.	DR 09-0202 — WML: BRM Resolution 6	503
218.	DR 09-0203 — DML: BRM Resolution 6	508
219.	DR 09-0204 — WML: Custom markup	528
220.	DR 09-0205 — WML: Definition of “round tripping” missing	529
221.	DR 09-0206 — WML: Custom markup wording improvement	530

222.	DR 09-0207 — WML: Custom XML and Smart Tags.....	531
223.	DR 09-0208 — WML: Custom XML and Smart Tags.....	532
224.	DR 09-0209 — WML: Custom XML and Smart Tags.....	533
225.	DR 09-0210 — WML: Custom XML and Smart Tags.....	535
226.	DR 09-0211 — WML: Custom XML and Smart Tags.....	536
227.	DR 09-0212 — WML: Custom XML and Smart Tags.....	537
228.	DR 09-0213 — WML: Custom XML and Smart Tags.....	538
229.	DR 09-0214 — WML: Custom XML and Smart Tags.....	539
230.	DR 09-0215 — WML: Custom XML and Smart Tags.....	540
231.	DR 09-0216 — WML: Custom XML and Smart Tags.....	541
232.	DR 09-0217 — WML: Custom XML and Smart Tags.....	542
233.	DR 09-0218 — WML: Custom XML Attribute	543
234.	DR 09-0219 — WML: Custom XML Attribute	544
235.	DR 09-0220 — WML: Definition of “property bag” missing	545
236.	DR 09-0221 — WNL: Custom XML Attribute	546
237.	DR 09-0222 — WML: Bibliography Structured Document Tag	547
238.	DR 09-0223 — WML: Structured Document Tags.....	548
239.	DR 09-0224 — WML: Combo Box Structured Document Tag	549
240.	DR 09-0225 — Part 4 should normatively reference Part 1.....	550
241.	DR 09-0226 — PML: ST_TransitionSideDirectionType.....	551
242.	DR 09-0227 — WML: Inconsistent use of ML style IDs in examples	553
243.	DR 09-0228 — General: Inappropriate first paragraph in §7 of Parts 1, 2 and 4.....	555
244.	DR 09-0229 — Period missing at end of sentence.....	557
245.	DR 09-0230 — Cross-reference to non-existent Example.....	559

IS 29500:2008 Defect Report Log

Introduction

This document contains the cumulative history of all Defect Report (DR) processing related to IS 29500:2008, "Office Open XML".

Each main clause covers one DR, and the following format is used for each:

DR Entry Title: DR-yy-nnnn — short title taken from **Subject** below. (yy is the last two digits of the base document year of publication [as in 08 for 29500:2008], and nnnn is a sequential number starting at 0001.)

Status: One of the following:

1. Open
2. Closed, and incorporated in COR n
3. Closed, and incorporated in AM n (or revision 29500:20 nn)
4. Closed without action
5. Further Consideration Required
6. Last Call

Subject: A brief but representative title

Qualifier: One of the following:

1. Editorial defect
2. Technical defect
3. Request for clarification

Submitter: Name of submitter (sponsor, such as NB, liaison, WG4, Editing Group)

Contact Information: preferably email address, so more information can be requested

Submitter's Defect Number: Optional; submitter's own tracking number

Supporting Document(s): Optional; any such documents should be made WG4 N-numbered documents

Date Circulated by Secretariat: yyyy-mm-dd (date on which the DR was formally accepted)

Deadline for Response from Editor: yyyy-mm-dd (date by which the editor is required to give a first response; that is, 2 months after initial circulation)

IS 29500 Reference(s): Part, clause, subclause, page, etc. identification

Related DR(s): Optional; pointers to other DRs that may be related

Nature of the Defect:

A detailed description of the defect or request for clarification

Solution Proposed by the Submitter:

Optional

Schema Change(s) Needed: No; Yes, in which case, say which schema(s)

Editor's Response:

Details of discussion, progress, and final resolution

Revision History

1. 2008-11-25: Provided responses for, and closed, 8 DRs, 0001–0004 and 0008–0011. Proposed resolutions for DRs 0005–0007, but need final wording for detailed text, so these DRs have the status “Further Consideration Required”.
2. 2009-01-02: Proposed resolutions for DRs 0012–0015, but need input from WG4, so these DRs have the status “Further Consideration Required”.
3. 2009-02-09:
 - Added/changed text for DRs 08-0001 through 08-0015 based on discussions at the Okinawa meeting. For DR 08-010, the editor added another instance to be corrected.
 - Added a field to each DR for indicating schema changes.
 - Added the DRs submitted by Ecma in WG4 N 0022, as DR 09-0001 through 09-0026.
 - Added the hyperlinked “DR Status at a Glance” section.
 - Added DRs 08-00000 through 08-00069 submitted through the web interface, as DR 09-0027 through 09-0075. (Closely related submissions from the website were combined into the same DR in this log.)
 - Added classification prefixes to all existing DR titles.
 - Created a DR (09-0076) for all trivial Editorial Defects for Part 1.
4. 2009-02-28:
 - Added discussion from the email list to the following DR entries: 09-0014, 09-0032, 09-0034, 09-0070.
 - Added DRs 08-00070 through 08-00072 submitted through the web interface, as DR 09-0077 through 09-0079.
 - Added the DRs submitted by GB in WG4 N 0029, as DR 09-0080 through 09-0099.
 - Added the DRs submitted by the editor as DR 09-0100 through 09-0102.
5. 2009-03-17:
 - Added the DRs submitted by GB in WG4 N 0032, as DR 09-0103 through 09-0142.
 - Added the DRs submitted by GB in WG4 N 0033, as DR 09-0143 through 09-0154.
 - Added discussion from the email list to the following DR entries: 09-0026, 09-0034.
 - Added Editor’s responses to numerous DRs.
6. 2009-04-03:
 - Corrected DRs 09-0072 through 09-0075. When I added these, I incorrectly attributed them to JP (Japan). In fact, they were submitted by IL (Israel).

- Added DRs 08-00073 through 08-00077 (08-00075 was a duplicate of 08-00074) submitted through the web interface by CZ, as DR 09-0155 through 09-0158.
- Added the DR submitted by GB in WG4 N 0035, as DR 09-0159.
- Added discussion from the email list to the following DR entries: 09-0026.
- Updated the status of almost all DRs processed at the Prague meeting.

7. 2009-04-24:

- Added DRs 08-00078 through 08-00088 submitted through the web interface by JP, as DR 09-0160 through 09-0170.
- Added DR 09-0171 submitted by the Editor.
- Added the new Status category “Last Call”. This is used to indicate a DR that has been closed by the Editor, but that the final wording has not yet been approved by WG4.
- Changed the status of a number of DRs from “Closed, to be incorporated in COR1” to “Last Call” to reflect the fact that the final wording has not been approved by WG4.
- Added DRs 08-00089 through 08-00107 submitted through the web interface by CH, as DR 09-0172 through 09-0189.
- Added discussion from the email list to various DR entries.
- Added DR 09-00190 submitted by AU.
- Added DR 09-00191 submitted by JP.
- Provided proposed solutions to many DRs, changing their status to “Last Call”.

8. 2009-05-09:

- Added DR 09-00192 submitted by DK.
- Provided proposed solutions to many DRs, changing their status to “Last Call”.
- Added DRs 08-00109 through 08-00113 submitted through the web interface by JP, as DR 09-0193 through 09-0197.
- Added discussion from the email list to various DR entries.
- Added information from the teleconference of 2009-04-30.

9. 2009-05-27:

- Added DR 09-00198 submitted by the editor.
- Added DRs 08-00114 through 08-00140 submitted through the web interface by various members, as DR 09-0199 through 09-0225.
- Integrated a substantial set of specific edits to resolve DR 09-0033, DR 09-0202, and DR 09-0203. (These were circulated by Shawn V. previously as attachments to a series of emails.)
- Integrated a substantial set of specific edits to resolve DR 08-0001, DR 08-0002, DR 08-0003, DR 08-0004, DR 08-0005, DR 08-0006, DR 08-0007, and DR 08-0008.
- Added DR 09-0227 through 09-0230 submitted by GB.

DR Status at a Glance

Status	DR Numbers
Open (64)	09-0144 , 09-0146 , 09-0156 , 09-0157 , 09-0159 , 09-0160 , 09-0161 , 09-0162 , 09-0163 , 09-0164 , 09-0165 , 09-0166 , 09-0167 , 09-0168 , 09-0169 , 09-0170 , 09-0172 , 09-0173 , 09-0174 , 09-0176 , 09-0177 , 09-0178 , 09-0179 , 09-0180 , 09-0181 , 09-0182 , 09-0183 , 09-0184 , 09-0185 , 09-0186 , 09-0187 , 09-0188 , 09-0189 , 09-0191 , 09-0193 , 09-0194 , 09-0195 , 09-0196 , 09-0197 , 09-0199 , 09-0200 , 09-0202 , 09-0203 , 09-0204 , 09-0205 , 09-0206 , 09-0207 , 09-0208 , 09-0209 , 09-0210 , 09-0211 , 09-0212 , 09-0213 , 09-0214 , 09-0215 , 09-0216 , 09-0217 , 09-0218 , 09-0219 , 09-0220 , 09-0221 , 09-0222 , 09-0223 , 09-0224 , 09-0225 , 09-0227 , 09-0228 , 09-0229 , 09-0230
Last Call (28)	08-0001 , 08-0002 , 08-0003 , 08-0004 , 08-0005 , 08-0006 , 08-0007 , 08-0008 , 08-0009 , 08-0010 , 08-0011 , 09-0001 , 09-0002 , 09-0003 , 09-0004 , 09-0005 , 09-0006 , 09-0007 , 09-0008 , 09-0009 , 09-0010 , 09-0011 , 09-0012 , 09-0013 , 09-0014 , 09-0015 , 09-0016 , 09-0017 , 09-0018 , 09-0022 , 09-0027 , 09-0143 , 09-0145 , 09-0147 , 09-0148 , 09-0149 , 09-0150 , 09-0151 , 09-0152 , 09-0153 , 09-0154 , 09-0155 , 09-0158 , 09-0190 , 09-0192 , 09-0198 , 09-0201 , 09-0226
Closed, to be incorporated in COR1 (83)	08-0009 , 08-0010 , 08-0011 , 09-0001 , 09-0002 , 09-0003 , 09-0004 , 09-0005 , 09-0006 , 09-0007 , 09-0008 , 09-0009 , 09-0010 , 09-0011 , 09-0012 , 09-0013 , 09-0014 , 09-0015 , 09-0020 , 09-0021 , 09-0024 , 09-0025 , 09-0035 , 09-0050 , 09-0062 , 09-0067 , 09-0072 , 09-0073 , 09-0076 , 09-0077 , 09-0078 , 09-0079 , 09-0080 , 09-0081 , 09-0082 , 09-0083 , 09-0084 , 09-0085 , 09-0086 , 09-0087 , 09-0088 , 09-0089 , 09-0090 , 09-0091 , 09-0093 , 09-0094 , 09-0095 , 09-0096 , 09-0097 , 09-0098 , 09-0100 , 09-0101 , 09-0102 , 09-0107 , 09-0108 , 09-0109 , 09-0110 , 09-0111 , 09-0112 , 09-0113 , 09-0114 , 09-0115 , 09-0116 , 09-0117 , 09-0118 , 09-0119 , 09-0120 , 09-0121 , 09-0122 , 09-0123 , 09-0124 , 09-0125 , 09-0126 , 09-0127 , 09-0128 , 09-0129 , 09-0130 , 09-0131 , 09-0133 , 09-0134 , 09-0135 , 09-0136 , 09-0137 , 09-0138 , 09-0139 , 09-0140 , 09-0141 , 09-0142 , 09-0171 , 09-0175 , 09-0190
Closed, to be incorporated in AMD1 (2)	09-0023 , 09-0051
Closed without action (5)	08-0013 , 09-0019 , 08-0015 , 09-0044 , 09-0132
Further Consideration Required (63)	08-0001 , 08-0002 , 08-0003 , 08-0004 , 08-0005 , 08-0006 , 08-0007 , 08-0008 , 08-0012 , 09-0003 , 09-0008 , 09-0010 , 09-0011 , 09-0012 , 09-0013 , 09-0016 , 09-0017 , 09-0018 , 09-0019 , 09-0026 , 09-0028 , 09-0029 , 09-0030 , 09-0031 , 09-0032 , 09-0033 , 09-0034 , 09-0036 , 09-0037 , 09-0038 , 09-0039 , 09-0040 , 09-0041 , 09-0042 , 09-0043 , 09-0045 , 09-0046 , 09-0047 , 09-0048 , 09-0049 , 09-0052 , 09-0053 , 09-0054 , 09-0055 , 09-0056 , 09-0057 , 09-0058 , 09-0059 , 09-0060 , 09-0061 , 09-0063 , 09-0064 , 09-0065 , 09-0066 , 09-0068 , 09-0069 , 09-0070 , 09-0071 , 09-0074 , 09-0075 , 09-0092 , 09-0099 , 09-0103 , 09-0104 , 09-0105 , 09-0106 , 09-0107 , 09-0144 , 09-0146 , 09-0156 , 09-0157 , 09-0159
Total (245)	

1. DR 08-0001 — DML, Framework: Removal of ST_PercentageDecimal from the strict schema

Status: Further Consideration RequiredLast Call

Subject: DML, Framework: Removal of ST_PercentageDecimal from the strict schema

Qualifier: Technical defect

Submitter: Mr. Makoto Murata (JP)

Contact Information: eb2m-mrt@asahi-net.or.jp

Submitter's Defect Number: JP1-1

Supporting Document(s): none

Date Circulated by Secretariat: 2008-09-26

Deadline for Response from Editor: 2008-11-26

IS 29500 Reference(s): Part 1, §A.4.1 (pp. 4529) and §B.4.1 (pp. 4834)

Related DR(s): none

Nature of the Defect:

The simple type ST_PercentageDecimal should be removed from the strict version of dml-main.xsd and dml-main.rnc, as instructed by Resolution 6 in the BRM.

Solution Proposed by the Submitter:

Remove this simple type from the printed annexes as well as from their corresponding electronic versions.

Schema Change(s) Needed: Yes, the strict version of dml-main.xsd and dml-main.rnc

```
<xsd:simpleType name="ST_PercentageDecimal">
  <xsd:restriction base="xsd:int"/>
</xsd:simpleType>
```

Editor's Response:

Agreed with submitter's proposed solution. (See notes below.)

Notes:

1. This type is described in Part 1, §20.1.10.41.
 2. This type is referenced in §20.1.10.62, "ST_TextBulletSizePercent (Bullet Size Percentage)", and is the base type of that type. (See DR 08-0007 — DML, Main: Format of ST_TextBulletSizePercent percentage, and a_ST_TextBulletSizePercent =
 - ~~3. xsd:int { minInclusive = "25000" maxInclusive = "400000" }~~
- ```

xsd:string {
 pattern = "((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%"
}
a ST_TextBulletSizeDecimal =
 xsd:int { minInclusive = "25000" maxInclusive = "400000" }

```
4. DR 08-0008 — DML, Main: Format of buSzPct percentage values in strict mode example.)

**2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

**2009-04-24 Editor:**

~~See document SC 34/WG4 N 0044 for the proposed response.~~

**2009-05-25 Editor:**

The exact changes are as follows:

Part 1, §20.1.10.41, "ST\_PercentageDecimal (Percentage as Decimal Number)", pp. 3298

**20.1.10.41 — ST\_PercentageDecimal (Percentage as Decimal Number)**

~~This simple type represents a percentage in 1000ths of a percent, e.g., a value of 1 represents 0.001% == 0.00001; a value of 100000 is equal to 100%. Percentages have no intrinsic units, but are used to scale other values with units.~~

~~This simple type's contents are a restriction of the W3C XML Schema int datatype.~~

| <b>Referenced By</b>                                                                          |
|-----------------------------------------------------------------------------------------------|
| <del>ST_Percentage (§Error! Reference source not found.); ST_TextBulletSizePercent (§0)</del> |

[Note: The W3C XML Schema definition of this simple type's content model (ST\_PercentageDecimal) is located in §Error! Reference source not found..end note]

Part 1, §A.4.1, “DrawingML – Main”, pp. 4529, lines 240–242

```
<xsd:simpleType name="ST_PercentageDecimal">
 <xsd:restriction base="xsd:int"/>
</xsd:simpleType>
```

Part 1, §B.4.1, “DrawingML – Main”, pp. 4834, line 134

```
a_ST_PercentageDecimal = xsd:int
```

Part 4, §12.1.2.xx, “ST\_PercentageDecimal (Percentage as Decimal Number)”, new subclause

This simple type represents a percentage in 1000ths of a percent, e.g., a value of 1 represents 0.001% == 0.00001; a value of 100000 is equal to 100%. Percentages have no intrinsic units, but are used to scale other values with units.

This simple type's contents are a restriction of the W3C XML Schema int datatype.

| <b>Referenced By</b>                                       |
|------------------------------------------------------------|
| <u><a href="#">ST_Percentage (Part 1, §20.1.10.40)</a></u> |

[Note: The W3C XML Schema definition of this simple type's content model (ST\_PercentageDecimal) is located in §A.4.1. end note]

Part 4, §12.1.2.2, “Additional member types for the union in ST\_Percentage (Part 1, §20.1.10.40)”, pp. 199–200

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_PercentageDecimal simple type ([Part 1, §20.1.10.41](#) [Part 4, §12.1.2.xx](#)).

## 2. DR 08-0002 — Primer: Format of ST\_PositivePercentage values in strict mode examples

**Status:** Further Consideration RequiredLast Call

**Subject:** Primer: Format of ST\_PositivePercentage values in strict mode examples

**Qualifier:** Editorial defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** eb2m-mrt@asahi-net.or.jp

**Submitter's Defect Number:** JP1-2

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §M.4.6.2.2 (pp. 5374)

**Related DR(s):** DR 08-0003 — DML, Main: Format of ST\_PositivePercentage values in strict mode examples

**Nature of the Defect:**

The use of ST\_PositivePercentage (zoom), which is defined as a percentage in 1,000<sup>th</sup> of a percent, is incorrect, since in the strict conformance class this type must be a decimal number followed by "%".

**Solution Proposed by the Submitter:** none

**Schema Change(s) Needed:** No

**Editor's Response:**

The changes described below will be made.

Notes:

1. A type by this name is described in §20.1.10.46, “ST\_PositivePercentage (Positive Percentage)”. (Another type by this name is described in §22.9.2.11, “ST\_PositivePercentage (Positive Percentage Value with Sign).”)
2. Part 1, §19.5.83, tmPct (Time Percentage), contains the example

```
<p:tmPct val="10000"/>
```

where the possible values for this attribute are defined by the type ST\_PositivePercentage. In strict conformance mode, such percentage values are required to have a “%” suffix, so "10000" should be changed to "10000%".

3. Part 1, §M.4.6.2.2, “Camera”, contains the example

```
<xsd:attribute name="zoom" type="ST_PositivePercentage"
use="optional" default="100000" />
```

"10000" should be changed to "10000%".

4. As these changes occur in non-normative text, strictly speaking, this is an editorial defect; however, it is recognized that incorrect examples can influence implementers.

#### **2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

#### **2009-04-24 Editor:**

See document SC 34/WG4 N 0044 for the proposed response.

#### **2009-05-25 Editor:**

The exact changes are as follows:

Part 1, §20.1.10.46, “ST\_PositivePercentage (Positive Percentage Value with Sign)”, pp. 3300

Part 1, §19.5.83, “tmPct (Time Percentage)”, pp. 2958

[Example: ...

```
<p:par>
<p:cTn id="5" >
<p:stCondLst> ... </p:stCondLst>
```

```

<p:iterate type="lt">
 <p:tmpPct val="10000010%" />
</p:iterate>
<p:childTnLst> ... </p:childTnLst>
</p:cTn>
</p:par>

```

*end example]*

Part 1, §M.4.6.2.2, “Camera”, pp. 5374

The only complex type contained in the camera, CT\_SphereCoords, is a complex type defined elsewhere within the DrawingML. There are three simple types associated with a camera:

- ST\_FOVAngle (field of view angle), which is a positive angle between 0 and 180 in 60,000th of a degree.
- ST\_PositivePercentage (zoom), which is defined as a percentage ~~in 1,000th of a percent~~.
- ST\_PresentCameraType (preset camera)

Part 1, §A.4.1, “DrawingML - Main”, pp. 4546, lines 1103–1110

```

<xsd:complexType name="CT_Camera">
 ...
 <xsd:attribute name="zoom" type="ST_PositivePercentage"
 use="optional" default="100000100%" />
</xsd:complexType>

```

### 3. DR 08-0003 — DML, Main: Format of ST\_PositivePercentage values in strict mode examples

**Status:** Further Consideration RequiredLast Call

**Subject:** DML, Main: Format of ST\_PositivePercentage values in strict mode examples

**Qualifier:** Editorial defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** eb2m-mrt@asahi-net.or.jp

**Submitter's Defect Number:** JP1-3

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §20.1.5.5 (pp. 3153)

**Related DR(s):** DR 08-0002 — Primer: Format of ST\_PositivePercentage values in strict mode examples

**Nature of the Defect:**

Since the conformance class strict uses the simple type ST\_PositivePercentage, the attribute zoom always requires the trailing percent sign. Thus, this example is incorrect.

**Solution Proposed by the Submitter:** none

**Schema Change(s) Needed:** No

**Editor's Response:**

The change described below will be made.

Notes:

1. Part 1, §19.5.83, “tmPct (Time Percentage)”, contains the example

```
<a:camera prst="perspectiveContrastingRightFacing"
 fov="6900000" zoom="200000">
 <a:rot lat="1200000" lon="18000000" rev="1200000"/>
</a:camera>
```

where the possible values for zoom are defined by the type ST\_PositivePercentage. In strict conformance mode, such percentage values are required to have a “%” suffix, so “200000” should be changed to “200000%”/>.

2. As these changes occur in non-normative text, strictly speaking, this is an editorial defect; however, it is recognized that incorrect examples can influence implementers.

#### **2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

#### **2009-04-24 Editor:**

~~See document SC 34/WG4 N 0044 for the proposed response.~~

#### **2009-05-25 Editor:**

The exact changes are as follows:

Part 1, §20.1.5.5, “camera (Camera)”, pp. 3153

| Attributes  | Description                                                                                                                                                                                                |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| zoom (Zoom) | <p>...</p> <pre>&lt;a:camera prst="perspectiveContrastingRightFacing"   fov="6900000" zoom="200000200%"&gt;   &lt;a:rot lat="1200000" lon="18000000" rev="1200000"/&gt; &lt;/a:camera&gt;</pre> <p>...</p> |

## 4. DR 08-0004 — DML, Diagrams: Type for prSet attributes

**Status:** ~~Further Consideration Required~~ [Last Call](#)

**Subject:** DML, Diagrams: Type for prSet attributes

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** JP1-4

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §21.4.3.4 (pp. 3983)

**Related DR(s):** none

**Nature of the Defect:**

Some attributes, namely custScaleX, custScaleY, custLinFactX, custLinFactY, custLinFactNeighborX, custLinFactNeighborY, custRadScaleRad, and custRadScaleInc, specify the 1000<sup>th</sup> of a percent rather than a decimal number followed by a percent. This is inconsistent with Resolution 6 in the BRM.

**Solution Proposed by the Submitter:** none

**Schema Change(s) Needed:** Yes

**Editor's Response:**

The changes described below will be made.

**Notes:**

1. The description of each of these attributes currently states, “The possible values for this attribute are defined by the W3C XML Schema int datatype.” The type should be ST\_PositivePercentage instead.
2. The schemas (both XSD and RelaxNG) and the itemized list in §M.4.15.2.4 will need to be revised.

#### **2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

#### **2009-04-24 Editor:**

~~See document SC 34/WG4 N 0044 for the proposed response.~~

#### **2009-05-25 Editor:**

The exact changes are as follows:

The exact changes are as follows:

Part 1, §21.4.7.xx, “ST\_PrSetCustVal (Property Set Customized Value)”, new subclause

This simple type defines customization percentage values for certain elements in DrawingML.

This simple type is a union of the following types:

- The ST\_Percentage simple type (§22.9.2.9).

#### Referenced By

|                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>prSet@custScaleX (§21.4.3.4); prSet@custScaleY (§21.4.3.4); prSet@custLinFactX (§21.4.3.4);</u><br><u>prSet@custLinFactY (§21.4.3.4); prSet@ custLinFactNeighborX (§21.4.3.4); prSet@ custLinFactNeighborY (§21.4.3.4); prSet@ custRadScaleRad (§21.4.3.4); prSet@custRadScaleInc (§21.4.3.4);</u> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

[Note: The W3C XML Schema definition of this simple type’s content model (ST\_PrSetCustVal) is located in §xx.  
end note]

Part 4, §12.1.2.xx, “Additional member types for the union in ST\_PrSetCustVal (Part 1, §xx)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The W3C XML Schema int datatype.

Part 1, §21.4.3.4, “prSet (Property Set)”, pp. 3983–3984

| Attributes                                     | Description                                                                                                                                                                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| custLinFactNeighb orX (Neighbor Offset Width)  | Specifies the percentage of the neighbor's width used for offsetting shape.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .             |
| custLinFactNeighb orY (Neighbor Offset Height) | Specifies the percentage of the neighbor's height used for offsetting shape.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .            |
| custLinFactX (Custom Factor Width)             | Specifies the percentage of the current shape width used for offsetting the shape.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .      |
| custLinFactY (Custom Factor Height)            | Specifies the percentage of the current shape height used for offsetting the shape.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .     |
| custRadScaleInc (Include Angle Scale)          | Specifies the <a href="#">amount percent</a> that the include angle has been scaled by.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> . |
| custRadScaleRad (Radius Scale)                 | Specifies <a href="#">the percent that how much</a> the radius has been scaled by.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .      |
| custScaleX (Width Scale)                       | Specifies the <a href="#">amount percent</a> that the width has been scaled by.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .         |
| custScaleY (Height Scale)                      | Specifies the <a href="#">amount percent</a> that the height has been scaled by.<br>The possible values for this attribute are defined by the <a href="#">W3C XML Schema int datatype ST_PrSetCustVal simple type (\$xx)</a> .        |

Part 1, §A.5.3, “DrawingML - Diagrams”, pp. 4628, lines 427–430

```

<xsd:simpleType name="ST_ModelId">
 <xsd:union memberTypes="xsd:int s:ST_Guid"/>
</xsd:simpleType>
<xsd:simpleType name="ST_PrSetCustVal">
 <xsd:union memberTypes="s:ST_Percentage"/>
</xsd:simpleType>
<xsd:complexType name="CT_ElemPropSet">

```

Part 1, §A.5.3, “DrawingML - Diagrams”, pp. 4628–4629, lines 455–463

```

<xsd:attribute name="custScaleX" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custScaleY" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custT" type="xsd:boolean" use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactX" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactY" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactNeighborX" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactNeighborY" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custRadScaleRad" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custRadScaleInc" type="xsd:int ST_PrSetCustVal"
use="optional">
</xsd:attribute>

```

Part 1, §B.5.3, “DrawingML - Diagrams”, pp. 4907, lines 373–374

```

ddgrm_ST_ModelId = xsd:int | s_ST_Guid
ddgrm_ST_PrSetCustVal = s_ST_Percentage | xsd:int

```

ddgrm\_CT\_ElemPropSet =

Part 1, §B.5.3, “DrawingML - Diagrams”, pp. 4908, lines 394–402

```
attribute custScaleX { xsd:intddgrm ST PrSetCustVal }?,
attribute custScaleY { xsd:intddgrm ST PrSetCustVal }?,
attribute custT { xsd:boolean }?,
attribute custLinFactX { xsd:intddgrm ST PrSetCustVal }?,
attribute custLinFactY { xsd:intddgrm ST PrSetCustVal }?,
attribute custLinFactNeighborX { xsd:intddgrm ST PrSetCustVal }?,
attribute custLinFactNeighborY { xsd:intddgrm ST PrSetCustVal }?,
attribute custRadScaleRad { xsd:intddgrm ST PrSetCustVal }?,
attribute custRadScaleInc { xsd:intddgrm ST PrSetCustVal }?,
```

Part 4, §A.5.3, “DrawingML - Diagrams”, pp. 4628, lines 427–430

```
<xsd:simpleType name="ST_ModelId">
 <xsd:union memberTypes="xsd:int s:ST_Guid"/>
</xsd:simpleType>
<xsd:simpleType name="ST_PrSetCustVal">
 <xsd:union memberTypes="s:ST_Percentage xsd:int"/>
</xsd:simpleType>
<xsd:complexType name="CT_ElemPropSet">
```

Part 4, §A.5.3, “DrawingML - Diagrams”, pp. 1100, lines 455–463

```
<xsd:attribute name="custScaleX" type="xsd:intST PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custScaleY" type="-xsd:intST PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custT" type="xsd:boolean" use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactX" type="-xsd:intST PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactY" type="-xsd:intST PrSetCustVal"
use="optional">
</xsd:attribute>
<xsd:attribute name="custLinFactNeighborX" type="-xsd:intST PrSetCustVal"
use="optional">
</xsd:attribute>
```

```

<xsd:attribute name="custLinFactNeighborY" type="xsd:int" use="optional">
</xsd:attribute>
<xsd:attribute name="custRadScaleRad" type="xsd:int" use="optional">
</xsd:attribute>
<xsd:attribute name="custRadScaleInc" type="xsd:int" use="optional">
</xsd:attribute>

```

Part 4, §B.5.3, “DrawingML - Diagrams”, pp. 1411, lines 373–374

```

ddgrm_ST_ModelId = xsd:int | s_ST_Guid
ddgrm ST PrSetCustVal = s ST Percentage
ddgrm_CT_ElemPropSet =

```

Part 4, §B.5.3, “DrawingML - Diagrams”, pp. 1412, lines 394–402

```

attribute custScaleX { xsd:int ddgrm_ST_PrSetCustVal }?,
attribute custScaleY { xsd:int ddgrm ST PrSetCustVal }?,
attribute custT { xsd:boolean }?,
attribute custLinFactX { xsd:int ddgrm ST PrSetCustVal }?,
attribute custLinFactY { xsd:int ddgrm ST PrSetCustVal }?,
attribute custLinFactNeighborX { xsd:int ddgrm ST PrSetCustVal }?,
attribute custLinFactNeighborY { xsd:int ddgrm ST PrSetCustVal }?,
attribute custRadScaleRad { xsd:int ddgrm ST PrSetCustVal }?,
attribute custRadScaleInc { xsd:int ddgrm ST PrSetCustVal }?,

```

## 5. DR 08-0005 — PML, Animation: Description of hsl attributes Lightness and Saturation

**Status:** Further Consideration RequiredLast Call

**Subject:** PML, Animation: Description of hsl attributes Lightness and Saturation

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** eb2m-mrt@asahi-net.or.jp

**Submitter's Defect Number:** JP1-5

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §19.5.46 (pp. 2921)

**Related DR(s):** none

### Nature of the Defect:

As permissible values of the attributes l (Lightness) and s (Saturation), the schema uses ST\_FixedPercentage (i.e., "%"), while the text says "1000<sup>th</sup> of a percent".

**Solution Proposed by the Submitter:** none

### Schema Change(s) Needed:

### Editor's Response:

The change described below will be made. (Specific details of new wording are still needed.)

Notes:

1. The description of each of these attributes currently states, "Specifies a ... as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present." We need to distinguish between strict and transitional conformance modes. Part 1 supports strict mode only.

**2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

**2009-04-24 Editor:**

See document SC 34/WG4 N 0044 for the proposed response.

**2009-05-25 Editor:**

The exact changes are as follows:

Part 1, §19.5.46, "hsl (HSL)", pp. 2920

| Attributes     | Description                                                                                                                                                                                                                                                                                                                         |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| l (Lightness)  | Specifies a lightness <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . The values range from [-100%, 100%].<br>The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx).  |
| s (Saturation) | Specifies a saturation <del>as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage</del> . The values range from [-100%, 100%].<br>The possible values for this attribute are defined by the ST_FixedPercentage simple type (\$xx). |

## 6. DR 08-0006 — PML, Animation: Description of rgb attributes Blue, Green and Red

**Status:** ~~Further Consideration Required~~ [Last Call](#)

**Subject:** PML, Animation: Description of rgb attributes Blue, Green and Red

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** JP1-6

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §19.5.63 (pp 2937)

**Related DR(s):** none

### **Nature of the Defect:**

As permissible values of the attributes b (Blue), g (Green), and r (Red), the schema uses ST\_FixedPercentage, while the text still allows "a fixed percentage in 1000ths of a percent".

**Solution Proposed by the Submitter:** none

### **Schema Change(s) Needed:**

### **Editor's Response:**

The change described below will be made. (Specific details of new wording are still needed.)

Notes:

1. The description of each of these attributes currently states, "Specifies a ... as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present." We need to distinguish between strict and transitional conformance modes. Part 1 supports strict mode only.

**2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

**2009-04-24 Editor:**

See document SC 34/WG4 N 0044 for the proposed response.

**2009-05-25 Editor:**

The exact changes are as follows:

Part 1, §19.5.63, "rgb (RGB)", pp. 2936–2937

| Attributes | Description                                                                                                                                                                                                                                                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| b (Blue)   | This attribute specifies a blue as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage. Values range from [-100%, 100%].<br><br>The possible values for this attribute are defined by the ST_FixedPercentage simple type (§xx).  |
| g (Green)  | This attribute specifies a green as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage. Values range from [-100%, 100%].<br><br>The possible values for this attribute are defined by the ST_FixedPercentage simple type (§xx). |
| r (Red)    | This attribute specifies a red as fixed percentage in 1000ths of a percent when no percent sign is included in the value or as percent when a percent sign is present as a percentage. Values range from [-100%, 100%].<br><br>The possible values for this attribute are defined by the ST_FixedPercentage simple type (§xx).   |

## 7. DR 08-0007 — DML, Main: Format of ST\_TextBulletSizePercent percentage

**Status:** ~~Further Consideration Required~~ [Last Call](#)

**Subject:** DML, Main: Format of ST\_TextBulletSizePercent percentage

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** JP1-7

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §20.1.10.62 (pp 3420)

**Related DR(s):** DR 08-0001 — DML, Framework: Removal of ST\_PercentageDecimal from the strict schema

### Nature of the Defect:

The simple type ST\_TextBulletSizePercent (Bullet Size Percentage) should allow the percent sign, as instructed by Resolution 6 in the BRM.

**Solution Proposed by the Submitter:** none

**Schema Change(s) Needed:**

**Editor's Response:**

Agreed; the percent sign should be allowed. (Specific details of new wording are still needed.)

**2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

**2009-04-24 Editor:**

See document SC 34/WG4 N 0044 for the proposed response.

**2009-05-25 Editor:**

The exact changes are as follows:

The exact changes are as follows:

Part 1, §20.1.10.xx, “ST\_TextBulletSize (Bullet Size Percentage)”, new subclause

This simple type specifies the range that the bullet percent can be. A bullet percent is the size of the bullet with respect to the text that should follow it, with a minimum size of 25% and maximum size of 400%.

This simple type is a union of the following types:

- The ST\_TextBulletSizePercent simple type (§20.1.10.62)

| Referenced By                                            |
|----------------------------------------------------------|
| <u>buSzPct@val (§Error! Reference source not found.)</u> |

[Note: The W3C XML Schema definition of this simple type's content model (ST\_TextBulletSize) is located in §Error! Reference source not found.. [end note](#)]

Part 1, §20.1.10.62, “ST\_TextBulletSizePercent (Bullet Size Percentage)”, pp. 3420

This simple type specifies the range that the bullet percent can be. A bullet percent is the size of the bullet with respect to the text that should follow it.  ~~$25000 = 25\%$~~   ~~$400000 = 400\%$~~

This simple type's contents are a restriction of the ST\_PercentageDecimal datatype (§0).

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 25000.
- This simple type has a maximum value of less than or equal to 400000.
- This simple type's contents shall match the following regular expression pattern:  
 $0*((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%$ .

| Referenced By                                                                           |
|-----------------------------------------------------------------------------------------|
| <u>buSzPct@val (§Error! Reference source not found.)</u> <u>ST_TextBulletSize (§xx)</u> |

[*Note: The W3C XML Schema definition of this simple type's content model (ST\_TextBulletSizePercent) is located in §Error! Reference source not found.. end note*]

Part 4, §12.1.2.xx, “ST\_TextBulletSizeDecimal (Bullet Size Percentage)”, new subclause

This simple type specifies the range that the bullet percent can be. A bullet percent is the size of the bullet with respect to the text that should follow it.  $25000 = 25\%$ ,  $400000 = 400\%$

This simple type's contents are a restriction of the ST\_PercentageDecimal datatype (Part 4, §xx).

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 25000.
- This simple type has a maximum value of less than or equal to 400000.

| <u>Referenced By</u>            |
|---------------------------------|
| ST_TextBulletSize (Part 1, §xx) |

[*Note: The W3C XML Schema definition of this simple type's content model (ST\_TextBulletSizeDecimal) is located in §xx. end note*]

Part 4, §12.1.2.xx, “Additional member types for the union in ST\_TextBulletSize (Part 1, §xx)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_TextBulletSizeDecimal simple type (Part 4, §xx).

Part 1, §A.4.1, “DrawingML - Main”, pp. 4577, lines 2742–2747

```

<xsd:simpleType name="ST_TextBulletSize">
 <xsd:union memberTypes="ST_TextBulletSizePercent"/>
</xsd:simpleType>
<xsd:simpleType name="ST_TextBulletSizePercent">
 <xsd:restriction base="ST_PercentageDecimal">
 <xsd:minInclusive value="25000"/>
 <xsd:maxInclusive value="400000"/>
 </xsd:restriction>
 <xsd:pattern value="0*((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%"/>
</xsd:simpleType>

```

Part 1, §B.4.1, “DrawingML - Main”, pp. 4871, lines 2115–2116

a ST\_TextBulletSize = a ST\_TextBulletSizePercent

```
a_ST_TextBulletSizePercent =
xsd:int { minInclusive = "25000" maxInclusive = "400000" }
xsd:string {
 pattern = "((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%"
}
```

Part 4, §A.4.1, “DrawingML - Main”, pp. 1048, lines 2765–2770

```
<xsd:simpleType name="ST_TextBulletSize">
 <xsd:union memberTypes="ST_TextBulletSizePercent
 ST_TextBulletSizeDecimal"/>
</xsd:simpleType>
<xsd:simpleType name="ST_TextBulletSizePercent">
 <xsd:restriction base="ST_PercentageDecimal">
 <xsd:minInclusive value="25000"/>
 <xsd:maxInclusive value="400000"/>
 </xsd:restriction>
 <xsd:pattern value="0*((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%"/>
</xsd:simpleType>
<xsd:simpleType name="ST_TextBulletSizeDecimal">
 <xsd:restriction base="ST_PercentageDecimal">
 <xsd:minInclusive value="25000"/>
 <xsd:maxInclusive value="400000"/>
 </xsd:restriction>
</xsd:simpleType>
```

Part 4, §B.4.1, “DrawingML - Main”, pp. 1374, lines 2126–2127

```
a_ST_TextBulletSize =
 a_ST_TextBulletSizePercent | a_ST_TextBulletSizeDecimal
a_ST_TextBulletSizePercent =
xsd:int { minInclusive = "25000" maxInclusive = "400000" }
xsd:string {
 pattern = "((2[5-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%"
}
a_ST_TextBulletSizeDecimal =
 xsd:int { minInclusive = "25000" maxInclusive = "400000" }
```

## 8. DR 08-0008 — DML, Main: Format of buSzPct percentage values in strict mode example

**Status:** Further Consideration Required

**Subject:** DML, Main: Format of buSzPct percentage values in strict mode example

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** JP1-8

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-09-26

**Deadline for Response from Editor:** 2008-11-26

**IS 29500 Reference(s):** Part 1, §21.1.2.4.9 (pp. 3640)

**Related DR(s):** DR 08-0007 — DML, Main: Format of ST\_TextBulletSizePercent percentage

### **Nature of the Defect:**

The element buSzPct should allow the percent sign, as instructed by Resolution 6 in the BRM.

**Solution Proposed by the Submitter:** none

The change described below will be made.

**Schema Change(s) Needed:** Yes, dml-main.xsd and dml-main.rnc

### **Editor's Response:**

The changes described below will be made.

Notes:

1. Part 1, §21.1.2.4.9, “buSzPct (Bullet Size Percentage)”, contains the example

```
<a:buSzPct val="111000"/>
```

where the possible values for this attribute are defined by the type ST\_TextBulletSizePercent. In strict conformance mode, such percentage values are required to have a “%” suffix, so “111000” should be changed to “111000%”.

2. The type for buSzPct in dml-main.xsd has to be changed as well.

In dml-main.xsd, ST\_TextBulletSizePercent should use

```
<xsd:simpleType name="ST_TextBulletSizePercent">
 <xsd:annotation>
 <xsd:documentation>Bullet Size Percentage</xsd:documentation>
 </xsd:annotation>
 <xsd:restriction base="ST_Percentage">
 <xsd:pattern value="((2[5-9])|([3-9][0-9])|([0-3][0-9][0-9]))%" />
 </xsd:restriction>
</xsd:simpleType>
```

In dml-main.rnc, s\_ST\_TextBulletSizePercent should be

```
a_ST_TextBulletSizePercent =
xsd:string { pattern = "((2[5-9])|([3-9][0-9])|([0-3][0-9][0-9]))%" }
```

#### **2009-01-28 Okinawa meeting:**

There was general agreement that this DR needs to be fixed, along the lines of the proposed change.

**Action:** Shawn Villaron will review DRs 08-0001 through 08-0008 as a group, and will come up with a detailed proposal that addresses them and any other situations involving percentages in a strict environment that he identifies.

#### **2009-04-24 Editor:**

**See document SC 34/WG4 N 0044 for the proposed response.**

#### **2009-05-25 Editor:**

**The exact changes are as follows:**

Part 1, §21.1.2.4.9, “buSzPct (Bullet Size Percentage)”, pp. 3640–3641

This element specifies the size in percentage of the surrounding text to be used on bullet characters within a given paragraph. ~~The size is specified using a percentage where 1000 is equal to 1 percent of the font size and 100000 is equal to 100 percent font of the font size.~~

[Example: Consider the DrawingML shown below.

```
<p:txBody>
 ...
 <a:p>
 <a:pPr ...>
 <a:buSzPct val="111000111%"/>
 </a:pPr>
 ...
 <a:t>Bullet 1</a:t>
 ...
 </a:p>
 ...
</p:txBody>
```

The size of the above bullet follows the text size in that it is always rendered at 111% the size of the text within the given text run. This is specified by val="111000111%", with a restriction on the values not being less than 25% or more than 400%. ~~A value of 100000 is equal to 100%, similarly a value of 1000 is equal to 1%.~~ This percentage size should only apply to the actual bullet character and not to the text within the bullet. *end example]*

...

| Attributes  | Description                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| val (Value) | <p>Specifies the percentage of the text size that this bullet should be. <del>It is specified here in terms of 100% being equal to 100000 and 1% being specified in increments of 1000.</del> This attribute should not be lower than 25%, <del>or 25000</del> and not be higher than 400%, <del>or 400000</del>.</p> <p>The possible values for this attribute are defined by the ST_TextBulletSizePercent simple type (\$0).</p> |

## 9. DR 08-0009 — WML, Fields: Inconsistency between FILESIZE behaviour and example

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Fields: Inconsistency between FILESIZE behavior and example

**Qualifier:** Editorial defect

**Submitter:** Mr. Inigo Surguy (GB)

**Contact Information:** [inigo.surguy@67bricks.com](mailto:inigo.surguy@67bricks.com)

**Submitter's Defect Number:** GB-29500-DR-20081001-1

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-10-02

**Deadline for Response from Editor:** 2008-12-02

**IS 29500 Reference(s):** Part 1, §17.16.5.18 (pp. 1357), "FILESIZE"

**Related DR(s):** none

### Nature of the Defect:

Inconsistency between FILESIZE behavior and example remains present after response 782 was rejected at the BRM (GB-0256). 4660736 rounded to kilobytes is 4552, not 4661.

### Solution Proposed by the Submitter:

Correct the example to read 4552 kb (alternatively, change the text to use thousands of bytes rather than kilobytes, and millions of bytes rather than megabytes).

**Schema Change(s) Needed:** No

### Editor's Response:

The Switches table will be changed, as follows:

|    |                                                                      |
|----|----------------------------------------------------------------------|
| \k | Round to the nearest <u>thousands of bytes</u> <del>kilobyte</del> . |
| \m | Round to the nearest <u>millions of bytes</u> <del>megabyte</del> .  |

Notes:

1. The Fast-Track comment GB-0256 proposed that the /k mean 1000 bytes and /m mean million bytes, rather than kilobyte and megabyte, respectively. This failed to pass at the BRM based on a vote of 6/6/16/4, resulting in a draw. The original intent was as GB proposed in GB-0256. Changing to other than that intent will gratuitously break prior art.

#### **2009-01-28 Okinawa meeting:**

Agreed to change the normative description to match the example, with the following wording changes to the proposed response: “nearest thousands of bytes” becomes “nearest thousand bytes” and “nearest millions of bytes” becomes “nearest million bytes”.

The exact changes are as follows:

Part 1: §17.16.5.18, “FILESIZE”, pp. 1358

|    |                                                                  |
|----|------------------------------------------------------------------|
| \k | Round to the nearest <u>thousand bytes</u> <del>kilobyte</del> . |
| \m | Round to the nearest <u>million bytes</u> <del>megabyte</del> .  |

## 10. DR 08-0010 — WML: Use of transitional attribute in tblLook strict mode examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Use of transitional attribute in tblLook strict mode examples

**Qualifier:** Editorial defect

**Submitter:** Mr. Inigo Surguy (GB)

**Contact Information:** [inigo.surguy@67bricks.com](mailto:inigo.surguy@67bricks.com)

**Submitter's Defect Number:** GB-29500-DR-20081001-2

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-10-02

**Deadline for Response from Editor:** 2008-12-02

**IS 29500 Reference(s):** Part 1, §17.4.59 (pp. 483), §17.7.6 (pp. 725), §17.13.5.34 (pp. 1014), §K.5.8.1 (pp. 5062) [this occurrence added by editor], §M.1.8.7 (pp. 5105-6)

**Related DR(s):** none

**Nature of the Defect:**

The application of Response 135 from the BRM has left the examples incorrect – example specifies tblLook with transitional w:val attribute, which no longer exists in the strict schema.

**Solution Proposed by the Submitter:**

Change the examples to use w:firstRow, w:lastRow etc. for tblLook.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed with submitter's proposed solution.

The exact changes are as follows:

The example in §17.4.59, “tblPr (Previous Table Properties)”, pp. 483:

```
<w:tblPr>
 <w:tblStyle w:val="TableGrid"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:jc w:val="center"/>
 <w:shd w:val="clear" w:color="auto" w:fill="FF0000"/>
 <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
 w:noVBand="true" />
 <w:tblPrChange w:id="0" ... >
 <w:tblPr>
 <w:tblStyle w:val="TableGrid"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
 w:noVBand="true"/>
 </w:tblPr>
 </w:tblPrChange>
</w:tblPr>
```

The text in §17.7.6, “Table Styles”, pp. 725:

The use or omission conditional formats shall be specified using the `tblLook` element, which contains a [bitmask representing a number of attributes that indicate](#) which properties are applied and omitted.

The example in §17.7.6, “Table Styles”, pp. 725:

```
<w:tbl>
 <w:tblPr>
 <w:tblStyle w:val="Style2"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="0660" w:firstRow="true" w:lastRow="true"
 w:noHBand="true" w:noVBand="true"/>
 </w:tblPr>
 ...
</w:tbl>
...
<w:tbl>
 <w:tblPr>
 <w:tblStyle w:val="Style2"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="0460" w:firstRow="true" w:lastRow="true"
 w:noVBand="true"/>
 </w:tblPr>
```

...

```
</w:tbl>
```

The example in §17.13.5.34, “tblPrChange (Revision Information for Table Properties)”, pp. 1014:

```
<w:tblPr>
 <w:tblStyle w:val="LightShading"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
 w:noVBand="true"/>
 <w:tblPrChange w:id="0" w:author="Tristan Davis" w:date="2006-06-
 01T13:39:00Z">
 <w:tblPr>
 <w:tblStyle w:val="LightList"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
 w:noVBand="true"/>
 </w:tblPr>
 </w:tblPrChange>
</w:tblPr>
```

The text in §M.1.8.7, “Table Styles”, pp. 5105:

The use or omission conditional formats are specified using the `tblLook` element, which contains a [bitmask representing a number of attributes that indicate](#) which properties are applied and omitted.

The example in §K.5.8.1, “Using Captions and Long Descriptions in WordprocessingML Tables”, pp. 5061–5062:

```
<w:body>
 <w:tbl>
 <w:tblPr>
 <w:tblStyle w:val="TableGrid"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="04A0" w:firstRow="true" w:firstColumn="true"
 w:noVBand="true"/>
 <w:tblCaption w:val="2004 Figures"/>
 <w:tblDescription w:val="This table shows that sales figure have been
 rising for the past five quarters."/>
 </w:tblPr>
 ...
 </w:tbl>
 ...
</w:body>
```

The example in §M.1.8.7, “Table Styles”, pp. 5106:

```
<w:tbl>
 <w:tblPr>
 <w:tblStyle w:val="Style2"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="0660" w:firstRow="true" w:lastRow="true"
 w:noHBand="true" w:noVBand="true"/>
 </w:tblPr>
 ...
</w:tbl>
...
<w:tbl>
 <w:tblPr>
 <w:tblStyle w:val="Style2"/>
 <w:tblW w:w="0" w:type="auto"/>
 <w:tblLook w:val="0460" w:firstRow="true" w:lastRow="true"
 w:noVBand="true"/>
 </w:tblPr>
 ...
</w:tbl>
```

2009-01-28 Okinawa meeting:

Approved as proposed.

**Action:** Editor to present the affected text showing specific changes. (Done; see above.)

# 11. DR 08-0011 — WML: Use of transitional attribute in cnfStyle strict mode example

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Use of transitional attribute in cnfStyle strict mode example

**Qualifier:** Editorial defect

**Submitter:** Mr. Inigo Surguy (GB)

**Contact Information:** [inigo.surguy@67bricks.com](mailto:inigo.surguy@67bricks.com)

**Submitter's Defect Number:** GB-29500-DR-20081001-3

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-10-02

**Deadline for Response from Editor:** 2008-12-02

**IS 29500 Reference(s):** Part 1, §17.13.5.36 (pp. 1018)

**Related DR(s):** none

## Nature of the Defect:

The application of Response 135 from the BRM has left the examples incorrect – example specifies cnfStyle with transitional w:val attribute that no longer exists in the strict schema.

## Solution Proposed by the Submitter:

Change the examples to use w:firstRow, w:lastRow etc. for cnfStyle.

**Schema Change(s) Needed:** No

## Editor's Response:

Agreed with submitter's proposed solution.

The example in §17.13.5.36, “tcPrChange (Revision Information for Table Cell Properties)”, pp. 1018:

<w:tcPr>

```
<w:cnfStyle w:val="001000000000"w:firstColumn="true"/>
<w:tcW w:w="3192" w:type="dxa"/>
<w:tcPrChange w:id="8" w:author="Tristan Davis" w:date="2006-06-01T13:39:00Z">
 <w:tcPr>
 <w:tcW w:w="3192" w:type="dxa"/>
 </w:tcPr>
</w:tcPrChange>
</w:tcPr>
```

**2009-01-28 Okinawa meeting:**

Approved as proposed.

**Action:** Editor to present the affected text showing specific changes. (Done; see above.)

## 12. DR 08-0012 — Schemas: Supposedly incorrect schema namespace names

**Status:** Further Consideration Required

**Subject:** Schemas: Supposedly incorrect schema namespace names

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 14.001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-11-03

**Deadline for Response from Editor:** 2009-01-03

**IS 29500 Reference(s):** All Parts and schemas

**Related DR(s):** DR 09-0168 — OPC: No mechanism to distinguish ECMA-376:2006 from IS 29500

### **Nature of the Defect:**

OOXML's schema namespace names are designed for implementing versioning by means of embedding the year in the namespace names. However, in this version of the specification "2006" is still used in the schema namespace names even though the schemas have changed. Unless this is corrected, this will result in significant problems in use-cases where applications need the ability to validate documents which are allowed to conform to either the schemas of ECMA-376:2006 or the schemas of ISO/IEC 29500:2008. This is a severe defect which must be corrected with high priority.

### **Solution Proposed by the Submitter:**

Update the "2006" in the namespace names to "2008".

**Schema Change(s) Needed:** No

### **Editor's Response:**

It would be useful to have a reliable mechanism for distinguishing between the two versions of schemas, as described. Updating the “2006” year that is embedded in the namespaces to “2008” for those namespaces that were modified during the DIS 29500 BRM process seems a reasonable and logical choice. However, several questions arise from this proposal:

- Should such a change be made to all schemas in IS 29500, or only to those that have changed since the 2006 version?
- Is this correcting a defect or is it a change in functionality? That is, does any resulting change belong in a COR or in an amendment/revision?

We recommend that this matter be discussed by WG4 during its next face-to-face meeting.

**2009-01-28 Okinawa meeting:**

There was consensus that something needed to be fixed, and two solutions were discussed:

- Adding an optional Version attribute (as done by ODF)
- Changing the schema name

Other solutions might also be investigated.

In the short term, it was agreed to solve the problem in a COR, and to defer a discussion of namespace name change to a future amendment/revision. (For example, several members raised the possibility of considering removing the year from the namespace names altogether.)

**Action:** Shawn Villaron will produce a detailed proposal.

**2009-03-24 Prague meeting:**

Shawn Villaron made a presentation then lead a discussion on this. At the end, the following possible approaches were identified:

- Option 1: Change all IS 9500-specific namespaces to allow for differentiation with the ECMA-376-specific schemas
- Option 2: Extend the conformance attribute on the root elements for WordprocessingML, SpreadsheetML and PresentationML
- Option 3: Add a new optional version attribute on the root elements for WordprocessingML, SpreadsheetML and PresentationML
- Option 4: Add a new optional version attribute on type element in the [Content\_Types].xml part for all packages
- Option 5: Add a new optional version attribute as an optional custom document property
- Option 6: Add a new optional part OPC that would include a version attribute

After a lengthy discussion, Murata-san asked a small group (Shawn, Florian, Inigo, Jesper, Mohamed) to go off and draft a more narrow set of proposals. The next day, this group reported it developed the following guiding principles to evaluate the options:

- To push producers gently towards strict conformance
- To improve interoperability
- To do no evil to the 29500 ecosystem (i.e., files, end users and implementations)

The group went through the set of options looking at the degree to which each would solve the problem as well as the "cost" imposed on applications to handle the consequence of the solution. As a result, the six options were reduced to the following two:

- Change the namespace name for strict schemas only
- Extend the existing conformance attribute

There was another lengthy discussion.

Regarding other standards (such as XPS) that are using OPC: The conformance attribute approach does *not* help them nor would any change to the namespace for Part 1 only.

**Action:** Jesper will produce a paper on the two remaining alternatives for circulation to WG4. Done (See N 0037).

The solution to this DR should be published in an Amendment.

#### **2009-04-07 Alex Brown:**

[Re N 0037] The last bullet point for Proposal 2's implications states:

"In most cases, documents complying with the strict conformance class using the conformance attribute will load in existing applications supporting only ECMA-376 1st Ed. without any problems."

Are we really confident about that "most cases" qualification?

#### **2009-04-07 Shawn Vilaron:**

Again, it's going to come down to how the implementers decide to deal with unexpected data. For example, if an implementation runs across the compliance attribute (not part of Ecma 376 1<sup>st</sup> ed.), the implementer will need to decide to abort the open, to ignore the attribute and continue opening the file, etc., etc. From what I've seen so far -- clearly not scientific -- is that most implementations deal with unexpected data loosely and hence can successfully open the file; in these cases, the implementations attempt to retain every bit of understood data they can; data which is understood is lost at open time.

To be clear, this is an implementer's choice. From a technical perspective, the implementer can write more code to improve the experience. Like many of these decisions which we defer to the implementer, this will be a great opportunity for innovation and competition.

**2009-04-07 Alex Brown:**

> Again, it's going to come down to how the implementers decide to deal with unexpected data.

Yes, and I think something we can all agree on is that this whole debate puts into sharp focus what it means to be "forwards compatible" (or not).

(And, BTW, this is also a big problem for ODF. Not currently our problem, though it may become the problem of some implementers here).

> For example, if an implementation runs across the compliance attribute (not part of Ecma 376 1st), the implementer will need to decide to abort the open, to ignore the attribute and continue opening the file, etc., etc.

As a validation purist I might say that applications should not process invalid XML inputs (for that is what we would have here). But I can appreciate some may find that an overly harsh approach. At the very least, a user must be \*aware\* they might suffer data loss, I think.

> From what I've seen so far -- clearly not scientific -- is that most implementations deal with unexpected data loosely and hence can successfully open the file; in these cases, the implementations attempt to retain every bit of understood data they can; data which is [not] understood is lost at open time.

This is always dangerous though: a publishing example is the @legal-embargo="true" attribute that gets introduced on an element. We may think we "understand" that element's content still, but because we don't understand the attribute, in fact we miss the fact that the new context modifies the meaning we assumed.

In general it is simply not possible to write software which will reliably deal with formats from the future (unless we had some way of indicating the semantics of elements/attributes in a pre-agreed way: now there's an idea -- can we annotate the schemas with concepts like "must-understand" for certain constructs?).

So, in general, the fail-safe method is to reject an invalid input.

> To be clear, this is an implementer's choice.

Or, to be more precise, it \_was\_ an implementer's choice. The software is already out there which is going to be shown these new files (especially if we don't resolve the media type and filename extension issues -- another aspect of this).

One of the other things we agreed on in Prague (and which didn't make it into the document) was that we can't travel in time :-) This wasn't just for fun -- the fact is that we have major implementations out there like Office 2007 and OO.o 3.x which will not deal gracefully with "formats from the future" which they wrongly treat as \*their\* formats.

> From a technical perspective, the implementer can write more code to improve the experience.

Sure, and I'm guessing there is a possibility of patching some installations to make them compatible with future formats.

> Like many of these decisions which we defer to the implementer, this will be a great opportunity for innovation and competition.

It's an interesting one. Some users will be utterly dismayed by seeing a dialog box which informs them a document can't be opened. Other users (perhaps those with the highest value documents) would actually prefer such a dialog, and would be horrified by the thought of silent data loss in their (say) financial spreadsheet.

We're all user-focused here, I think. What we're trying to reach consensus on is the approach that will best serve those users ...

#### **2009-04-07 Makoto Murata:**

The main topic of the "Namespace Discussion" paper is versioning of Parts 1 and 4, although versioning of Part 2 is mentioned. Again, to finish one issue at a time, I submitted another defect report (DR 09-0168) about versioning of Part 2.

#### **2009-04-12 Makoto Murata:**

First, the beginning of this document is "Proposal 1 and proposal 2 are not mutually exclusive -- indeed, if proposal 1 is accepted, then it may be desirable if proposal 2 was also accepted."

where Proposal 1 is:

To change the namespace for the strict schemas for Part 1.

The new namespace should no longer contain a year.

and Proposal 2 is:

To change the conformance attribute to support the attribute including version information as part of the conformance information.

I see two options for combining Proposal 1 and proposal 2.

Option 1: To change the namespace for the strict schemas and change the conformance attribute for both conformance classes.

Option 2: To change the namespace for the strict schemas and change the conformance attribute for the conformance class "transitional" only.

Second, I do not think that Proposal 1 without Proposal 2 provides any mechanisms for distinguishing the first edition Ecma 376 OOXML and "transitional" of 29500.

#### **2009-04-16 Teleconference:**

Jesper's paper WG4 N 0037 was discussed.

Several members spoke in favor of a solution that combined both proposals.

Should we address Parts 1 and 4 only, or should we also include a solution for Part 2? Several members spoke in favor of solving the larger problem; one thought Part 2 could wait. Murata-san reminded us of the new DR he submitted, DR 09-0168, which specifically covers namespace version detection for Part 2.

**Action:** Shawn and Jesper will write a new paper showing the detailed changes needed for an integrated proposal that addresses Parts 1 and 4 only.

#### **2009-04-29 Gareth Horton:**

[Regarding paper N 0037] Not a very pleasant prospect. I can see the reasoning, but not something that would be acceptable in a product release in my house, so to speak.

Obviously, the strict namespace does need to change. For data integrity purposes, I think there is also a very good case for the transitional namespace to change.

The issue I am focused on is the date issue, as you already know.

In a previous document, N1194 you mention the impacts:

"Attempting to open an ISO/IEC 29500 transitional document in an application that only understands ECMA 376 1<sup>st</sup> Ed. will depend on whether the transitional document uses any of the new syntax (e.g. ISO 8601 dates, comments in spreadsheets, bitmasks or object embedding) added at the BRM.

- If the transitional document uses the new syntax, behaviour will be application defined. ISO 8601 dates will be corrupted in MS Office and OpenOffice.org as described above (an application bug). Most documents will most likely be opened with no errors."

The problem is that anyone implementing transitional would certainly implement ISO 8601 dates in spreadsheets, going from the intent of the spec, which uses an ISO 8601 date as an example. The fact that there is now an attribute to indicate ISO8601 dates does not really help 'legacy' apps.

In 18.17.4.1 – "All date values stored in cells within a SpreadsheetML file are stored in the ISO 8601 format."

Would you implement writing a serial date by default going off the spec? No. We can assume that going forward, all dates in transitional and strict files will be ISO 8601. Maybe some apps will roundtrip the existing data, so there won't be an acceleration of existing documents being silently updated, but we can assume all new instances will write ISO 8601.

I contend that a reasonable proportion of spreadsheets contain dates. Most reporting and analysis has a date element – even if that is just shown as a month, quarter etc using a formatting mask. It will still be a date. I also disagree that the problem lies with the apps – they are working absolutely to the spec as it was designed at the time – the semantic meaning of the string element involved was a serial date number. The change made at the

BRM was not well thought out. One could say that the spec caused the problem, it is its duty to solve it. This approach leaves it utterly on the shoulders of implementers (and indeed users – via updates/patch management) to fix it.

Of course, all this would be moot if there was a mechanism to determine versions of documents instances back in ECMA376-1, but there wasn't. As I might have mentioned before, Office 2007 implemented the change in specs with a namespace change during the beta, so we, as probably others, reasonably assumed that the lack of any other versioning strategy implied a namespace change would be the future mechanism.

If we don't change the transitional namespace, then there will be a big education job with customers and implementers to ensure that they retrofit existing apps to safely consume the "ISO" version of Open XML files. That will not give either of these parties a good feeling. "Don't use anything that produces ISO Open XML until all your software is patched" does not have a good ring to it.

On the other hand, I have not heard the all the detailed arguments for keeping the transitional namespace, so I'll reserve judgment until then, as I have not had a lot of time to consider the other side.

A point regarding the proposal adding the new conformance attributes – what is the reason for not using a version number now?

**2009-04-30 Jirka Kosek:**

[Regarding Gareth's comments]

As Strict is a proper subset of Transitional it will be really strange to use different namespaces for those two document types. Changing namespace only for Strict will prevent consumption of Strict documents in applications written for consumption of Transitional documents.

I think that pragmatic implementer will by default save dates as serial numbers. Otherwise he will produce documents which will be failing in currently deployed applications like MSO2007 or OOo3. At least for few years until existing applications are patched. There is nothing in specs which prevents writing dates as serial values.

I think that this is not reasonable assumption but merely wish.

If the namespace is changed existing applications will not be able to open and process new OOXML files. This will prevent mangled ISO dates and several other problems but it will greatly confuse people. Why my .xlsx file is not working in this app which can work with other .xlsx files? Namespace change results in completely new document type, which should have new content type and file extension.

I don't think that users will have sympathy for another XML based office format in this very short period of time. Especially when this new format is not that much better than ECMA-376. We should give users some break and maybe after few years when we got more feedback and experience we can finally come with a great new and lucid office file format which will supersede OOXML, ODF, ... But we are not yet there.

Standards should create stable and predictable environment both for users and implementers. If we decide to change namespace now, this change will be voted on and eventually published more than one year after IS 29500 was accepted by vote and almost a year after the standard was published. I don't think this is a stable ground which IS should create.

**2009-04-30 Teleconference:**

Discussed further.

**2009-05-14 Teleconference:**

Discussed further, resulting in a lot of email traffic, most of which is *not* recorded here.

## 13. DR 08-0013 — Shared MLs, Shared Simple Types: ST\_String allowed characters and max length

**Status:** Closed Without Action

**Subject:** Shared MLs, Shared Simple Types: ST\_String allowed characters and maximum length

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 14.001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-11-03

**Deadline for Response from Editor:** 2009-01-03

**IS 29500 Reference(s):** Part 1, §22.9.2.13 (pp. 4329), first sentence

**Related DR(s):** none

### Nature of the Defect:

For a string data type, it needs to be precisely specified what set of characters is allowed in the string, and whether there are any restrictions on the length of the string.

### Solution Proposed by the Submitter:

Specify this.

**Schema Change(s) Needed:** No

### Editor's Response:

The simple type ST\_String is referenced in more than 200 places throughout IS 29500, and in a wide variety of contexts. (Examples include font names, headings, control names, various identifiers, field

codes, namespaces, MRU values, XPath expressions, author name, and bookmark names.) Due to this broad usage of ST\_String, it is defined as a generic string type. Although it may be possible to add specific constraints for a particular reference to ST\_String, such restrictions might not be applicable in other contexts, so any restrictions defined at the ST\_String level would, of necessity, be too broad to be meaningful.

A more focused approach would be to add length or character restrictions for specific instances of ST\_String, as appropriate based on their context. Suggestions for such constraints are welcome.

We recommend that this matter be discussed by WG4 during its next face-to-face meeting.

**2009-01-28 Okinawa meeting:**

It was agreed that this is not an issue with the type itself, but that specific instances certainly might have constraints. As the submission does not identify any such specific instances, members saw no problem that needed solving. As a result, this DR was rejected. Any specific instance of this type with constraints should be submitted as a new DR.

## 14. DR 08-0014 — Shared MLs, Shared Simple Types: ST\_String example description error

**Status:** Last Call

**Subject:** Shared MLs, Shared Simple Types: ST\_String example description error

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 14.001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-11-03

**Deadline for Response from Editor:** 2009-01-03

**IS 29500 Reference(s):** Part 1, §22.9.2.13 (pp. 4329), last paragraph of the example

**Related DR(s):** none

**Nature of the Defect:**

There appears to be an editing error here, as the val attribute does not contain a decimal number.

**Solution Proposed by the Submitter:**

Replace “the decimal number in” with “the value of”.

**Schema Change(s) Needed:** No

**Editor's Response:**

Notes:

1. As this change occurs in non-normative text, strictly speaking, this is an editorial defect; however, it is recognized that incorrect examples can influence implementers.

We believe that the error occurred because the example is an instance of the alias element and it should have been an instance of the id element, whose val attribute does contain a decimal number. The proposed change will address this problem; alternatively, it could be corrected by replacing the existing alias example with the following, more appropriate, example: <w:id w:val="28565032"/>

We recommend that this matter be discussed by WG4 during its next face-to-face meeting.

#### **2009-01-28 Okinawa meeting:**

It was agreed to take the alternate approach proposed by the editor; that is, replacing the existing alias example.

**Action:** Shawn Villaron will check that this approach is adequate.

The example in §22.9.2.13, pp. 4329:

```
<w:sdtPr>
 <w:alias w:val="SDT Title Example" />
 <w:id w:val="28565032"/>
 ...
</w:sdtPr>
```

#### **2009-04-22 Shawn Villaron:**

I had an action item to review the example in §22.9.2.13. I recommend that we accept the change as proposed above.

#### **2009-04-23 Makoto Murata:**

If we accept the proposed solution of another defect report DR 09-0027, the example in §22.9.2.13 will be gone. Since some people have mentioned some more (minor) issues in this example, I think that we should simply remove from §22.9.2.13 the second sentence and the example and we should close both DR 09-0027 and DR-08-0014.

#### **2009-04-23 Jesper Lund Stockholm:**

I agree to Murata-san's suggestion to solve DR 08-0014 by accepting the proposed solution to DR 09-0027. The text in ST\_String is irrelevant to the simple type itself and should not be there.

The schema definition of ST\_String simply

s\_ST\_String = xsd:string

So the text in the description should be aligned with the proposed solution in DR 09-0027.

#### **2009-04-23 Shawn Villaron:**

Although I don't feel strongly about this, I do believe that the current text of §22.9.2.13 serves a purpose: that attributes of the same name, used in different contexts, have potentially different meanings.

My personal preference is to resolve DR-09-0027 as no action required, and make the proposed changes to DR-08-0014.

**2009-04-23 Makoto Murata:**

Context dependencies do not belong to ST\_String but belong to attributes or elements, and thus should not be described here.

There are other semantic issues about strings, such as case-(in)sensitivity.

When no other such semantic issues are mentioned here, why should we care [about] context dependencies?

**2009-04-22 Shawn Villaron:**

22.9.2.13 ST\_String (String)

This simple type specifies that its contents contains a string. ~~The contents of this string are interpreted based on the context of the parent XML element.~~

~~[Example: Consider the following WordprocessingML fragment:~~

```
<w:pPr>
 <w:pStyle w:val="heading1" />
</w:pPr>
```

~~The value of the val attribute is the ID of the associated paragraph style's styleId. However, consider the following fragment:~~

```
<w:sdtPr>
 <w:alias w:val="SDT_Title_Example" />
 ...
</w:sdtPr>
```

~~In this case, the decimal number in the val attribute is the caption of the parent structured document tag. In each case, the value is of type ST\_String, and therefore must be interpreted in the context of the parent element. end example}~~

This simple type's contents are a restriction of the W3C XML Schema string datatype.

**2009-05-02 Makoto Murata:**

I believe that WG4 has agreed to move DR-08-0014 to Last Call

The exact changes are as follows:

Part 1, §22.9.2.13, “22.9.2.13 ST\_String (String)”, pp. 4329

This simple type specifies that its contents contains a string. ~~The contents of this string are interpreted based on the context of the parent XML element.~~

*[Example: Consider the following WordprocessingML fragment:*

```
<w:pPr>
 <w:pStyle w:val="heading1" />
</w:pPr>
```

~~The value of the val attribute is the ID of the associated paragraph style's styleId. However, consider the following fragment:~~

```
<w:sdtPr>
 <w:alias w:val="SDT Title Example" />
 ...
</w:sdtPr>
```

~~In this case, the decimal number in the val attribute is the caption of the parent structured document tag. In each case, the value is of type ST\_String, and therefore must be interpreted in the context of the parent element. end example]~~

This simple type's contents are a restriction of the W3C XML Schema string datatype.

## 15. DR 08-0015 — General: Differences between ISO/IEC 29500:2008 and ECMA-376:2006, SpreadsheetML

**Status:** Closed Without Action

**Subject:** General: Differences between ISO/IEC 29500:2008 and ECMA-376:2006, SpreadsheetML

**Qualifier:** Editorial defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 14.001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2008-11-03

**Deadline for Response from Editor:** 2009-01-03

**IS 29500 Reference(s):** Part 1, §N.2 (pp. 5556)

**Related DR(s):** none

### Nature of the Defect:

ECMA-376:2006 specifies that dates and times are stored as serial values in SpreadsheetML files. ISO/IEC 29500:2008 specifies that they are stored in the ISO 8601 format. Although it is the purpose of Annex N.2 to list all major changes, it fails to mention this one.

### Solution Proposed by the Submitter:

Mention that the date representation has changed, with a reference to §18.17.4.1.

**Schema Change(s) Needed:** No

### Editor's Response:

Notes:

1. The first paragraph of this informative annex clearly states: "This annex highlights the differences between the versions of the Strict form of the Office Open XML schemas, as defined in ISO/IEC 29500:2008 and the schemas as defined by ECMA-376:2006." As such, it contains differences relating only to schema changes.
2. If it is agreed that other differences are to go in this annex, these would have to include the changes made at the BRM for various formulas (such as CONVERT).
3. Corresponding versions of this annex also exist for Parts 2 and 4.

We recommend that this matter be discussed by WG4 during its next face-to-face meeting.

**2009-01-28 Okinawa meeting:**

As implemented, the annex reflects what was agreed to at the BRM. As such, the lack of further description of non-schema changes was not viewed as a defect. As such, this DR was rejected.

## 16. DR 09-0001 — SML, Charts, Trend lines: Incorrect range restriction in backward and forward

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Charts, Trend lines: Incorrect range restriction in backward and forward

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):**

Part 1: §21.2.2.12, “backward (Backward)”, pp. 3763

Part 1: §21.2.2.73, “forward (Forward)”, pp. 3795

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that when the backward element is used to define a trend line for non-scatter charts, only two values are valid: 0 and 0.5.

The standard fails to state the valid values for the backward element when it is used to define a trend line for scatter charts.

The standard states that when the forward element is used to define a trend line for non-scatter charts, the value of this element must be a multiple of 0.5.

The standard fails to state the valid values for the forward element when it is used to define a trend line for scatter charts.

These observations are incompatible with existing documents and should be updated to reflect such prior art.

### **Background**

These two elements define the number of categories, or units in the case of a scatter chart, that the trend line extends before, or after, the data for the series that is being trended.

Existing documents contain trend lines defined using backward and forward values that do not satisfy the documented restrictions. Such documents contain non-negative values for both the backward and forward elements.

### **Solution Proposed by the Submitter:**

Revise the standard such that when used for any chart type, the backward and forward elements can be any non-negative number.

### **Schema Change(s) Needed:** none

### **Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

The failure of the standard to state the valid values sounds like a defect.

#### **2009-03-24 Prague meeting:**

Agreed with the proposed solution.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

#### **Part 1: §21.2.2.12, “backward (Backward)”, pp. 3763**

This element specifies the number of categories (or units on a scatter chart) that the trend line extends before the data for the series that is being trended. On scatter and non-scatter charts, the value shall be any non-negative value 0 or 0.5.

#### **Part 1: §21.2.2.73, “forward (Forward)”, pp. 3795**

This element specifies the number of categories (or units on a scatter chart) that the trend line extends after the data for the series that is being trended. On [scatter and](#) non-scatter charts, the value shall be [any non-negative value](#)~~a multiple of 0.5.~~

# 17. DR 09-0002 — SML, Charts: Incorrect range restriction in ST\_HoleSize

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Charts: Incorrect range restriction in ST\_HoleSize

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-002

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.3.18, “ST\_HoleSize (Hole Size)”, pp. 3884

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that the ST\_HoleSize simple type has a minimum value of 10.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

When defining a donut chart, the ST\_HoleSize simple type is used to define the size of the hole in the chart. This simple type expresses the size of the hole as a percentage of the size of the chart.

Existing documents contain donut charts with hole sizes in the range of 1 percent to 90 percent.

**Solution Proposed by the Submitter:**

Change the new minimum value for the ST\_HoleSize simple type to 1.

**Schema Change(s) Needed:** Yes, strict and transitional versions of dml-chart.xsd and dml-chart.rnc.

```
<xsd:simpleType name="ST_HoleSize">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="101"/>
 <xsd:maxInclusive value="90"/>
 </xsd:restriction>
</xsd:simpleType>
```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

**Part 1: §21.2.3.18, “ST\_HoleSize (Hole Size)”, pp. 3884**

This simple type specifies that its contents contain an integer between 10 and 90, whose contents are a percentage.

and

- This simple type has a minimum value of greater than or equal to 10.

**Part 1: §A.5.1, “Drawing ML - Charts”, pp. 4596, lines 309–314**

```
<xsd:simpleType name="ST_HoleSize">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="10"/>
 <xsd:maxInclusive value="90"/>
 </xsd:restriction>
</xsd:simpleType>
```

**Part 1: §B.5.1, “Drawing ML - Charts”, pp. 4884, lines 192–193**

```
dchrt_ST_HoleSize =
 xsd:unsignedByte { minInclusive = "10" maxInclusive = "90" }
```

## 18. DR 09-0003 — SML, Charts, Trend lines: Incorrect data type and range restriction in ST\_Period

**Status:** [Further Consideration Required](#) ~~Closed; will be incorporated in COR1~~

**Subject:** SML, Charts, Trend lines: Incorrect data type and range restriction in ST\_Period

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-003

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.3.33, "ST\_Period (Period)", pp. 3892

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that the ST\_Period simple type uses the XML Schema ST\_Period data type and supports a range 2–255.

These observations are incompatible with existing documents and should be updated to reflect such prior art.

**Background**

When defining a moving average trend line, the ST\_Period simple type is used to define the period of the trend line.

Existing documents contain trend lines with their periods defined such that they do not satisfy the documented restrictions. Such documents specify the period using the XML Schema unsignedInt data type and contain values larger than the specified maximum of 255.

**Solution Proposed by the Submitter:**

Define the ST\_Period simple type using the XML Schema unsignedInt data type and with an unbounded maximum value.

**Schema Change(s) Needed:** Yes, strict and transitional versions of dml-chart.xsd and dml-chart.rnc.

```
<xsd:simpleType name="ST_Period">
 <xsd:restriction base="xsd:unsignedBytexsd:unsignedInt">
 <xsd:minInclusive value="2"/>
 <xsd:maxInclusive value="255unbounded"/>
 </xsd:restriction>
</xsd:simpleType>
```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Editor needs to make corresponding changes to the narrative as well.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §21.2.3.33, “ST\_Period (Period)”, pp. 3892

This simple type specifies that its contents contain an integer greater than or equal to 2~~between 2 and 255~~.

This simple type's contents are a restriction of the W3C XML Schema unsignedIntByte datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 2.
- This simple type has an unbounded maximum value ~~of less than or equal to 255~~.

Part 1: §A.5.1, “Drawing ML - Charts”, pp. 4599, lines 493–498

```
<xsd:simpleType name="ST_Period">
 <xsd:restriction base="xsd:unsignedBytexsd:unsignedInt">
```

```
<xsd:minInclusive value="2"/>
<xsd:maxInclusive value="255unbounded" />
</xsd:restriction>
</xsd:simpleType>
```

Part 1: §B.5.1, “Drawing ML - Charts”, pp. 4886, lines 311–312

```
dchrt_ST_Period =
xsd:unsignedBytexsd:unsignedInt { minInclusive = "2" maxInclusive = "255" [A1] }
```

# 19. DR 09-0004 — SML, Charts: Incomplete enumeration definition for ST\_MarkerStyle

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Charts: Incomplete enumeration definition for ST\_MarkerStyle

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-004

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.3.27, “ST\_MarkerStyle (Marker Style)”, pp. 3888

**Related DR(s):** none

**Nature of the Defect:**

**Defect Summary**

The standard states that ST\_MarkerStyle is defined as an enumeration of a set of supported marker styles.

The defined set of supported marker styles is incomplete as it fails to include all marker styles in use with existing documents and should be updated to reflect such prior art.

**Background**

It is often useful to emphasize data points in a chart. This emphasis is called a marker. Markers can be styled to take the form of, for example, a diamond shape or a square shape. The style of a marker can

also be specified such that the application can determine the style to be used. Such a specification is called “auto”.

Existing documents contain marker styles specified as “auto”.

**Solution Proposed by the Submitter:**

Add a value of “auto” to the ST\_MarkerStyle simple type’s enumeration.

**Schema Change(s) Needed:** Yes, strict and transitional versions of dml-chart.xsd and dml-chart.rnc.

```

<xsd:simpleType name="ST_MarkerStyle">
 <xsd:restriction base="xsd:string">
 <xsd:enumeration value="circle"/>
 <xsd:enumeration value="dash"/>
 <xsd:enumeration value="diamond"/>
 <xsd:enumeration value="dot"/>
 <xsd:enumeration value="none"/>
 <xsd:enumeration value="picture"/>
 <xsd:enumeration value="plus"/>
 <xsd:enumeration value="square"/>
 <xsd:enumeration value="star"/>
 <xsd:enumeration value="triangle"/>
 <xsd:enumeration value="x"/>
 <xsd:enumeration value="auto"/>
 </xsd:restriction>
</xsd:simpleType>

```

**Editor’s Response:**

**2009-01-28 Okinawa meeting:**

A potential alternate solution is that if this attribute is optional make the default value “auto”. However, it appears that this attribute is required, in which case, not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §21.2.3.33, “ST\_Period (Period)”, pp. 3889

| Enumeration Value           | Description                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------|
| <a href="#">auto (Auto)</a> | <a href="#">Specifies an application-specific marker shall be drawn at each data point.</a> |
| circle (Circle)             | Specifies a circle shall be drawn at each data point.                                       |

Part 1: §A.5.1, “Drawing ML - Charts”, pp. 4598, lines 424–438

```
<xsd:simpleType name="ST_MarkerStyle">
 <xsd:restriction base="xsd:string">
 <xsd:enumeration value="circle"/>
 ...
 <xsd:enumeration value="x"/>
 <xsd:enumeration value="auto"/>
 </xsd:restriction>
```

Part 1: §B.5.1, “Drawing ML - Charts”, pp. 4885–4886, lines 261–272

```
dchrt_ST_MarkerStyle =
 string "circle"
 ...
 | string "x"
 | string "auto"
```

## 20. DR 09-0005 — SML, Charts: Incorrect measurement unit/range restriction in ST\_Perspective

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Charts: Incorrect measurement unit and range restriction in ST\_Perspective

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-005

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.3.34, “ST\_Perspective (Perspective)”, pp. 3892

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard provides contradictory information regarding the allowed range for the ST\_Perspective simple type:

“This simple type specifies that its contents contain an integer between 0 and 100, ...”, and

“This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 240.”

The standard also states that the ST\_Perspective simple type represents a percentage.

The contradictory definition of the range restriction and the representation unit of ST\_Perspective is unclear and incompatible with existing documents. It should be updated for clarity and to reflect such prior art.

### **Background**

In order to visualize a chart in 3 dimensions, a perspective angle needs to be defined.

Existing documents contain charts with perspectives defined using one-half degrees as their unit of measurement, and they contain measurements in the range 0–240 one-half degrees.

### **Solution Proposed by the Submitter:**

Change ST\_Perspective simple type's unit of measurement to be one-half degree with a supported range from 0–240 one-half degrees.

**Schema Change(s) Needed:** No

### **Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

As this is a conflict, this is a defect.

#### **2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §21.2.3.34, "ST\_Perspective (Perspective)", pp. 3892

This simple type specifies that its contents contain an integer between 0 and 240~~100~~, whose unit is one-half degrees~~contents are a percentage~~.

## 21. DR 09-0006 — SML, Charts: Incorrect data type in ST\_Skip

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Charts: Incorrect data type in ST\_Skip

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-006

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.3.44, “ST\_Skip (Skip)”, pp. 3897

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that the ST\_Skip simple type is defined using the XML Schema unsignedShort data type.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

When defining a chart it is often necessary to skip rendering tick labels or tick marks in order to adequately display the chart within the space provided. The ST\_Skip simple type is used to declare how many tick labels or tick marks, should be skipped for a given category or series axis.

Existing documents declare the number of skipped tick labels or tick marks using the XML Schema unsignedInt data type.

**Solution Proposed by the Submitter:**

Change the ST\_Skip simple type to use the XML Schema unsignedInt data type.

**Schema Change(s) Needed:** Yes, strict and transitional versions of dml-chart.xsd and dml-chart.rnc.

```
<xsd:simpleType name="ST_Skip">
 <xsd:restriction base="xsd:unsignedShortxsd:unsignedInt">
 <xsd:minInclusive value="1"/>
 </xsd:restriction>
</xsd:simpleType>
```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §21.2.3.44, “ST\_Skip (Skip)”, pp. 3897

This simple type's contents are a restriction of the W3C XML Schema unsignedIntShort datatype.

Part 1: §A.5.1, “Drawing ML - Charts”, pp. 4609, lines 1024–1028

```
<xsd:simpleType name="ST_Skip">
 <xsd:restriction base="xsd:unsignedIntShort">
 <xsd:minInclusive value="1"/>
 </xsd:restriction>
</xsd:simpleType>
```

Part 1: §B.5.1, “Drawing ML - Charts”, pp. 4892, lines 652

```
dchrt_ST_Skip = xsd:unsignedIntShort { minInclusive = "1" }
```

## 22. DR 09-0007 — SML: Incorrect range for Precision value space

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Incorrect range for Precision value space

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-008

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.17.5.2, “Precision”, pp. 2296

**Related DR(s):** none

### **Nature of the Defect:**

The standard states that “The value space consists of the values  $m \times 2^n$ , where  $m$  is an integer whose absolute value is less than  $2^{53}$ , and  $n$  is an integer between -1075 and 970, inclusive.”

This is incompatible with existing documents and should be updated to reflect such prior art.

### **Solution Proposed by the Submitter:**

Define the value space as follows:

The value space consists of the values  $(-1)^s * m * 2^n$ , where  $s$  is 0 or 1,  $m$  is an integer greater than or equal to 0 and less than  $2^{53}$ , and  $n$  is an integer between -1074 and 971, inclusive.

**Schema Change(s) Needed:** none

### **Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution.

The solution to this DR should be published in an Amendment.

The exact changes are as follows:

Part 1: §18.17.5.2, "Precision", pp. 2296

The *value space* consists of the values  $(-1)^s \times m \times 2^n$ , where  $s$  is 0 or 1, where  $m$  is an integer greater than or equal to 0 and whose absolute value is less than  $2^{53}$ , and  $n$  is an integer between -107<sup>45</sup> and 97<sup>10</sup>, inclusive.

## 23. DR 09-0008 — WML, Mail Merge: Incorrect definition of uniqueTag

**Status:** Further Consideration Required~~Closed; will be incorporated in COR1~~

**Subject:** WML, Mail Merge: Incorrect definition of uniqueTag

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-009

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §17.14.35, “uniqueTag (Unique Value for Record)”, pp. 1088

**Related DR(s):** none

**Nature of the Defect:**

### Defect Summary

The standard states that the uniqueTag element in the CT\_RecipientData complex type contains a text node defined by the base XML Schema base64Binary datatype.

This definition is incompatible with existing documents and should be updated to reflect such prior art (as well as to conform to the WordprocessingML design goal of storing only user text in text nodes).

### Background

This element defines the unique key for a single data record within a data source used for a mail merge operation, allowing that record to be explicitly included/excluded from the mail merge.

Existing documents store this information using a val attribute on the uniqueTag element in the CT\_RecipientData complex type

**Solution Proposed by the Submitter:**

Define the uniqueTag element with a val attribute of type XML Schema base64Binary.

**Schema Change(s) Needed:** Yes, both strict and relaxed versions of wml.xsd and wml.rnc.

```

<xsd:complexType name="CT_RecipientData">
 <xsd:sequence>
 <xsd:element name="active" type="CT_OnOff" minOccurs="0"/>
 <xsd:element name="column" type="CT_DecimalNumber" minOccurs="1"/>
 <xsd:element name="uniqueTag" type="xsd:base64Binary<u>CT_Base64Binary</u>">
 minOccurs="1"/>
 </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="CT_Base64Binary">
 <xsd:attribute name="val" type="xsd:base64Binary" use="required">
 </xsd:attribute>
</xsd:complexType>

```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

This issue is not related to preserving old binary formats.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in an Amendment.

The exact changes are as follows:

Part 1: §17.14.35, “uniqueTag (Unique Value for Record)”, pp. 1088–1089

The possible values for this element are defined by the [CT\\_Base64Binary](#)[W3C XML Schema base64Binary](#) datatype.

Part 1: §A.1, “WordprocessingML”, pp. 4392, lines 2500–2506

```

<xsd:complexType name="CT_RecipientData">
 <xsd:sequence>
 <xsd:element name="active" type="CT_OnOff" minOccurs="0"/>

```

```

<xsd:element name="column" type="CT_DecimalNumber" minOccurs="1"/>
<xsd:element name="uniqueTag" type="xsd:base64BinaryCT_Base64Binary" minOccurs="1"/>
</xsd:sequence>
</xsd:complexType>

<xsd:complexType name="CT_Base64Binary">
<xsd:attribute name="val" type="xsd:base64Binary" use="required">
</xsd:attribute>
</xsd:complexType>

```

Part 1: §B.1, “WordprocessingML”, pp. 4392, lines 2500–2506

```
w_CT_RecipientData =
 element active { w_CT_OnOff }?,
 element column { w_CT_DecimalNumber },
 element uniqueTag { w_CT_Base64Binaryxsd:base64Binary }
```

Relax NG equivalent of new type CT\_Base64Binary goes here.[\[A2\]](#)

```
w_CT_Base64Binary =
```

## 24. DR 09-0009 — SML, Pivot Tables: Incorrect description of calculatedMember

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Pivot Tables: Incorrect description of calculatedMember

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-010

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.10.1.10, “calculatedMember (Calculated Member)”, pp. 2030

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that calculated items in a PivotTable cannot be added:

Represents a calculated OLAP hierarchy. A calculated member is a member of an OLAP-based PivotTable whose value is calculated on the OLAP server. For PivotTables that are created from OLAP cubes the summarized values are precalculated on the OLAP server before the SpreadsheetML application displays the results. These fields appear in the PivotTable field list but cannot be changed from within the PivotTable. You cannot change the summary function used to calculate data fields or subtotals, or add calculated items.

This is incompatible with existing documents and should be updated to reflect such prior art.

The noun “you” is also ambiguous and should be clarified.

**Solution Proposed by the Submitter:**

The standard should be updated to remove this restriction, as well as clarify who “you” is, by the following replacement:

~~Represents a calculated OLAP hierarchy. A calculated member is a member of an OLAP-based PivotTable whose value is calculated on the OLAP server. For PivotTables that are created from OLAP cubes the summarized values are precalculated on the OLAP server before the SpreadsheetML application displays the results. These fields appear in the PivotTable field list but cannot be changed from within the PivotTable. You cannot change the summary function used to calculate data fields or subtotals, or add calculated items.~~

A calculated member is a member in an OLAP hierarchy for which the value is calculated by an OLAP server using a Multidimensional Expressions (MDX) expression. For PivotTables that are created from OLAP cubes the summarized values are calculated by an OLAP server before the SpreadsheetML application displays the results. In OLAP PivotTables, the consuming application cannot change the summary function used to calculate totals and subtotals.

**Schema Change(s) Needed:** none

**Editor’s Response:**

**2009-01-28 Okinawa meeting:**

Although this is not an internal conflict in the standard, it is ambiguous in the context of current OLAP usage.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §18.10.1.10, “calculatedMember (Calculated Member)”, pp. 2030

~~Represents a calculated OLAP hierarchy. A calculated member is a member of an OLAP-based PivotTable whose value is calculated on the OLAP server. For PivotTables that are created from OLAP cubes the summarized values are precalculated on the OLAP server before the SpreadsheetML application displays the results. These fields appear in the PivotTable field list but cannot be changed from within the PivotTable. You cannot change the summary function used to calculate data fields or subtotals, or add calculated items.~~

A calculated member is a member in an OLAP hierarchy for which the value is calculated by an OLAP server using a Multidimensional Expressions (MDX) expression. For PivotTables that are created from

OLAP cubes the summarized values are calculated by an OLAP server before the SpreadsheetML application displays the results. In OLAP PivotTables, the consuming application cannot change the summary function used to calculate totals and subtotals.

## 25. DR 09-0010 — SML, Workbook: Extensibility broken for externalLink

**Status:** [Further Consideration Required](#) ~~Closed; will be incorporated in COR1~~

**Subject:** SML, Workbook: Extensibility broken for externalLink

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-011

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.14.8, “externalLink (External Reference)”, pp. 2248

**Related DR(s):** none

**Nature of the Defect:**

### Summary

The standard states that the extLst child element is mutually exclusive with the externalBook, ddeLink and oleLink child elements.

This will limit the future proofing of the externalLink element as it directly forces a trade-off between extensibility (extLst) and content (externalBook, ddeLink and oleLink).

The intent of the extList child element is to add data in a backward compatible manner to the externalLink element when it is used in external book, DDE link and OLE link scenarios.

### Solution Proposed by the Submitter:

The standard should be updated such that the externalBook, ddeLink and oleLink child elements are not mutually exclusive with the extLst child element.

**Schema Change(s) Needed:** Yes, both strict and relaxed versions of sml.xsd and sml.rnc.

```
<xsd:complexType name="CT_ExternalLink">
 <xsd:choice>
 <xsd:element name="externalBook" type="CT_ExternalBook"
 minOccurs="0" maxOccurs="1"/>
 <xsd:element name="ddeLink" type="CT_DdeLink" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="oleLink" type="CT_OleLink" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
 </xsd:choice>
 <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
</xsd:complexType>
```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

This looks like a defect as it contradicts the intent of extLists.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §A.2, "SpreadsheetML", pp. 4482, lines 3822–3829

```
<xsd:complexType name="CT_ExternalLink">
 <xsd:choice>
 <xsd:element name="externalBook" type="CT_ExternalBook"
 minOccurs="0" maxOccurs="1"/>
 <xsd:element name="ddeLink" type="CT_DdeLink" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="oleLink" type="CT_OleLink" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
 </xsd:choice>
 <xsd:element name="extLst" minOccurs="0" type="CT_ExtensionList"/>
</xsd:complexType>
```

Part 1: §B.2, “SpreadsheetML”, pp. 4789, lines 4056–4060

```
sml_Ct_ExternalLink =
 element externalBook { sml_Ct_ExternalBook }?
 | element ddeLink { sml_Ct_DdeLink }?
 | element oleLink { sml_Ct_OleLink }?
 | element extLst { sml_Ct_ExtensionList }? [A3]
```

## 26. DR 09-0011 — Shared MLs, Math: Incomplete list of valid child elements for Math objects

**Status:** [Further Consideration Required](#) ~~Closed; will be incorporated in COR1~~

**Subject:** Shared MLs, Math: Incomplete list of valid child elements for Math objects

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-012

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

### IS 29500 Reference(s):

Part 1: §17.5.1.3, “customXml (Inline-Level Custom XML Element)”, pp. 534

Part 1: §17.5.1.9, “smartTag (Inline-Level Smart Tag)”, pp. 546

Part 1: §17.5.2.31, “sdt (Inline-Level Structured Document Tag)”, pp. 590

Part 1: §17.16.19, “fldSimple (Simple Field)”, pp. 1417

Part 1: §17.16.22, “hyperlink (Hyperlink)”, pp. 1423

Part 1: §22.1.2.26, “deg (Degree)”, pp. 4105

Part 1: §22.1.2.28, “den (Denominator)”, pp. 4108

Part 1: §22.1.2.32, “e (Element (Argument))”, pp. 4113

Part 1: §22.1.2.37, “fName (Function Name)”, pp. 4122

Part 1: §22.1.2.52, “lim (Limit)”, pp. 4137

Part 1: §22.1.2.75, “num (Numerator)”, pp. 4170

Part 1: §22.1.2.77, “oMath (Office Math)”, pp. 4173

Part 1: §22.1.2.112, “sub (Subscript (Pre-Sub-Superscript))”, pp. 4208

Part 1: §22.1.2.114, “sup (Superscript (Superscript object))”, pp. 4211

**Related DR(s):** none

#### **Nature of the Defect:**

##### **Summary**

The standard provides a list of the child elements that are allowed within elements defining objects in Office Open XML Math.

The corresponding schema definition for these elements fails to include several common WordprocessingML objects that are used within Office Open XML Math in existing documents, and should be updated to reflect such prior art.

##### **Background**

The elements in question enable the use of common WordprocessingML constructs such as custom XML markup, fields, smart tags, structured document tags, and hyperlinks within Math elements.

##### **Solution Proposed by the Submitter:**

The standard should be updated to include the following parent elements for the customXml, fldSimple, hyperlink, sdt, and smartTag elements:

[deg \(§22.1.2.26\)](#); [den \(§22.1.2.28\)](#); [e \(§22.1.2.32\)](#); [fName \(§22.1.2.37\)](#); [lim \(§22.1.2.52\)](#); [num \(§22.1.2.75\)](#); [oMath \(§22.1.2.77\)](#); [sub \(§22.1.2.112\)](#); [sup \(§22.1.2.114\)](#)

The following child elements should be listed for the deg, den, e, fName, lim, num, oMath, sub, and sup elements:

|                                                                    |                                   |
|--------------------------------------------------------------------|-----------------------------------|
| <u><a href="#">customXml (Inline-Level Custom XML Element)</a></u> | <u><a href="#">§17.5.1.3</a></u>  |
| <u><a href="#">fldSimple (Simple Field)</a></u>                    | <u><a href="#">§17.16.19</a></u>  |
| <u><a href="#">hyperlink (Hyperlink)</a></u>                       | <u><a href="#">§17.16.22</a></u>  |
| <u><a href="#">sdt (Inline-Level Structured Document Tag)</a></u>  | <u><a href="#">§17.5.2.31</a></u> |
| <u><a href="#">smartTag (Inline-Level Smart Tag)</a></u>           | <u><a href="#">§17.5.1.9</a></u>  |

**Schema Change(s) Needed:** Yes

In shared-math.xsd (and corresponding RELAX NG schema):

```
<xsd:group name="EG_OMathElements">
 <xsd:choice>
 <xsd:group ref="EG_OMathMathElements"/>
 <xsd:group ref="w:EG_RunLevelElts w:EG_PContentMath"/>
 </xsd:choice>
</xsd:group>
```

Add the corresponding new groups to wml.xsd (and corresponding RELAX NG change):

```
<xsd:group name="EG_PContentMath">
 <xsd:choice>
 <xsd:group ref="EG_PContentBase" minOccurs="0" maxOccurs="unbounded" />
 <xsd:group ref="EG_ContentRunContentBase" minOccurs="0"
maxOccurs="unbounded" />
 </xsd:choice>
</xsd:group>
<xsd:group name="EG_PContentBase">
 <xsd:choice>
 <xsd:element name="customXml" type="CT_CustomXmlRun"/>
 <xsd:element name="fldSimple" type="CT_SimpleField" minOccurs="0"
maxOccurs="unbounded"/>
 <xsd:element name="hyperlink" type="CT_Hyperlink"/>
 </xsd:choice>
</xsd:group>
<xsd:group name="EG_ContentRunContentBase">
 <xsd:choice>
 <xsd:element name="smartTag" type="CT_SmartTagRun"/>
 <xsd:element name="sdt" type="CT_SdtRun"/>
 <xsd:group ref="EG_RunLevelElts" minOccurs="0" maxOccurs="unbounded" />
 </xsd:choice>
</xsd:group>
```

**Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

Including the parent elements is editorial. The proposal to change the schema needs more discussion.

#### **2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

Note that this problem is not related to binary file migration.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

**Part 1, §17.5.1.3 customXml, “Inline-Level Custom XML Element”, pp. 534**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; del (\$xx); <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (§22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (§22.1.2.75)</a> ; oMath ( <a href="#">§22.1.2.77</a> ); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Part 1, §17.5.1.9 smartTag, “Inline-Level Smart Tag”, pp. 547

**Parent Elements**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; del (\$xx); <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (§22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (§22.1.2.75)</a> ; oMath ( <a href="#">§22.1.2.77</a> ); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Part 1, §17.5.2.31 sdt, “Inline-Level Structured Document Tag”, pp. 590

**Parent Elements**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; del (\$xx); <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); ins (\$xx); <a href="#">lim (§22.1.2.52)</a> ; moveFrom (\$xx); moveTo (\$xx); <a href="#">num (§22.1.2.75)</a> ; oMath ( <a href="#">§22.1.2.77</a> ); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Part 1, §17.16.19 fldSimple, “Simple Field”, pp. 1418

**Parent Elements**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); <a href="#">lim (§22.1.2.52)</a> ; num ( <a href="#">§22.1.2.75</a> ); oMath ( <a href="#">§22.1.2.77</a> ); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Part 1, §17.16.22 hyperlink, “Hyperlink”, pp. 1424

**Parent Elements**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bdo (\$xx); customXml (\$xx); <a href="#">deg (§22.1.2.26)</a> ; <a href="#">den (§22.1.2.28)</a> ; dir (\$xx); <a href="#">e (§22.1.2.32)</a> ; fldSimple (\$xx); <a href="#">fName (§22.1.2.37)</a> ; hyperlink (\$xx); <a href="#">lim (§22.1.2.52)</a> ; num ( <a href="#">§22.1.2.75</a> ); oMath ( <a href="#">§22.1.2.77</a> ); p (\$xx); sdtContent (\$xx); smartTag (\$xx); <a href="#">sub (§22.1.2.112)</a> ; <a href="#">sup (§22.1.2.114)</a> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Part 1, §22.1.2.26 deg (Degree), pp. 4104–4107

| Child Elements | Subclause |
|----------------|-----------|
|----------------|-----------|

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.28 den (Denominator), pp. 4108–4110

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.32 e (Element), pp. 4115–4117

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.37 fName (Function Name), pp. 4123–4125

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.52 lim (Limit), pp. 4138–4139

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.75 num (Numerator), pp. 4171–4172

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.77 oMath (Office Math), pp. 4174–4176

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.112 sub (Subscript (Pre-Sub-Superscript)), pp. 4209–4210

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1, §22.1.2.114 sup (Superscript (Superscript object)), pp. 4212–4213

| Child Elements                                              | Subclause                  |
|-------------------------------------------------------------|----------------------------|
| <a href="#">customXml (Inline-Level Custom XML Element)</a> | <a href="#">§17.5.1.3</a>  |
| <a href="#">fldSimple (Simple Field)</a>                    | <a href="#">§17.16.19</a>  |
| <a href="#">hyperlink (Hyperlink)</a>                       | <a href="#">§17.16.22</a>  |
| <a href="#">sdt (Inline-Level Structured Document Tag)</a>  | <a href="#">§17.5.2.31</a> |
| <a href="#">smartTag (Inline-Level Smart Tag)</a>           | <a href="#">§17.5.1.9</a>  |

Part 1: §A.6.1, “Math”, pp. 4650, lines 488–493

```
<xsd:group name="EG_OMathElements">
 <xsd:choice>
 <xsd:group ref="EG_OMathMathElements"/>
 <xsd:group ref="w:EG_RunLevelElts w:EG_PContentMath"/>
 </xsd:choice>
</xsd:group>
```

Part 1: §A.1, “WordprocessingML”

```
<xsd:group name="EG_PContentMath">
 <xsd:choice>
 <xsd:group ref="EG_PContentBase" minOccurs="0" maxOccurs="unbounded" />
 <xsd:group ref="EG_ContentRunContentBase" minOccurs="0"
maxOccurs="unbounded" />
 </xsd:choice>
</xsd:group>
<xsd:group name="EG_PContentBase">
 <xsd:choice>
 <xsd:element name="customXml" type="CT_CustomXmlRun"/>
 <xsd:element name="fldSimple" type="CT_SimpleField" minOccurs="0"
maxOccurs="unbounded"/>
 <xsd:element name="hyperlink" type="CT_Hyperlink"/>
 </xsd:choice>
</xsd:group>
<xsd:group name="EG_ContentRunContentBase">
 <xsd:choice>
 <xsd:element name="smartTag" type="CT_SmartTagRun"/>
 <xsd:element name="sdt" type="CT_SdtRun"/>
 <xsd:group ref="EG_RunLevelElts" minOccurs="0" maxOccurs="unbounded" />
 </xsd:choice>
</xsd:group>
```

Part 1: §B.6.1, “Math”, pp. 4920, line 240

~~m\_EG\_OMathElements = m\_EG\_OMathMathElements | w\_EG\_RunLevelElts w\_EG\_PContentMath~~

Part 1: §B.1, “WordprocessingML”

The Relax NG equivalent of the new groups above goes here[A4].

## 27. DR 09-0012 — Parts, Font Part: Incomplete definition for Font Part

**Status:** Further Consideration Required

**Subject:** Parts, Font Part: Incomplete definition for Font Part

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-013

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §15.2.13, “Font Part”, pp. 159

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard declares three content types for the Font Part, yet only defines the contents for the first two content types:

- application/x-fontdata
- application/x-font-ttf

The standard fails to define the contents for the third content type:

- application/vnd.openxmlformats officedocument.obfuscatedFont

This content type is used within existing Office Open XML documents and should be properly defined by the standard.

## Background

The content type in question allows applications to distinguish between TrueType/OpenType fonts included in Office Open XML documents without obfuscation, and those obfuscated using the algorithm defined by the Font Embedding (§17.8.1) subclause within WordprocessingML.

Existing documents use the `obfuscatedFont` content type to specify that the font in question has been obfuscated and must be handled according to the rules in the section referenced above.

### Solution Proposed by the Submitter:

Include a definition of the third content type: `application/vnd.openxmlformats-officedocument.obfuscatedFont`. Specifically, add the following to the list on pp. 160 to define this content type:

[application/vnd.openxmlformats-officedocument.obfuscatedFont specifies that the font is stored in the TrueType or OpenType format and is obfuscated using the algorithm specified by Font Embedding \(§17.8.1\). Only packages of type WordprocessingML are permitted to reference this content type.](#)

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability. Binary documents use obfuscated fonts. If this proposal is accepted, we'll need to register the additional media type with IANA.

**2009-03-24 Prague meeting:**

Postpone until WG2 can weigh in on this.

The solution to this DR should be published in a Technical Corrigendum.

## 28. DR 09-0013 — SML: Incorrect restriction on externalData

**Status:** Further Consideration Required

**Subject:** SML: Incorrect restriction on externalData

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-014

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §21.2.2.63, “externalData (External Data Relationship)”, pp. 3790

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard declares a single valid relationship type for this element via the id attribute:

[http://schemas.openxmlformats.org/officeDocument/2006/relationships\\_package](http://schemas.openxmlformats.org/officeDocument/2006/relationships_package)

This is incompatible with existing documents and should be updated to reflect such prior art.

**Solution Proposed by the Submitter:**

Add the following relationship type to the list of valid relationship types for this element via the id attribute:

[http://schemas.openxmlformats.org/officeDocument/2006/relationships\\_oleObject](http://schemas.openxmlformats.org/officeDocument/2006/relationships_oleObject)

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Postpone

## 29. DR 09-0014 — SML: Incorrect restriction on the Name Representation

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Incorrect restriction on the Name Representation

**Qualifier:** Editorial defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-015

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.17.6.5, “Name Representation”, pp. 2300

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that named cells, or cell ranges, should be defined in the Worksheet part, implying that uniqueness is at the Worksheet part.

It is asserted that this is inconsistent with the intent of this element. Looking at the list of valid parent elements, we only see Workbook and not Worksheet. As such, there is a conflict between the intent implied in the XML and the prose as currently written.

**Solution Proposed by the Submitter:**

Correct the location as to where named cells, or cell ranges, need to be defined, as follows:

“These names shall be defined in the ~~Worksheet~~Workbook part’s XML ...”

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

This is editorial; make the text match the schema.

**2009-02-18 Shawn Villaron:**

*[Ed: The file "thinkfree-namedcell.xls" was attached to Shawn's email.]*

Not everyone was able to attend Okinawa last month and so I wanted to take some time today to write up a summary mail regarding this particular defect for your review. I've incorporated some of the feedback I received in Okinawa, so even for the folks who were able to attend that meeting, there is some new information contained herein.

As background information for this defect, it is important to remember that the intent of the IS 29500 standard was to fully encode existing binary documents, binary spreadsheets and binary presentations using XML. The latest document from Microsoft regarding these binary file formats can be found here:

<http://download.microsoft.com/download/2/4/8/24862317-78F0-4C4B-B355-C7B2C1D997DB/%5BMS-XLS%5D.pdf>

*[Ed: The URL that Shawn originally supplied was incorrect.]*

In that documentation, the structure in question is `l!l`.

The applicable documentation for this issue can be found in the spreadsheet documentation. In particular, we're addressing the encoding of record 218h which is defined on page 144 in the PDF version.

**DR-09-0014**

This issue deals with the scope of named cells within a spreadsheet.

Named cells are a common spreadsheet feature where one or more cells in a spreadsheet can be given a "friendly" name which makes it easier to reference those cells elsewhere in the spreadsheet.

For example, suppose you want to calculate the payment on a loan and you want to evaluate the impact that various interest rates would have on that payment. One way to do this would be to use a cell to represent the interest rate, name that cell `interestRate` and then use that name in the formula that calculates the payment. This way you could play with the value in the cell and not have to modify the actual formula to see the impact it has on the payment.

If we consider ThinkFree's Office Calc 3 implementation, the customer experience is pretty simple: select the cell that you will use for the interest rate and use the **Insert / Name / Define ...** menu. This will bring up a dialog that shows you any named cells found in the spreadsheet. In the dialog you can provide the name for the

selected cell(s). At this point, any time you want to refer to the contents of this cell, you can refer to it as “interestRate” as opposed to “A:B2”.

An important observation here is that the scope of the named cells is at the *workbook* level and not the *worksheet* level. Given that worksheets can refer to cells in other worksheets, the uniqueness of named cells needs to be scoped at the workbook level. Otherwise, there could be two different cell ranges with the same name causing confusion as to which named cell(s) value(s) should be used. Clearly this would be a problem for data integrity and interoperability.

Other vendors’ products such as OpenOffice.org Calc 3, Corel Quattro Pro X4 and Microsoft’s Excel 2003 all have similar implementations: they support the ability to name cells, they require workbook-level uniqueness and they express named cells using the same manner described in the binary file format document above. Because these four vendors have chosen similar implementations, spreadsheets with named cells can be successfully passed between these vendors’ products.

I’ve attached a sample file generated from Think Free’s Office Calc 3 product in case folks would like to experiment with this functionality and the associated interop scenarios themselves. Naturally there are some bugs in the vendors’ implementations, but you can take the attached Think Free file and open it up successfully in the other implementations. The spreadsheets open, the named cells are persisted and the function which consumes the named cells continues to work as expected.

Additionally, Apple’s iWorks ’09 Numbers can consume files generated from such implementations and make use of those named cells. While they have similar functionality to named cells, I would not go so far as to say they have native support for authoring named cells ( I can go into more detail if anyone cares ).

If we look at the IS 29500 standard, the prose states the following ( *italics mine* ):

#### 18.17.6.5 Name Representation

A formula can contain one or more names. These names shall be defined in the *Worksheet* part’s XML with each being the subject of a *definedName* element, inside a *definedNames* element.

Not only does this conflict with existing binary spreadsheets, it also conflicts with the intent of the schema. The only valid parent element for the *definedNames* element is the *workbook* element. I interpret this such that the intent of the standard was to match the existing binary spreadsheets’ design and scope the uniqueness of named cells to the *workbook* and not the *worksheet*.

Given that the standard’s prose conflicts with the standard’s schema, that the industry has a common implementation of this that successfully enables interoperability through the exchange of binary spreadsheets and that the vendors’ implementation is consistent with the binary spreadsheet documentation, I would recommend we change the prose to scope the uniqueness of named cells to the *workbook*. The updated text would look as follows ( *italics* to emphasize changed text):

#### 18.17.6.5 Name Representation

A formula can contain one or more names. These names shall be defined in the *Workbook* part's XML with each being the subject of a `definedName` element, inside a `definedNames` element.

**2009-02-22 MURATA Makoto:**

First, I agree that this is a real problem and has to be addressed. I intend to declare consensus about this in Prague if nobody raises reasonable doubts. WG4 members are requested to study this DR and prepare in advance.

Second, I agree that the schema does not allow us to specify the scope worksheet and that the prose does conflict with the schema. Thus, I am convinced that this is a defect and should be addressed by a DCOR rather than an AM. I also intend to declare consensus in Prague if there are no reasonable objections. WG4 members are requested to study this DR and prepare in advance.

**2009-03-24 Prague meeting:**

Agreed with the proposed change; closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §18.17.6.5, “Name Representation”, pp. 2300

A formula can contain one or more names. These names shall be defined in the *Worksheet**Workbook* part's XML with each being the subject of a `definedName` element, inside a `definedNames` element. ...

## 30. DR 09-0015 — SML: Incomplete list of error value constants and valid expression error values

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Incomplete list of error value constants and valid expression error values

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-016

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):**

Part 1: §18.17.2.1, “Constants”, pp. 2276

Part 1: §18.17.3, “Error values”, pp. 2291

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard defines a set of valid formula error constants, which is incomplete as it fails to include the #GETTING\_DATA error constant.

The standard defines a set of valid error values for expressions, which is incomplete as it fails to include the #GETTING\_DATA error.

This is incompatible with existing documents and should be updated to reflect such prior art.

## Background

Existing documents make use of the constant and the expression error when using external data.

### Solution Proposed by the Submitter:

Include the #GETTING\_DATA error constant in the list of formula error values:

```
error-constant=
 "#DIV/0! " | "#N/A" | "#NAME? " | "#NULL! " |
 "#NUM! " | "#REF! " | "#VALUE! " | "#GETTING DATA" ;
```

Include the #GETTING\_DATA error in the list of valid error values for expressions:

|                      |                                                                                                                                     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <u>#GETTING DATA</u> | Intended to indicate when a cell reference cannot be evaluated because the value for the cell has not been retrieved or calculated. |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------|

**Schema Change(s) Needed:** none

### Editor's Response:

#### 2009-01-28 Okinawa meeting:

Not addressing this will complicate interoperability. Binary documents use this.

#### 2009-03-24 Prague meeting:

Looks ok, but we need to see the difference between #N/A and #GETTING\_DATA as they appear to overlap.

Shawn reported that #N/A is returned when there is no result. #GETTING\_DATA is returned when you have requested data, but there is none now, but some might be coming (for example, when connected to an OLAP cube). Possibly add an example.

Rex to investigate implications of adding this constant (is\* functions, and such). Needs more work.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §18.17.2.1, “Constants”, pp. 2276

```
error-constant=
 "#DIV/0! " | "#N/A" | "#NAME? " | "#NULL! " |
 "#NUM! " | "#REF! " | "#VALUE! " | "#GETTING DATA" ;
```

Part 1: §18.17.3, “Error values”, pp. 2292

| Error Value                          | Reason for Occurrence                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...                                  | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <a href="#"><b>#GETTING_DATA</b></a> | <p><u>Intended to indicate when a cell reference cannot be evaluated because the value for the cell has not been retrieved or calculated. [Note: This can happen when connected to an OLAP cube. <i>end note</i>]</u></p> <p><u>This error constant differs from #N/A in that #GETTING DATA is used when there is an expectation that the value for the cell will eventually be available, whereas #N/A is used when there is no such expectation.</u></p> |

Part 1: §18.17.7.110, “ERROR.TYPE”, pp. 2429

| value                                | Return Value             |
|--------------------------------------|--------------------------|
| ...                                  |                          |
| #N/A                                 | 7                        |
| <a href="#"><b>#GETTING DATA</b></a> | <a href="#"><u>8</u></a> |
| Anything else                        | #N/A                     |

# 31. DR 09-0016 — SML, Formulas: Incorrect attribute name in Array Formulas

**Status:** Further Consideration Required~~Last Call~~

**Subject:** SML, Formulas: Incorrect attribute name in Array Formulas

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-018

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.17.6.3, “Array Formulas”, pp. 2298

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states that the attribute used to define the reference to which the formula applies is named r.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

Existing documents contain an attribute with name ref whose function is identical to the attribute r, which is in the schema for both transitional and strict modes. Hence this is a defect in the transitional schema by its omitting the attribute ref.

**Solution Proposed by the Submitter:**

Use the name ref for the ST\_CellRef in array formulas. Updates include those to prose, examples and schemas.

**Schema Change(s) Needed:** Yes, both strict and relaxed versions of sml.xsd and sml.rnc.

```

<xsd:complexType name="CT_CalcCell">
 <xsd:attribute name="rref" type="ST_CellRef" use="required"/>
 <xsd:attribute name="i" type="xsd:int" use="optional" default="0"/>
 <xsd:attribute name="s" type="xsd:boolean" use="optional"
 default="false"/>
 <xsd:attribute name="l" type="xsd:boolean" use="optional"
 default="false"/>
 <xsd:attribute name="t" type="xsd:boolean" use="optional"
 default="false"/>
 <xsd:attribute name="a" type="xsd:boolean" use="optional"
 default="false"/>
</xsd:complexType>
```

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Change the Background statement to “Existing documents contain an attribute with name ref whose function is identical to the attribute r, which is in the schema for both transitional and strict modes. Hence this is a defect in the transitional schema by its omitting the attribute ref.”

In the transitional schema, allow ref as a synonym for r, but only one or the other can be defined in any given instance. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 4: §10.6B, “Formulas”, pp. 186

#### 10.6B Formulas

##### 10.6B.1 Attribute synonym for c element (Part 1, §18.6.1)

The following additional attribute can be specified for a document of a transitional conformance class:

| <u>Attributes</u>                    | <u>Description</u>                                                                                                                           |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">ref (Cell Reference)</a> | An A-1 style reference to a cell.<br>The possible values for this attribute are defined by the ST_CellRef simple type<br>(Part 1, §18.18.7). |

[This attribute is semantically equivalent to r \(Part 1, §18.6.1\).](#)

[Only one or the other of r and ref can be defined in any given instance.](#)

Part 4: §A.2, “SpreadsheetML”, pp. 884, lines 264–271

```
<xsd:complexType name="CT_CalcCell">
 <xsd:attribute name="r" type="ST_CellRef" use="optionalrequired" />
 <xsd:attribute name="ref" type="ST_CellRef" use="optionalrequired" />
 ...
</xsd:complexType>
```

Part 4: §B.2, “SpreadsheetML”, pp. 1216, lines 218–219

```
sml_CalcCell =
 attribute r { sml_ST_CellRef },
 attribute ref { sml_ST_CellRef },
[A5] ...
```

## 32. DR 09-0017 — WML, Annotations: Inserted math control character missing valid child

**Status:** [Further Consideration Required](#) ~~Last Call~~

**Subject:** WML, Annotations: Inserted math control character missing valid child

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-019

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §17.13.5.16, “ins (Inserted Math Control Character)”, pp. 957

**Related DR(s):** [DR 09-0018](#) — Shared MLs, Math: Invalid child Previous Run Properties

**Nature of the Defect:**

**Defect Summary**

The standard states that the ins and del elements are mutually exclusive when present as a child element of the ctrlPr element (when storing revision information for a Math control character, such as a fraction bar).

However, this definition is incompatible with existing documents that store insertion and deletion data simultaneously for the same control character.

**Background**

When a range of text in a WordprocessingML document is inserted by one user, then subsequently deleted by another user (common in heavily revised documents), the revision data must store an insertion containing a deletion in order to be fully expressive.

This is done by allowing the del element optionally to appear within the ins element to store these precise conditions.

### **Solution Proposed by the Submitter:**

Allow the del element to be a valid child when a math control character is part of both a tracked insertion and tracked deletion in order to represent the condition mentioned above.

**Schema Change(s) Needed:** Yes, both strict and relaxed versions of wml.xsd and wml.rnc.

```

<xsd:group name="EG_RPrMath">
 <xsd:choice>
 <xsd:group ref="EG_RPr"/>
 <xsd:element name="ins" type="CT_RPrChangeCT_MathCtrlIns"/>
 <xsd:element name="del" type="CT_RPrChange"/>
 </xsd:choice>
</xsd:group>
<xsd:complexType name="CT_MathCtrlIns">
 <xsd:complexContent>
 <xsd:extension base="CT_TrackChange">
 <xsd:choice minOccurs="0">
 <xsd:element name="del" type="CT_RPrChange" minOccurs="1"/>
 <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
 </xsd:choice>
 </xsd:extension>
 </xsd:complexContent>
</xsd:complexType>

```

### **Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

Failure to fix this precludes implementers of WordprocessingML from supporting change tracking of Math objects.

Does this apply to the entire Math object or to individual elements within?

#### **2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §17.13.5.16, “ins (Inserted Math Control Character)”, pp. 957

[Note: The W3C XML Schema definition of this element’s content model ([CT\\_MathCtrlIns](#)[CT\\_RPrChange](#)) is located in §A.1. *end note*]

Part 1: §A.1, “WordprocessingML”, pp. 4378, lines 1780–1786

```
<xsd:group name="EG_RPrMath">
 <xsd:choice>
 <xsd:group ref="EG_RPr"/>
 <xsd:element name="ins" type="CT_RPrChangeCT_MathCtrlIns"/>
 <xsd:element name="del" type="CT_RPrChange"/>
 </xsd:choice>
</xsd:group>
<xsd:complexType name="CT_MathCtrlIns">
 <xsd:complexContent>
 <xsd:extension base="CT_TrackChange">
 <xsd:choice minOccurs="0">
 <xsd:element name="del" type="CT_RPrChange" minOccurs="1"/>
 <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
 </xsd:choice>
 </xsd:extension>
 </xsd:complexContent>
</xsd:complexType>
```

Part 1: §B.1, “WordprocessingML”, pp. 4688, lines 1134–1137

```
w_EG_RPrMath =
 w_EG_RPr
 | element ins { w_CT_RPrChange w CT_MathCtrlIns }
 | element del { w_CT_RPrChange }
w_CT_MathCtrlIns =
 ... |
```

# 33. [A6] DR 09-0018 — Shared MLs, Math: Invalid child Previous Run Properties

**Status:** Further Consideration Required~~Last Call~~

**Subject:** Shared MLs, Math: Previous Run Properties not valid child of deleted math control character

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-020

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §17.13.5.13, “del (Deleted Math Control Character)”, pp. 949

**Related DR(s):** DR 09-0017 — WML, Annotations: Inserted math control character missing valid child

**Nature of the Defect:**

**Summary**

The standard states that the rPr element stored within the del element is of type CT\_RPrOriginal, which means that this set of run properties is incapable of storing formatting revision information.

However, there exist existing documents that contain formatting revision information data for a deleted control character, which must be maintained.

**Background**

When formatting of a run is changed and that change is tracked, the original formatting information is typically stored beneath an rPrChange element within the parent rPr element. The CT\_RPrOriginal complex type does not permit the presence of an rPrChange element to store this information.

**Solution Proposed by the Submitter:**

Remove rPr (Previous Run Properties - §17.3.2.27) as a valid child, and replace it with rPr (Run Properties - §17.3.2.28), which includes the rPrChange element.

**Schema Change(s) Needed:** Yes, both strict and relaxed versions of wml.xsd and wml.rnc.

```

<xsd:group name="EG_RPrMath">
 <xsd:choice>
 <xsd:group ref="EG_RPr"/>
 <xsd:element name="ins" type="CT_RPrChange"/>
 <xsd:element name="del" type="CT_RPrChange CT_MathCtrlDel"/>
 </xsd:choice>
</xsd:group>
<xsd:complexType name="CT_MathCtrlDel">
 <xsd:complexContent>
 <xsd:extension base="CT_TrackChange">
 <xsd:choice minOccurs="0">
 <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
 </xsd:choice>
 </xsd:extension>
 </xsd:complexContent>
</xsd:complexType>

```

**Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

Failure to fix this precludes implementers of WordprocessingML from supporting change tracking of Math objects.

#### **2009-03-24 Prague meeting:**

Agreed with the proposed solution. Applies to Part 1 and 4 schemas.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §17.13.5.13, “del (Deleted Math Control Character)”, pp. 949

[Note: The W3C XML Schema definition of this element's content model ([CT\\_MathCtrlDel](#)[CT\\_RPrChange](#)) is located in §A.1. *end note*]

Part 1: §A.1, “WordprocessingML”, pp. 4378, lines 1780–1786

```

<xsd:group name="EG_RPrMath">
 <xsd:choice>

```

```

<xsd:group ref="EG_RPr"/>
<xsd:element name="ins" type="CT_RPrChange"/>
<xsd:element name="del" type="CT_RPrChange CT_MathCtrlDel"/>
</xsd:choice>
</xsd:group>
<xsd:complexType name="CT_MathCtrlDel">
 <xsd:complexContent>
 <xsd:extension base="CT_TrackChange">
 <xsd:choice minOccurs="0">
 <xsd:element name="rPr" type="CT_RPr" minOccurs="1"/>
 </xsd:choice>
 </xsd:extension>
 </xsd:complexContent>
</xsd:complexType>

```

Part 1: §B.1, “WordprocessingML”, pp. 4688, lines 1134–1137

```

w_EG_RPrMath =
 w_EG_RPr
 | element ins { w_CT_RPrChange }
 | element del { w_CT_RPrChange w_CT_MathCtrlDel }
w_CT_MathCtrlDel =
 ...

```

[A7]

## 34. DR 09-0019 — Shared MLs, Math: Invalid Child Previous Run Properties

**Status:** ~~Further Consideration Required~~ [Closed without action](#)

**Subject:** Shared MLs, Math: Previous Run Properties not valid child of inserted math control character

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-021

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §17.13.5.16, “ins (Inserted Math Control Character)”, pp. 957

**Related DR(s):** [DR 09-0017](#) — WML, Annotations: Inserted math control character missing valid child.  
[DR 09-0018](#) — Shared MLs, Math: Invalid child Previous Run Properties

### Nature of the Defect:

#### Summary

The standard states that the rPr element stored within the ins element is of type CT\_RPrOriginal, which means that this set of run properties is incapable of storing formatting revision information.

However, there exist existing documents which contain formatting revision information data for an inserted control character, which must be maintained.

#### Background

When formatting of a run is changed and that change is tracked, the original formatting information is typically stored beneath an rPrChange element within the parent rPr element. The CT\_RPrOriginal complex type does not permit the presence of an rPrChange element to store this information.

**Solution Proposed by the Submitter:**

Remove rPr (Previous Run Properties - §17.3.2.27) as a valid child, and replace it with rPr (Run Properties - §17.3.2.28), which includes the rPrChange element.

**Schema Change(s) Needed:** none

The type of the rPr element in the newly created CT\_MathCtrlIns complex type should be CT\_RPr, not CT\_RPrOriginal:

```
<xsd:complexType name="CT_MathCtrlIns">
 <xsd:complexContent>
 <xsd:extension base="CT_TrackChange">
 <xsd:choice minOccurs="0">
 <xsd:element name="del" type="CT_RPrChange" minOccurs="1"/>
 <xsd:element name="rPr" type="CT_RPrOriginal|CT_RPr" minOccurs="1"/>
 </xsd:choice>
 </xsd:extension>
 </xsd:complexContent>
</xsd:complexType>
```

**Editor's Response:**

**2009-03-24 Prague meeting:**

Appears to be resolved by 17 and 18 above. Shawn needs to check on this, however.

The solution to this DR should be published in a Technical Corrigendum.

**2009-05-24 Editor:**

[The resolution of this DR is subsumed by those for DR 09-0017 and DR 09-0018.](#)

## 35. DR 09-0020 — SML: Incorrect restriction on scenario

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Incorrect restriction on scenario

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-022

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.3.1.75, “scenario (Scenario)”, pp. 1853

**Related DR(s):** none

**Nature of the Defect:**

**Defect Summary**

The standard states that named scenarios should be defined in the Workbook part, implying that uniqueness is at the Workbook part.

It is asserted that this is inconsistent with the intent of this element. Looking at the list of valid parent elements, we only see Worksheet and not Workbook. As such, there is a conflict between the intent implied in the XML and the prose as currently written.

**Solution Proposed by the Submitter:**

Correct the location as to where named scenarios need to be defined:

“Scenario’s name (user input). Shall be unique for the ~~workbook~~worksheet.”

**Schema Change(s) Needed:** none

**Editor's Response:****2009-01-28 Okinawa meeting:**

This is a defect.

**2009-03-24 Prague meeting:**

Adopted the proposed solution. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §18.3.1.75, “scenario (Scenario)”, pp. 1854

| Attributes           | Description                                                                                                                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| name (Scenario Name) | <p>Scenario's name (user input). Shall be unique for the <a href="#">workbook</a><a href="#">worksheet</a>.</p> <p>The possible values for this attribute are defined by the ST_Xstring simple type (§22.9.2.19).</p> |

## 36. DR 09-0021 — SML, Pivot Tables: Incorrect restriction on item

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Pivot Tables: Incorrect restriction on item

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-023

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.10.1.45, “item (PivotTable Field Item)”, pp. 2069

**Related DR(s):** none

**Nature of the Defect:**

**Defect Summary**

The standard states that the x attribute (item index) for the item element applies only to non-OLAP PivotTables.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

Existing documents use the x attribute for both OLAP and non-OLAP PivotTables.

**Solution Proposed by the Submitter:**

Remove the non-OLAP restriction:

~~Applies only to non-OLAP PivotTables.~~

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Adopted the proposed solution. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §18.10.1.45, “item (PivotTable Field Item)”, pp. 2071

| Attributes     | Description                                                                                                                                                                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x (Item Index) | <p>Specifies the item index in pivotFields collection in the PivotCache. <i>Applies only non-OLAP PivotTables.</i></p> <p>[Example: ... end example]</p> <p>The possible values for this attribute are defined by the W3C XML Schema unsignedInt datatype.</p> |

## 37. DR 09-0022 — SML: Incomplete set of format symbols for numFmts

**Status:** Last Call

**Subject:** SML: Incomplete set of format symbols for numFmts

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-024

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §18.8.31, “numFmts (Number Formats)”, pp. 1972

**Related DR(s):** none

**Nature of the Defect:**

**Defect Summary**

The standard states does not include the fraction format symbol, “/”, in the list of valid format symbols for numFmts.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

Existing documents contain the fraction format symbol.

**Solution Proposed by the Submitter:**

Add the fraction format symbol, “/”, to the list of valid format symbols, as follows:

The fraction format symbol displays the number in the format of a fraction. It is interpreted as the fraction format symbol only when preceded and followed by a number symbol (0, #, and ?).

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution, but also update the table to include an entry for \ (Part 1, pp. 1984). Shawn to provide final text.

The solution to this DR should be published in a Technical Corrigendum.

**2009-04-22 Shawn Villaron:**

In Prague we had a discussion regarding this defect report which yielded consensus that we needed to address the missing case when the '/' symbol was used to indicate a fraction. The remaining action item was to provide the exact changes proposed. I propose the following changes.

Part 1, §18.8.31, Entitled "numFmts (Number Formats)"

|             |                                                                                                                                                                                                                                                                                                                                 |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \$-+/\space | Displays the symbol. If it is desired to display a character that differs from one of these symbols, precede the character with a backslash (\). Alternatively, enclose the character in quotation marks. [Example: If the number format is (000), and the value 12 is in the cell, the number (012) is displayed. end example] |
| L           | If this symbol is preceded and followed by a number symbol (0, #, and ?), it is interpreted as the fraction format symbol and will display the number in the format of a fraction. Otherwise, it is interpreted as the forward slash character and is displayed as such.                                                        |

In summary: we remove the '/' symbol from the row it current resides in and then add a dedicated row to this symbol, which addresses both use cases (literal symbol and fractional symbol).

**2009-04-30 Teleconference:**

Move to “Last Call”

The exact changes are as follows:

Part 1, §18.8.31, Entitled “numFmts (Number Formats)”, pp. 1974

| Format symbol                      | Description and result                                                                                                                                                                                                                                                                                                          |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \$-<br>+ <del>F</del> ()<br>:space | Displays the symbol. If it is desired to display a character that differs from one of these symbols, precede the character with a backslash (\). Alternatively, enclose the character in quotation marks. [Example: If the number format is (000), and the value 12 is in the cell, the number (012) is displayed. end example] |
| <u>L</u>                           | <u>If this symbol is preceded and followed by a number symbol (0, #, and ?), it is interpreted as the fraction format symbol and will display the number in the format of a fraction.</u><br><u>Otherwise, it is interpreted as the forward slash character and is displayed as such.</u>                                       |

## 38. DR 09-0023 — SML, Parts: Incorrect naming of Root Element for certain parts

**Status:** Closed; will be incorporated in AMD1.

**Subject:** SML, Parts: Incorrect naming of Root Element for certain parts

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-025

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §12.3, “Part Summary”, pp. 67

**Related DR(s):** none

**Nature of the Defect:**

### Summary

The standard states a set of root element names for each part in SpreadsheetML.

As defined in this set, the standard uses the following root element names:

| Part                         | Relationship Target of | Root Element      | Ref.    |
|------------------------------|------------------------|-------------------|---------|
| Custom XML Mappings          | Workbook               | mapInfo           | §12.3.6 |
| Dialogsheet                  | Workbook               | dialogSheet       | §12.3.7 |
| External Workbook References | Workbook               | externalReference | §12.3.9 |

|                               |                        |             |          |
|-------------------------------|------------------------|-------------|----------|
| Single Cell Table Definitions | Dialogsheet, Worksheet | singleCells | §12.3.19 |
|-------------------------------|------------------------|-------------|----------|

These entries are incompatible with existing documents and should be updated to reflect such prior art.

### Background

Existing documents use different root element names for these parts.

### Solution Proposed by the Submitter:

Use root element names that are found in existing documents:

| Part                          | Relationship Target of | Root Element                                              | Ref.     |
|-------------------------------|------------------------|-----------------------------------------------------------|----------|
| Custom XML Mappings           | Workbook               | <del>mapInfo</del> <a href="#">MapInfo</a>                | §12.3.6  |
| Dialogsheet                   | Workbook               | <del>dialogSheet</del> <a href="#">dialogsheets</a>       | §12.3.7  |
| External Workbook References  | Workbook               | <del>externalReference</del> <a href="#">externalLink</a> | §12.3.9  |
| Single Cell Table Definitions | Dialogsheet, Worksheet | <del>singleCells</del> <a href="#">singleXmlCells</a>     | §12.3.19 |

**Schema Change(s) Needed:** none

### Editor's Response:

#### 2009-01-28 Okinawa meeting:

Not addressing this will complicate interoperability.

#### 2009-03-24 Prague meeting:

Adopted the proposed solution.

Closed.

The solution to this DR should be published in an Amendment.

The exact changes are as follows:

Part 1: §12.3, "Part Summary", pp. 67–68

| <b>Part</b>                   | <b>Relationship Target of</b> | <b>Root Element</b>                                       | <b>Ref.</b> |
|-------------------------------|-------------------------------|-----------------------------------------------------------|-------------|
| Custom XML Mappings           | Workbook                      | <del>mapInfo</del> <a href="#">MapInfo</a>                | §xx         |
| Dialogsheet                   | Workbook                      | <del>dialogSheet</del> <a href="#">dialogsheets</a>       | §xx         |
| External Workbook References  | Workbook                      | <del>externalReference</del> <a href="#">externalLink</a> | §xx         |
| Single Cell Table Definitions | Dialogsheet, Worksheet        | <del>singleCells</del> <a href="#">singleXmlCells</a>     | §xx         |

## 39. DR 09-0024 — SML, Parts: Incomplete set of implicit relationships for Worksheet Part

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Parts: Incomplete set of implicit relationships for Worksheet Part

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-026

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §12.3.24, "Worksheet Part", pp. 99

**Related DR(s):** none

**Nature of the Defect:**

**Defect Summary**

The standard states an incomplete set of valid implicit relationships for the Worksheet Part. This set is missing the relationship to the Query Table Part as defined in §12.3.14.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

Existing documents contain implicit relationships between the Worksheet Part and the Query Table Part.

**Solution Proposed by the Submitter:**

Add the Query Table Part to the list of valid implicit relationships for the Worksheet Part.

**Schema Change(s) Needed:** none

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will likely result in implementations ignoring what the standard says in this regard.

**2009-03-24 Prague meeting:**

Agreed with the proposed solution.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1: §12.3.24, "Worksheet Part", pp. 101

A Worksheet part is permitted to have implicit relationships to the following parts defined by ISO/IEC 29500:

- Comments (§12.3.3)
- Pivot Table Definitions (§12.3.11)
- Printer Settings (§15.2.15)
- [Query Table Part \(§12.3.14\)](#)
- Single Cell Table Definitions (§12.3.19)
- Table Definition (§12.3.21)

## 40. DR 09-0025 — SML, Parts: Incorrect Root Namespace for the Styles Part

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Parts: Incorrect Root Namespace for the Styles Part

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-027

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

**IS 29500 Reference(s):** Part 1: §12.3.20, “Styles Part”, pp. 94

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The standard states an incorrect root namespace for the Style Part of a spreadsheet:

<http://schemas.openxmlformats.org/spreadsheetml/2006/mains>

The trailing “s” character is inconsistent with all other root namespaces for all other spreadsheet parts, and in fact, all other parts within the standard. It is asserted that the trailing “s” character is a typographical error.

This is incompatible with existing documents and should be updated to reflect such prior art.

**Background**

Existing documents contain Style Parts with root namespaces of this form:

<http://schemas.openxmlformats.org/spreadsheetml/2006/main>

**Solution Proposed by the Submitter:**

Remove the trailing “s” character:

<http://schemas.openxmlformats.org/spreadsheetml/2006/main>s

**Schema Change(s) Needed:** none

**Editor’s Response:**

**2009-01-28 Okinawa meeting:**

Not addressing this will complicate interoperability. As the narrative doesn’t match the schemas, this is a defect.

**2009-03-24 Prague meeting:**

Adopted the proposed solution. Closed.

The solution to this DR should be published in an Amendment.

The exact changes are as follows:

Part 1: §12.3.20, “Styles Part”, pp. 94

|                 |                                                                                                                                     |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Root Namespace: | <a href="http://schemas.openxmlformats.org/spreadsheetml/2006/main">http://schemas.openxmlformats.org/spreadsheetml/2006/main</a> s |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------|

# 41. DR 09-0026 — SML: xml:space attribute note declared in SpreadsheetML

**Status:** Further Consideration Required

**Subject:** SML: xml:space attribute note declared in SpreadsheetML

**Qualifier:** Technical defect

**Submitter:** Ecma TC45

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** Ecma-09-028

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-21

**Deadline for Response from Editor:** 2009-03-21

## IS 29500 Reference(s):

Part 1: §18.2.5 definedName (Defined Name), pp. 1715

Part 1: §18.3.1.38 evenFooter (Even pp. Footer), pp. 1802

Part 1: §18.3.1.29 evenHeader (Even pp. Header), pp. 1803

Part 1: §18.3.1.40 f (Formula), pp. 1805

Part 1: §18.3.1.41 firstFooter (First pp. Footer), pp. 1808

Part 1: §18.3.1.42 firstHeader (First pp. Header), pp. 1809

Part 1: §18.3.1.43 formula (Formula), pp. 1809

Part 1: §18.3.1.44 formula1 (Formula1), pp. 1809

Part 1: §18.3.1.45 formula2 (Formula2), pp. 1810

Part 1: §18.3.1.57 oddFooter (Odd pp. Footer), pp. 1823

Part 1: §18.3.1.58 oddHeader (Odd pp. Header), pp. 1823

Part 1: §18.3.1.96 v (Cell Value), pp. 1883

Part 1: §18.4.12 t (Text), pp. 1906

Part 1: §18.5.1.1 calculatedColumnFormula (Calculated Column Formula), pp. 1908

Part 1: §18.7.1 author (Author), pp. 1929

Part 1: §21.2.2.59 evenFooter (Even Footer), pp. 3788

Part 1: §21.2.2.60 evenHeader (Even Header), pp. 3789

Part 1: §21.2.2.66 firstFooter (First Footer), pp. 3792

Part 1: §21.2.2.67 firstHeader (First Header), pp. 3792

Part 1: §21.2.2.124 oddFooter (Odd Footer), pp. 3817

Part 1: §21.2.2.125 oddHeader (Odd Header), pp. 3818

Part 1: §22.6.2.5 author (Author), pp. 4269

**Related DR(s):** none

**Nature of the Defect:**

**Summary**

The above referenced elements are intended to capture customer data, which may or may not include white space (spaces, tabs and blank lines). In the context of customer data, such white space should be considered significant and that that intention needs to be signaled to the consuming application program.

The xml:space attribute, as defined in the XML 1.0 specification, is used to “signal an intention that in that element, white space should be preserved by applications”. The standard fails to declare the xml:space attribute for the above reference elements. Without declaring the xml:space attribute, there is no manner to signal to a consuming application program that such data should be considered significant and hence preserved. Without such a signal, there is a potential data loss scenario.

**Solution Proposed by the Submitter:**

The standard should be updated to declare the xml:space attribute as valid for the above referenced elements.

**Schema Change(s) Needed:** Yes

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

We need to examine the XML recommendation regarding the use of `xml:space`, in general, as well as in schemas.

**2009-03-01 MURATA Makoto:**

I was probably the only person in Okinawa who was opposed to the addition of `xml:space` as proposed. As an expert, I still think that this addition is not needed. `xml:space` is for generic XML tools such as XML browsers. Since SpreadsheetML documents are very unlikely to be displayed by generic XML tools, every OOXML application program can be hardcoded so that it preserves whitespace, when necessary.

Note that DocBook 5 application programs are required to preserve whitespace in the verbatim environment even when this attribute is not specified. Having said that, as a convener, I am inclined to close this issue rather quickly in Prague unless others also oppose to the addition of `xml:space`.

**2009-03-18 Jirka Kosek:**

Yes, the whole `xml:space` usage in OOXML is little bit perverse, but I think that `xml:space` should be added to SpreadsheetML to be aligned with WordprocessingML. (Actually I found this inconsistency myself long time ago, but I haven't yet time to review already submitted comments and only "fresh" issues.)

**2009-03-18 Alex Brown:**

In my view it would be marginally better, in a perfect world, not to use `xml:space` in 29500.

However, since it is used elsewhere in 29500 there is an argument for adding it here, so that usage is consistent across the different MLs.

Overall this is a question of taste and I agree with Murata-san we shouldn't dwell on it, as there are more substantive issues that await us!

**2009-03-24 Prague meeting:**

Agreed with the proposed solution.

See Shawn about getting some write-up w.r.t whitespace discussion. Is the problem as stated correct?

The solution to this DR should be published in a Technical Corrigendum.

## 42. DR 09-0027 — Shared Simple Types: Unnecessary text in description of ST\_String

**Status:** Last Call

**Subject:** Shared Simple Types: Unnecessary text in description of ST\_String

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00000

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §22.9.2.13, “ST\_String (String)”, pp. 4329

**Related DR(s):** none

### Nature of the Defect:

With the exception of the first and last sentence, this entire subclause is misguided, since context dependencies should not be described here. It is true that the semantics of text in ISO/IEC 29500 is sometimes dependent on parent or ancestor elements. However, such context dependencies have nothing to do with the datatype ST\_String, but are part of the element or attribute semantics.

### Solution Proposed by the Submitter:

Remove from §22.9.2.13 the second sentence and the example.

**Schema Change(s) Needed:** No

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

There were doubts about whether this is a DR. In any event, it's an editorial change. No decision was made.

**2009-04-30 Teleconference:**

See the resolution to DR-08-0014, which also resolves this DR. Move to "Last Call"

## 43. DR 09-0028 — WML, Custom XML and Smart Tags: Tighten data types

**Status:** Further Consideration Required

**Subject:** WML, Custom XML and Smart Tags: Tighten data types

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.5.1, “Custom XML and Smart Tags”, pp. 528

**Related DR(s):** none

### **Nature of the Defect:**

The attributes name, element, and uri are of the datatype ST\_String, which allows every string. The use of ST\_String is too loose, since namespace names are IRIs and element or attribute names are XML names without colons.

### **Solution Proposed by the Submitter:**

Use xsd:anyURI for the attribute uri, and use xsd:NCName for the attributes name and element.

**Schema Change(s) Needed:** Yes, transitional and strict versions of ??.

### **Editor's Response:**

#### **2009-01-28 Okinawa meeting:**

The situation could be improved by changing the schema, but this is not a defect, per se. No decision was made.

**2009-03-01 MURATA Makoto:**

This defect report proposes that xsd:NCName and xsd:anyURI be used rather than ST\_String for constraining permissible local names and namespace names, respectively. But what does OOXML allow as local names and permissible names? The answer depends on the version or edition of the underlying XML specification. XML 1.0 (up to the fourth editions), XML 1.1, and XML 1.0 (5th edition) differ in the definition of permissible names. To my surprise, OOXML references to XML 1.1 and Namespaces 1.1, which I believe are dead.

**2009-03-24 Prague meeting:**

WG1 has issued a recommendation. See the SC 34 minutes from Friday. XML 1.0 4<sup>th</sup> edition.

**2009-04-08 Makoto Murata:**

To concentrate on the original issue, I would like to separate the discussion of XML 1.1 .vs. XML 1.0 from this issue. So, I submitted two defect reports. One is about XML 1.1 (DR 09-0169), and the other is about Namespaces in XML 1.1 (DR 09-0170).

## 44. DR 09-0029 — WML, Custom XML and Smart Tags: Specification for Validation Lacking

**Status:** Further Consideration Required

**Subject:** WML, Custom XML and Smart Tags: Specification for Validation Lacking

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00002

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.5.1, "Custom XML and Smart Tags", pp. 528

**Related DR(s):** none

**Nature of the Defect:**

Validation of custom XML markups is not clearly specified. Demonstrating examples are strongly needed.

**Solution Proposed by the Submitter:**

Show an XML fragment constructed from the example in pp. 530. Explain which schema is used for validating the XML fragment and how that schema is found.

**Schema Change(s) Needed:** No

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

**Action:** Shawn Villaron will look at this.

No decision was made.

**2009-03-24 Prague meeting:**

**Action:** Shawn to write up text for this.

**2009-04-22 Shawn Villaron:**

I'd like to propose the following response regarding this defect report which is described as "[v]alidation of custom XML markups is not clearly specified. Demonstrating examples are strongly needed."

The informative Annex F for Part 1 currently demonstrates how to extract the custom XML from a document. To address this concern, the following text will be appended to that Annex:

Once this information is extracted, the resulting custom markup + text can be validated separately from the document.

For example, the custom XML for the example on pp. 530, once extracted, would be:

```
<invoice xmlns="http://www.example.com/2006/invoice">
 <customerName>Tristan Davis</customerName>
 </invoice>
```

An application can employ any desired method to find the appropriate schema(s) for validation. As an example, one such approach using information defined by this Standard might be:

- Locate the schema element (§23.2.1) in the Document Settings part whose uri attribute matches the root namespace of the custom markup.
- If that element also specifies a schemaLocation attribute, the resulting path is used to locate the schema used for validation.
- Once this schema is located, validation should be triggered based on the value of doNotValidateAgainstSchema (§17.15.1.43).

Please advise if you see this as a satisfactory response or if you have specific improvements you'd like to see.

**2009-04-22 Jirka Kosek:**

> The informative Annex F for Part 1 currently demonstrates how to extract the custom XML from a document. To address this concern, the following text will be appended to that Annex:

> Once this information is extracted, the resulting custom markup + text can be validated separately from the document.

I would prefer less ambiguous wording like:

"Once this custom markup is extracted, the resulting XML document can be validated separately from the WordprocessingML document."

> \* Locate the schema element (section 23.2.1) in the Document Settings part whose uri attribute matches the root namespace of the custom markup.

... matches the namespace of root element in the XML document extracted from custom XML markup

**2009-04-22 Shawn Villaron:**

So it sounds like this is the proposed text (italics indicate Jirka's proposed changes):

The informative Annex F for Part 1 currently demonstrates how to extract the custom XML from a document. To address this concern, the following text will be appended to that Annex:

*Once this custom markup is extracted, the resulting XML document can be validated separately from the WordprocessingML document.*

For example, the custom XML for the example on pp. 530, once extracted, would be:

```
<invoice xmlns="http://www.example.com/2006/invoice">
 <customerName>Tristan Davis</customerName>
</invoice>
```

An application can employ any desired method to find the appropriate schema(s) for validation. As an example, one such approach using information defined by this Standard might be:

- Locate the schema element (section 23.2.1) in the Document Settings part whose uri attribute matches the namespace of root element in the XML document extracted from custom XML markup
- If that element also specifies a schemaLocation attribute, the resulting path is used to locate the schema used for validation.
- Once this schema is located, validation should be triggered based on the value of doNotValidateAgainstSchema (section 17.15.1.43).

**2009-04-22 Makoto Murata:**

I am thinking about the differences between custom schema lookup for WML and that for SML. In my understanding, custom schema lookup for SML always uses Schema elements within the MapInfo element,

while that for WML references to a schema by specifying an external location. A note about this difference might help.

BTW, I find that 29500 specifies almost nothing about the values of the schemaLocation attribute. Can it be an absolute IRI or relative IRI reference? Are fragment identifiers allowed? I do believe that non-ASCII characters (i.e., IRIs) are allowed. I will submit another DR for this.

# 45. DR 09-0030 — OPC: Placement of package RelationshipReference elements

**Status:** Further Consideration Required

**Subject:** OPC: Placement of package RelationshipReference elements

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00003

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 2, §13.2.4.22, “RelationshipReference Element”, pp. 55

**Related DR(s):** none

## **Nature of the Defect:**

It is not clear where in an OPC package RelationshipReference elements can appear. We can imagine that they are allowed in a XML digital signature, but this is never clearly stated, with the exception of diagrams and opc-digSig.rnc. The same thing applies to RelationshipsGroupReference elements (§13.2.4.23) and SignatureTime elements (§13.2.4.19).

## **Solution Proposed by the Submitter:**

Explicitly state that RelationshipReference and RelationshipsGroupReference elements can appear only in Transform elements of a XML digital signature, and that SignatureTime elements can appear only in SignaturePropertyType elements of a XML digital signature. Furthermore, please clearly state whether or not Transform and SignaturePropertyType elements can have any other elements as children.

**Schema Change(s) Needed:** Yes, (which?)

**Editor's Response:**

None

## 46. DR 09-0031 — General: Request for support of Unicode 5.1.0

**Status:** Further Consideration Required

**Subject:** General: Request for support of Unicode 5.1.0

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00004

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §3, “Normative References”, pp. 8

**Related DR(s):** none

### **Nature of the Defect:**

ISO/IEC 10646:2003 and the Unicode Standard Version 5.0 are referenced. However, Unicode 5.1.0 adds 1,624 newly encoded characters. OOXML is unable to take advantage of such characters.

### **Solution Proposed by the Submitter:**

Follow the conformance criteria C062, C063, C064, and C065 in “Character Model for the World Wide Web 1.0: Fundamentals” (W3C Recommendation 15 February 2005) and make a generic reference to the Unicode Standard and ISO/IEC 10646.

Specifically, we propose references as below:

Unicode: The Unicode Consortium, The Unicode Standard, Version 5, ISBN 0321480910, as updated from time to time by the publication of new versions. (See <http://www.unicode.org/unicode/standard/versions> for the latest version and additional information

on versions of the standard and of the Unicode 5.1.0: The Unicode Consortium. The Unicode Standard, Version 5.1.0, defined by: The Unicode Standard, Version 5.0 (Boston, MA, Addison-Wesley, 2007. ISBN 0-321-48091-0) (<http://www.unicode.org/versions/Unicode5.0.0/>), as amended by Unicode 5.1.0 (<http://www.unicode.org/versions/Unicode5.1.0/>).

ISO/IEC 10646: ISO/IEC 10646:2003, Information technology – Universal Multiple-Octet Coded Character Set (UCS), as, from time to time, amended, replaced by a new edition or expanded by the addition of new parts. (See <http://standards.iso.org/ittf/PubliclyAvailableStandards/index.html> for the latest version.)

**Schema Change(s) Needed:** None

**Editor's Response:**

**2009-03-24 Prague meeting:**

After a brief discussion, it was suggested this topic be put on the agenda for an up-coming teleconference.

**Action:** TC45 members to come up with rationale used when dated versions of 10646 and Unicode were chosen for the Normative References.

## 47. DR 09-0032 — General: Inappropriate use of “content type”

**Status:** Further Consideration Required

**Subject:** General: Inappropriate use of “content type”

**Qualifier:** Editorial defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00005

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §4, “Terms and Definitions”, pp. 12

**Related DR(s):** none

### **Nature of the Defect:**

The term "content type" is inappropriate. MIME RFCs use "media type".

Also, the reference to RFC 2616 in the definition of "content type" is inappropriate. RFC 2616 is the HTTP 1.1 specification and never defines "content type" or "media type", although HTTP 1.1 and MIME RFCs have a field named "content-type".

### **Solution Proposed by the Submitter:**

Replace "content type" with "media type" everywhere.

Reference RFC 2046 rather than RFC 2616.

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-02-16 Shawn Villaron:**

I've been going through many of the items listed in the latest defect log and I was hoping someone could help me better understand DR-09-0032.

In DR-09-0032, it is pointed out that in the Terms and Definitions section, we define the term *content type* and provide a reference to RFC 2616. The issue is that the term as it is currently used would better be described using the term *media type* and that the better reference would be RFC 2046.

While I can appreciate being as specific as possible regarding the terminology we use, I believe the intent of the opening paragraph was to pre-empt this issue (bold emphasis mine):

For the purposes of this document, the following terms and definitions apply. Other terms are defined where they appear in *italic* typeface, on the left side of a syntax rule, or within subclauses of language-specific grammars (§17.16 and §18.17). **Terms explicitly defined in this Part of ISO/IEC 29500 are not to be presumed to refer implicitly to similar terms defined elsewhere.** [Note: This part uses OPC-related terms, which are defined in ISO/IEC 29500-2. *end note*]

Regardless of the intent, I am curious as to what form of remedy we are being asked for; for example, is the remedy to change the prose only in the Terms and Definitions section, is it to change the prose throughout the standard, and/or does it include making schema changes? For example, how does this relate to the [Content\_Types].xml part in OPC? Changes impacting schema and OPC could have profound consequences to existing implementations as well as the corpus of existing documents.

**2009-02-16 MURATA Makoto:**

I would like to change prose and do not change file names, element names, attribute names, or any names appearing in schemas. I even believe that this is what MIME and HTTP have done. In these specs, the name of the field is "content-type" while what is specified in this field is called media types in prose.

I do not think that the sentence you highlighted gives us a license to use different names when other standardization organizations have established the appropriate terminology.

**2009-02-16 Shawn Villaron:**

Great. Does everyone agree with Murata-san that this issue's scope is limited to the prose in the Terms and Definitions section? I realize that we can't make a definitive decision in email, but if we learned that no one objected to this scoping, we could make more progress in the run-up to Prague ...

Do we have a preference for the prose change itself? For example, do we leave content type as-is and then add another term called media type and explain the relationship between the two?

And regarding the highlighted sentence, I was trying to imply we don't need to do anything; rather, I was trying to convey that this issue was considered earlier in the standard evolution and was decided to leave it as-is. Again, doesn't mean we can't make a change to the T&D section ...

**2009-02-16 MURATA Makoto:**

IMHO, the scope of this issue is the prose \*everywhere\* in ISO/IEC 29500 rather than the prose in the Terms and Definitions section. Parts 1, 2, and 4 uses "content type" 199, 186, and 17 times.

If we are going to publish a reprint, I would like to change all these occurrences. If not, I can live with (1) replacing "content type" by "media type" in the Terms and Definitions section, and (2) adding a note about our abuse.

**2009-04-30 Shawn Villaron:**

I noticed that this response is still listed as FURTHER CONSIDERATION REQUIRED. It appears from the mail thread that we're relatively close to closing on this one and so I was hoping we could make a few decisions about it.

The first question is of scope: do we change all 402 instances of "content type" as Murata-san identified, or do we scope our changes to the Terms and Definitions (T&W) section of the standard. I propose that we limit our response to the T&D section of the standard.

The next question is, if we agree with the current scope, what are the exact changes for the T&D section? I propose that we add a note regarding our abuse to the existing content type definition; I further propose that we add a new term called "media type" to the T&D section. Here are the specific changes I'm proposing:

Part 1, §4 Updates

**content type** — Describes the content stored in a part. Content types define a media type, a subtype, and an optional set of parameters, as defined in RFC 2616. Strictly speaking, many instances where content type is used throughout the standard, a more correct description would be "media type."

Part 1, §4 Additions

**media type** – Describes the content stored in a part, as defined in RFC 2616.

I don't think we need to make either of these changes as I don't believe that they will have any impact on vendors ability to implement the standard, nor their ability to implement interoperable solutions. That said, I understand that some folks in WG4 believe that this is an important issue. My motivation at this point is to generate consensus on this defect report response and move it along.

**2009-05-04 MURATA Makoto:**

I would like to change all 402 instances of "content type" but I think that the right decision depends on the format of our upcoming DCORs, FPDAMs, and beyond. So, I do not think that we are ready to make a decision.

Frankly, I think that in the original submission that too little attention was paid to MIME. (See DR 09-0034.)

## 48. DR 09-0033 — DML, Charts, Simple Types: Lack of support for percent sign

**Status:** Further Consideration Required [A8]

**Subject:** DML, Charts, Simple Types: Lack of support for percent sign

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00006

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §21.2.2.41, “depthPercent (Depth Percent)”, pp. 3780

Part 1, §21.2.2.83, “hPercent (Height Percent)”, pp. 3800

Part 1, §21.2.3.9, “ST\_DepthPercent (Depth Percent)”, pp. 3880

Part 1, §21.2.3.19, “ST\_HPercent (Height Percent)”, pp. 3885

**Related DR(s):** none

**Nature of the Defect:**

Two simple types in the strict dml-chart.xsd, namely ST\_DepthPercent and ST\_HPercent, are used to represent percent values, but they do not allow the percent sign (see BRM Resolution 6).

Part 1, §21.2.2.41, depthPercent (Depth Percent) ... Specifies an integer value for the property defined by the parent XML element. The possible values for this attribute are defined by the ST\_DepthPercent simple type (§21.2.3.9).

Part 1, §21.2.2.83, hPercent (Height Percent) ... Specifies that the contents of this attribute contain a height percent between 5 and 500. The possible values for this attribute are defined by the ST\_HPercent simple type (§21.2.3.19).

Part 1, §21.2.3.9, ST\_DepthPercent (Depth Percent): This simple type specifies that its contents contain a whole number between 20 and 2000, whose contents are a percentage. This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

Part 1, §21.2.3.19, ST\_HPercent (Height Percent): This simple type specifies that its contents contain an integer between 5 and 500, whose contents are a percentage. This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

### **Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:** Yes, strict dml-chart.xsd

### **Editor's Response:**

#### **2009-04-24 Editor:**

The exact changes are as follows:

Part 1, §21.2.2.41, "depthPercent (Depth Percent)", pp. 3780

Attributes	Description
val (Depth Percent Value)	Specifies <del>an integer</del> <ins>a percentage</ins> value for the property defined by the parent XML element. The possible values for this attribute are defined by the ST_DepthPercent simple type (§xx).

Part 1, §21.2.3.9, "ST\_DepthPercent (Depth Percent)", pp. 3880

This simple type specifies that its contents contain a ~~whole number~~percentage between 20~~%~~0 and 2000~~%~~0, ~~whose contents are a percentage~~.

~~This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype is a union of the following types:~~

- [ST\\_DepthPercentWithSymbol simple type \(§xx\)](#).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 20.~~

- ~~This simple type has a maximum value of less than or equal to 2000.~~

Part 1, §21.2.3.xx, “ST\_DepthPercentWithSymbol (Depth Percent with Symbol)”, new subclause

This simple type specifies that its contents contain a percentage between 20% and 2000%.

The simple type’s contents shall match the following regular expression pattern:

0\*(([2-9][0-9])|([1-9][0-9][0-9])|(1[0-9][0-9][0-9])|2000)%.

<u>Referenced By</u>
<a href="#">ST_DepthPercent (§21.2.3.9)</a>

Part 1, §A.5.1, “DrawingML - Charts”, pp. 4594, lines 216–224

```

<xsd:simpleType name="ST_DepthPercent">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="20"/>
 <xsd:maxInclusive value="2000"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_DepthPercentWithSymbol"/>
</xsd:simpleType>

<xsd:simpleType name="ST_DepthPercentWithSymbol">
 <xsd:pattern value="0*(([2-9][0-9])|([1-9][0-9][0-9])|(1[0-9][0-9][0-9])|2000)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_DepthPercent">
 <xsd:attribute name="val" type="ST_DepthPercent" default="100%"/>
</xsd:complexType>
```

Part 4, §13.1.xx, “Simple Types”, new subclause

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_DepthPercent”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_DepthPercentUShort simple type (§xx).

Part 4, §13.1.xx.xx, “ST\_DepthPercentUShort (Depth Percent UnsignedShort) (Part 1, §21.2.3.9)”, new subclause

This simple type specifies that its contents contain a whole number between 20 and 2000, whose contents are a percentage.

[This simple type's contents are a restriction of the W3C XML Schema `unsignedShort` datatype.](#)

[This simple type also specifies the following restrictions:](#)

- [This simple type has a minimum value of greater than or equal to 20.](#)
- [This simple type has a maximum value of less than or equal to 2000.](#)

<a href="#">Referenced By</a>
<a href="#">ST_DepthPercent (Part 1, §21.2.3.9)</a>

Part 4, §A.5.1, “DrawingML - Charts”, pp. 1066, lines 216–224

```

<xsd:simpleType name="ST_DepthPercent">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="20"/>
 <xsd:maxInclusive value="2000"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_DepthPercentWithSymbol ST_DepthPercentUShort"/>
</xsd:simpleType>

<xsd:simpleType name="ST_DepthPercentWithSymbol">
 <xsd:pattern value="0*(([2-9][0-9])|([1-9][0-9][0-9])|(1[0-9][0-9][0-9])|2000)% "/>
</xsd:simpleType>

<xsd:simpleType name="ST_DepthPercentUShort">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="20"/>
 <xsd:maxInclusive value="2000"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_DepthPercent">
 <xsd:attribute name="val" type="ST_DepthPercent" default="100%"/>
</xsd:complexType>
```

Part 1, §21.2.2.83, “hPercent (Height Percent)”, pp. 3800

Attributes	Description
val (Height Percent Value)	<p>Specifies that the contents of this attribute contain a height percent between <u>5%</u> and <u>500%</u>.</p> <p>The possible values for this attribute are defined by the ST_HPercent simple type (§xx).</p>

Part 1, §21.2.3.19, “ST\_HPercent (Height Percent)”, pp. 3885

This simple type specifies that its contents contain ~~an integer or percentage~~ between 5% and 500%, ~~whose contents are a percentage~~.

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype~~, is a union of the following types:

- ST\_HPercentWithSymbol simple type (§xx).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 5.~~
- ~~This simple type has a maximum value of less than or equal to 500.~~

Part 1, §21.2.3.xx, “ST\_HPercentWithSymbol (Height Percent with Symbol)”, new subclause

This simple type specifies that its contents contain a percentage between 5% and 500%.

The simple type's contents shall match the following regular expression pattern:

0\*(([5-9])|([1-9][0-9])|([1-4][0-9][0-9])|500)%.

<u>Referenced By</u>
<u>ST_HPercent (§21.2.3.19)</u>

Part 1, §A.5.1, “DrawingML - Charts”, pp. 4594, lines 198–206

```

<xsd:simpleType name="ST_HPercent">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_HPercentWithSymbol"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HPercentWithSymbol">
 <xsd:pattern value="0*(([5-9])|([1-9][0-9])|([1-4][0-9][0-9])|500)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_HPercent">
 <xsd:attribute name="val" type="ST_HPercent" default="100%"/>
</xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_HPercent (Part 1, §21.2.3.19)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_HPercentUShort simple type (§NEW).

Part 4, §13.1.xx.xx, “ST\_HPercentUShort (Depth Percent UnsignedShort)”, new subclause

This simple type specifies that its contents contain a whole number between 5 and 500, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 5.
- This simple type has a maximum value of less than or equal to 500.

<u>Referenced By</u>
<u><a href="#">ST_HPercent (Part 1, §21.2.3.19)</a></u>

Part 4, §A.5.1, “DrawingML - Charts”, pp. 1066, lines 198–206

```

<xsd:simpleType name="ST_HPercent">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_HPercentWithSymbol ST_HPercentUShort"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HPercentWithSymbol">
 <xsd:pattern value="0*(([5-9])|([1-9][0-9])|([1-4][0-9][0-9])|500)%"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HPercentUShort">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_HPercent">
 <xsd:attribute name="val" type="ST_HPercent" default="100%"/>
</xsd:complexType>

```

## 49. DR 09-0034 — General: Numerous media types should be registered at IANA

**Status:** Further Consideration Required

**Subject:** General: Numerous media types should be registered at IANA

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00007

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §1, pp. N/A

**Related DR(s):** none

**Nature of the Defect:**

The following OOXML media types are not registered at IANA:

1. application/vnd.ms-officeactivex+xml
2. application/vnd.openxmlformats-officedocument.customXmlProperties+xml
3. application/vnd.openxmlformats-officedocument.drawing+xml
4. application/vnd.openxmlformats-officedocument.drawingml.chart+xml
5. application/vnd.openxmlformats-officedocument.drawingml.chartshapes+xml
6. application/vnd.openxmlformats-officedocument.drawingml.diagramColors+xml
7. application/vnd.openxmlformats-officedocument.drawingml.diagramData+xml
8. application/vnd.openxmlformats-officedocument.drawingml.diagramLayout+xml
9. application/vnd.openxmlformats-officedocument.drawingml.diagramStyle+xml
10. application/vnd.openxmlformats-officedocument.obfuscatedFont
11. application/vnd.openxmlformats-officedocument.presentationml.commentAuthors+xml
12. application/vnd.openxmlformats-officedocument.presentationml.comments+xml

13. application/vnd.openxmlformats-officedocument.presentationml.handoutMaster+xml
14. application/vnd.openxmlformats-officedocument.presentationml.notesMaster+xml
15. application/vnd.openxmlformats-officedocument.presentationml.notesSlide+xml
16. application/vnd.openxmlformats-officedocument.presentationml.presProps+xml
17. application/vnd.openxmlformats-officedocument.presentationml.presentation.main+xml
18. application/vnd.openxmlformats-officedocument.presentationml.slide+xml
19. application/vnd.openxmlformats-officedocument.presentationml.slideLayout+xml
20. application/vnd.openxmlformats-officedocument.presentationml.slideMaster+xml
21. application/vnd.openxmlformats-officedocument.presentationml.slideUpdateInfo+xml
22. application/vnd.openxmlformats-officedocument.presentationml.slideUpdateInfo+xml.
23. application/vnd.openxmlformats-officedocument.presentationml.slideshow.main+xml
24. application/vnd.openxmlformats-officedocument.presentationml.tableStyles+xml
25. application/vnd.openxmlformats-officedocument.presentationml.tags+xml
26. application/vnd.openxmlformats-officedocument.presentationml.template.main+xml
27. application/vnd.openxmlformats-officedocument.presentationml.viewProps+xml
28. application/vnd.openxmlformats-officedocument.spreadsheetml.calcChain+xml
29. application/vnd.openxmlformats-officedocument.spreadsheetml.chartsheet+xml
30. application/vnd.openxmlformats-officedocument.spreadsheetml.comments+xml
31. application/vnd.openxmlformats-officedocument.spreadsheetml.connections+xml
32. application/vnd.openxmlformats-officedocument.spreadsheetml.customProperty
33. application/vnd.openxmlformats-officedocument.spreadsheetml.dialogsheet+xml
34. application/vnd.openxmlformats-officedocument.spreadsheetml.externalLink+xml
35. application/vnd.openxmlformats-officedocument.spreadsheetml.pivotCacheDefinition+xml
36. application/vnd.openxmlformats-officedocument.spreadsheetml.pivotCacheRecords+xml
37. application/vnd.openxmlformats-officedocument.spreadsheetml.pivotTable+xml
38. application/vnd.openxmlformats-officedocument.spreadsheetml.printerSettings(in
39. application/vnd.openxmlformats-officedocument.spreadsheetml.queryTable+xml
40. application/vnd.openxmlformats-officedocument.spreadsheetml.revisionHeaders+xml
41. application/vnd.openxmlformats-officedocument.spreadsheetml.revisionLog+xml
42. application/vnd.openxmlformats-officedocument.spreadsheetml.sharedStrings+xml
43. application/vnd.openxmlformats-officedocument.spreadsheetml.sheet.main+xml
44. application/vnd.openxmlformats-officedocument.spreadsheetml.sheetMetadata+xml
45. application/vnd.openxmlformats-officedocument.spreadsheetml.styles+xml
46. application/vnd.openxmlformats-officedocument.spreadsheetml.table+xml
47. application/vnd.openxmlformats-officedocument.spreadsheetml.tableSingleCells+xml
48. application/vnd.openxmlformats-officedocument.spreadsheetml.template.main+xml
49. application/vnd.openxmlformats-officedocument.spreadsheetml.userNames+xml
50. application/vnd.openxmlformats-officedocument.spreadsheetml.volatileDependencies+xml
51. application/vnd.openxmlformats-officedocument.spreadsheetml.worksheet+xml
52. application/vnd.openxmlformats-officedocument.theme+xml
53. application/vnd.openxmlformats-officedocument.themeOverride+xml
54. application/vnd.openxmlformats-officedocument.vmlDrawing

55. application/vnd.openxmlformats-officedocument.wordprocessingml.comments+xml
56. application/vnd.openxmlformats-officedocument.wordprocessingml.document
57. application/vnd.openxmlformats-officedocument.wordprocessingml.document.glossary+xml
58. application/vnd.openxmlformats-officedocument.wordprocessingml.endnotes+xml
59. application/vnd.openxmlformats-officedocument.wordprocessingml.fontTable+xml
60. application/vnd.openxmlformats-officedocument.wordprocessingml.footer+xml
61. application/vnd.openxmlformats-officedocument.wordprocessingml.footnotes+xml
62. application/vnd.openxmlformats-officedocument.wordprocessingml.header+xml
63. application/vnd.openxmlformats-officedocument.wordprocessingml.numbering+xml
64. application/vnd.openxmlformats-officedocument.wordprocessingml.printerSettings
65. application/vnd.openxmlformats-officedocument.wordprocessingml.settings+xml
66. application/vnd.openxmlformats-officedocument.wordprocessingml.styles+xml
67. application/vnd.openxmlformats-officedocument.wordprocessingml.template.main+xml
68. application/vnd.openxmlformats-officedocument.wordprocessingml.webSettings+xml
69. application/vnd.openxmlformats-package.core-properties+xml
70. application/vnd.openxmlformats-package.digital-signature-origin
71. application/vnd.openxmlformats-package.digital-signature-xmlsignature+xml

**Solution Proposed by the Submitter:**

Register these media types with IANA.

**Schema Change(s) Needed:** No

**Editor's Response:**

**2009-02-16 Shawn Villaron:**

I've been going through many of the items listed in the latest defect log and I was hoping someone could help me better understand DR-09-0034.

We are being asked to register the set of content types/media types found in the standard. I must admit that my understanding with regard to the pros/cons of IANA registration is lacking. Could someone help me understand the benefits of registering these types? Are there any tangible consequences to their registration? Does the group have thoughts as to which entity should do the registration? Learning a bit more about IANA registration would help me evaluate the practical impact on interoperability these changes would have.

**2009-02-16 MURATA Makoto:**

I would argue that it is our obligation to register OOXML media types. ODF people have registered their media types. The media types for XML are registered at IANA, and the media type for RELAX NG compact syntax is also registered (I was involved in both). I do not want my working group to ignore

best practices of Internet. Now, people can rightly claim that we are bad guys and ODF people are good guys.

Since these media types belong to the vendor tree (as opposed to the standard tree), it should not be difficult to register these media types. We only have to send some e-mails to the ietf-types mailing list. More about this, see <http://tools.ietf.org/html/rfc4288>

I also think that 29500 should provide some more information about these media types. Such information should cover parameters at least.

Are the media types listed in OOXML intended to be used in the HTTP or MIME content-field? Or, are these media types used only in [Content\_Types].xml?

If they are used only in [Content\_Types].xml, I do not think we need parameters for these media types.

**2009-02-16 Shawn Villaron:**

I certainly don't want to do anything that would make us seem like bad guys. I'm only interested in understanding the practical benefit of registering these things -- so I'm not opposed to the registration; I'd just like to understand the ramifications of us doing this. I spent time earlier today on the IANA web site, and registration seems pretty straight-forward. There were some questions for which I didn't have immediate answers for, but nothing seemed insurmountable. One of the biggest questions is who should register these types?

Regarding the HTTP or MIME content-field, I'm not sure. I was hoping someone with more knowledge could make a recommendation on this front.

Regarding their usage, I believe it is limited to the [Content\_Types].xml part. That said, I'd want to go through the spec again. I recall there might have been a BRM issue or two regarding media where a change was considered to make this information more local to the XML itself. I'd need to look into this, unless someone knows off-hand?

**2009-02-16 MURATA Makoto:**

Since I have done the registration procedure twice, I am probably the best person for leading this registration. But I do need some help from those who know the intended usage of these media types.

**2009-02-24 Shawn Villaron:**

Murata-san, I'd be happy to look into collecting the necessary registration information ( or at least coming up with a starting point for further discussions ). To ensure that I provide the intended information, could you please verify that we'll need to register the content/media types identified in DR-09-0034 by filling out the form found here: <http://www.iana.org/cgi-bin/mediatypes.pl>?

As I understand it, we'll need the following information ( in addition to what we already have ):

- Required parameters
- Optional parameters
- Encoding considerations
- Security considerations
- Interoperability considerations
- Published Specification
- Applications using this type
- Magic number(s)
- File extension(s)
- Mac File Type(s)
- OID(s)

If you could verify that this in the information request, I'll start pulling this information together.

**2009-02-25 MURATA Makoto:**

I didn't know the web form you mentioned, but it is mentioned in RFC 4288. Thank you for enlightening me.

Here is my first cut.

- Required parameters: None.
- Optional parameters: charset, as specified in 3.2 of RFC 3023.
- Encoding considerations: The same as in application/xml (3.2 of RFC 3023).
- Security considerations: The same as in application/xml (3.2 of RFC 3023).
- Interoperability considerations: The same as in application/xml (3.2 of RFC 3023).
- Published Specification: ISO/IEC 29500:2008, Part X, Clause X.X.X
- Applications using this type: OOXML applications
- Magic number(s): None
- File extension(s): xml
- Mac File Type(s): "TEXT"
- OID(s): ???? (I do not understand. Can we simply skip this field?)
- Intended usage: Common

We might want to say that OOXML documents are zip files and that our media types are labels for files within such zip files. By the way, when the pack URI scheme is used to reference to files within OOXML zip files, will our media types be returned?

Although we can directly contact IANA, I think we should first send a proposal to the IETF-type ML.

**2009-02-25 Caroline Arms:**

I strongly agree with Murata-san that mediatypes should be registered with IANA for the OOXML document types. I actually argued for it a long way back within TC45. I would be inclined to consult the ODF registrations for an indication of what might be appropriate. OASIS has registered a series of media types with the shared prefix 'vnd.oasis.opendocument' and I would be inclined to take the same approach for OOXML. There does seem to be the question of what organization the registration should come from (SC34, ECMA, ??).

<http://www.iana.org/assignments/media-types/application/vnd.oasis.opendocument.chart> is an example.

Note the security considerations. I imagine something similar (mentioning the possibility of macros being embedded, privacy, etc.) would be needed for OOXML.

**2009-03-03 MURATA Makoto:**

In the case of RELAX NG compact syntax, I used the standard tree rather than the vendor tree. Note that SC34 can use the standard tree if some standard or amendment explains the media type to be registered.

We can now do the same thing for OOXML media types, but I am inclined to continue to use media type names as shown in 29500. Since the maintainer of OOXML is now SC34/WG4, I believe that SC34/WG4 is now the "vendor" for OOXML.

Security considerations are required. RFC 3023 already explains them, but we might want to add more. Which of the currently use media types (see R-09-0034) contains scripts or programs?

By the way, if my understanding is correct, there are no media types for OOXML documents. Although we have media types for logical parts of OOXML documents, there are no media types for OOXML documents as a whole. (Note: application/pdf exists.)

I believe that we are obliged to create and register a media type for OOXML documents. (I will submit another defect report.)

I wrote:

- > By the way,
- > when the pack URI scheme is used to reference to files within OOXML
- > zip files, will our media types be returned?

Having read Part 2, I guess URIs using the pack scheme are required to return the content type as specified in [Content\_Types].xml.

Since this is not clearly specified in Annex B of Part 2, we should probably introduce "B.5 Media types" and explicitly state this requirement. (I will submit yet another defect report.)

**2009-03-04 MURATA Makoto:**

I reviewed all media types appearing in OOXML again. Specialized XML media types in 29500 shouldn't be difficult to register. But I do not find some problems in other media types. I plan to submit more defect reports thru JISC.

I am inclined to register easy ones in a hurry even when we do not provide enough information about security considerations.

### 1. Specialized XML media types

#### 1) Shouldn't be difficult

29500 has a number of specialized XML media types (i.e., "\*+xml"). The format of the MIME bodies are clearly defined in 29500. It should not be difficult to register them in the vendor tree.

Note: If I had been involved in TC45, I would have been against them and proposed to rely on application/xml and content sniffing.

#### 11.3.2 Comments Part

application/vnd.openxmlformats-officedocument.wordprocessingml.comments+xml

#### 11.3.3 Document Settings Part

application/vnd.openxmlformats-officedocument.wordprocessingml.settings+xml

#### 11.3.4 Endnotes Part

application/vnd.openxmlformats-officedocument.wordprocessingml.endnotes+xml

#### 11.3.5 Font Table Part

application/vnd.openxmlformats-officedocument.wordprocessingml.fontTable+xml

#### 11.3.6 Footer Part

application/vnd.openxmlformats-officedocument.wordprocessingml.footer+xml

#### 11.3.7 Footnotes Part

application/vnd.openxmlformats-officedocument.wordprocessingml.footnotes+xml

#### 11.3.8 Glossary Document Part

application/vnd.openxmlformats-officedocument.wordprocessingml.document.glossary+xml

#### 11.3.9 Header Part

application/vnd.openxmlformats-officedocument.wordprocessingml.header+xml

#### 11.3.10 Main Document Part

application/vnd.openxmlformats-officedocument.wordprocessingml.document.main+xml

#### 11.3.10 Main Document Part

application/vnd.openxmlformats-officedocument.wordprocessingml.template.main+xml

#### 11.3.11 Numbering Definitions Part

application/vnd.openxmlformats-officedocument.wordprocessingml.numbering+xml

#### 11.3.12 Style Definitions Part

application/vnd.openxmlformats-officedocument.wordprocessingml.styles+xml

#### 11.3.13 Web Settings Part

- application/vnd.openxmlformats-officedocument.wordprocessingml.webSettings+xml
- 12.3.1 Calculation Chain Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.calcChain+xml
- 12.3.2 Chartsheet Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.chartsheet+xml
- 12.3.3 Comments Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.comments+xml
- 12.3.4 Connections Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.connections+xml
- 12.3.7 Dialogsheet Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.dialogsheet+xml
- 12.3.8 Drawings Part
  - application/vnd.openxmlformats-officedocument.drawing+xml
- 12.3.9 External Workbook References Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.externalLink+xml
- 12.3.10 Metadata Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.sheetMetadata+xml
- 12.3.11 Pivot Table Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.pivotTable+xml
- 12.3.12 Pivot Table Cache Definition Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.pivotCacheDefinition+xml
- 12.3.13 Pivot Table Cache Records Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.pivotCacheRecords+xml
- 12.3.14 Query Table Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.queryTable+xml
- 12.3.15 Shared String Table Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.sharedStrings+xml
- 12.3.16 Shared Workbook Revision Headers Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.revisionHeaders+xml
- 12.3.17 Shared Workbook Revision Log Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.revisionLog+xml
- 12.3.18 Shared Workbook User Data Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.userNames+xml
- 12.3.19 Single Cell Table Definitions Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.tableSingleCells+xml
- 12.3.20 Styles Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.styles+xml
- 12.3.21 Table Definition Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.table+xml
- 12.3.22 Volatile Dependencies Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.volatileDependencies+xml
- 12.3.23 Workbook Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.sheet.main+xml
- 12.3.23 Workbook Part

- application/vnd.openxmlformats-officedocument.spreadsheetml.template.main+xml
- 12.3.24 Worksheet Part
  - application/vnd.openxmlformats-officedocument.spreadsheetml.worksheet+xml
- 13.3.1 Comment Authors Part
  - application/vnd.openxmlformats-officedocument.presentationml.commentAuthors+xml
- 13.3.2 Comments Part
  - application/vnd.openxmlformats-officedocument.presentationml.comments+xml
- 13.3.3 Handout Master Part
  - application/vnd.openxmlformats-officedocument.presentationml.handoutMaster+xml
- 13.3.4 Notes Master Part
  - application/vnd.openxmlformats-officedocument.presentationml.notesMaster+xml
- 13.3.5 Notes Slide Part
  - application/vnd.openxmlformats-officedocument.presentationml.notesSlide+xml
- 13.3.6 Presentation Part
  - application/vnd.openxmlformats-officedocument.presentationml.presentation.main+xml
- 13.3.6 Presentation Part
  - application/vnd.openxmlformats-officedocument.presentationml.slideshow.main+xml
- 13.3.6 Presentation Part
  - application/vnd.openxmlformats-officedocument.presentationml.template.main+xml
- 13.3.7 Presentation Properties Part
  - application/vnd.openxmlformats-officedocument.presentationml.presProps+xml
- 13.3.8 Slide Part
  - application/vnd.openxmlformats-officedocument.presentationml.slide+xml
- 13.3.9 Slide Layout Part
  - application/vnd.openxmlformats-officedocument.presentationml.slideLayout+xml
- 13.3.10 Slide Master Part
  - application/vnd.openxmlformats-officedocument.presentationml.slideMaster+xml
- 13.3.11 Slide Synchronization Data Part
  - application/vnd.openxmlformats-officedocument.presentationml.slideUpdateInfo+xml
- 13.3.12 User Defined Tags Part
  - application/vnd.openxmlformats-officedocument.presentationml.tags+xml
- 13.3.13 View Properties Part
  - application/vnd.openxmlformats-officedocument.presentationml.viewProps+xml
- 14.2.1 Chart Part
  - application/vnd.openxmlformats-officedocument.drawingml.chart+xml
- 14.2.2 Chart Drawing Part
  - application/vnd.openxmlformats-officedocument.drawingml.chartshapes+xml
- 14.2.3 Diagram Colors Part
  - application/vnd.openxmlformats-officedocument.drawingml.diagramColors+xml
- 14.2.4 Diagram Data Part
  - application/vnd.openxmlformats-officedocument.drawingml.diagramData+xml
- 14.2.5 Diagram Layout Definition Part
  - application/vnd.openxmlformats-officedocument.drawingml.diagramLayout+xml
- 14.2.6 Diagram Style Part
  - application/vnd.openxmlformats-officedocument.drawingml.diagramStyle+xml

application/vnd.openxmlformats-officedocument.drawingml.diagramStyle+xml

14.2.7 Theme Part

application/vnd.openxmlformats-officedocument.theme+xml

14.2.8 Theme Override Part

application/vnd.openxmlformats-officedocument.themeOverride+xml

14.2.9 Table Styles Part

application/vnd.openxmlformats-officedocument.presentationml.tableStyles+xml

15.2.12.1 Core File Properties Part

application/vnd.openxmlformats-package.core-properties+xml

15.2.12.2 Custom File Properties Part

application/vnd.openxmlformats-officedocument.custom-properties+xml

15.2.12.3 Extended File Properties Part

application/vnd.openxmlformats-officedocument.extended-properties+xml

15.2.6 Custom XML Data Storage Properties Part

application/vnd.openxmlformats-officedocument.customXmlProperties+xml

15.2.8 Digital Signature XML Signature Part

application/vnd.openxmlformats-package.digital-signature-xmlsignature+xml

2) Should have been specialized media types?

12.3.6 Custom XML Mappings Part

application/xml http://schemas.openxmlformats.org/spreadsheetml/2006/main

15.2.1 Additional Characteristics Part

application/xml

http://schemas.openxmlformats.org/officeDocument/2006/additionalCharacteristics

15.2.3 Bibliography Part

application/xml http://schemas.openxmlformats.org/officeDocument/2006/bibliography

Since OOXML has so many specialized media types (i.e., ones ending with "+xml"), I do not understand why the above parts do not have specialized media types.

Note: One could argue that this is not a defect but merely a peculiar design choice.

2. Doubtful media types

1) 15.2.7 Digital Signature Origin Part

application/vnd.openxmlformats-package.digital-signature-origin

The MIME body of this media type is always empty. Thus, this media type does look strange to me. Should we register this anyway?

2) 15.2.13 Font Part

application/vnd.openxmlformats-officedocument.obfuscatedFont

DR 09-0012 already reports that this media type has no definitions.

3) 15.2.15 Printer Settings Part

application/vnd.openxmlformats-officedocument.spreadsheetml.printerSettings (in SpreadsheetML documents)

15.2.15 Printer Settings Part

application/vnd.openxmlformats-officedocument.wordprocessingml.printerSettings (in WordprocessingML documents)

These media types are very strange, since they do not provide any information about the MIME body.

"An instance of this part type contains information about the initialization and environment of a printer or a display device. The layout of this information is application-defined."

We could have registered a media type for DEVMODE and another for the print record of MAC OS.

4) Part4 8.1 VML Drawing Part

application/vnd.openxmlformats-officedocument.vmlDrawing

This media type should have ended with "+xml" so that generic XML tools can handle VML Drawing parts.

5) 11.3.1 Alternative Format Import Part

application/vnd.openxmlformats-officedocument.wordprocessingml.document

There are no clear definitions of this media type. Is the MIME body a WML package?

6) 12.3.5 Custom Property Part

application/vnd.openxmlformats-officedocument.spreadsheetml.customProperty

This media type is very strange, since it does not provide any information about the MIME body.

"This part supports the storage of user-defined data."

7) 15.2.9 Embedded Control Persistence Part

application/vnd.ms-office.activeX+xml

This media type has no definitions. What is the MIME body? Is the MIME body of this media type really XML? If not, why "+xml"?

8) application/x-fontdata and application/x-font-ttf

See DR 09-0036 and DR 09-0039.

**2009-03-04 MURATA Makoto:**

> I wrote:  
> > By the way,  
> > when the pack URI scheme is used to reference to files within OOXML  
> > zip files, will our media types be returned?  
>  
> Having read Part 2, I guess URIs using the pack scheme are required to  
> return the content type as specified in [Content\_Types].xml.  
> Since this is not clearly specified in Annex B of Part 2, we should  
> probably introduce "B.5 Media types" and explicitly state this  
> requirement. (I will submit yet another defect report.)

I find that the pack URI scheme registered at IANA is based on an Internet Draft <draft-shur-pack-uri-scheme-05.txt>, available at: <http://www.ietf.org/internet-drafts/draft-shur-pack-uri-scheme-05.txt>

This document is brand new but is still based on Ecma-376 (1st edition). In particular, non-ASCII logical part names are not allowed.

Moreover, this I-D does not say anything about what is a package, what happens when a non-package MIME entity is located, and what is returned.

Q1: If a non-zip file is returned, what will happen?

Q2: If a non-OPC zip file is returned, what will happen?

Q3: Does this pack scheme apply to both Ecma OOXML OPC packages (1<sup>st</sup> edition) and 29500 OPC packages?

Q4: What happens when non-ASCII part names are used? In other words, what will happen when the pack scheme is used for IRIs?

Q5: Will the returned MIME header contain media types as specified in [Content\_Types].xml?

#### **2009-04-08 Makoto Murata:**

Apparently, there are several issues here. They are related but different.

I would like to cover the easiest issue here. In other words, we consider registration of non-problematic specialized XML media types.

I have already submitted defect reports for the other issues mentioned in my last mail. They are:

- > 2) Should have been specialized media types?
- > 12.3.6 Custom XML Mappings Part

> application/xml <http://schemas.openxmlformats.org/spreadsheetml/2006/main>

> 15.2.1 Additional Characteristics Part

> application/xml <http://schemas.openxmlformats.org/officeDocument/2006/additionalCharacteristics>

> 15.2.3 Bibliography Part

> application/xml <http://schemas.openxmlformats.org/officeDocument/2006/bibliography>

..

> 2. Doubtful media types

> 1) 15.2.7 Digital Signature Origin Part

> application/vnd.openxmlformats-package.digital-signature-origin

..

> 2) 15.2.13 Font Part

> application/vnd.openxmlformats-officedocument.obfuscatedFont

..

> 3) 15.2.15 Printer Settings Part

> application/vnd.openxmlformats-officedocument.spreadsheetml.printerSettings (in SpreadsheetML documents)

> 15.2.15 Printer Settings Part

> application/vnd.openxmlformats-officedocument.wordprocessingml.printerSettings (in WordprocessingML documents)

..

> 4) Part4 8.1 VML Drawing Part

> application/vnd.openxmlformats-officedocument.vmlDrawing

..

> 5) 11.3.1 Alternative Format Import Part

> application/vnd.openxmlformats-officedocument.wordprocessingml.document

..

> 6) 12.3.5 Custom Property Part

> application/vnd.openxmlformats-officedocument.spreadsheetml.customProperty

..

> 7) 15.2.9 Embedded Control Persistence Part

> application/vnd.ms-officeactivex+xml

..

> 8) application/x-fontdata and application/x-font-ttf

## 50. DR 09-0035 — WML, Parts: Incorrect media types for Alternative Format Import Part

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Parts: Incorrect media types for Alternative Format Import Part

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00008

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §11.3.1, "Alternative Format Import Part", pp. 32

**Related DR(s):** none

**Nature of the Defect:**

The following are incorrect media types: application/text/plain and application/text/html.

**Solution Proposed by the Submitter:**

Use text/plain and text/html, respectively, instead.

**Schema Change(s) Needed:** No

**Editor's Response:**

**2009-01-28 Okinawa meeting:**

It is likely that existing documents contain such strings. Is this a breaking change? No decision was made.

**2009-03-24 Prague meeting:**

Adopted the proposed solution with the Editor to write the specific change words. Closed.

The exact changes are as follows:

Part 1, §11.3.1, "Alternative Format Import Part", pp. 32

Content Type:	One of the following formats: <ul style="list-style-type: none"><li>• Text = application/text/plain</li><li>• HTML = application/text/html</li><li>• WordprocessingML = application/vnd.openxmlformats-officedocument.wordprocessingml.document</li><li>• XHTML = application/xhtml+xml</li></ul>
---------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# 51. DR 09-0036 — Shared, Parts, Font Part: Inappropriate media types

**Status:** Further Consideration Required

**Subject:** Shared, Parts, Font Part: Inappropriate media types

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00009

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §15.2.13, "Font Part", pp. 160

**Related DR(s):** none

## **Nature of the Defect:**

The media types application/x-fontdata and application/x-font-ttf are inappropriate. RFC 4288 clearly says "Therefore, use of both "x-" and "x." forms is discouraged."

## **Solution Proposed by the Submitter:**

Register two media types in the standard tree. See RFC 4288.

As for application/x-font-ttf, registration should not be difficult.

Fortunately, SC34/WG2 has 9541-4 (Font information interchange – Part 4: Harmonization to Open Font Format). Publish registration information for an open type media type as a COR or AM to 9541-4, request the registration to IESG, and publish a COR to 29500 for the new media type.

**Schema Change(s) Needed:** No

**Editor's Response:**

None

## 52. DR 09-0037 — PML, Presentation: Clarify description of properties in embeddedFontLst

**Status:** Further Consideration Required

**Subject:** PML, Presentation: Clarify description of properties in embeddedFontLst

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00010

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §19.2.1.10, "font (Embedded Font Name)", pp. 2766

**Related DR(s):** none

### **Nature of the Defect:**

The entry of the referred to font in the embeddedFontLst, "font (Embedded Font Name)" (19.2.1.13) includes the properties like charset, panose, and pitchFamily, but they are already specified in the referencing part by the feature of DrawingML, or it should be described how the inconsistency should be handled when they are different between the referencing part and the referred to part. In the case of WordprocessingML, this information is not specified in the referencing part "rFont"; they are collected in "Font Table".

### **Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:** No

**Editor's Response:**

None

## 53. DR 09-0038 — WML/PML/DML: Panose-1 Typeface Classification

**Status:** Further Consideration Required

**Subject:** WML/PML/DML: Panose-1 Typeface Classification

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00011

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §19.2.1.13, “font (Embedded Font Name)”, pp. 2766

§17.8.3.13, “panose1 (Panose-1 Typeface Classification Number)”, pp. 766

§19.2.1.13, “font (Embedded Font Name)”, pp. 2768

§21.1.2.3.1, “cs (Complex Script Font)”, pp. 3598

§21.1.2.3.3, “ea (East Asian Font)”, pp. 3606

§21.1.2.3.7, “latin (Latin Font)”, pp. 3614

§21.1.2.3.10, “sym (Symbol Font)”, pp. 3623

§21.1.2.3.7, “buFont (Specified)”, pp. 3638

**Related DR(s):** none

**Nature of the Defect:**

The element or attribute name used to represent Panose-1 Typeface Classification Number is sometimes "panose1" (§17.8.3.13 in WordprocessingML) and sometimes "panose" (§19.2.1.13 in PresentationML). Considering the fact that there was a white paper for Panose-2.0, which is not compatible with Panose-1.0: <http://www.w3.org/Fonts/Panose/pan2.html> "panose1" is better than "panose" to avoid the confusion.

The subclause using "panose1" instead of "panose" is:

- §17.8.3.13, panose1 (Panose-1 Typeface Classification Number), pp. 766

The subclauses using "panose" instead of "panose1" are:

- §19.2.1.13, font (Embedded Font Name), pp. 2768
- §21.1.2.3.1, cs (Complex Script Font), pp. 3598
- §21.1.2.3.3, ea (East Asian Font), pp. 3606
- §21.1.2.3.7, latin (Latin Font), pp. 3614
- §21.1.2.3.10, sym (Symbol Font), pp. 3623
- §21.1.2.3.7, buFont (Specified), pp. 3638

Also the type names like "CT\_Panose", "ST\_Panose" (§22.9.2.8) should be changed to "CT\_Panose1", "ST\_Panose1".

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Request to add a note regarding changing “Panose” to “Panose1” in narrative.

## 54. DR 09-0039 — Shared, Parts, Font Part: File format for "bitmapped font" is missing

**Status:** Further Consideration Required

**Subject:** Shared, Parts, Font Part: File format for "bitmapped font" is missing

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00012

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §15.2.13, "Font Part", pp. 159

**Related DR(s):** none

### **Nature of the Defect:**

The text “\* application/x-fontdata specifies that the font shall be stored as a bitmapped font (each glyph is stored as a raster image)” provides no description about the file format of the “bitmapped font”. It reminds of “.FNT” in MS-DOS or “.FON” file format introduced in Microsoft Windows 3.0, but there are too many mutually incompatible bitmap font formats.

### **Solution Proposed by the Submitter:**

Clarify “the bitmapped font” file format specification or remove the permission to embed “the bitmapped font”.

**Schema Change(s) Needed:** No

### **Editor's Response:**

**2009-03-24 Prague meeting:**

More investigation needed, but the problem is understood.

## 55. DR 09-0040 — WML/DML: Complex scripts

**Status:** Further Consideration Required

**Subject:** WML/DML: Complex scripts

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00013, 08-00014, 08-00015, 08-00016, 08-00017, 08-00018, 08-00019

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §17.3.2.2, “bCs (Complex Script Bold)”, pp. 281

Part 1, §17.3.2.7, “cs (Use Complex Script Formatting on Run)”, pp. 289

Part 1, §17.3.2.17, “iCs (Complex Script Italics)”, pp. 304

Part 1, §17.3.2.20, “lang (Languages for Run Content)”, pp. 304

Part 1, §17.3.2.39, “szCs (Complex Script Font Size)”, pp. 335

Part 1, §21.1.2.3.1, “cs (Complex Script Font)”, pp. 3596

Part 1, §21.1.2.3.3, “ea (East Asian Font)”, pp. 3605

**Related DR(s):** none

**Nature of the Defect:**

The coverage of "complex script", "east asian" "latin", "ascii", and "hansi" is unclear. At least, it should be made clear whether the ranges in Unicode are sufficient to determine whether a script is included

in "complex script", or it is dependent on the consumers' text rendering systems and their font resource.

In some groups (e.g., sz, szCs), the scripts are classified into 2 groups: complex and non-complex script. In other groups (e.g., bidi/easiAsia/val attributes in lang element), the scripts are classified into 3 groups: complex script, eastAsia, and latin. Also there are a few groups that the scripts are classified into 4 groups: ascii, cs, eastAsia, hAnsi. In such group, hAnsi is defined as "which does not fall into one of the three categories defined above", so the definition of complex script is important in such group.

In the case of ISO/IEC 14496-4:2004/Amd.26 (the conformance levels of OFF in MPEG stream), all OpenType layout tables are classified as complex scripts, so vertical writing mode in east Asian scripts is also classified as complex scripts.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

We need to provide more documentation.

## 56. DR 09-0041 — WML, Fonts: Font resource search

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Font resource search

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00020

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.2, “Font Substitution”, pp. 751

**Related DR(s):** none

### **Nature of the Defect:**

Regarding the priorities of the information to search an appropriate font resource for a document, there is the following note: “ISO/IEC 29500 recommends that applications looking for the closest match to the following pieces of information (in descending priority) in order to determine a suitable alternative font; however, applications are free to apply more sophisticated logic in its place:

- panose1 (§17.8.3.13)
- sig (§17.8.3.16)
- charset (§17.8.3.2)
- pitch (§17.8.3.14)
- family (§17.8.3.9)
- altName (§17.8.3.1)

This information come from Microsoft Windows GDI (the classifications in charset, pitch, family are designed to be identical with those in GDI), but the order of the priority is different from Microsoft

Windows GDI's font substitution algorithm described in Microsoft GDI Technical Article "Windows Font Mapping" (<http://msdn.microsoft.com/en-us/library/ms969909.aspx>). The remarkable difference is that "panose1" and "sig" are not used in GDI's font substitution. Therefore, the substituted fonts by ISO/IEC 29500-1 recommendation in §17.8.2 and that by existing Microsoft Office Word can be quite different. The order of the priority described in §17.8.2 should be improved to minimize the difference from GDI's font substitution algorithm.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

The character set is more important than Panose1. Potential bias against Asian character sets.

## 57. DR 09-0042 — WML, Fonts: notTrueType attribute missing from list

**Status:** Further Consideration Required

**Subject:** WML, Fonts: notTrueType attribute missing from list

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00021

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.12, “notTrueType (Raster or Vector Font)”, pp. 766

**Related DR(s):** none

**Nature of the Defect:**

These attributes are described as: “This information can be used as defined in font substitution logic to locate an appropriate substitute font when this font is not available. This information is determined by querying the font when present and shall not be modified when the font is not available.”

However, the notTrueType attribute is not in the list of attributes in §17.8.2.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

More investigation needed.

## 58. DR 09-0043 — WML, Fonts: notTrueType attribute and bitmap fonts

**Status:** Further Consideration Required

**Subject:** WML, Fonts: notTrueType attribute and bitmap fonts

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00022

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.12, “notTrueType (Raster or Vector Font)”, pp. 766

**Related DR(s):** none

**Nature of the Defect:**

ISO/IEC 14496-22 permits implementation of a font file including only bitmap and no outline (so-called "sbit font" is popular in Macintosh). It is not clear whether such bitmap-only OFF should be declared as notTrueType.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 59. DR 09-0044 — WML, Fonts: Support for commas in font family/subfamily/full names

**Status:** Closed Without Action

**Subject:** WML, Fonts: Support for commas in font family/subfamily/full names

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00023

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.1, “altName (Alternate Names for Font)”, pp. 751

**Related DR(s):** DR 09-0050 — SML, Worksheets: comma delimiter between font name and type

### Nature of the Defect:

ISO/IEC 14496-22 permits commas in font family/subfamily/full names. It should be made clear how names containing commas can be represented in a comma-delimited list.

### Solution Proposed by the Submitter:

None

### Schema Change(s) Needed:

### Editor's Response:

2009-03-24 Prague meeting:

Currently, this is not supported. Closed without change.

## 60. DR 09-0045 — WML, Fonts: Character encodings of font names

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Character encodings of font names

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00024

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.1, “altName (Alternate Names for Font)”, pp. 751

**Related DR(s):** none

### **Nature of the Defect:**

The Open Font Format described in ISO/IEC 14496-22 can include various font names in various character encodings. For example, a name table of OFF can include 2 font family names, one coded by Unicode, the other coded by ShiftJIS. It should be made clear that OOXML relies on XML parsers for encodings.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

# 61. DR 09-0046 — WML, Fonts: Misleading example

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Misleading example

**Qualifier:** Editorial defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00025

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.2, “charset (Character Set Supported By Font)”, pp. 753

**Related DR(s):** none

## Nature of the Defect:

"The charset element specifies via its characterSet attribute value of GBK that this font uses the GB-2312 character set."

The example is misleading because GBK is not identical to GB 2312. See  
<http://www.iana.org/assignments/charset-reg/GBK>.

## Solution Proposed by the Submitter:

None

## Schema Change(s) Needed:

## Editor's Response:

**2009-03-24 Prague meeting:**

Understood; more work needed. GBK is a proper superset of GB 2312.

## 62. DR 09-0047 — WML, Fonts: Identifying a face in an embedded font file

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Identifying a face in an embedded font file

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00026, 01-00027, 01-00028, 01-00029

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §17.8.3.3, "embedBold (Bold Style Font Style Embedding)", pp. 753

Part 1, §17.8.3.4, "embedBoldItalic (Bold Italic Font Style Embedding)", pp. 755

Part 1, §17.8.3.5, "embedItalic (Italic Font Style Embedding)", pp. 757

Part 1, §17.8.3.6, "embedRegular (Regular Font Style Embedding)", pp. 759

**Related DR(s):** none

**Nature of the Defect:**

Although the embedded font "file" in the package is specified by the attribute id, a "file" defined by ISO/IEC 14496-22 can include multiple faces by TrueType Collection (TTC) file format. So, the procedure to identify a face in an embedded font file in the package should be described.

**Solution Proposed by the Submitter:**

There are 3 scenarios:

1. Forbid the TTC file format; only TTF or OTF file formats including single face are permitted. A document producer has to convert TTC to TTF when it embeds a font into OOXML.
2. Use name or altName in the root element to select a face from an embedded TTC.
3. Add a new attribute to specify a face in TTC.

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 63. DR 09-0048 — WML, Fonts: Panose-1 classification mechanism missing

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Panose-1 classification mechanism missing

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00030

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.8.3.13, “panose1 (Panose-1 Typeface Classification Number)”, pp. 767

**Related DR(s):** none

### Nature of the Defect:

The first sentence is: "This element specifies the Panose-1 classification number for the current font using the mechanism defined in 4.2.7.17 of ISO/IEC 14496-22:2007." However, 4.2.7.17 of ISO/IEC 14496-22 does not provide any such mechanism.

### Solution Proposed by the Submitter:

Change this sentence to the following: "This element specifies the Panose-1 classification number shown in 4.2.7.17 of ISO/IEC 14496-22:2007." It might be a good idea to reference to the original Panose specification, available at <http://www.panose.com>.

### Schema Change(s) Needed:

### Editor's Response:

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 64. DR 09-0049 — WML, Fields: SYMBOL switch proper charset name usage

**Status:** Further Consideration Required

**Subject:** WML, Fields: SYMBOL switch proper charset name usage

**Qualifier:** Editorial defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00024

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.16.5.61, "SYMBOL", pp. 1391.

**Related DR(s):** none

**Nature of the Defect:**

"\j Interprets text in field-argument as the value of a SHIFT-JIS character". "SHIFT-JIS" should be replaced by Windows-31J, which is an IANA charset name.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

None

## 65. DR 09-0050 — SML, Worksheets: comma delimiter between font name and type

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Worksheets: comma delimiter between font name and type

**Qualifier:** Technical Defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00032

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.3.1.39, “evenHeader”, pp. 1804

**Related DR(s):** none

**Nature of the Defect:**

Re & "font name,font type", since ISO/IEC 14496-22 permits commas in font family/subfamily/full names, it is not clear which "," is the delimiter between the font name and font type.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Change DR qualifier to “Technical Defect”, write text to say that “the lexically first comma is the one recognized as the delimiter”. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1, §18.3.1.39, "evenHeader", pp. 1804

*&"font name,font type"* - code for "text font name" and "text font type", where *font name* and *font type* are strings specifying the name and type of the font, separated by a comma. When a hyphen appears in *font name*, it means "none specified". Both of *font name* and *font type* can be localized values. [Although ISO/IEC 14496-22 permits commas in font family/subfamily/full names, name and font type, the lexically first comma in the string is the one recognized as the separating comma.](#)

## 66. DR 09-0051 — SML, Shared String Table: charset value duplicate

**Status:** Closed; will be incorporated in AMD1.

**Subject:** SML, Shared String Table: charset value duplicate

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00033

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.4.1, "charset (Character Set)", pp. 1898

**Related DR(s):** none

**Nature of the Defect:**

There are two entries, namely "HANGUEL\_CHARSET" and "HANGUL\_CHARSET", for the integer value 129.

**Solution Proposed by the Submitter:**

Remove one of them.

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Remove "HANGUEL\_CHARSET". Closed.

The solution to this DR should be published in an Amendment.

The exact changes are as follows:

Part 1, §18.4.1, “charset (Character Set)”, pp. 1898

INT Value	Character Set
...	...
129	HANGEUL_CHARSET
129	HANGUL_CHARSET
...	...

## 67. DR 09-0052 — SML, Styles: family attribute range issue

**Status:** Further Consideration Required

**Subject:** SML, Styles: family attribute range issue

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00034

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.8.18, “family (Font Family)”, pp. 1952

**Related DR(s):** none

**Nature of the Defect:**

The attribute description allows integer values ranging from 0–255, while the table allows values ranging from 0–5 only.

Ideally, as in WordprocessingML (§17.8.3.9), use the simple type ST\_FontFamily, shown in §17.18.30. If this is not possible, the attribute value should be restricted.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

None

## 68. DR 09-0053 — PML, Presentation: Attribute name pitchFamily is misleading

**Status:** Further Consideration Required

**Subject:** PML, Presentation: Attribute name pitchFamily is misleading

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00035

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §19.2.1.13, “font (Embedded Font Name)”, pp. 2769

**Related DR(s):** none

**Nature of the Defect:**

The attribute name pitchFamily is misleading. It should be pitchAndFamily.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

A prose change explaining this attribute is preferred to changing the name of the attribute. Will propose wording.

## 69. DR 09-0054 — DML, run formatting: Attribute name pitchFamily is misleading

**Status:** Further Consideration Required

**Subject:** PML, run formatting: Attribute name pitchFamily is misleading

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00036, 08-00037, 08-00038, 08-00039, 08-00040

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §21.1.2.3.1, “cs (Complex Script Font”, pp. 3596

Part 1, §21.1.2.3.3, “ea (East Asian Font)”, pp. 3605

Part 1, §21.1.2.3.7, “latin (Latin Font)”, pp. 3613

Part 1, §21.1.2.3.10, “sym (Symbol Font)”, pp. 3622

Part 1, §21.1.2.4.6, “buFont (Specified)”, pp. 3636

**Related DR(s):** none

**Nature of the Defect:**

The attribute name pitchFamily is misleading. It should be pitchAndFamily.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

A prose change explaining this attribute is preferred to changing the name of the attribute. Will propose wording.

## 70. DR 09-0055 — PML, Presentation: Type of the attribute pitchFamily is too loose

**Status:** Further Consideration Required

**Subject:** PML, Presentation: Type of the attribute pitchFamily is too loose

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00041

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §19.2.1.13, “font (Embedded Font Name)”, pp. 2769

**Related DR(s):** none

### **Nature of the Defect:**

The type of the attribute pitchFamily is defined as "W3C XML Schema byte datatype", but that is too loose. Provide an enumerated list or the union of ranges 00–02, 10–12, 20–22, 30–32, 40–42, and 50–52. Observe that the higher 4 bits, which represents the typeface family (see §17.8.3.9 of WordprocessingML), must be 0x0–0x5, and that the lower 4 bits, which represents the pitch (see §17.8.3.14 of WordprocessingML), must be 0x0–0x2.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

# 71. DR 09-0056 — DML, Main: Type of the attribute pitchFamily is too loose

**Status:** Further Consideration Required

**Subject:** DML, Main: Type of the attribute pitchFamily is too loose

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00042, 08-00043, 08-00044, 08-00045, 08-00046

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

## IS 29500 Reference(s):

Part 1, §21.1.2.3.1, “cs (Complex Script Font)”, pp. 3596

Part 1, §21.1.2.3.3, “ea (East Asian Font)”, pp. 3605

Part 1, §21.1.2.3.7, “font (Embedded Font Name)”, pp. 3613

Part 1, §21.1.2.3.10, “sym (Symbol Font)”, pp. 3622

Part 1, §21.1.2.4.6, “buFont (Specified)”, pp. 3636

## Related DR(s): none

## Nature of the Defect:

The type of the attribute pitchFamily is defined as "W3C XML Schema byte datatype", but that is too loose. Provide an enumerated list or the union of ranges 00–02, 10–12, 20–22, 30–32, 40–42, and 50–52. Observe that the higher 4 bits, which represents the typeface family (see §17.8.3.9 of WordprocessingML), must be 0x0–0x5, and that the lower 4 bits, which represents the pitch (see §17.8.3.14 of WordprocessingML), must be 0x0–0x2.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 72. DR 09-0057 — PML, Presentation: Allow aliases as values for attribute typeface

**Status:** Further Consideration Required

**Subject:** PML, Presentation: Allow aliases as values for attribute typeface

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00047

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §19.2.1.13, “font (Embedded Font Name)”, pp. 2769

**Related DR(s):** none

### **Nature of the Defect:**

The attribute typeface can be used for selecting an alternate font. However, unlike the attribute altName of WordprocessingML (§17.8.3.1), this attribute cannot specify aliases as attribute values.

### **Solution Proposed by the Submitter:**

Allow typeface to specify aliases.

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 73. DR 09-0058 — DML, Main: Possible values of attribute script are unclear

**Status:** Further Consideration Required

**Subject:** DML, Main: Possible values of attribute script are unclear

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00048

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §20.1.4.1.16, “font (Font)”, pp. 3105

**Related DR(s):** none

### **Nature of the Defect:**

The attribute script is very unclear. What is the value of this attribute? We can imagine four possibilities:

1. ISO 15924 script names. Also the extra attribute to interchange ISO 639 language code is expected.
2. Open Font Format 4-byte script tags defined in §5.4.1 of ISO/IEC 14496-22. Also the extra attribute to interchange Open Font Format 4-byte language tags (§5.4.2 of ISO/IEC 14496-22) is expected.
3. ST\_Lang defined in ISO/IEC 29500-1, §22.9.2.6.
4. Unicode subrange specifications like ISO/IEC 29500-1, §17.8.3.16.

The examples shown in §20.1.4.1.24 and §20.1.4.1.25 suggest Option 1. However, Option 2 is most appropriate, since the value can easily be extracted from concrete font files, and we can search for compatible fonts from the given attribute.

### **Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 74. DR 09-0059 — DML, Main: Relationship between the symbol font and Symbol character set

**Status:** Further Consideration Required

**Subject:** DML, Main: Clarify relationship between the symbol font and Symbol character set

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00049

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §21.1.2.3.10, “sym (Symbol Font)”, pp. 3622

**Related DR(s):** none

### **Nature of the Defect:**

The relationship between the symbol font and Symbol character set (used in the charset attribute description) is unclear. Are they expected to be identical?

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-03-24 Prague meeting:**

Understood; more work needed.

## 75. DR 09-0060 — WML, Fonts: Names should be registered at IANA

**Status:** Further Consideration Required

**Subject:** WML, Fonts: Names should be registered at IANA

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00050

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 4, §9.4.1.1, “Additional attribute for charset element”, pp. 28

**Related DR(s):** none

### **Nature of the Defect:**

In comparison with IANA names listed in <http://www.iana.org/assignments/character-sets>, the table includes many names which are not registered in IANA. Also some entries are described with incorrect IANA names.

### **Solution Proposed by the Submitter:**

1. 0x80: shift\_jis should be replaced by Windows-31J.
2. 0x81: Microsoft Windows Codepage 949 should be registered in IANA, and use the name in the description.
3. 0x82: Microsoft Windows Codepage 1361 should be registered in IANA and use the name in the description.
4. 0x86: GB2312 should be replaced by GBK.
5. 0x88: Microsoft Windows Codepage 950 should be registered in IANA, and use the name in the description, because there are various Big5 diversions.

6. 0xDE: windows-874 is not registered in IANA. It should be registered.

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Apparently, this is clean-up from the BRM where it was agreed that code pages names should be replaced.

## 76. DR 09-0061 — Shared MLs, Shared Simple Types: Constrain ST\_Panose value set

**Status:** Further Consideration Required

**Subject:** Shared MLs, Shared Simple Types: Constrain ST\_Panose value set

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00051

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §22.9.2.8, "ST\_Panose (Panose-1 Number)", pp. 4326

**Related DR(s):** none

### Nature of the Defect:

ST\_Panose is declared as unrestricted 20 hexadecimal digits. According to the official definition of Panose-1 (<http://www.panose.com/ProductsServices/pan1.aspx>) the valid Panose number has a more restricted range (in most cases, 0–10).

### Solution Proposed by the Submitter:

ST\_Panose should be declared as the type which permits the valid number only.

**Schema Change(s) Needed:** Yes, (which?)

Replace Panose-1 type definition with something like the following:

```
<xsd:simpleType name="Panose1">
```

```
<xsd:restriction base="xsd:string">
 <xsd:pattern value="\s*[\s0]?2\s*[\s0]?[0-9A-Fa-f]\s*[\s0]?[0-
9ABab]\s*[\s0]?[0-9]\s*[\s0]?[0-9]\s*[\s0]?[0-9Aa]\s*0?[0-9ABab]\s*[\s0]?[0-9A-
Fa-f]\s*[\s0]?[0-9A-Da-d]\s*[\s0]?[0-7]\s*"/>
</xsd:restriction>
</xsd:simpleType>
```

The interpretation of the numerical values of Panose-1 in Windows GDI is different from genuine Panose-1 definition. The definition in above restricts the scope to the values that genuine Panose-1 definition and Windows GDI interpretation are consistent.

**Editor's Response:**

**2009-03-24 Prague meeting:**

Can we still continue to use the xsd:hexBinary type and use the proposed regular expression?

## 77. DR 09-0062 — WML, Settings: Semantics of short file names

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Settings: Semantics of short file names

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00052, 08-00053

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):**

Part 1, §17.15.2, "Web Page Settings", pp. 1219

Part 1, §17.15.2.13, "doNotUseLongFileNames", pp. 1237

Part 1, §17.15.2.46, "webSettings (Web pp. Settings)", pp. 1288

**Related DR(s):** none

**Nature of the Defect:**

The doNotUseLongFileNames element specifies that applications should ensure that all file names generated when this document is subsequently saved as a web page do not exceed the 8.3 character file name limitation.

Also it should be clarified if the file names are case sensitive or not.

**Solution Proposed by the Submitter:**

This feature is supposed to be introduced for the short file names on FAT file system; therefore, "8.3 characters" should be 8.3 octets.

### **Schema Change(s) Needed:**

#### **Editor's Response:**

##### **2009-03-24 Prague meeting:**

Adopted the proposed solution and added text saying that short names are not case-sensitive. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1, §17.15.2, "Web Page Settings", pp. 1219

[*Example:* Consider the following WordprocessingML fragment for the web page settings in a WordprocessingML document:

...

The webSettings element contains all of the web page settings for this document. In this case, the web page settings specified for this document are: a frameset defined using the frameset element (§xx); and a setting specifying that when this file is saved as a web page, all resulting files must not exceed 8.3 ~~characters~~octets in length using the doNotUseLongFileNames element (§xx). *end example*]

Part 1, §17.15.2.13, "doNotUseLongFileNames", pp. 1237

This element specifies that applications shall ensure that the file names for all files generated when saving this document as a web page do not exceed eight ~~characters~~octets with a three ~~character~~octet extension. This includes all supporting files (images which are part of this HTML web page, etc.). The file names generated are not case-sensitive.

[*Example:* Consider a WordprocessingML document which contains the following content within the web settings part:

...

The doNotUseLongFileNames element specifies that applications should ensure that all file names generated when this document is subsequently saved as a web page do not exceed the 8.3 ~~character~~octet file name limitation. *end example*]

Part 1, §17.15.2.46, "webSettings (Web Page Settings)", pp. 1288

[*Example:* Consider the following WordprocessingML fragment for the web page settings in a WordprocessingML document:

...

The webSettings element contains all of the web page settings for this document. In this case, the web page settings specified for this document are: a frameset defined using the frameset element (§xx); and a setting specifying that when this file is saved as a web page, all resulting files must not exceed 8.3 ~~characters~~octets in length using the doNotUseLongFileNames element (§xx). *end example*]

## 78. DR 09-0063 — WML, Fields: Form Field Properties length

**Status:** Further Consideration Required

**Subject:** WML, Fields: Form Field Properties length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00055

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.16.17, “ffData (Form Field Properties)”, pp. 1412

**Related DR(s):** none

**Nature of the Defect:**

“... a maximum character length of 10 characters via the maxLength element”

If the length is counted by the octet instead of the Unicode character, it should be stated, because the length is quite short.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Still not sure of the units.

## 79. DR 09-0064 — WML, Simple Types: ST\_FFHelpTextVal length

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: ST\_FFHelpTextVal length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00056

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.18.25, "ST\_FFHelpTextVal", pp. 1534

**Related DR(s):** none

### **Nature of the Defect:**

This simple type's contents have a maximum length of 256 characters.

If the length is counted by the octet instead of the Unicode character, it should be stated, because the length is rather short for a help text.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

### **2009-03-24 Prague meeting:**

Still not sure of the units.

## 80. DR 09-0065 — WML, Simple Types: ST\_FFName length

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: ST\_FFName length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00057

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.18.26, ST\_FFName, pp. 1535

**Related DR(s):** none

**Nature of the Defect:**

This simple type's contents have a maximum length of 65 characters.

If the length is counted by the octet instead of the Unicode character, it should be stated, because the length is rather short.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Still not sure of the units.

# 81. DR 09-0066 — WML, Simple Types: ST\_MacroName length

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: ST\_MacroName length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00058

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.18.51, "ST\_MacroName", pp. 1563

**Related DR(s):** none

## **Nature of the Defect:**

This simple type's contents have a maximum length of 33 characters.

If the length is counted by the octet instead of the Unicode character, it should be stated, because the length is rather short.

## **Solution Proposed by the Submitter:**

None

## **Schema Change(s) Needed:**

## **Editor's Response:**

## **2009-03-24 Prague meeting:**

Still not sure of the units.

## 82. DR 09-0067 — SML, Workbook: Semantics of short file names

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Workbook: Semantics of short file names

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00059

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.2.24, "webPublishing", pp. 1736

**Related DR(s):** none

### **Nature of the Defect:**

longFileNames (Enable Long File Names) attribute: Specifies a boolean value that indicates whether the application allows file names longer than 8 characters for Web pages.

Also the case sensitive or not should be clarified.

### **Solution Proposed by the Submitter:**

This feature is supposed to be introduced for the short file names on FAT file system; therefore, "8.3 characters" should be 8.3 octets.

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-03-24 Prague meeting:**

Adopted the proposed solution and added text saying that short names are not case-sensitive. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1, §18.2.24, “webPublishing”, pp. 1736

Attributes	Description
longFileNames (Enable Long File Names)	<p>Specifies a boolean value that indicates whether the application allows file names longer than 8 <del>characters</del><ins>octets</ins> for Web pages. <a href="#">File names are not case-sensitive</a>.</p> <p>The possible values for this attribute are defined by the W3C XML Schema boolean datatype.</p>

## 83. DR 09-0068 — SML, Styles: name attribute length

**Status:** Further Consideration Required

**Subject:** SML, Styles: name attribute length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00060

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.8.29, “name (Font Name)”, pp. 1965

**Related DR(s):** none

**Nature of the Defect:**

“The string length for this attribute shall be 0 to 31 characters.”

If the length is counted by the octet instead of the Unicode character, it should be stated, because the length is quite short.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

62 octets.

IS 29500:2008 Defect Report Log

## 84. DR 09-0069 — SML, Pivot Tables: longText attribute length

**Status:** Further Consideration Required

**Subject:** SML, Pivot Tables: longText attribute length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00061

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §18.10.1.90, “sharedItems (Shared Items)”, pp. 2164

**Related DR(s):** none

**Nature of the Defect:**

“longText (Long Text) attribute: A string is considered long if it is over 255 characters. A value of 1 or true indicates the value contains more than 255 characters of text. A value of 0 or false indicates the value contains less than 255 characters. [Note: This is used as many legacy spreadsheet application support a limit of 255 characters for text values. end note]

If the length is counted by the octet instead of the Unicode character, it should be stated. Also it should be stated whether the assumed legacy spreadsheet applications can handle Unicode text.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

510 octets

## 85. DR 09-0070 — PML, Presentation: modifyVerifier password length

**Status:** Further Consideration Required

**Subject:** PML, Presentation: modifyVerifier password length

**Qualifier:** Request for clarification

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00062

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §19.2.1.19, “modifyVerifier (Modification Verifier)”, pp. 2774

**Related DR(s):** none

### **Nature of the Defect:**

“The password supplied to the algorithm is to be a UTF-16LE encoded string; strings longer than 255 characters are truncated to 255 characters. If there is a leading BOM character (U+FEFF) in the encoded password it is removed before hash calculation.”

If the surrogate pair is counted as 2 characters, it should be stated.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

**2009-02-16 Shawn Villaron:**

This issue deals with some ambiguity associated with the length of the supplied password in PresentationML. The current text states the following:

The password supplied to the algorithm is to be a UTF-16LE encoded string; strings longer than 255 characters are truncated to 255 characters. If there is a leading BOM character (U+FEFF) in the encoded password it is removed before hash calculation.

The question relates to the meaning of "longer than 255 characters." I believe that the intent of this limitation is to support up to 510 bytes.

I'm curious as to how everyone thinks we should rephrase things. Do we think that this updated text would suffice addressing this issue:

The password supplied to the algorithm is to be a UTF-16LE encoded string; strings longer than 510 bytes are truncated to 510 bytes. If there is a leading BOM character (U+FEFF) in the encoded password it is removed before hash calculation.

Do we think we need more information here?

**2009-02-16 MURATA Makoto:**

I support the idea of replacing "255 characters" with "510 bytes". Although "255 characters" are actually correct, some people will think that a surrogate pair is a single character and thus misinterpret this sentence.

**2009-02-17 Jesper Lund Stockholm:**

I agree. The sentence is quite specific in terms of "UTF16LE"-encoding and using the (layman's) term "characters" is a bit confusing. Using 510 /bytes/ would be in line with the "level" of the rest of the paragraph.

**2009-02-17 MURATA Makoto:**

Oops, we are a part of ISO. We should use "octet" rather than "byte", since a byte is not always 8 bits. ISO/IEC 10646 uses "octet".

**2009-02-18 Shawn Villaron:**

Thanks. I was wondering if we should add an additional constraint regarding the number of octets. For example, what do we think about this text:

The password supplied to the algorithm is to be a UTF-16LE encoded string; strings longer than 510 octets are truncated to 510 octets. Further, the number of octets should be evenly divisible by the size of the octets of the character in the target octet set. If there is a leading BOM character (U+FEFF) in the encoded password it is removed before hash calculation.

Does this add any value?

**2009-03-24 Prague meeting:**

Adopted the proposed solution. Closed.

The solution to this DR should be published in a Technical Corrigendum.

## 86. DR 09-0071 — WML, Simple Types: Katakana enumeration examples

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: Katakana enumeration examples

**Qualifier:** Technical defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00063

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-01-28

**Deadline for Response from Editor:** 2009-03-28

**IS 29500 Reference(s):** Part 1, §17.18.59, "ST\_NumberFormat (Numbering Format)", pp. 1572, 1573

**Related DR(s):** none

**Nature of the Defect:**

aiveoFullWidth (AIUEO Order Full-Width Katakana) and aiveo (AIUEO Order Half-Width Katakana) are incorrect.

The original spec mentioned repeating a set of characters like ?, ?, ?, ..., ?, ?, ??, ??, ??, ...; it is incorrect. Expected order is simply to repeat a set of characters (values 1–46) again from the beginning of the values; e.g., ?, ?, ?, ..., ?, ?, ?, ?, ?, ....

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

If the proposed solution is adopted, this becomes a technical change as the Description column of the table entry needs to be changed, as well as the example at its end.

**2009-03-24 Prague meeting:**

It appears that after one pass through the syllabary, the characters are used again from the start rather than appending a duplicate character.

## 87. DR 09-0072 — WML, Simple Types: ST\_BrClear terminology usage

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Simple Types: ST\_BrClear terminology usage

**Qualifier:** Request for clarification

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00064, 08-00065

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-05

**Deadline for Response from Editor:** 2009-04-05

**IS 29500 Reference(s):** Part 1, §17.18.3, "ST\_BrClear (Line Break Text Wrapping Restart Location)", pp. 1508

**Related DR(s):** none

**Nature of the Defect:**

In the description of the "left" value and "right" values, the words "type" and "style" are used indiscriminately. There should be a unified terminology.

**Solution Proposed by the Submitter:**

We suggest using the word "type".

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Editor to show exact wording changes. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1, §17.18.3, "ST\_BrClear (Line Break Text Wrapping Restart Location)", pp. 1508–1509

Enumeration Value	Description
left (Restart In Next Text Region Left to Right)	<p>Specifies that the text wrapping break shall behave as follows when this line intersects a floating object:</p> <p>If the parent paragraph is left-to-right:</p> <ul style="list-style-type: none"> <li>• If this is the leftmost region of text flow currently on this line,           <ul style="list-style-type: none"> <li>• If a floating object occurs to the left of the break, treat this as a break of type all.</li> <li>• Otherwise, advance the text to the next position on the line where text can be displayed</li> </ul> </li> <li>• Otherwise, treat this as a text wrapping break of <b>styletype</b> none.</li> </ul> <p>If the parent paragraph is right to left:</p> <ul style="list-style-type: none"> <li>• If the object occurs to the left of the break, treat this as a break of <b>styletype</b> all.</li> <li>• Otherwise, treat this as a text wrapping break of type none.</li> </ul> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of <b>styletype</b> none.</p>

Enumeration Value	Description
right (Restart In Next Text Region Right to Left)	<p>Specifies that the text wrapping break shall behave as follows when this line intersects a floating object:</p> <p>If the parent paragraph is left-to-right:</p> <ul style="list-style-type: none"> <li>• If the object occurs to the right of the break, treat this as a break of <a href="#">styletype</a> all.</li> <li>• Otherwise, treat this as a text wrapping break of <a href="#">styletype</a> none.</li> </ul> <p>If the parent paragraph is right to left:</p> <ul style="list-style-type: none"> <li>• If this is the rightmost region of text flow currently on this line, <ul style="list-style-type: none"> <li>• If a floating object occurs to the right of the break, treat this as a break of <a href="#">styletype</a> all.</li> <li>• Otherwise, advance the text to the next position on the line where text can be displayed</li> </ul> </li> <li>• Otherwise, treat this as a text wrapping break of <a href="#">styletype</a> none.</li> </ul> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of <a href="#">styletype</a> none.</p> <p>If the parent paragraph is right to left, then these behaviors are also reversed.</p> <p><i>[Note: This break type is used to control the text wrapping on the right side of a floating image without preventing text from appearing on the opposite side. end note]</i></p>

## 88. DR 09-0073 — WML, Simple Types: ST\_BrClear extraneous text

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Simple Types: ST\_BrClear extraneous text

**Qualifier:** Editorial defect

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00066, 08-00067

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-05

**Deadline for Response from Editor:** 2009-04-05

**IS 29500 Reference(s):** Part 1, §17.18.3, "ST\_BrClear (Line Break Text Wrapping Restart Location)", pp. 1509

**Related DR(s):** none

**Nature of the Defect:**

In the description of the "right" value, the sentence "If the parent paragraph is right to left, then these behaviors are also reversed." seems to be a left-over of the previous version, as is the note.

**Solution Proposed by the Submitter:**

Remove this sentence and the note.

**Schema Change(s) Needed:**

**Editor's Response:**

**2009-03-24 Prague meeting:**

Agreed with the proposed solution. Closed.

The solution to this DR should be published in a Technical Corrigendum.

The exact changes are as follows:

Part 1, §17.18.3, "ST\_BrClear (Line Break Text Wrapping Restart Location)", pp. 1508–1509

Enumeration Value	Description
right (Restart In Next Text Region Right to Left)	<p>Specifies that the text wrapping break shall behave as follows when this line intersects a floating object:</p> <p>If the parent paragraph is left-to-right:</p> <ul style="list-style-type: none"> <li>• If the object occurs to the right of the break, treat this as a break of style all.</li> <li>• Otherwise, treat this as a text wrapping break of style none.</li> </ul> <p>If the parent paragraph is right to left:</p> <ul style="list-style-type: none"> <li>• If this is the rightmost region of text flow currently on this line, <ul style="list-style-type: none"> <li>• If a floating object occurs to the right of the break, treat this as a break of style all.</li> <li>• Otherwise, advance the text to the next position on the line where text can be displayed</li> </ul> </li> <li>• Otherwise, treat this as a text wrapping break of style none.</li> </ul> <p>In either case, if this line does not intersect a floating object, then treat this break as a text wrapping break of style none.</p> <p><i>If the parent paragraph is right to left, then these behaviors are also reversed.</i></p> <p><i>[Note: This break type is used to control the text wrapping on the right side of a floating image without preventing text from appearing on the opposite side. end note]</i></p>

## 89. DR 09-0074 — WML, Simple Types: ST\_TextDirection direction of rotation

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: ST\_TextDirection direction of rotation

**Qualifier:** Request for clarification

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00068

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-05

**Deadline for Response from Editor:** 2009-04-05

**IS 29500 Reference(s):** Part 1, §17.18.93, "ST\_TextDirection (Text Flow Direction)", pp. 1665

**Related DR(s):** none

**Nature of the Defect:**

The description for value 1rV says "This flow is also rotated such that text which is not in an East Asian script is rotated 90 degrees when displayed on a page" but does not say if it is rotated clockwise or counter-clockwise.

**Solution Proposed by the Submitter:**

Specify the direction of the rotation.

**Schema Change(s) Needed:**

**Editor's Response:**

None

## 90. DR 09-0075 — WML, Simple Types: ST\_TextDirection conflict between attribute values

**Status:** Further Consideration Required

**Subject:** WML, Simple Types: ST\_TextDirection conflict between attribute values

**Qualifier:** Request for clarification

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00069

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-05

**Deadline for Response from Editor:** 2009-04-05

**IS 29500 Reference(s):** Part 1, §17.18.93, "ST\_TextDirection (Text Flow Direction)", pp. 1666

**Related DR(s):** none

**Nature of the Defect:**

The description for value r1v says "text which is in an East Asian script is rotated". The discrepancy with the description of lrv (for which East Asian script is **not** rotated) seems to indicate that at least one of them is in error.

**Solution Proposed by the Submitter:**

Check the two descriptions and fix whatever needs fixing.

**Schema Change(s) Needed:**

**Editor's Response:**

None

# 91. DR 09-0076 — Part 1: Trivial Editorial Defects

**Status:** Closed; will be incorporated in COR1

**Subject:** Part 1: Trivial Editorial Defects

**Qualifier:** Editorial defect

**Submitter:** Project Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** None

**Supporting Document(s):** None

**Date Circulated by Secretariat:** 2009-02-08

**Deadline for Response from Editor:** 2009-04-08

**IS 29500 Reference(s):** Part 1, numerous clauses and subclauses on various pages

**Related DR(s):** none

**Nature of the Defect:**

See below under "Solution"

**Solution Proposed by the Submitter:**

1. Part 1, §4, "Terms and Definitions", pp. 12.  
[Note: This part uses OPC-related terms, which are defined in ISO/IEC 29500-2. *end note*]
2. Part 1, §7, "General Description", pp. 16, Numbered list item 4: The numbers in "clauses 17–23" are not actual hyperlinked forward references, and should be.
3. Part 1, §8.1, "Packages and Parts", pp. 17. First paragraph, final (parenthesized) sentence.  
(Packages are discussed further in ISO/IEC 29500-2.)
4. Part 1, §9.2, "Relationships in Office Open XML", pp. 23.  
All other relationships are implicit. [Note: ... *end note*].
5. Part 1, §10.1.2, "Office Open XML Native Extensibility Constructs", pp. 28.  
See the reference material in §17–23 ...

6. Part 1, §17.16.1, "Syntax", pp. 1301.

numbering=<blank line>"LISTNUM", [field-argument] | ...

**Schema Change(s) Needed:** None

**Editor's Response:**

Accepted

## 92. DR 09-0077 — Schemas, RELAX NG: Error in Theme Override Part

**Status:** Closed; will be incorporated in COR1

**Subject:** RELAX NG Schema error in Theme Override Part

**Qualifier:** Editorial Defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00070

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §B.4.1.1.3, "Theme Override Part", pp. 4875, schema line 10; Part 4, §B.4.1.1.3, "Theme Override Part", pp. 1379, schema line 11.

**Related DR(s):** none

**Nature of the Defect:**

a\_theme in the RELAX NG Schema for the part "Theme Override Part"  
(DrawingML\_Theme\_Override.rnc) should be a\_themeOverride.

**Solution Proposed by the Submitter:**

See above.

**Schema Change(s) Needed:** Yes

**Editor's Response:**

Agreed

The exact changes are as follows:

Part 1, §B.4.1.1.3, “Theme Override Part”, pp. 4875, schema line 10

`start = a_themeOverride`

Part 4, §B.4.1.1.3, “Theme Override Part”, pp. 1379, schema line 11

`start = a_themeOverride`

## 93. DR 09-0078 — Schemas, RELAX NG: Schema missing

**Status:** Closed; will be incorporated in COR1

**Subject:** RELAX NG Schema missing

**Qualifier:** Editorial defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00071

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 4, §B.2.1, “Part Schemas”, pp. 1301

**Related DR(s):** none

### **Nature of the Defect:**

The schema for the VML Drawing Part (§8.1, Part 4) is missing.

### **Solution Proposed by the Submitter:**

Add the following schema, SpreadsheetML\_VML\_Drawing.rnc:

```
include "wml.rnc"
include "shared-relationshipReference.rnc"
include "dml-wordprocessingDrawing.rnc"
include "dml-main.rnc"
include "dml-diagram.rnc"
include "shared-commonSimpleTypes.rnc"
include "dml-lockedCanvas.rnc"
include "any.rnc"
include "dml-chart.rnc"
```

```

include "dml-chartDrawing.rnc"
include "dml-picture.rnc"
include "dml-compatibility.rnc"
include "vml-presentationDrawing.rnc"
include "xml.rnc"
include "shared-customXmlSchemaProperties.rnc"
include "vml-officeDrawing.rnc"
include "vml-main.rnc"
include "vml-spreadsheetDrawing.rnc"
include "vml-wordprocessingDrawing.rnc"
include "shared-math.rnc"
start = element xml {(vml-main | vml-officeDrawing | vml-spreadsheetDrawing | vml-presentationDrawing)* }

vml-main =
v_shape
| v_shapetype
| v_group
| v_background
| v_fill
| v_formulas
| v_handles
| v_imagedata
| v_path
| v_textbox
| v_shadow
| v_stroke
| v_textpath
| v_arc
| v_curve
| v_image
| v_line
| v_oval
| v_polyline
| v_rect
| v_roundrect

vml-officeDrawing =
o_shapedefaults
| o_shapelayout
| o_signatureline
| o_ink
| o_diagram

```

```

| o_equationxml
| o_skew
| o_extrusion
| o_callout
| o_lock
| o_OLEObject
| o_complex
| o_left
| o_top
| o_right
| o_bottom
| o_column
| o_clippath
| o_fill

vml-wordprocessingDrawing =
w10_bordertop
| w10_borderleft
| w10_borderright
| w10_borderbottom
| w10_wrap
| w10_anchorlock

vml-spreadsheetDrawing = x_ClientData

vml-presentationDrawing = pvm1_iscomment | pvm1_textdata

```

**Schema Change(s) Needed:** Yes

**Editor's Response:**

Agreed

The exact changes are as follows:

Part 4, §B.2.1, “Part Schemas”, pp. 1301

Add the missing schema SpreadsheetML\_VML\_Drawing.rnc, whose contents are shown above.

## 94. DR 09-0079 — Schemas, RELAX NG: Error in PML

**Status:** Closed; will be incorporated in COR1

**Subject:** RELAX NG Schema error in PML

**Qualifier:** Editorial defect

**Submitter:** JISC

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00072

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §B.3, "PresentationML", pp. 4818; Part 4, §B.3, "PresentationML", pp. 1319

**Related DR(s):** none

### Nature of the Defect:

Two parameters of the same name "minInclusive" appear in the definition of p\_ST\_SlideSizeCoordinate.

```
p_ST_SlideSizeCoordinate =
 xsd:int {
 minInclusive = "0"
 minInclusive = "914400"
 maxInclusive = "51206400"
 }
```

### Solution Proposed by the Submitter:

Delete the line minInclusive = "0".

**Schema Change(s) Needed:** Yes

**Editor's Response:**

Agreed

The exact changes are as follows:

Part 1, §B.3, "PresentationML", pp. 4818, line 606

```
p_ST_SlideSizeCoordinate =
 xsd:int {
 minInclusive = "0"
 minInclusive = "914400"
 maxInclusive = "51206400"
 }
```

Part 4, §B.3, "PresentationML", pp. 1319, line 621

```
p_ST_SlideSizeCoordinate =
 xsd:int {
 minInclusive = "0"
 minInclusive = "914400"
 maxInclusive = "51206400"
 }
```

## 95. DR 09-0080 — General: Unintended underscore characters in text

**Status:** Closed; will be incorporated in COR1

**Subject:** Unintended underscore characters in text

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-4

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.2.1 (pp. 193), §17.3.4 (pp. 386), §17.6.2 (pp. 617), §17.6.7 (pp. 632), §17.6.15 (pp. 655), §17.6.21 (pp. 673), §17.13.4.2 (pp. 905), §17.16.5 (pps. 1340, 1341, 1342, 1343), §17.18.59 (pps. 1574, 1587, 1590, 1591, 1592, 1613), §18.2.3 (pps. 1709, 1710), §18.3.1.40 (pp. 1806), §18.3.1.85 (pp. 1870), §18.10.1.73 (pps. 2142, 2146), §18.14.11 (pp. 2251), §18.17.7.2 (pps. 2306, 2307), §18.17.7.66 (pp. 2385), §18.17.7.74 (pp. 2393), §18.17.7.76 (pp. 2397), §18.17.7.298 (pp. 2605), §19.5.46 (pp. 2921), §19.5.63 (pps. 2936, 2937), §19.5.68 (pp. 2942), §19.5.70 (pp. 2943), §20.1.2.2.32 (pp. 3044), §20.1.3.7 (pp. 3089), §21.1.2.2.2 (pps. 3569, 3570 (in Arabic example)), §21.1.2.2.7 (pps. 3590, 3591 (in Arabic example)), §21.1.2.4.13 (pps. 3651, 3652 (in Arabic example)), §21.1.2.4.14 (pps. 3660, 3661 (in Arabic example)), §21.1.2.4.15 (pps. 3669, 3669 (in Arabic example)), §21.1.2.4.16 (pps. 3677, 3678 (in Arabic example)), §21.1.2.4.17 (pps. 3686, 3686 (in Arabic example)), §21.1.2.4.18 (pp. 3694, 3695 (in Arabic example)), §21.1.2.4.19 (pps. 3703, 3703 (in Arabic example)), §21.1.2.4.20 (pps. 3711, 3712 (in Arabic example)), §21.1.2.4.21 (pps. 3720, 3720 (in Arabic example)),

**Related DR(s):** none

**Nature of the Defect:**

As a result of incorporation of revised text from Ecma responses to NB comments that were agreed at the BRM a number of unintended underscore characters remain in the text, coloured blue.

**Solution Proposed by the Submitter:**

Remove blue underscore formatting where indicated.

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §17.2.1 (pp. 193), “color (Background Color)”

Change “*... end example]*.RGB ...” to “*... end example]*. RGB ...”

Part 1, §17.3.4 (pp. 388), “themeShade (Border Theme Color Shade)”

Change “*... instance.*If the ...” to “*... instance. If the ...*”

Part 1, §17.6.2 (pp. 617), “themeShade (Border Theme Color Shade)”

Change “*... instance.*If the ...” to “*... instance. If the ...*”

Part 1, §17.6.7 (pp. 632), “themeShade (Border Theme Color Shade)”

Change “*... instance.*If the ...” to “*... instance. If the ...*”

Part 1, §17.6.15 (pp. 655), “themeShade (Border Theme Color Shade)”

Change “*... instance.*If the ...” to “*... instance. If the ...*”

Part 1, §17.6.21 (pp. 673), “themeShade (Border Theme Color Shade)”

Change “*... instance.*If the ...” to “*... instance. If the ...*”

Part 1, §17.13.4.2 (pp. 905), initials (Initials of Comment Author)

Change “*... application.*If there ...” to “*... application. If there ...*”

Part 1, §17.16.5 (pp. 1341), “User Information”

Change “*... a user*\_account under which the document is manipulated.\_[Note: These ...]” to “*... a user account* under which the document is manipulated. [Note: These ...]”

Part 1, §17.16.5.1 (pp. 1342), “Switch \d”

Change “*... the recipient*\_as defined ...” to “*... the recipient as defined ...*”

Part 1, §17.16.5.1 (pp. 1342), “Switch \f”

Change “*... placeholders*\_in the ...” to “*... placeholders in the ...*”

Part 1, §17.16.5.1 (pp. 1343), “Switch \l”

Change “... document. This language ...” to “... document. This language ...”

Part 1, §17.18.59 (pp. 1574), “arabicAlpha (Arabic Alphabet)”

Change “... alphabet from the ...” to “... alphabet from the ...”

Part 1, §17.18.59 (pp. 1587), “hebrew1 (Hebrew Letters)”

Change “To determine ...” to “To determine ...”

Part 1, §17.18.59 (pp. 1590), “hindiConsonants (Hindi Consonants)”

Change “... consonant from ...” to “... consonant from ...”

Part 1, §17.18.59 (pp. 1591), “hindiNumbers (Hindi Numbers)”

Change “... number from ...” to “... number from ...”

Part 1, §17.18.59 (pp. 1592), “hindiVowels (Hindi Vowels)”

Change “... vowel from ...” to “... vowel from ...”

Part 1, §17.18.59 (pp. 1613), “thaiLetters (Thai Letters)”

Change “... letter from ...” to “... letter from ...”

Part 1, §18.2.3 (pp. 1709), “autoUpdate (Auto Update)”

Change “... that if the ...” to “... that if the ...”

Part 1, §18.2.3 (pp. 1710), “autoUpdate (Auto Update)”

Change “... the spreadsheet ...” to “... the spreadsheet ...”

Part 1, §18.3.1.40 (pp. 1806), “aca (Always Calculate Array)”

Change “... needed. The ...” to “... needed. The ...”

Part 1, §18.3.1.85 (pp. 1870), “scenarios (Scenarios Locked)”

Change “... Scenarios should ...” to “... Scenarios should ...”

Part 1, §18.10.1.73 (pp. 2142), “printDrill (Print Drill Indicators)”

Change “... indicates that ...” to “... indicates that ...”

Part 1, §18.10.1.73 (pp. 2146), “useAutoFormatting (Auto Formatting)”

Change "... indicates that ..." to "... indicates that ..."

Part 1, §18.14.11 (pp. 2251), "progId (Object Link Identifier)"

Change "... connection. [Example: ...]" to "... connection. [Example: ...]"

Part 1, §18.17.7.2 (pp. 2306), "0 or omitted"

Change "... 30/360. Assumes ..." to "... 30/360. Assumes ..."

Part 1, §18.17.7.2 (pp. 2307), "4"

Change "... 30/360. The ..." to "... 30/360. The ..."

Part 1, §18.17.7.66 (pp. 2385), "*member-expression*"

Change "... constant. [Note: ...]" to "... constant. [Note: ...]"

Part 1, §18.17.7.74 (pp. 2393), "*year*"

Change "... integer representing ..." to "... integer representing ..."

Part 1, §18.17.7.76 (pp. 2397), "*date-time-string*"

Change "... ignored. When ..." to "... ignored. When ..."

Part 1, §18.17.7.298 (pp. 2605), "*mean*"

Change "... distribution. Represented ..." to "... distribution. Represented ..."

Part 1, §18.17.7.298 (pp. 2605), "*standard-dev*"

Change "... distribution. Represented ..." to "... distribution. Represented ..."

Part 1, §19.5.46 (pp. 2921), "l (Lightness)"

Change "... percent when ..." to "... percent when ..."

Part 1, §19.5.46 (pp. 2921), "s (Saturation)"

Change "... percent when ..." to "... percent when ..."

Part 1, §19.5.63 (pp. 2936), "b (Blue)"

Change "... percent when ..." to "... percent when ..."

Part 1, §19.5.63 (pp. 2937), "g (Green)"

Change "... percent when ..." to "... percent when ..."

Part 1, §19.5.63 (pp. 2937), “r (Red)”

Change “... percent when ...” to “... percent when ...”

Part 1, §19.5.68 (pp. 2942), “embed (Embedded Audio File Relationship ID)”

Change “... file. [Note: ...” to “... file. [Note: ...”

Part 1, §19.5.70 (pp. 2943), “embed (Embedded Audio File Relationship ID)”

Change “... file. [Note: ...” to “... file. [Note: ...”

Part 1, §20.1.2.2.32 (pp. 3044), “embed (Embedded Audio File Relationship ID)”

Change “... file. [Note: ...” to “... file. [Note: ...”

Part 1, §20.1.3.7 (pp. 3089)), “embed (Embedded Audio File Relationship ID)”

Change “... file. [Note: ...” to “... file. [Note: ...”

Part 1, §21.1.2.2.2 (pp. 3569), “rtl (Right To Left)”

Change “[Example: Consider ...” to “[Example: Consider ...”

Part 1, §21.1.2.2.2 (pp. 3570 (in Arabic example)), “rtl (Right To Left)”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

Part 1, §21.1.2.2.7 (pp. 3587), “rtl (Right To Left)”

Change “[Example: Consider ...” to “[Example: Consider ...”

Part 1, §21.1.2.2.7 (pp. 3570 (in Arabic example)), “rtl (Right To Left)”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

Part 1, §21.1.2.4.13 (pp. 3651), “rtl (Right To Left)”

Change “[Example: Consider ...” to “[Example: Consider ...”

Part 1, §21.1.2.4.13 (pp. 3652 (in Arabic example)), “rtl (Right To Left)”

Change “... <a:t> تجربة </a:t> ...” to “... <a:t> تجربة </a:t> ...”

Part 1, §21.1.2.4.14 (pp. 3660), “rtl (Right To Left)”

Change “[Example: Consider ...” to “[Example: Consider ...”

Part 1, §21.1.2.4.14 (pp. 3661 (in Arabic example)), “rtl (Right To Left)”

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.15 (pp. 3669), "rtl (Right To Left)"

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.16 (pp. 3677), "rtl (Right To Left)"

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Part 1, §21.1.2.4.16 (pp. 3678 (in Arabic example)), "rtl (Right To Left)"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.17 (pp. 3686)

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.18 (pp. 3694), "rtl (Right To Left)"

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Part 1, §21.1.2.4.18 (pp. 3695 (in Arabic example)), "rtl (Right To Left)"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.19 (pp. 3703), "rtl (Right To Left)"

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.20 (pp. 3711), "rtl (Right To Left)"

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Part 1, §21.1.2.4.20 (pp. 3712 (in Arabic example)), "rtl (Right To Left)"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

Part 1, §21.1.2.4.21 (pp. 3720)

Change "[Example: Consider ...]" to "[Example: Consider ...]"

Change "... <a:t> تجربة </a:t> ..." to "... <a:t> تجربة </a:t> ..."

## 96. DR 09-0081 — General: Inter-word space missing

**Status:** Closed; will be incorporated in COR1

**Subject:** Inter-word space missing

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-5

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §15.2.15 (pp. 162), §17.16.5.33 (pp. 1369), §M.1.8.5 (pp. 5100)

**Related DR(s):** none

**Nature of the Defect:**

Inter-word space characters missing.

**Solution Proposed by the Submitter:**

Insert space where required (NOTE - space underlined in blue):

In §15.2.15:

[*Example:* An Office Open XML producer on Windows might store the DEVMODE structure defined here: [http://msdn.microsoft.com/library/default.asp?url=/library/en-us/gdi/prntspol\\_8nle.asp](http://msdn.microsoft.com/library/default.asp?url=/library/en-us/gdi/prntspol_8nle.asp), while an application on the Mac OS might choose to store the print record defined here: <http://developer.apple.com/documentation/Printing/index.html>. *end example*]

In §17.16.5.33:

**Description:** Computes the next value from a specific level of a numbering definition, or a specific value from a specific level of a numbering definition.

In §M.1.8.5:

Consider the following two styles which comprise a linked style pairing that defines the following: font is Arial, font color is green; paragraph spacing is double, and indent is 1\_inch left. The resulting style definitions would be:

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §15.2.15 (pp. 162), “Printer Settings Part”

[*Example:* An Office Open XML producer on Windows might store the DEVMODE structure defined here: [http://msdn.microsoft.com/library/default.asp?url=/library/en-us/gdi/prntspol\\_8nle.asp](http://msdn.microsoft.com/library/default.asp?url=/library/en-us/gdi/prntspol_8nle.asp), while an application on the Mac OS might choose to store the print record defined here: <http://developer.apple.com/documentation/Printing/index.html>. *end example*]

Part 1, §17.16.5.33 (pp. 1369), “LISTNUM”

**Description:** Computes the next value from a specific level of a numbering definition, or a specific value from a specific level of a numbering definition.

Part 1, §M.1.8.5 (pp. 5100), “Linked Styles”

Consider the following two styles which comprise a linked style pairing that defines the following: font is Arial, font color is green; paragraph spacing is double, and indent is 1\_inch left. The resulting style definitions would be:

## 97. DR 09-0082 — General: Unsatisfactory attribute name example

**Status:** Closed; will be incorporated in COR1

**Subject:** Unsatisfactory choice of attribute name example in §5 Notational Conventions and unsatisfactory styling of tag, attribute and datatype names throughout

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-6

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §5 (pp. 14) specifically and generally throughout

**Related DR(s):** none

### **Nature of the Defect:**

The decision of the BRM to accept Response 891 does not appear to have been implemented. The style of presentation of element, attribute and data type names does not make it easy to distinguish between them. It was agreed in Response 891 that a longer attribute name should be used in §5, but it is still as in the DIS text.

### **Solution Proposed by the Submitter:**

Choose more distinctive styles for presenting element, attribute and data type names. Choose a longer example of an attribute name for §5, e.g. 'linkTarget'

**Schema Change(s) Needed:** No

### **Editor's Response:**

Note that the response did *not* propose changing any styles.

After discussion with members of the submitting NB, it was decided to restore the format of each bullet item to that going into the BRM (i.e., with trailing examples, as shown below) and to use examples taken directly from the text. Also, when IS 29500 is reprinted or revised, the editor will look at using easily recognizable distinct typographical forms for each of the six conventions.

The exact changes are as follows:

#### Part 1, §5 (pp. 14), “Notational Conventions”

The following typographical conventions are used in ISO/IEC 29500:

- The first occurrence of a new term is written in italics, ~~as in "normative"~~. [\[Example: The text in ISO/IEC 29500 is divided into normative and informative categories. end example\]](#)
- In each definition of a term in §4 (Terms and Definitions), the term is written in bold, ~~as in "behavior"~~. [\[Example: behavior — External appearance or action. end example\]](#)
- The tag name of an XML element is written using an Element style, ~~as in "document"~~. [\[Example: The bookmarkStart and bookmarkEnd elements specify ... end example\]](#)
- The name of an XML attribute is written using an Attribute style, ~~as in "id"~~. [\[Example: The dropCap attribute specifies ... end example\]](#)
- The value of an XML attribute is written using a constant-width style, ~~as in "CommentReference"~~. [\[Example: The attribute value of auto specifies ... end example\]](#)
- The qualified or unqualified name of a simple type, complex type, or base datatype is written using a Type style, ~~as in "xsd:anyURI"~~. [\[Example: The possible values for this attribute are defined by the ST\\_HexColor simple type. end example\]](#)

## 98. DR 09-0083 — DML chart element ‘userShapes’ lacking Parent Element box

**Status:** Closed; will be incorporated in COR1

**Subject:** DML chart element ‘userShapes’ lacking Parent Element box

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter’s Defect Number:** GB-7

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §21.2.2.220 (pp. 3867–3868)

**Related DR(s):** none

**Nature of the Defect:**

The Parent Elements box has not been added (see Ecma Response 893 agreed by BRM).

**Solution Proposed by the Submitter:**

Replace existing §21.2.2.220 with (new text highlighted in blue and underlined):

### 98.1.1.1      userShapes (User Shapes)

This element shall specify the shapes drawn on top of the chart.

<u>Parent Elements</u>
<u>Root element of Chart Drawing part.</u>

Child Elements	Subclause
----------------	-----------

Child Elements	Subclause
absSizeAnchor (Absolute Anchor Shape Size)	§xx
relSizeAnchor (Relative Anchor Shape Size)	§xx

[Note: The W3C XML Schema definition of this element's content model ([CT\\_Drawing](#)) is located in §xx. *end note*]

### Schema Change(s) Needed:

#### Editor's Response:

I agree that the changes promised in Response 893 did not get implemented.

The exact changes are as follows:

Part 1, §21.2.2.220 (pp. 3867), “userShapes (User Shapes)”

This element shall specify the shapes drawn on top of the chart

<a href="#"><u>Parent Elements</u></a>
<a href="#"><u>Root element of Chart Drawing Part</u></a>

Child Elements	Subclause
absSizeAnchor (Absolute Anchor Shape Size)	§xx
relSizeAnchor (Relative Anchor Shape Size)	§xx

## 99. DR 09-0084 — WML: Ecma Response 261 not fully implemented

**Status:** Closed; will be incorporated in COR1

**Subject:** Ecma Response 261 not fully implemented

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-8

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.4.66 (pps. 494, 495), §17.4.79 (pps. 512, 513)

**Related DR(s):** none

**Nature of the Defect:**

The text of the example "Hello World", appears first (twice) without then with a comma. The word "World" should be "world" (see Response 261 agreed by BRM).

**Solution Proposed by the Submitter:**

Revise text at the start of the Example in each case with:

[*Example:* Consider a table consisting of a single table cell, which contains the text Hello, world:

Hello, world

**Schema Change(s) Needed:** No

**Editor's Response:**

Just to be clear, Response 261 was implemented as proposed. It applied only to the Primer (formerly Part 3), with the result being in Part 1, §M.1.5.4, pp. 5081.

Separately, throughout Part 1 there are a number of uses of the phrase “Hello world” in which the letter w is sometimes capitalized and sometimes not, and sometimes preceded by a comma and sometimes not. §17.4.66 and §17.4.79 are two more instances of the same kind of discrepancy as was dealt with by, but not included in, Response 261. I will make all such usages correct and consistent.

The exact changes are as follows:

Part 1, §17.3.2.5, “caps (Display All Characters As Capital Letters)” (pp. 285)

*[Example:* Consider the words Hello, World, which must be displayed in all capital letters in a document. This constraint is specified as follows in the WordprocessingML:

```
<w:r>
 <w:rPr>
 <w:caps w:val="true" />
 </w:rPr>
 <w:t>Hello, World</w:t>
</w:r>
```

This run displays as HELLO, WORLD, even though the lowercase characters are used in the run contents due to the use of the caps element. If this property is removed, the original character forms is displayed (they are not lost). *end example]*

Part 1, §17.3.2.33, “smallCaps (Small Caps)”, (pp. 330)

*[Example:* Consider the words Hello, World, which must be displayed in small capital letters in a document. This constraint is specified as follows in the WordprocessingML:

```
<w:r>
 <w:rPr>
 <w:smallCaps w:val="true" />
 <w:sz w:val="24" />
 </w:rPr>
 <w:t>Hello, World</w:t>
</w:r>
```

*... end example]*

Part 1, §17.4.66, “tc (Table Cell)”, (pps. 494, 495)

*[Example:* Consider a table consisting of a single table cell, which contains the text Hello, World:

Hello, <u>W</u> orld
----------------------

This table cell's content is represented by the following WordprocessingML:

```

<w:tc>
 <w:tcPr>
 <w:tcW w:w="0" w:type="auto"/>
 </w:tcPr>
 <w:p>
 <w:r>
 <w:t>Hello, World</w:t>
 </w:r>
 </w:p>
</w:tc>

```

*... end example]*

Part 1, §17.4.79, “tr (Table Row)”, (pps. 512, 513)

[*Example*: Consider a table consisting of a single table cell, which contains the text Hello, World:

Hello World
-------------

This table row's content is represented by the following WordprocessingML:

```

<w:tr>
 <w:tc>
 <w:tcPr>
 <w:tcW w:w="0" w:type="auto"/>
 </w:tcPr>
 <w:p>
 <w:r>
 <w:t>Hello, World</w:t>
 </w:r>
 </w:p>
 </w:tc>
</w:tr>

```

*... end example]*

Part 1, §17.5.2.5, “comboBox (Combo Box Structured Document Tag)”, (pps. 555, 556)

[*Example*: Consider a combo box structured document tag defined as follows:

```

<w:sdt>
 <w:sdtPr>
 <w:dataBinding ... />
 <w:comboBox w:lastValue="2"/>
 </w:sdtPr>
 <w:sdtContent>
 <w:r>
 <w:t>Hello 2 world</w:t>
 </w:r>
 </w:sdtContent>
</w:sdt>

```

The current run content of the structured document tag reads Hello 2 world. When this document is opened, if the current value of the associated custom XML data is 2, the matching lastValue attribute specifies that the contents of the combo box must continue to be the current display text of the combo box even though there is no listItem whose value is 2 (and normally, the content of the structured document tag would be set to 2. Essentially, this attribute specifies a listItem whose value is 2 and whose displayText is Hello 2 world (the current structured document tag contents). *end example]*

Part 1, §17.5.2.15, “dropDownList (Drop-Down List Structured Document Tag)”, (pp. 570)

[*Example*: Consider a drop-down list structured document tag defined as follows:

```

<w:sdt>
 <w:sdtPr>
 <w:dataBinding ... />
 <w:dropDownList w:lastValue="2"/>
 </w:sdtPr>
 <w:sdtContent>
 <w:r>
 <w:t>Hello 2 world</w:t>
 </w:r>
 </w:sdtContent>
</w:sdt>

```

The current run content of the structured document tag reads Hello 2 world. When this document is opened, if the current value of the associated custom XML data is 2, the matching lastValue attribute specifies that the contents of the combo box must continue to be the current display text of the combo box even though there is no listItem whose value is 2 (and normally, the content of the structured document tag would be set to 2. Essentially, this attribute specifies a listItem whose value is 2 and whose displayText is Hello 2 world (the current structured document tag contents). *end example]*

Part 1, §17.7.5, “Document Defaults”, (pp. 715)

[*Example*: Consider the following fragment from the main document part of a WordprocessingML document:

```
<w:body>
 <w:p>
 <w:r>
 <w:t>Hello_ world!

```

*... end example]*

Part 1, §17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, (pp. 716)

```
<w:body>
 <w:p>
 <w:r>
 <w:t> Hello_ world!</w:t>
 </w:r>
 </w:p>
</w:body>
```

Part 1, §17.15.1.77, “saveXmlDataOnly (Only Save Custom XML Markup)”, (pp. 1194)

[*Example:* ...

```
<w:body>
 <w:p>
 <w:customXml w:element="root" w:namespaceuri="urn:example">
 <w:r>
 <w:t>Hello_ world</w:t>
 </w:r>
 </w:customXml>
 </w:p>
</w:body>
```

The presence of this element specifies that the resulting document only contains the custom XML markup, resulting in the following:

```
<ns0:root xmlns:ns0="urn:example">Hello_ world</ns0:root>
```

*end example]*

# 100. DR 09-0085 — WML: Incorrect style name in ‘w:val’ attributes in Examples

**Status:** Closed; will be incorporated in COR1

**Subject:** Incorrect style name in ‘w:val’ attributes in Examples

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-9

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.7.4 (pp. 683), §17.7.4.17 (pp. 707), §17.15.1.29 (pp. 1144)

**Related DR(s):** none

## **Nature of the Defect:**

There are still occurrences where “heading 1” has not been changed to “Heading 1” in w:val attributes in Examples (see Ecma Response 264 agreed by the BRM).

## **Solution Proposed by the Submitter:**

In §17.7.4 and §17.7.4.17 revise text of the Examples as shown below:

[*Example:* Consider a style called Heading 1 in a document as follows:

```

<w:style w:type="paragraph" w:styleId="Heading1">
 <w:name w:val="hHeading 1"/>
 <w:basedOn w:val="Normal"/>
 <w:next w:val="Normal"/>
 <w:link w:val="Heading1Char"/>
 <w:uiPriority w:val="1"/>
 <w:qformat/>
 <w:rsid w:val="00F303CE"/>
 ...
</w:style>

```

In §17.15.1.29 revise text of the Example as shown below:

```

<w:style w:type="paragraph" w:styleId="Heading1">
 <w:name w:val="hHeading 1" />
 <w:locked w:val="1" />
 ...
</w:style>

```

**Schema Change(s) Needed:** No

**Editor's Response:**

Just to be clear, Response 264 was implemented as proposed. It applied only to one instance in the Primer (formerly Part 3), with the result being in Part 1, §M.1.8.2, pp. 5097.

§17.7.4 and §17.7.4.17 are two more instances of the same kind of discrepancy as was dealt with by, but not included in, Response 264. As such, I agree to make these changes. In the case of §17.15.1.29, there is no mention in narrative of the style's name, so, as it stands, the example does not appear to be in error; however, I see no harm in changing that one too, to be consistent.

The exact changes are as follows:

Part 1, §17.7.4, "General Style Properties", (pp. 683)

[Example: Consider a style called Heading 1 in a document as follows:

```

<w:style w:type="paragraph" w:styleId="Heading1">
 <w:name w:val="hHeading 1"/>
 <w:basedOn w:val="Normal"/>
 <w:next w:val="Normal"/>
 <w:link w:val="Heading1Char"/>
 <w:uiPriority w:val="1"/>
 <w:qformat/>
 <w:rsid w:val="00F303CE"/>
 ...
</w:style>

```

Part 1, §17.7.4.17, “style (Style Definition)”, (pp. 706–707)

[Example: Consider a style called Heading 1 in a document as follows:

```

<w:style w:type="paragraph" w:styleId="Heading1">
 <w:name w:val="hHeading 1"/>
 <w:basedOn w:val="Normal"/>
 <w:next w:val="Normal"/>
 <w:link w:val="Heading1Char"/>
 <w:uiPriority w:val="1"/>
 <w:qformat/>
 <w:rsid w:val="00F303CE"/>
 ...
</w:style>

```

Part 1, §17.15.1.29, “documentProtection (Document Editing Restrictions)”, (pp. 1144)

```

<w:style w:type="paragraph" w:styleId="Heading1">
 <w:name w:val="hHeading 1" />
 <w:locked w:val="1" />
 ...
</w:style>

```

# 101. DR 09-0086 — Primer: Duplicate mathematical expressions in Primer

**Status:** Closed; will be incorporated in COR1

**Subject:** Duplicate mathematical expressions in Primer

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-10

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §M.6.1 (pp. 5507)

**Related DR(s):** none

## Nature of the Defect:

Duplicate mathematical expressions (text paired with stretching character, bar fraction, stack object).

## Solution Proposed by the Submitter:

Revise text of paragraph as follows (NOTE – revised text in blue but *not* underscored or struck through, for clarity):

The following subclauses introduce each of the math objects that comprise the majority of the OMML schema. Since this language is designed for text processing rather than calculations, when writing math zones in an XML representation, more attention is given to the layout and appearance of mathematical text than to mathematical semantics. That is,  $\overbrace{abc}^{\rightarrow}$  and  $\overbrace{abc}^{\curvearrowright}$  are represented by the same object, although they have different mathematical meanings, because both consist of text paired with a stretching character. Similarly,  $\frac{n}{k}$  and  $\frac{n}{k}$  are both represented by a fraction object. Though mathematically they have different meaning, their

layout is similar. Another example is  $x^2$ , which could be  $x$  squared or a tensor component. Regardless of these semantics, it is represented by a superscript object.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §M.6.1, "Math", (pp. 5507) [the right-most of each pair of figure is to be removed, as shown below]

The following subclauses introduce each of the math objects that comprise the majority of the OMM schema. Since this language is designed for text processing rather than calculations, when writing math zones in an XML representation, more attention is given to the layout and appearance of mathematical text than to mathematical semantics. That is,  $\overrightarrow{abc}$  and  $\overbrace{abc}^{\text{abc}}$  are represented by the same object, although they have different mathematical meanings, because both consist of text paired with a stretching character. Similarly,  $\frac{n}{k}$  and  $\frac{n^m}{k}$  are both represented by a fraction object. Though mathematically they have different meaning, their layout is similar. Another example is  $x^2$ , which could be  $x$  squared or a tensor component. Regardless of these semantics, it is represented by a superscript object.

## 102. DR 09-0087 — Strict Part Normative References to transitional features

**Status:** Closed; will be incorporated in COR1

**Subject:** Strict Part Normative references to transitional features

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-11

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §12.3.10 (pp. 82), §12.3.12 (pp. 85), §17.16.5.49 (pp. 1382), §18.10.1.67 (pps. 2093, 2096), §M.2.9.3.2 (pps. 5239, 5242), §M.2.12.3 (pp. 5269)

**Related DR(s):** none

### Nature of the Defect:

References to transitional features are confusing because they are not defined in this Part, and this Part cannot depend normatively upon Part 4 where they are defined.

### Solution Proposed by the Submitter:

Re-word the text to omit references to transitional features:

In §12.3.10, §12.3.12, §18.10.1.67, §M.2.9.3.2, §M.2.12.3 replace ‘refreshedDate’ with ‘refreshedDateAlso’.

In §17.16.5.49 revise text as follows:

**Description:** Retrieves the text specified by *text* in *field-argument*. This text can include any other fields except **AUTONUM, AUTONUMLGL, AUTONUMOUT, and SYMBOL**.

**Schema Change(s) Needed:** No

**Editor's Response:**

Regarding replacing “refreshedDate” with “refreshedDateIso”, I agree. In addition, in §18.10.1.67, in the attribute table entry for “refreshedDateIso” must be corrected, as follows:

~~If refreshedDateIso and refreshedDate are both present, refreshedDateIso shall take precedence.~~

as in strict mode, refreshedDate must not be present.

Regarding §17.16.5.49, I agree. However, a consequence of this is that we need to add this extra constraint to Part 4, as follows:

#### Part 4, 9.9.4.8 QUOTE

This field retrieves the text specified by *text* in *field-argument*. In strict conformance mode, this text may include any other fields except SYMBOL. However, in transitional conformance mode, this text may include any other fields except AUTONUM, AUTONUMLGL, AUTONUMOUT, and SYMBOL.

As such, this DR results in changes to Parts 1 and 4, which will be handled by different CORs.

The exact changes are as follows:

Part 1, §12.3.10, “Metadata Part”, (pp. 82-83)

```
<pivotCacheDefinition ... saveData="0" refreshedBy="..."
refreshedDateIso="2005-11-28T16:55:44" backgroundQuery="1" createdVersion="3"
refreshedVersion="3" recordCount="0">
...
</pivotCacheDefinition>
```

Part 1, §12.3.12, “Pivot Table Cache Definition Part”, (pp. 85)

```
<pivotCacheDefinition ... r:id="rId1" refreshedBy="John Jones"
refreshedDateIso="2005-11-18T16:47:49" createdVersion="3"
refreshedVersion="3" recordCount="11">
...
</pivotCacheDefinition>
```

Part 1, §17.16.5.49, “QUOTE”, (pp. 1382)

**Description:** Retrieves the text specified by *text* in *field-argument*. This text can include any other fields except ~~AUTONUM, AUTONUMLGL, AUTONUMOUT, and SYMBOL~~.

Part 1, §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, (pps. 2093-2094)

```

<pivotCacheDefinition xmlns="..." xmlns:r="..." r:id="rId1" refreshedBy="AnonUser"
 refreshedDateIso="2006-05-22T10:07:16" createdVersion="3" refreshedVersion="3"
 minRefreshableVersion="3" recordCount="182">
 ...
</pivotCacheDefinition>
```

Part 1, §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, (pp. 2096), attribute table entry for refreshedDateIso

~~If refreshedDateIso and refreshedDate are both present, refreshedDateIso shall take precedence.~~

Part 1, §M.2.9.3.2, “XML - pivotCacheDefinition part”, (pp. 5239)

```

<pivotCacheDefinition xmlns:r="..." r:id="rId1" refreshedBy="AnonUser"
 refreshedDateIso="2006-05-22T10:07:16" createdVersion="3"
 refreshedVersion="3" minRefreshableVersion="3" recordCount="182">
 ...
</pivotCacheDefinition>
```

Part 1, §M.2.9.3.2, “XML - pivotCacheDefinition part”, (pp. 5242)

- refreshedDateIso indicates when the PivotCache was last refreshed.

Part 1, §M.2.12.3, “Pivot XML fragment”, (pp. 5269)

```

<pivotCacheDefinition ... saveData="0" refreshedBy="Chad Rothschilder"
 refreshedDateIso="2006-04-13T16:02:14" backgroundQuery="1"
 createdVersion="3"
 refreshedVersion="3" minRefreshableVersion="3" recordCount="0">
 ...
</pivotCacheDefinition>
```

Part 4, §9.9.4.8, “QUOTE”, (pp. 165), [Add a new subclause]

#### 9.9.4.8 QUOTE

This field retrieves the text specified by *text* in *field-argument*. In strict conformance mode, this text may include any other fields except SYMBOL. However, in transitional conformance mode, this text may include any other fields except AUTONUM, AUTONUMLGL, AUTONUMOUT, and SYMBOL.

# 103. DR 09-0088 — Shared MLs: Incorrect citation of Normative Reference

**Status:** Closed; will be incorporated in COR1

**Subject:** Incorrect citation of Normative Reference

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-12

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §22.9.2.1 (pp. 4319)

**Related DR(s):** none

## Nature of the Defect:

The citation of the normative reference "Har'El, Zvi" for the description of the Hebrew lunar calendar is missing. The document in question is correctly listed in §3 (Normative References).

## Solution Proposed by the Submitter:

Remove the word "CITATION" and replace with "Har'El":

Enumeration Value	Description
...	...
hebrew (Hebrew)	Specifies that the Hebrew lunar calendar, as described by the Gauss formula for Passover [ <a href="#">Har'El, Zvi</a> <del>CITATION</del> ] and The Complete Restatement of Oral Law (Mishneh Torah), shall be used.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §22.9.2.1, "ST\_CalendarType (Calendar Types)", (pp. 4319)

Enumeration Value	Description
...	...
hebrew (Hebrew)	Specifies that the Hebrew lunar calendar, as described by the Gauss formula for Passover [ <a href="#">Har'El</a> , <a href="#">ZviCITATION</a> ] and The Complete Restatement of Oral Law (Mishneh Torah), shall be used.

# 104. DR 09-0089 — WML: DATE Field switch names incorrectly styled

**Status:** Closed; will be incorporated in COR1

**Subject:** Field switch names incorrectly styled

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-13

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.16.5.13 (pp. 1353)

**Related DR(s):** none

**Nature of the Defect:**

Italics have been lost in the table and should be reinstated for field switch names, for consistency with text elsewhere.

**Solution Proposed by the Submitter:**

Revise table to reinstate use of italics for field switch names:

**Switches:** Zero or one *date-and-time-formatting-switch* and zero or one of the following *field-specific-switches*.

\h	Use the Hijri Lunar or Hebrew Lunar calendar, depending on the language specified by the lang element (§xx).
----	--------------------------------------------------------------------------------------------------------------

\1	When a field update is performed, if no <i>date-and-time-formatting-switch</i> is used, this switch is an instruction specifying that the field shall use the <i>date-and-time-formatting-switch</i> last used by the hosting application when inserting a new DATE field. If there is no last-used date format available, then the <i>date-and-time-formatting-switch</i> used is implementation-defined.
\s	Use the Saka Era calendar.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §17.16.5.13, “DATE”, (pp. 1353)

**Switches:** Zero or one *date-and-time-formatting-switch* and zero or one of the following *field-specific-switches*.

\h	Use the Hijri Lunar or Hebrew Lunar calendar, depending on the language specified by the lang element (§xx).
\1	When a field update is performed, if no <i>date-and-time-formatting-switch</i> is used, this switch is an instruction specifying that the field shall use the <i>date-and-time-formatting-switch</i> last used by the hosting application when inserting a new DATE field. If there is no last-used date format available, then the <i>date-and-time-formatting-switch</i> used is implementation-defined.
\s	Use the Saka Era calendar.

## 105. DR 09-0090 — WML: Incorrect case used for ISO country code in 'en-ca'

**Status:** Closed; will be incorporated in COR1

**Subject:** Incorrect case used for ISO country code in 'en-ca'

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-14

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.3.1.30 (pp. 258), §17.3.2.27 (pp. 321), §17.3.2.28 (pp. 323)

**Related DR(s):** none

**Nature of the Defect:**

ISO country codes should always be in upper-case, including when used as locale codes with language codes.

**Solution Proposed by the Submitter:**

Change all instances of "en-ca" to "en-CA".

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §17.3.1.30, “rPr (Previous Run Properties for the Paragraph Mark)”, (pp. 258)

```
<w:lang w:val="en-CAea" />
```

Part 1, §17.3.2.27, “rPr (Previous Run Properties)”, (pp. 321)

```
<w:lang w:val="en-CAea" />
```

Part 1, §17.3.2.28, “rPr (Run Properties)”, (pp. 323)

```
<w:lang w:val="en-CAea" />
```

## 106. DR 09-0091 — WML: Inconsistent citation of Normative Reference ‘XSLT’

**Status:** Closed; will be incorporated in COR1

**Subject:** Inconsistent citation of Normative Reference ‘XSLT’

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter’s Defect Number:** GB-15

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.9.18 (pp. 804), §17.11.17 (pp. 866), §17.11.18 (pp. 867)

**Related DR(s):** DR 08-0100

### **Nature of the Defect:**

Inconsistent citation of normative reference "XSLT". All except in this case are "XSLT 1.0". However, may be better to change all to "XSLT", so that only §3 needs to be revised in future. [NOTE – An exception is the introductory text to §E, in which “XSLT 1.0” is referring to the specific version of XSLT used to test the processing of bitfields.]

### **Solution Proposed by the Submitter:**

Replace “XSLT 1.0” with “XSLT”:

Attributes	Description
------------	-------------

Attributes	Description
format (Custom Defined Number Format)	<p>Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del>-format attribute. This format shall be used for all numbering in the parent object.</p> <p><i>[Example: A value of &amp;#x30A2; indicates that a consumer must use Katakana numbering. end example]</i></p> <p>The possible values for this attribute are defined by the ST_String simple type (§xx).</p>

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed. Note that the response to DR-0100 results in the removal of Annex E, in which case, the mention of a specific version will go away.

The exact changes are as follows:

Part 1, §17.9.18, “numFmt (Numbering Format)”, (pp. 804)

Attributes	Description
format (Custom Defined Number Format)	<p>Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del>-format attribute. This format shall be used for all numbering in the parent object.</p> <p><i>[Example: A value of &amp;#x30A2; indicates that a consumer must use Katakana numbering. end example]</i></p> <p>The possible values for this attribute are defined by the ST_String simple type (§xx).</p>

Part 1, §17.11.17, “numFmt (Endnote Numbering Format)”, (pp. 866)

Attributes	Description
format (Custom Defined Number Format)	<p>Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del>-format attribute. This format shall be used for all numbering in the parent object.</p> <p><i>[Example: A value of &amp;#x30A2; indicates that a consumer must use Katakana numbering. end example]</i></p> <p>The possible values for this attribute are defined by the ST_String simple type (§xx).</p>

Part 1, §17.11.18, “numFmt (Footnote Numbering Format)”, (pp. 867)

Attributes	Description
format (Custom Defined Number Format)	<p>Specifies a custom number format using the syntax defined by the XSLT <del>1.0</del>-format attribute. This format shall be used for all numbering in the parent object.</p> <p><i>[Example: A value of &amp;#x30A2; indicates that a consumer must use Katakana numbering. end example]</i></p> <p>The possible values for this attribute are defined by the ST_String simple type (§xx).</p>

# 107. DR 09-0092 — WML: Identical definitions for ST\_NumberFormat enumeration values

**Status:** Open

**Subject:** Identical definitions for ST\_NumberFormat enumeration values

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-16

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.18.59 (pp. 1584)

**Related DR(s):** none

## **Nature of the Defect:**

The description of "decimalFullWidth2" is the same as that for "decimalFullWidth" (see Ecma Response 70 agreed by the BRM).

## **Solution Proposed by the Submitter:**

Revise the description of 'decimalFullWidth2' to commence as follows:

Specifies that the sequence shall consist of an alternative set of full-width Arabic numbering, if one exists in the run font.

**Schema Change(s) Needed:** No

## **Editor's Response:**

While it is true that the text of Response 70 does include the wording you propose above, in the original binary format these two enumeration values are equivalent.

**2009-03-24 Prague meeting:**

If they truly are equivalent, can we move decimalFullWidth2 to transitional only? If so, this becomes a technical DR with a schema change to Parts 1 and 4.

# 108. DR 09-0093 — WML: Incorrect simple type name in example of 'ST\_UcharHexNumber'

**Status:** Closed; will be incorporated in COR1

**Subject:** Incorrect simple type name in example of 'ST\_UcharHexNumber'

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-17

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.18.98 (pp. 1672)

**Related DR(s):** none

**Nature of the Defect:**

The example contains the wrong simple type name.

**Solution Proposed by the Submitter:**

Change "ST\_LongHexNumber" to "ST\_UcharHexNumber":

[*Example:* Consider the following value for a node of type ST\_Uchar**Long**HexNumber: BE.]

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §17.18.98, "ST\_UcharHexNumber (Two Digit Hexadecimal Value)", (pp. 1672)

[*Example:* Consider the following value for a node of type ST\_UcharLongHexNumber: BE.

This value is permitted, as it contains two hexadecimal digits, as an encoding of an octet of the actual decimal number value. *end example*]

# 109. DR 09-0094 — WML: Ecma Response 71 not fully implemented in definition of 'ST\_Shade'

**Status:** Closed; will be incorporated in COR1

**Subject:** Ecma Response 71 not fully implemented in definition of 'ST\_Shade'

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-18

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.18.78 (pp. 1633)

**Related DR(s):** none

## **Nature of the Defect:**

The changes to the text agreed by the BRM (see Ecma Response 71) have not been made.

## **Solution Proposed by the Submitter:**

Revise the first two paragraphs of as follows:

This simple type specifies the pattern which shall be used to lay the pattern color over the background color for ~~a~~-shading.

This pattern consists of a mask which is applied over the background shading color to get the locations where the pattern color should be shown. Each of these possible masks ~~are-is~~ shown in the enumeration values ~~located~~ below. In each example, [an 8 pixel by 8 pixel mask is displayed where](#) black has been used as the fill color [\(the](#)

parent element's fill attribute), and white has been used as the pattern color (the parent element's color attribute). When the shading is applied, the mask is tiled as necessary to match the size of the shaded area.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed; although the Description for each Enumeration Value was changed correctly, the introductory text cited above was not.

The exact changes are as follows:

Part 1, §17.18.78, "ST\_Shading Patterns)", (pp. 1633)

This simple type specifies the pattern thatwhich shall be used to lay the pattern color over the background color for a-shading.

This pattern consists of a mask thatwhich is applied over the background shading color to get the locations where the pattern color should be shown. Each of these possible masks areis shown in the enumeration values located below. In each example, an 8 pixel by 8 pixel mask is displayed where black has been used as the fill color (the parent element's fill attribute), and white has been used as the pattern color (the parent element's color attribute). When the shading is applied, the mask is tiled as necessary to match the size of the shaded area.

## 110. DR 09-0095 — SML: References to non-existent attribute ‘paperUnits’

**Status:** Closed; will be incorporated in COR1

**Subject:** References to non-existent attribute ‘paperUnits’

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter’s Defect Number:** GB-19

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §18.3.1.63 (pps. 1827, 1830), §18.3.1.64 (pps. 1832, 1834), §21.2.2.134 (pps. 3822, 3825)

**Related DR(s):** none

### Nature of the Defect:

There are references to a non-existent attribute ‘paperUnits’ in Examples and in definitions of the attribute ‘paperSize’.

### Solution Proposed by the Submitter:

Remove references to ‘paperUnits’:

In Examples (pps. 1827, 1832, 3822):

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm" />
```

In definitions of the attribute ‘paperSize’ (pps. 1830, 1834, 3825):

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §18.3.1.63, “pageSetup (Page Setup Settings)”, (pp. 1827)

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm"/>
```

Part 1, §18.3.1.63, “pageSetup (Page Setup Settings)”, (pp. 1830)

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

Part 1, §18.3.1.64 (pp. 1832)

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm"/>
```

Part 1, §18.3.1.64 (pp. 1834)

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

Part 1, §21.2.2.134 (pp. 3822)

```
<pageSetup blackAndWhite="true" draft="false" paperHeight="1189mm"
paperWidth="841mm" paperUnits="mm"/>
```

Part 1, §21.2.2.134 (pp. 3825)

When paperHeight, and paperWidth, ~~and paperUnits~~ are specified, paperSize should be ignored.

# 111. DR 09-0096 — DML: Error in definition of attribute 'paperSize'

**Status:** Closed; will be incorporated in COR1

**Subject:** Error in definition of attribute 'paperSize'

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-20

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §21.2.2.134 (pp. 3823)

**Related DR(s):** none

## **Nature of the Defect:**

Text following name of attribute 'paperSize' in the definition table says "(Page size)" but should say "(Paper size)".

## **Solution Proposed by the Submitter:**

Change "(Page size)" to "(Paper size)":

paperSize (~~Page~~Paper Size)

**Schema Change(s) Needed:** No

## **Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §21.2.2.134, “pageSetup (Page Setup)”, (pp. 3823)

Attributes	Description
paperSize ( <a href="#">Page</a> <a href="#">Paper</a> Size)	Specifies the paper size according to the following table. ...

## 112. DR 09-0097 — General: Miscellaneous mis-spellings

**Status:** Closed; will be incorporated in COR1

**Subject:** Miscellaneous mis-spellings

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-21

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §18.3.1.25 (pp. 1786), §18.3.2.2 (pp. 1888), §18.10.1.46 (pp. 2072)

**Related DR(s):** none

**Nature of the Defect:**

In §18.3.1.25 the token ‘AutoFilter’ is mis-spelt ‘AutoFitler’ in text following the attribute name ‘showAutoFilter’ in the attribute definition table.

In §18.3.2.2 ‘filter’ is mis-spelt ‘fitler’ in the first paragraph.

In §18.10.1.46 the word ‘if’ is mis-spelt ‘f’ in the first paragraph of the example.

**Solution Proposed by the Submitter:**

Correct the spelling:

In §18.3.1.25:

showAutoFilter (Show AutoFitler Drop Down Controls)

In §18.3.2.2:

A custom AutoFilter specifies an operator and a value. There can be at most two customFilters specified, and in that case the parent element specifies whether the two conditions are joined by 'and' or 'or'. For any cells whose values do not meet the specified criteria, the corresponding rows shall be hidden from view when the filter is applied.

In §18.10.1.46:

[Example: In the following SpreadsheetML example, the first field is "Customer Name" and the first item referenced here is <item x="66"/> which references the value "Adam L Flores" in the pivotCacheDefinition. Therefore if you added "Customer Name" to the row axis, "Adam L Flores" would be the first row item listed.]

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed.

The exact changes are as follows:

Part 1, §18.3.1.25, “customSheetView (Custom Sheet View)”, (pp. 1786)

Attributes	Description
showAutoFilter (Show AutoFilter Drop Down Controls)	Flag indicating whether the autofilter dropdown buttons are visible in this custom view. The possible values for this attribute are defined by the W3C XML Schema boolean datatype.

Part 1, §18.3.2.2, “customFilter (Custom Filter Criteria)”, (pp. 1888)

A custom AutoFilter specifies an operator and a value. There can be at most two customFilters specified, and in that case the parent element specifies whether the two conditions are joined by 'and' or 'or'. For any cells whose values do not meet the specified criteria, the corresponding rows shall be hidden from view when the filter is applied.

Part 1, §18.10.1.46, “items (Field Items)”, (pp.2072)

[Example: In the following SpreadsheetML example, the first field is "Customer Name" and the first item referenced here is <item x="66"/>, which references the value "Adam L Flores" in the pivotCacheDefinition. Therefore if you added "Customer Name" to the row axis, "Adam L Flores" would be the first row item listed.]

# 113. DR 09-0098 — SML: Duplicate mathematical expressions in function definitions

**Status:** Closed; will be incorporated in COR1

**Subject:** Duplicate mathematical expressions in function definitions

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-22

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §18.17.7.49 (pp. 2360), §18.17.7.89 (pp. 2410), §18.17.7.126 (pp. 2442), §18.17.7.170 (pp. 2482), §18.17.7.195 (pp. 2500), §18.17.7.247 (pp. 2557), §18.17.7.283 (pp. 2593), §18.17.7.292 (pp. 2600), §18.17.7.294 (pp. 2602), §18.17.7.303 (pp. 2609)

**Related DR(s):** none

## Nature of the Defect:

A number of mathematical expressions appear to have been duplicated as a result of some automated replacement process during preparation of the final text.

## Solution Proposed by the Submitter:

Remove duplicate expressions:

In §18.17.7.49:

- $\bar{y}$  = the sample mean  $\text{AVERAGE}(\text{array-2})$

In §18.17.7.89, §18.17.7.292:

- $\bar{x}$  = the mean of the elements in *argument-list*

In §18.17.7.126 (NOTE – styling of productions ‘known-xs’ and ‘known-ys’ probably also wrong in this case – see blue underlined text), §18.17.7.170, §18.17.7.195, §18.17.7.283, §18.17.7.294, §18.17.7.303:

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(known-xs)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(known-ys)

In §18.17.7.247:

- $x$  = a sample value
- $\bar{x}$  = the sample mean AVERAGE(*array-1*)
- $y$  = a sample value
- $\bar{y}$  = the sample mean AVERAGE(*array-2*)

**Schema Change(s) Needed:** No

**Editor’s Response:**

Agreed, and, yes, the style of those two productions is incorrect and will be fixed.

The exact changes are as follows:

Part 1, §18.17.7.49, “CORREL”, (pp. 2360)

- $\bar{y}$  = the sample mean AVERAGE(*array-2*)

Part 1, §18.17.7.89, “DEVSQ”, (pp. 2410)

- $\bar{x}$  = the mean of the elements in *argument-list*

Part 1, §18.17.7.126, “FORECAST”, (pp. 2442)

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(known-xs)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(known-ys)

Part 1, §18.17.7.170, “INTERCEPT”, (pp. 2482)

- $x$  = a sample value

- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

Part 1, §18.17.7.195, "", (pp. 2500)

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

Part 1, §18.17.7.247, "LINEST", (pp. 2557)

- $x$  = a sample value
- $\bar{x}$  = the sample mean AVERAGE(*array-1*)
- $y$  = a sample value
- $\bar{y}$  = the sample mean AVERAGE(*array-2*)

Part 1, §18.17.7.283, "RSQ", (pp. 2593)

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

Part 1, §18.17.7.292, "SKEW", (pp. 2600)

- $\bar{x}$  = the mean of the elements in *argument-list*

Part 1, §18.17.7.294, "STDEVA", (pp. 2602)

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

Part 1, §18.17.7.303, "STEYX", (pp. 2609)

- $x$  = a sample value
- $\bar{x}$  is the sample mean AVERAGE(*known-xs*)
- $y$  = a sample value
- $\bar{y}$  is the sample mean AVERAGE(*known-ys*)

## 114. DR 09-0099 — SML: No Normative References or Definitions for “MDX” and “OLAP”

**Status:** Open

**Subject:** No Normative References or Definitions for “MDX” and “OLAP”

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-23

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §12.3.10 (pps. 81, 83), §18.9 (pps. 1993–2010), §18.10.1.10 (pps. 2030, 2031), §18.10.1.11 (pp. 2032), §18.10.1.73 (pp. 2139, 2140), §18.10.1.75 (pp. 2148), §18.10.1.88 (pp. 2162, 2163), §18.13.5 (pp. 2228), §18.17.7.66 (pp. 2385), §18.17.7.67 (pp. 2386), §18.17.7.71 (pp. 2390), §18.18.44 (pp. 2698), §18.18.45 (pp. 2699), §18.18.46 (pp. 2700), §22.7.2.2 (pp. 4313), §22.9.2.19 (pp. 4336, 4337), and many locations in §M (Primer).

**Related DR(s):** none

**Nature of the Defect:**

There are no Normative References or Definitions for “OLAP” or “MDX”, which are cited in several places in §18.9 and elsewhere. There is a Note buried in §18.17.7.66 (and in several places thereafter), that says that “MDX is a standard query language for OLAP cubes.” (NOTE – inconsistent spelling of “MDX”, which is sometimes spelt “mdx”, especially in the Primer from §M.2.8.1 onwards.)

**Solution Proposed by the Submitter:**

Add Normative References and/or Definitions as appropriate, and, if necessary, make the corresponding specifications available. Correct spelling inconsistencies.

**Schema Change(s) Needed:** No

**Editor's Response:**

Work in progress.

**2009-03-24 Prague meeting:**

Is MDX covered by the OSP? Action for Doug.

# 115. DR 09-0100 — Part 1: Unnecessary annex

**Status:** Closed; will be incorporated in COR1

**Subject:** Part 1: Unnecessary annex

**Qualifier:** Editorial defect

**Submitter:** Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §E, “Processing Bitfields with XSLT”, pp. 4937–4939

**Related DR(s):** none

## **Nature of the Defect:**

As a result of the BRM, in strict conformance mode all elements using bitfields had those changed to named attributes. As a result, Annex E is no longer necessary and should be removed.

## **Solution Proposed by the Submitter:**

Remove Annex E.

**Schema Change(s) Needed:** No

## **Editor's Response:**

Agreed

## **2009-03-24 Prague meeting:**

Confirmed. Remove annex from Part 1, and do *not* move it to Part 4.

The exact changes are as follows:

Part 1, §E, “Processing Bitfields with XSLT”, pp. 4937–4939

Delete this annex.

# 116. DR 09-0101 — WML, Fields: Grammar Production letter

**Status:** Closed; will be incorporated in COR1

**Subject:** WML, Fields: Grammar Production letter

**Qualifier:** Editorial defect

**Submitter:** Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.16.1, "Syntax", pp. 1304.

**Related DR(s):** none

## Nature of the Defect:

The definition of the production letter is, as follows:

```
letter=
 "a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
 "n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
 "a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
 "n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z" ;
```

In DIS 29500, as considered by the BRM, the equivalent of `letter` was described in narrative, where both upper- and lowercase letters were permitted. As a result of the BRM, the editor was directed to express the complete field grammar using the notation defined by ISO/IEC 14977. What resulted was a duplicate set of 26 lowercase letters, when one of the sets should have been uppercase.

## Solution Proposed by the Submitter:

Correct the definition of the production letter, as follows:

```
letter=
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
"a""b""c""d""e""f""g""h""i""j""k""l""m""n""o""p""q""r""s""t""u""v""w""x""y""z":
" A"|"B"|"C"|"D"|"E"|"F"|"G"|"H"|"I"|"J"|"K"|"L"|"M"|
" n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z" ;
" N"|"O"|"P"|"Q"|"R"|"S"|"T"|"U"|"V"|"W"|"X"|"Y"|"Z" ;
```

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed

The exact changes are as follows:

Part 1, §17.16.1, "Syntax", pp. 1304.

```
letter=
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
"a""b""c""d""e""f""g""h""i""j""k""l""m""n""o""p""q""r""s""t""u""v""w""x""y""z":
" A"|"B"|"C"|"D"|"E"|"F"|"G"|"H"|"I"|"J"|"K"|"L"|"M"|
" n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z" ;
" N"|"O"|"P"|"Q"|"R"|"S"|"T"|"U"|"V"|"W"|"X"|"Y"|"Z" ;
```

# 117. DR 09-0102 — SML, Formulas: Grammar Production letter

**Status:** Closed; will be incorporated in COR1

**Subject:** SML, Formulas: Grammar Production letter

**Qualifier:** Editorial defect

**Submitter:** Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §18.17.2.3.1, “A1-Style Cell References”, pp. 2285.

**Related DR(s):** none

## Nature of the Defect:

The definition of the production letter is, as follows:

```
letter=
 "a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
 "n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
 "a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
 "n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z" ;
```

In DIS 29500, as considered by the BRM, the equivalent of `letter` was described in narrative, where both upper- and lowercase letters were permitted. As a result of the BRM, the editor was directed to express the complete formulas grammar using the notation defined by ISO/IEC 14977. What resulted was a duplicate set of 26 lowercase letters, when one of the sets should have been uppercase.

## Solution Proposed by the Submitter:

Correct the definition of the production letter, as follows:

```
letter=
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"
"A"|"B"|"C"|"D"|"E"|"F"|"G"|"H"|"I"|"J"|"K"|"L"|"M"
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z";
"N"|"O"|"P"|"Q"|"R"|"S"|"T"|"U"|"V"|"W"|"X"|"Y"|"Z" ;
```

**Schema Change(s) Needed:** No

**Editor's Response:**

Agreed

The exact changes are as follows:

Part 1, §18.17.2.3.1, "A1-Style Cell References", pp. 2285.

```
letter=
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"|
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z"|
"a"|"b"|"c"|"d"|"e"|"f"|"g"|"h"|"i"|"j"|"k"|"l"|"m"
"A"|"B"|"C"|"D"|"E"|"F"|"G"|"H"|"I"|"J"|"K"|"L"|"M"
"n"|"o"|"p"|"q"|"r"|"s"|"t"|"u"|"v"|"w"|"x"|"y"|"z";
"N"|"O"|"P"|"Q"|"R"|"S"|"T"|"U"|"V"|"W"|"X"|"Y"|"Z" ;
```

# 118. DR 09-0103 — WML: Error in WML schema

**Status:** Open

**Subject:** WNL: Error in WML schema

**Qualifier:** Technical defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-034

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** wml.xsd, Part 1, §17.4.88, “...”.

**Related DR(s):** none Murata-san's DR 08-0001 through 0008

**Nature of the Defect:**

Error in wml.xsd schema - ST\_DecimalNumberOrPercent is missing ST\_DecimalNumber from its definition (only allows ST\_Percentage)

**Solution Proposed by the Submitter:**

Correct schema so ST\_DecimalNumberOrPercent is a union of ST\_DecimalNumber and ST\_Percentage

**Schema Change(s) Needed:** wml.xsd

**Editor's Response:**

# 119. DR 09-0104 — DML: Contradiction between text and dml-wordProcessingDrawing schema

**Status:** Open

**Subject:** DML: Contradiction between text and schema

**Qualifier:** Technical defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-035

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §20.4.2.3, dml-wordProcessingDrawing.xsd

**Related DR(s):** none

## **Nature of the Defect:**

behindDoc, locked, allowOverlap and layoutInCell attributes on CT\_Anchor are implicitly optional from the text of §20.4.2.3, but are required by the schema.

## **Solution Proposed by the Submitter:**

Alter schema to make these attributes on CT\_Anchor optional

**Schema Change(s) Needed:** dml-wordProcessingDrawing.xsd

## **Editor's Response:**

**2009-03-24 Prague meeting:**

Discussed; change schema or prose?

## 120. DR 09-0105 — WML: Errors in examples

**Status:** Open

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-036

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.16.21 (pp. 1422), §17.16.27, §17.16.28, §17.16.31, §17.18.25, §17.18.26, §17.18.27, §17.16.14, §17.16.17

**Related DR(s):** none

**Nature of the Defect:**

Element w:ffData is used in examples directly inside w:fldSimple, which is not valid.

**Solution Proposed by the Submitter:**

This could be resolved by adding a w:r inside the w:fldSimple to wrap the w:ffData, or by altering the schema to allow w:ffData directly inside the w:fldSimple.

**Schema Change(s) Needed:** No

**Editor's Response:**

**2009-03-24 Prague meeting:**

Discussed; no resolution

The instances of this problem are as follows:

Part 1, §17.16.6, “calcOnExit (Recalculate Fields When Current Field Is Modified)”, pp. 1402

```
<w:fldSimple w:instr="FORMFIELDTEXT">
 <w:ffData>
 ...
 </w:ffData>
 ...
</w:fldSimple>
```

Part 1, §17.16.14, “enabled (Form Field Enabled)”, pp. 1410

```
<w:fldSimple w:instr="FORMTEXT">
 <w:ffData>
 ...
 </w:ffData>
 ...
</w:fldSimple>
```

Part 1, §17.16.17, “ffData (Form Field Properties)”, pp. 1413

```
<w:fldSimple w:instr="FORMTEXT">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.16.21, “helpText (Associated Help Text)”, pp. 1422

```
<w:fldSimple w:instr="FORMDROPDOWN">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.16.27, “name (Form Field Name)”, pp. 1433

```
<w:fldSimple w:instr="FORMTEXT">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.16.28, “result (Drop-Down List Selection)”, pp. 1434

```
<w:fldSimple w:instr="FORMDROPDOWN">
```

```
<w:ffData>
 ...
</w:ffData>
</w:fldSimple>
```

Part 1, §17.16.31, “statusText (Associated Status Text)”, pp. 1437

```
<w:fldSimple w:instr="FORMDROPDOWN">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.18.25, “ST\_FFHelpTextVal (Help Text Value)”, pp. 1534

```
<w:fldSimple w:instr="FORMDROPDOWN">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.18.26, “ST\_FFFName (Form Field Name Value)”, pp. 1535

```
<w:fldSimple w:instr="FORMTEXT">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

Part 1, §17.18.27, “ST\_FFStatusTextVal (Status Text Value)”, pp. 1535

```
<w:fldSimple w:instr="FORMDROPDOWN">
 <w:ffData>
 ...
 </w:ffData>
</w:fldSimple>
```

## 121. DR 09-0106 — PML: Errors in examples

**Status:** Open

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-037

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §19.5.44, §19.5.88

**Related DR(s):** none

### **Nature of the Defect:**

from and to attributes take values for x and y defined by ST\_Percentage for a starting co-ordinate - which is inconsistent with the values in the examples, and seems unusual for a co-ordinate.

### **Solution Proposed by the Submitter:**

Make example, text and schema consistent for these sections - either by switching type of "from" and "to" to another type, or by changing the example to use percentages

### **Schema Change(s) Needed:**

### **Editor's Response:**

I agree that ST\_Percentage seems to be an unusual type for a co-ordinate. If the type is incorrect, clearly, this is not an editorial defect.

**2009-03-24 Prague meeting:**

Discussed; no resolution

## 122. DR 09-0107 — WML: Errors in examples

**Status:** [Further Consideration Required](#) ~~Closed; will be incorporated in COR1~~

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-038

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.3.1.16 (pp. 237), §17.3.1.32 (pp. 261), §17.3.1.33 (pps. 263, 265), §17.3.1.43 (pp. 277), §17.3.1.44 (pp. 279), §17.3.1.45 (pp. 280), §17.3.2 .10 (pps. 294 (twice), 295 (twice), 297), §17.3.2 .34 (pp. 331), §17.9.5 (pp. 781), §17.9.12 (pp. 797), §17.14.13 (pp. 1062) , §17.14.14 (pp. 1062) , §17.15.1.76 (pp. 1192) , §17.15.2.33 (pp. 1269 (twice)) , §17.15.2.38 (pp. 1276) , §17.18.8 (pp. 1514)

**Related DR(s):** DR 09-0159 — General: Unintended incompatibilities between Transitional schema and Ecma-376~~none~~

### Nature of the Defect:

Errors in examples: 'on' or 'off' is not a valid value for Boolean for examples in the specified sections.

### Solution Proposed by the Submitter:

Change the examples to use 'true' or 'false' in place of 'on' or 'off'

### Schema Change(s) Needed:

### Editor's Response:

Agreed.

The exact changes are as follows:

Part 1, §17.3.1.15, “kinsoku (Use East Asian Typography Rules for First and Last Character per Line)”, (pp. 237)

```
<w:pPr>
 <w:kinsoku w:val="falseoff" />
</w:pPr>
```

Part 1, §17.3.1.32, “snapToGrid (Use Document Grid Settings for Inter-Line Paragraph Spacing)”, (pp. 261)

```
<w:p>
 <w:pPr>
 <w:snapToGrid w:val="falseoff" />
 </w:pPr>
 ...
</w:p>
```

Part 1, §17.3.1.33, “spacing (Spacing Between Lines and Above/Below Paragraph)”, (pp. 263), attribute afterAutospacing

```
<w:pPr>
 <w:spacing ... w:afterAutospacing="trueon" />
</w:pPr>
```

Part 1, §17.3.1.33, “”, (pp. 265), attribute beforeAutospacing

```
<w:pPr>
 <w:spacing ... w:beforeAutospacing="trueon" />
</w:pPr>
```

Part 1, §17.3.1.43, “topLinePunct (Compress Punctuation at Start of a Line)”, (pp. 277)

```
<w:pPr>
 <w:topLinePunct w:val="trueon" />
</w:pPr>
```

Part 1, §17.3.1.44, “widowControl (Allow First/Last Line to Display on a Separate Page)”, (pp. 279)

```
<w:pPr>
 <w:widowControl w:val="falseoff" />
</w:pPr>
```

Part 1, §17.3.1.45, “wordWrap (Allow Line Breaking At Character Level)”, (pp. 280)

```
<w:pPr>
 <w:wordWrap w:val="falseoff" />
```

```
</w:pPr>
```

Part 1, §17.3.2 .10, “eastAsianLayout (East Asian Typography Settings)”, (pp. 294)

```
<w:rPr>
 <w:eastAsianLayout w:id="1" w:combine="trueon" />
</w:rPr>
...
<w:r>
 <w:rPr>
 <w:eastAsianLayout w:id="2" w:vert="trueon" />
 </w:rPr>
 <w:t>vertical</w:t>
</w:r>
```

Part 1, §17.3.2 .10, “eastAsianLayout (East Asian Typography Settings)”, (pp. 295), attribute combine

```
<w:rPr>
 <w:eastAsianLayout w:id="1" w:combine="trueon" />
</w:rPr>
```

Part 1, §17.3.2 .10, “eastAsianLayout (East Asian Typography Settings)”, (pp. 295), attribute combineBrackets

```
<w:r>
 <w:rPr>
 <w:eastAsianLayout w:id="1" w:combine="trueon" w:combineBrackets="curly"/>
 </w:rPr>
 <w:t>two lines in one</w:t>
</w:r>
```

Part 1, §17.3.2 .10, “eastAsianLayout (East Asian Typography Settings)”, (pp. 296), attribute vert

```
<w:r>
 <w:rPr>
 <w:eastAsianLayout w:id="2" w:vert="trueon" />
 </w:rPr>
 <w:t>vertical</w:t>
</w:r>
```

Part 1, §17.3.2 .34, “snapToGrid (Use Document Grid Settings For Inter-Character Spacing)”, (pp. 331)

```
<w:rPr>
 <w:snapToGrid w:val="falseoff" />
</w:rPr>
```

Part 1, §17.9.5, “legacy (Legacy Numbering Level Properties)”, (pp. 781), attribute legacy

```
<w:legacy w:legacy="falseoff" w:legacySpace="820"
w:legacyIndent="960" />
```

Part 1, §17.9.12, “lvlText (Numbering Level Text)”, (pp. 797), attribute null

```
<w:lvl w:ilvl="1">
...
<w:lvlText w:null="trueon" />
...
</w:lvl>
```

Part 1, §17.14.13, “dynamicAddress (Use Country-Based Address Field Ordering)”, (pp. 1062)

```
<w:fieldMapData>
...
<w:dynamicAddress w:val="falseoff" />
</w:fieldMapData>
```

Part 1, §17.14.14, “fHdr (First Row of Data Source Contains Column Names)”, (pp. 1062)

```
<w:fHdr w:val="trueon" />
```

Part 1, §17.15.1.76, “saveThroughXslt (Custom XSL Transform To Use When Saving As XML File)”, (pp. 1192)

```
<w:useXSLTWhenSaving w:val="trueon" />
```

Part 1, §17.15.2.33, “optimizeForBrowser (Disable Features Not Supported by Target Web Profile)”, (pp. 1269)

```
<w:webSettings>
...
<w:optimizeForBrowser w:target="W3C XHTML+CSS1" />
<w:allowPNG w:val="trueon" />
<w:relyOnVML w:val="trueon" />
</w:webSettings>
```

Part 1, §17.15.2.38, “scrollbar (Scrollbar Display Option)”, (pp. 1276), attribute val

```
<w:frame>
 <w:scrollbar w:val="trueon" />
 ...
</w:frame>
```

Part 1, §17.18.8, “ST\_CombineBrackets (Two Lines in One Enclosing Character Type)”, (pp. 1514)

```
<w:rPr>
 <w:eastAsianLayout w:id="1" w:combine="trueon" w:combineBrackets="curly"/>
</w:rPr>
```

**2009-05-08 MURATA, Makoto**

DR 09-107 (examples containing "on" or "off" are incorrect) is "LAST CALL", but I disagree. If we accept the change proposed by DR 09-0159, "on" and "off" will become correct. This DR should go back to "FURTHER CONSIDERATION".

## 123. DR 09-0108 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-039

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §11.3.11 (pp. 55), §17.3.1.13 (pp. 231), §17.3.1.37 (pps. 269, 270 twice), §17.3.1.38 (pp. 271 twice), §17.3.3.23 (pp. 371 twice), §17.3.3.32 (pp. 383 twice), §17.4.27 (pp. 441), §17.4.28 (pp. 442), §17.4.29 (pp. 443), §17.4.32 (pp. 446), §17.4.51 (pp. 469 twice), §17.9 (pp. 773), §17.9.1 (pp. 774, 775), §17.9.5 (pp. 780), §17.9.6 (pp. 782, 783), §17.9.8 (pp. 788), §17.9.9 (pp. 790 twice, 791 twice), §17.9.11 (pp. 793 twice), §17.9.18 (pp. 802), §17.9.18 (pp. 804), §17.18.84 (pp. 1651), §M.1.10.3 (pp. 5116), §M.1.10.4 (pp. 5118), §M.1.10.6 (pp. 5122), §M.1.10.8 (pp. 5125, 5126)

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: specified examples use values "left" and "right" in the w:val attribute for w:tab or w:jc or w:lvlJc which are not valid - should be replaced with bi-directional aware values

**Solution Proposed by the Submitter:**

Change "left" to "start" in the specified examples, and "right" to "end"

**Schema Change(s) Needed:**

**Editor's Response:**

Agreed. (I located some other instances, and added those to the list above.)

The exact changes are as follows:

Part 1, §11.3.11, “Numbering Definitions Part”, (pp. 55)

```
<w:lvl w:ilvl="0" w:tplc="151C4798">
 ...
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §17.3.1.13, “jc (Paragraph Alignment)”, (pp. 231)

```
<w:pPr>
 <w:jc w:val="endright" />
</w:pPr>
```

Part 1, §17.3.1.37, “tab (Custom Tab Stop)”, (pp. 269)

```
<w:tab w:val="startleft" w:pos="2160" />
```

Part 1, §17.3.1.37, “tab (Custom Tab Stop)”, (pp. 270), attribute pos

```
<w:tab w:val="startleft" w:pos="2160" />
```

Part 1, §17.3.1.37, “tab (Custom Tab Stop)”, (pp. 270), attribute val

```
<w:tab w:val="startleft" w:pos="2160" />
```

Part 1, §17.3.1.38, “tabs (Set of Custom Tab Stops)”, (pp. 271)

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="startleft" w:pos="2160" />
 <w:tab w:val="startleft" w:pos="5040" />
 </w:tabs>
</w:pPr>
```

Part 1, §17.3.3.23, “ptab (Absolute Position Tab Character)”, (pp. 371)

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="startleft" w:pos="2160" />
 <w:tab w:val="startleft" w:pos="5040" />
 </w:tabs>
```

```
</w:pPr>
```

Part 1, §17.3.3.32, “tab (Tab Character)”, (pp. 383)

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="startLeft" w:pos="2160" />
 <w:tab w:val="startLeft" w:pos="5040" />
 </w:tabs>
</w:pPr>
```

Part 1, §17.4.27, “jc (Table Alignment Exception)”, (pp. 441)

```
<w:tblPrEx>
 <w:jc w:val="startLeft"/>
</w:tblPrEx>
```

Part 1, §17.4.28, “jc (Table Row Alignment)”, (pp. 442)

```
<w:trPr>
 <w:jc w:val="startLeft"/>
</w:trPr>
```

Part 1, §17.4.29, “jc (Table Alignment)”, (pp. 443)

```
<w:tblPr>
 <w:jc w:val="endRight"/>
</w:tblPr>
```

Part 1, §17.4.31, “shd (Table Shading Exception)”, (pp. 446)

```
<w:tblPrEx>
 <w:jc w:val="startLeft" />
 <w:shd w:val="clear" w:color="auto" w:fill="EEECE1" w:themeFill="background2"
 />
</w:tblPrEx>
```

Part 1, §17.4.51, “tblInd (Table Indent from Leading Margin)”, (pp. 469)

```
<w:tblPr>
 <w:jc w:val="startLeft"/>
 <w:tblInd w:w="1440" w:type="dxa"/>
</w:tblPr>
```

...

```
<w:tblPr>
 <w:jc w:val="endRight"/>
```

```
<w:tblInd w:w="1440" w:type="dxa"/>
</w:tblPr>
```

Part 1, §17.9, “Numbering”, (pp. 773)

```
<w:lvl w:ilvl="0">
 <w:start w:val="1" />
 <w:lvlText w:val="%1." />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §17.9.1, “abstractNum (Abstract Numbering Definition)”, (pp. 774, 775)

```
<w:lvl w:ilvl="0">
 <w:start w:val="1" />
 <w:lvlText w:val="%1." />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §17.9.5, “legacy (Legacy Numbering Level Properties)”, (pp. 780)

```
<w:lvl w:ilvl="0">
 ...
 <w:legacy w:legacySpace="820" w:legacyIndent="960" />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §17.9.6, “lvl (Numbering Level Override Definition)”, (pp. 782)

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §17.9.6, “lvl (Numbering Level Override Definition)”, (pp. 783)

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

```
</w:lvl>
```

Part 1, §17.9.8, “lvlJc (Justification)”, (pp. 788)

```
<w:lvl w:ilvl="8" w:tplc="756C1446" w:tentative="1">
 <w:start w:val="1" />
 <w:numFmt w:val="bullet" />
 <w:lvlText w:val="•" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
```

Part 1, §17.9.9, “lvlOverride (Numbering Level Definition Override)”, (pp. 790)

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
...
<w:lvl w:ilvl="1">
 <w:start w:val="5" />
 <w:lvlText w:val="%Test)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
```

Part 1, §17.9.9, “lvlOverride (Numbering Level Definition Override)”, (pp. 791)

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
```

Part 1, §17.9.9, “lvlOverride (Numbering Level Definition Override)”, (pp. 791), attribute ilvl

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
```

Part 1, §17.9.11, “lvlRestart (Restart Numbering Level Symbol)”, (pp. 793-794)

```

<w:lvl w:ilvl="0">
 <w:start w:val="1" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>
<w:lvl w:ilvl="1">
 <w:start w:val="1" />
 <w:numFmt w:val="upperLetter" />
 <w:lvlText w:val="%2)" />
 <w:lvlJc w:val="startLeft" />
</w:lvl>
<w:lvl w:ilvl="2">
 <w:start w:val="1" />
 <w:numFmt w:val="lowerRoman" />
 <w:lvlRestart w:val="0">
 <w:lvlText w:val="%3)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>

```

Part 1, §17.9.18, “num (Numbering Definition Instance)”, (pp. 802)

```

<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>

```

Part 1, §17.9.18, “numFmt (Numbering Format)”, (pp. 804)

```

<w:lvl w:ilvl="2">
 <w:start w:val="1" />
 <w:numFmt w:val="lowerRoman" />
 <w:lvlRestart w:val="0" />
 <w:lvlText w:val="%3)" />
 <w:lvlJc w:val="startLeft" />
 ...
</w:lvl>

```

Part 1, §17.18.84, “ST\_TabJc (Custom Tab Stop Type)”, (pp. 1651)

```
<w:tab w:val="startleft" w:pos="2160" />
```

Part 1, §M.1.10.3, “Abstract Numbering Definitions”, (pp. 5116)

```
<w:lvl w:ilvl="1">
 <w:start w:val="4"/>
 <w:nfc w:val="3"/>
 <w:pStyle w:val="Heading1"/>
 <w:lvlText w:val="BEFORE %2 AFTER %1 END"/>
 <w:lvlJc w:val="startleft"/>
 ...
</w:lvl>
```

Part 1, §M.1.10.4, “Numbering Definition Instances”, (pp. 5118)

```
<w:lvl w:ilvl="0">
 <w:start w:val="4" />
 <w:lvlText w:val="%1)" />
 <w:lvlJc w:val="startleft" />
 <w:pPr>
 <w:ind w:left="360" w:hanging="360" />
 </w:pPr>
</w:lvl>
```

Part 1, §M.1.10.6, “The Complete Story”, (pp. 5122)

```
<w:lvl w:ilvl="0">
 <w:start w:val="1" />
 <w:lvlText w:val="%1." />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §M.1.10.8, “Referencing Numbering Styles”, (pp. 5125)

```
<w:lvl w:ilvl="0">
 <w:lvlText w:val="%1 %1 %1" />
 <w:lvlJc w:val="startleft" />
 ...
</w:lvl>
```

Part 1, §M.1.10.8, “Referencing Numbering Styles”, (pp. 5126)

```
<w:lvl w:ilvl="0">
 <w:lvlText w:val="%1 %1 %1" />
 <w:lvlJc w:val="startleft" />
```

...  
</w:lvl>

## 124. DR 09-0109 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-040

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.15.1.7, §17.15.1.8, §17.15.1.16, §17.15.1.16, §17.15.1.18

**Related DR(s):** none

### **Nature of the Defect:**

Errors in examples: specified examples use value 8212 for w:sep attribute on w:caption element

### **Solution Proposed by the Submitter:**

Change "8212" to "colon" in the specified examples

### **Schema Change(s) Needed:**

### **Editor's Response:**

After discussion with the submitter, it was agreed that the correct replacement text was "hyphen" rather than "colon".

The exact changes are as follows:

Part 1, §17.15.1.7, "autoCaption (Single Automatic Captioning Setting)", pp. 1098

```

<w:captions>
 <w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
 w:numFmt="upperLetter" w:sep="hyphen8212" />
 <w:autoCaptions>
 <w:autoCaption w:name="wfwTable" w:caption="Table" />
 </w:autoCaptions>
</w:captions>

```

Part 1, §17.15.1.8, “autoCaptions (Automatic Captioning Settings)”, pp. 1101

```

<w:captions>
 <w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
 w:numFmt="upperLetter" w:sep="hyphen8212" />
 <w:autoCaptions>
 <w:autoCaption w:name="wfwTable" w:caption="Table" />
 </w:autoCaptions>
</w:captions>

```

Part 1, §17.15.1.16, “caption (Single Caption Type Definition)”, pp. 1114, attribute chapNum

```

<w:caption w:name="Table" w:pos="below" w:chapNum="true"
 w:heading="2" w:numFmt="upperLetter" w:sep="hyphen8212" />

```

Part 1, §17.15.1.16, “caption (Single Caption Type Definition)”, pp. 1115, attribute heading

```

<w:caption w:name="Table" w:pos="below" w:chapNum="1"
 w:heading="2" w:numFmt="upperLetter" w:sep="hyphen8212" />

```

In other words, the WordprocessingML above can be used to label tables inserted in a given WordprocessingML document generated by an application with a caption consisting of: the string Table followed by a decimal number corresponding with the chapter number in which the table is present, a hyphendash as defined in the sep attribute, and a capital English letter defined by the numFmt attribute corresponding with the given table's ordering within the current chapter. *end example]*

Part 1, §17.15.1.18, “captions (Caption Settings)”, pp. 1122

```

<w:caption w:name="Table" w:pos="below" w:chapNum="1" w:heading="2"
 w:numFmt="upperLetter" w:sep="hyphen8212" />

```

## 125. DR 09-0110 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-041

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.3.1.40

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: <w:textboxTightWrap w:val="all" /> is using invalid value "all" - should be "allLines"

### **Solution Proposed by the Submitter:**

Change "all" to "allLines" in the specified examples

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §17.3.1.40, “textboxTightWrap (Allow Surrounding Paragraphs to Tight Wrap to Text Box Contents)”, pp. 273

```
<w:pPr>
 <w:textboxTightWrap w:val="allLines" />
</w:pPr>
```

## 126. DR 09-0111 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-042

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.3.1.41, §17.3.1.41, §17.4.73, §17.6.20, §17.6.20

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: <w:sectPr>... <w:textDirection w:val="btLr" /></w:sectPr> is using invalid value btLr - should be "1r" - also w:textFlow used rather than correct w:textDirection in first example, and tbRl used in place of rl.

**Solution Proposed by the Submitter:**

Change "btLr" to "1r", also change "w:textDirection" not "w:textFlow" where necessary in example

**Schema Change(s) Needed:**

**Editor's Response:**

The narrative relating to most of these examples is confusing (if not incorrect) as it was not updated when the set of old attribute values was replaced. Part 1, §17.18.93, "ST\_TextDirection (Text Flow Direction)", pp. 1665,

contains the correct descriptions for the new set of attribute values, and I have rewritten the narratives below to reflect those descriptions.

The exact changes are as follows:

Part 1, §17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, pp. 275

[*Example:* Consider a document with a paragraph in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally~~. This setting would be specified with the following WordprocessingML:

```
<w:pPr>
 <w:textDirection w:val="lrbtLr" />
</w:pPr>
```

The textDirectionFlow element specifies via the lrbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~should go bottom to top, and left to right~~.  
*end example]*

Part 1, §17.3.1.41, “textDirection (Paragraph Text Flow Direction)”, pp. 275, attribute val

[*Example:* Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally~~. This setting requires the following WordprocessingML:

```
<w:sectPr>
 ...
 <w:textDirection w:val="lrbtLr" />
</w:sectPr>
```

The textDirection element specifies via the lrbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~should go bottom to top, and left to right~~.  
*end example]*

Part 1, §17.4.73, “textDirection (Table Cell Text Flow Direction)”, pp. 507

[*Example:* Consider a table with one cell in which all the table cell's text flow is oriented vertically, flowing from right to left horizontally within that cell.~~top to bottom right to left~~:

	Text in table this cell
--	-------------------------------

This table cell would specify this text flow using the following WordprocessingML:

```
<w:tc>
```

```

<w:tcPr>
 ...
 <w:textDirection w:val="rltbRl" />
 </w:tcPr>
 ...
</w:tc>
```

The textDirection element specifies via the rltbRl value in the val attribute that the text flow is to be oriented vertically, with subsequent lines stacked from right to left.~~should go top to bottom, then right to left.~~ end example]

Part 1, §17.4.73, “textDirection (Table Cell Text Flow Direction)”, pp. 508, attribute val

[Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally.~~ This setting requires the following WordprocessingML:

```

<w:sectPr>
 ...
 <w:textDirection w:val="lrbtLr" />
 </w:sectPr>
```

The textDirection element specifies via the lrbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~go bottom to top, and left to right.~~ end example]

Part 1, §17.6.20, “textDirection (Text Flow Direction)”, pp. 667

[Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally.~~ This setting requires the following WordprocessingML:

```

<w:sectPr>
 ...
 <w:textDirection w:val="lrbtLr" />
 </w:sectPr>
```

The textDirection element specifies via the lrbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right.~~go bottom to top, and left to right.~~ end example]

Part 1, §17.6.20, “textDirection (Text Flow Direction)”, pp. 667, attribute val

[Example: Consider a document with a section in which text must be oriented vertically, flowing from left to right horizontally on the page.~~should flow bottom to top vertically, and left to right horizontally.~~ This setting requires the following WordprocessingML:

```
<w:sectPr>
 ...
 <w:textDirection w:val="1rbtLr" />
</w:sectPr>
```

The textDirection element specifies via the 1rbtLr value in the val attribute that the text flow must be oriented vertically, with subsequent lines stacked from left to right. go bottom to top, and left to right. end example

Part 1, §17.18.93, “ST\_TextDirection (Text Flow Direction)”, pp. 1665

[*Example: Consider an object in which text must be oriented vertically, flowing from left to right horizontally on the page. flow bottom to top vertically, and left to right horizontally. This is achieved by using an 1rbtLr value in an element of type ST\_TextDirection specifies that the text flow must go bottom to top, and left to right. end example*]

Part 1, §N.1, “WordprocessingML”, pp. 5554

- The following enumeration values were added to the ST\_TextDirection simple type (§xx): bt, tb, r1, lr, tbV, r1V, and lrV.

## 127. DR 09-0112 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-043

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.15.1.44, §17.15.1.46

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: examples reference "dontUseMarginsForDrawingGridOrigin" rather than "doNotUseMarginsForDrawingGridOrigin"

**Solution Proposed by the Submitter:**

Change "dontUseMarginsForDrawingGridOrigin" to "doNotUseMarginsForDrawingGridOrigin" in example

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §17.15.1.44, "drawingGridHorizontalOrigin (Drawing Grid Horizontal Origin Point)", pp. 1158

```

<w:settings>
...
<w:doNotUseMarginsForDrawingGridOrigin w:val="true" />
<w:drawingGridHorizontalOrigin w:val="4320" />
...
</w:settings>

```

The drawingGridHorizontalOrigin element's val attribute is equal to 4320 specifying that the horizontal edge of the document's drawing grid must begin three inches (4320 twentieths of a point) from the left edge of the page, since the doNotUseMarginsForDrawingGridOrigin element's val attribute is equal to true. *end example]*

Part 1, §17.15.1.46, “drawingGridVerticalOrigin (Drawing Grid Vertical Origin Point)”, pp. 1160

[*Example:* Consider a WordprocessingML document whose drawing grid must begin one inch (1440 twentieths of a point) before the top edge of the page. This requirement would be specified using the following WordprocessingML markup in the document settings:

```

<w:settings>
...
<w:doNotUseMarginsForDrawingGridOrigin w:val="true" />
<w:drawingGridVerticalOrigin w:val="1440" />
...
</w:settings>

```

The drawingGridVerticalOrigin element's val attribute is equal to 1440 specifying that the vertical edge of the document's drawing grid must begin one inch (1440 twentieths of a point) from the top edge of the page, since the doNotUseMarginsForDrawingGridOrigin element's val attribute is equal to true. *end example]*

## 128. DR 09-0113 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-044

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.15.1.93

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: examples use invalid attribute w:hash on w:writeProtection

**Solution Proposed by the Submitter:**

Change "w:hash" to "w:hashValue" in example

**Schema Change(s) Needed:**

**Editor's Response:**

In reviewing the prose in this example, I noticed that it was nonsensical, so I've replaced it.

The exact changes are as follows:

Part 1, §17.15.1.93, "writeProtection (Write Protection)", pp. 1213

[*Example:* Consider a WordprocessingML document that can be opened but only in a write protected state unless a password is provided, in which case the file would be opened in an editable state. This requirement would be specified using the following WordprocessingML in the document settings:

```
<w:writeProtection w:hashValue="9oN7nWkCAyEZib1RomSJTjmPpCY=" />
```

If the attributes specified in the password attribute group AG\_Password (\$xx) are present, then the application shall require a password to exit write protection. If the supplied password does not match the hash value in the attribute hashValue, then write protection shall be enabled. The writeProtection element is present which specifies that write protection must be turned on for this document. Since the password attribute is equal to 9oN7nWkCAyEZib1RomSJTjmPpCY= the given WordprocessingML document can only be opened in a write protected state unless a password which matches the hash value 9oN7nWkCAyEZib1RomSJTjmPpCY= is provided; in which case the file would be opened in an editable state. end example]

## 129. DR 09-0114 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-045

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.3.3.18

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: example uses invalid element nonBreakHyphen

**Solution Proposed by the Submitter:**

Change "nonBreakHyphen" to "noBreakHyphen" in example

**Schema Change(s) Needed:**

**Editor's Response:**

I will improve the description of this element, and replace the example with one that is much more practical.

The exact changes are as follows:

Part 1, §17.3.3.18, “noBreakHyphen (Non Breaking Hyphen Character)”, pp. 363–364

This element specifies that a non-breaking hyphen character shall be placed at the current location in the run content. ~~A non-breaking hyphen is the equivalent of Unicode character U+002D (the hyphen-minus); however, it shall not be used as a line breaking character for the current line of text when displaying this WordprocessingML content.~~

The behavior of a non-breaking hyphen in run content shall be to display using the same glyph as the hyphen-minus character ([U+002D](#)), however, without [that hyphen](#) being a line breaking position (unlike the hyphen-minus character, which does allow line breaking).

[Example: Consider the following sentence in a WordprocessingML document: ‘Each citizen has a unique Social Security Number of the form “999-99-9999”, where each 9 represents a decimal digit.’ The fragment of this sentence involving the string literal might be represented in WordprocessingML, as follows:

```
<w:r>
 <w:t>Number of the form “999-99-9999”, where</w:t>
</w:r>
```

However, consider the case in which, on rendering, the right margin was such that the quoted string is broken across multiple lines with the hyphens being used as possible line breaking points; for example:

Each citizen has a unique Social Security Number of the form “999-99-9999”, where ...

If such line breaks are undesirable, those hyphens can be marked as non-breaking, as follows:

```
<w:r>
 <w:t>Number of the form “999</w:t>
</w:r>
<w:r>
 <w:noBreakHyphen />
 <w:t>99</w:t>
</w:r>
<w:r>
 <w:noBreakHyphen />
 <w:t>9999”, where</w:t>
</w:r>
```

in which case, for the same margin settings, the rendered result might be like the following:

Each citizen has a unique Social Security Number of the form  
“999-99-9999”, where ...

end example]

[Example: Consider the following sentence in a WordprocessingML document:

~~This makes a very very very wordy and deliberately overcomplicated sentence.~~

~~Normally, just as shown above, this sentence not would be displayed on a single line as it is long enough to require line breaking (given the width of the current page). However, if a hyphen minus were inserted after the letter s in sentence, as follows:~~

```
<w:r>
—<w:t>This makes a very very very wordy and deliberately overcomplicated s-entence.</w:t>
</w:r>
```

~~This would allow a break at that position, and break the word after that character:~~

~~This makes a very very very wordy and deliberately overcomplicated s-entence.~~

~~If this was not desired, the non breaking hyphen character could be specified as follows:~~

```
<w:r>
—<w:t>This makes a very very very wordy and deliberately overcomplicated s</w:t>
—<w:nonBreakHyphen/>
—<w:t>entence.</w:t>
</w:r>
```

~~This would display a hyphen character, but would not allow the text to break at that location:~~

~~This makes a very very very wordy and deliberately overcomplicated s-entence.~~

*end example]*

## 130. DR 09-0115 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Iñigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-046

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.4.22, §17.4.85, §17.18.57, §M.1.5.9

**Related DR(s):** none

### **Nature of the Defect:**

Errors in examples: examples use invalid elements hmerge and vmerge

### **Solution Proposed by the Submitter:**

Change "hmerge" to "hMerge", and "vmerge" to "vMerge" in example

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §17.4.22, “hMerge (Horizontally Merged Cell)”, pp. 436

```
<w:tc>
<w:tcPr>
```

```

<w:hMerge w:val="restart"/>
</w:tcPr>
...
</w:tc>
<w:tc>
<w:tcPr>
<w:hMerge/>
</w:tcPr>
...
</w:tc>
...

```

The **hMerge** element defines the cells that**which** are horizontally merged, and how each group is merged together. *end example]*

Part 1, §17.4.22, “hMerge (Horizontally Merged Cell)”, pp. 436, attribute val

```

<w:tcPr>
<w:hMerge w:val="restart"/>
</w:tcPr>

```

Part 1, §17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524

```

<w:tc>
<w:tcPr>
<w:vMerge w:val="restart"/>
</w:tcPr>
...
</w:tc>
...
<w:tc>
<w:tcPr>
<w:vMerge w:val="continue"/>
</w:tcPr>
...
</w:tc>
...
<w:tc>
<w:tcPr>
<w:vMerge w:val="continue"/>
</w:tcPr>
...
</w:tc>
...

```

The vM~~M~~erge element defines the cells that~~which~~ are vertically merged, and how each cell is merged together.  
*end example]*

Part 1, §17.4.85, “vMerge (Vertically Merged Cell)”, pp. 523–524, attribute val

```
<w:tcPr>
 <w:vMMerge w:val="restart"/>
</w:tcPr>
```

Part 1, §17.18.57, “ST\_Merge (Merged Cell Type)”, pp. 1569–1570

```
<w:tc>
 <w:tcPr>
 <w:vMMerge w:val="restart"/>
 </w:tcPr>
 ...
</w:tc>
...
<w:tc>
 <w:tcPr>
 <w:vMMerge w:val="continue"/>
 </w:tcPr>
 ...
</w:tc>
...
<w:tc>
 <w:tcPr>
 <w:vMMerge w:val="continue"/>
 </w:tcPr>
 ...
</w:tc>
```

The val attribute of type ST\_Merge on the vM~~M~~erge element defines the cells that~~which~~ are vertically merged, and how each cell is merged together. *end example]*

Part 1, §M.1.5.9, “Vertically Merged Cells”, pp. 5085

Although the previous examples might have implied that tables have strict definition of rows, table cells can also be merged vertically. The tcPr element can contain the vM~~M~~erge element that defines the extent of vertically merged grid columns within a table. A vM~~M~~erge element with its val attribute set to **restart** marks the start of a vertically merged cell range. A vM~~M~~erge element with the val attribute set to **continue** (the default value) marks the continuation of a vertically merged grid column. Cells between the first and last merged cell that are part of the vertical merge each must have a vM~~M~~erge element to continue the vertical merge.

Part 1, §M.1.5.9, “Vertically Merged Cells”, pp. 5086–5087

```
<w:tcPr>
 <w:vMerge w:val="restart"/>
</w:tcPr>
...
<w:tcPr>
 <w:vMerge/>
</w:tcPr>
```

As shown, the vMerge with a value of restart begins (or restarts) a merged region, and the cell with no value is merged with the one above.

# 131. DR 09-0116 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-047

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.14.23

**Related DR(s):** none

## **Nature of the Defect:**

Errors in examples: ordering of fieldMapData content elements doesn't match schema

## **Solution Proposed by the Submitter:**

Move "name" and "mappedName" to before "column" in example

## **Schema Change(s) Needed:**

## **Editor's Response:**

The exact changes are as follows:

Part 1, §17.14.23, “mappedName (Predefined Merge Field Name)”, pp. 1072

```
<w:fieldMapData>
 <w:column w:val="0" />
 <w:name w:val="Column Name A" />
 <w:mappedName w:val="First Name" />
 <w:column w:val="0" />
...
</w:fieldMapData>
<w:fieldMapData>
 <w:column w:val="1" />
 <w:name w:val="Column Name B" />
 <w:mappedName w:val="Last Name" />
 <w:column w:val="1" />
...
</w:fieldMapData>
```

## 132. DR 09-0117 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-048

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.15.1.1

**Related DR(s):** none

### **Nature of the Defect:**

Errors in examples: initial example of activeWritingStyle should include required attribute w:appName

### **Solution Proposed by the Submitter:**

Add attribute w:appName with value "testApp" to initial example

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §17.15.1.1, "activeWritingStyle (Grammar Checking Settings)", pp.

[Example: Consider the following WordprocessingML fragment from the document settings:

```
<w:activeWritingStyle w:lang="en-CA" w:vendorID="64" w:dllVersion="131078"
w:nlCheck="1" w:checkStyle="0" w:appName="testApp" />
```

The activeWritingStyle element's lang attribute specifies that the English (Canada) language setting for grammatical and stylistic checks must be applied; the vendorID attribute specifies information about the vendor associated with the DLL used to perform the grammatical and stylistic checks; the dllVersion attribute specifies the version of this DLL; the nlCheck attribute specifies if natural language checks were performed or not; **and** the checkStyle attribute specifies that the hosting application should allow its grammar engine to check both the grammar and style of the given WordprocessingML document, if that functionality is available; **and the appName attribute indicates that an application called testApp specified the grammar checking rules of the given WordprocessingML.** *end example]*

## 133. DR 09-0118 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-049

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §19.5.69, §19.5.76, §19.5.68

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: attribute r:link appears in examples for r:rnd element, which is not valid

**Solution Proposed by the Submitter:**

Remove r:link attribute from these examples

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §19.5.68, “rnd (Sound)”, pp.

```
<p:stSnd>
 <p:snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

Part 1, §19.5.69, “sndAc (Sound Action)”, pp. 2942

```
<p:stSnd>
 <p:snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

Part 1, §19.5.76, “stSnd (Start Sound Action)”, pp. 2949

```
<p:stSnd>
 <p:snd r:embed="rId2" r:link="rId3"/>
</p:stSnd>
```

## 134. DR 09-0119 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-050

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.3.1.39

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: attribute textAlignment has value baseLine, which is not valid

**Solution Proposed by the Submitter:**

Change value "baseLine" to "baseline" in these examples

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §17.3.1.39, "textAlignment (Vertical Character Alignment on Line)", pp. 272, attribute val

```
<w:pPr>
 <w:textAlignment w:val="baseLine" />
</w:pPr>
```

# 135. DR 09-0120 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-051

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §19.5.79, §19.5.80

**Related DR(s):** none

## **Nature of the Defect:**

Errors in examples: attribute tm of p:tav has value 0, which is not valid. Text does not make it clear whether tm 0 is a reasonable value or not

## **Solution Proposed by the Submitter:**

Change value "0" to value "1" in these examples - or change schema definition of ST\_TLTimeAnimateValueTime to allow 0 as a value

## **Schema Change(s) Needed:**

## **Editor's Response:**

By following the type hierarchy, I deduce that 0 is a well-defined value. However, a trailing % appears to be required, so I've kept the 0 value and added a %. However, as tm="100000" is incorrect even with a % added, I changed those to tm="100%".

The exact changes are as follows:

Part 1, §19.5.79, “tav (Time Animate Value)”, pp. 2952

```
<p:tavLst>
 <p:tav tm="0%">
 ...
 </p:tav>
 <p:tav tm="100000%">
 ...
 </p:tav>
</p:tavLst>
```

Part 1, §19.5.79, “tav (Time Animate Value)”, pp. 2955, attribute fmla

```
<p:tavLst>
 <p:tav tm="0%" fmla="#ppt_y-sin(pi*$)/3">
 ...
 </p:tav>
 <p:tav tm="100000%">
 ...
 </p:tav>
</p:tavLst>
```

Part 1, §19.5.80, “tavLst (Time Animated Value List)”, pp. 2956

```
<p:tavLst>
 <p:tav tm="0%">
 ...
 </p:tav>
 ...
</p:tavLst>
```

Part 1, §19.5.92, “tavLst val (Value)”, pp. 2965–2966

```
<p:tavLst>
 <p:tav tm="0%">
 ...
 </p:tav>
 <p:tav tm="100000%">
 ...
 </p:tav>
</p:tavLst>
```

# 136. DR 09-0121 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-052

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.7.4, §17.7.4.17, §17.7.8, §17.7.9, §M.1.8.2, §M.1.8.3, §M.1.8.4, §M.1.8.5, §M.1.8.11

**Related DR(s):** none

**Nature of the Defect:**

Errors in examples: invalid element name qformat is used

**Solution Proposed by the Submitter:**

Change "qformat" to "qFormat" in these examples

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §17.7.4, “General Style Properties”, pp. 683

<w:style w:type="paragraph" w:styleId="Heading1">

```

...
<w:qFformat/>
...
</w:style>
```

Part 1, §17.7.4.17, “style (Style Definition)”, pp. 707

```
<w:style w:type="paragraph" w:styleId="Heading1">
...
<w:qFformat/>
...
</w:style>
```

```
<w:style w:type="paragraph" w:styleId="Heading1">
...
<w:qFformat/>
...
</w:style>
```

Part 1, §17.7.8, “Paragraph Styles”, pp. 742

```
<w:style w:type="paragraph" w:styleId="TestParagraphStyle">
...
<w:qFformat/>
...
</w:style>
```

Part 1, §17.7.9, “Run (Character) Styles”, pp. 747

```
<w:style w:type="character" w:styleId="TestCharacterStyle">
...
<w:qFformat/>
...
</w:style>
```

Part 1, §M.1.8.2, “Style Definitions”, pp. 5097

```
<w:style w:type="paragraph" w:styleId="Heading1">
...
<w:qFformat/>
...
</w:style>
```

Part 1, §M.1.8.3, “Paragraph Styles”, pp. 5098

```
<w:style w:type="paragraph" w:styleId="TestParagraphStyle">
...
<w:qEformat/>
...
</w:style>
```

Part 1, §M.1.8.4, “Character Styles”, pp. 5099

```
<w:style w:type="character" w:styleId="TestCharacterStyle">
...
<w:qEformat/>
...
</w:style>
```

Part 1, §M.1.8.5, “Linked Styles”, pp. 5100

```
<w:style w:type="paragraph" w:styleId="TestLinkedStyle">
...
<w:qEformat/>
...
</w:style>
```

Part 1, §M.1.8.11, “Latent Styles”, pp. 5109

```
<w:latentStyles w:defLockedState="0" w:defUIPriority="99"
 w:defSemiHidden="1" w:defUnhideWhenUsed="1" w:defQFormat="0"
 w:count="180">
 <w:lsdException w:name="Normal" w:unhideWhenUsed="0"
 w:qEformat="1"/>
 <w:lsdException w:name="heading 1" w:semiHidden="0" w:uiPriority="1"/>
 <w:lsdException w:name="heading 2" w:uiPriority="1"
 w:unhideWhenUsed="1"/>
 <w:lsdException w:name="heading 3" w:semiHidden="0"/>
 <w:lsdException w:name="heading 4" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="heading 5" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="heading 6" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="heading 7" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="heading 8" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="heading 9" w:uiPriority="1" w:qEformat="1"/>
 <w:lsdException w:name="Normal Indent" w:uiPriority="6" w:qEformat="1"/>
</w:latentStyles>
```

## 137. DR 09-0122 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-053

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.4.39, §17.4.47, §17.4.60, §17.4.69, §17.4.66, §17.7.6, §17.7.6.8

**Related DR(s):** none

### Nature of the Defect:

Errors in examples: within w:tblBorders, elements w:left and w:right have been renamed to w:start and w:end, but examples are still using the former

### Solution Proposed by the Submitter:

Change "w:left" to "w:start" and "w:right" to "w:end" in these examples

### Schema Change(s) Needed:

### Editor's Response:

In searching for “<w:left ...” and “<w:right ...”, in general, I found a number of other examples (inside different parent elements) that are invalid for the same reason, so I took the liberty of extending this DR to include those as well. They are:

<w:tblCellMar>

§17.4.42, “tblCellMar (Table Cell Margin Exceptions)”, pp. 459

§17.4.43, “tblCellMar (Table Cell Margin Defaults)”, pp. 460

§17.4.70, “tcPr (Table Cell Properties)”, pp. 502

§17.7.4.17, “style (Style Definition)”, pp. 708

Part 1, §17.7.6, “Table Styles”, pp. 724

<w:tcBorders>

§17.4.67, “tcBorders (Table Cell Borders)”, pp. 499

<w:tcMar>

§17.4.69, “tcMar (Single Table Cell Margins)”, pp. 501

§17.4.70, “tcPr (Table Cell Properties)”, pp. 502

The exact changes are as follows:

Part 1, §17.4, “Tables”, pp. 399

```
<w:tblBorders>
...
<w:startleft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...
<w:endright w:val="single" w:sz="4" w:space="0" w:color="auto"/>
</w:tblBorders>
```

Part 1, §17.4.38, “tbl (Table)”, pp. 453

```
<w:tblBorders>
...
<w:startleft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...
<w:endright w:val="single" w:sz="4" w:space="0" w:color="auto"/>
</w:tblBorders>
```

Part 1, §17.4.39, “tblBorders (Table Borders)”, pp. 455

```

<w:tblBorders>
...
<w:startLeft w:val="single" w:sz="4" w:space="0" w:color="000000"
 w:themeColor="text1"/>
...
<w:endRight w:val="single" w:sz="4" w:space="0" w:color="000000"
 w:themeColor="text1"/>
...
<w:tblBorders>

```

Part 1, §17.4.40, “tblBorders (Table Borders Exceptions)”, pp. 457

```

<w:tblBorders>
...
<w:startLeft w:val="single" w:sz="24" w:space="0" w:color="000000"
 w:themeColor="text1"/>
...
<w:endRight w:val="single" w:sz="24" w:space="0" w:color="000000"
 w:themeColor="text1"/>
...
</w:tblBorders>

```

Part 1, §17.4.42, “tblCellMar (Table Cell Margin Exceptions)”, pp. 459

```

<w:tblCellMar>
...
<w:startLeft w:w="144" w:type="dxa"/>
...
<w:endRight w:w="144" w:type="dxa"/>
</w:tblCellMar>

```

Part 1, §17.4.43, “tblCellMar (Table Cell Margin Defaults)”, pp. 460

```

<w:tblCellMar>
...
<w:startLeft w:w="144" w:type="dxa"/>
...
<w:endRight w:w="144" w:type="dxa"/>
</w:tblCellMar>

```

Part 1, §17.4.60, “tblPr (Table Properties)”, pp. 485

```

<w:tblBorders>
...
<w:startLeft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...

```

```

<w:endright w:val="single" w:sz="4" w:space="0" w:color="auto"/>
...
</w:tblBorders>

```

Part 1, §17.4.61, “tblPrEx (Table-Level Property Exceptions)”, pp. 487

```

<w:tblBorders>
...
<w:startleft w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
 w:color="auto"/>
...
<w:endright w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
 w:color="auto"/>
...
</w:tblBorders>

```

Part 1, §17.4.62, “tblPrEx (Previous Table-Level Property Exceptions)”, pp. 489

```

<w:tr>
 <w:tblPrEx>
 <w:tblBorders>
 ...
 <w:startleft w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
 w:color="auto"/>
 ...
 <w:endright w:val="thinThickThinMediumGap" w:sz="24" w:space="0"
 w:color="auto"/>
 ...
 </w:tblBorders>
 <w:tblPrExChange w:id="9" ... >
 <w:tblPrEx>
 <w:tblBorders>
 ...
 <w:startleft w:val="thinThickThinSmallGap" w:sz="24" w:space="0"
 w:color="FF0000"/>
 ...
 <w:endright w:val="thinThickThinSmallGap" w:sz="24" w:space="0"
 w:color="FF0000"/>
 ...
 </w:tblBorders>
 ...
 </w:tblPrExChange>
 </w:tblPrEx>
</w:tr>

```

Part 1, §17.4.67, “tcBorders (Table Cell Borders)”, pp. 499

```

<w:tcPr>
 <w:tcBorders>
 ...
 <w:startLeft w:val="double" w:sz="24" w:space="0" w:color="FF0000"/>
 ...
 <w:endRight w:val="double" w:sz="24" w:space="0" w:color="FF0000"/>
 </w:tcBorders>
</w:tcPr>

```

Part 1, §17.4.69, “tcMar (Single Table Cell Margins)”, pp. 501

```

<w:tcMar>
 <w:top w:w="720" w:type="dxa"/>
 <w:startLeft w:w="720" w:type="dxa"/>
 <w:bottom w:w="720" w:type="dxa"/>
 <w:endRight w:w="720" w:type="dxa"/>
</w:tcMar>

```

Part 1, §17.4.70, “tcPr (Table Cell Properties)”, pp. 502

```

<w:tbl>
 <w:tblPr>
 <w:tblCellMar>
 <w:startLeft w:w="0" w:type="dxa"/>
 </w:tblCellMar>
 </w:tblPr>
 ...
 <w:tr>
 <w:tc>
 <w:tcPr>
 <w:tcMar>
 <w:startLeft w:w="720" w:type="dxa"/>
 </w:tcMar>
 </w:tcPr>
 ...
 </w:tc>
 </w:tr>
</w:tbl>

```

Part 1, §17.7.4.17, “style (Style Definition)”, pp. 708

```

<w:tblCellMar>
 ...
 <w:startLeft w:w="108" w:type="dxa"/>
 ...

```

```
<w:endright w:w="108" w:type="dxa"/>
</w:tblCellMar>
```

Part 1, §17.7.6, “Table Styles”, pp. 724

```
<w:tblPr>
 <w:tblBorders>
 ...
 <w:startleft w:val="single" w:sz="4" w:space="0" w:color="auto"/>
 ...
 <w:endright w:val="single" w:sz="4" w:space="0" w:color="auto"/>
 ...
 </w:tblBorders>
 <w:tblCellMar>
 ...
 <w:startleft w:w="108" w:type="dxa"/>
 ...
 <w:endright w:w="108" w:type="dxa"/>
 </w:tblCellMar>
</w:tblPr>
```

Part 1, §17.7.6.8, “tcPr (Table Style Conditional Formatting Table Cell Properties)”, pp. 736

```
<w:tcBorders>
 ...
 <w:startleft w:val="nil" />
 ...
 <w:endright w:val="nil" />
 ...
</w:tcBorders>
```

# 138. DR 09-0123 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-054

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §17.7.8.1, §17.9.6, §17.9.11, §17.9.11, §17.9.18, §17.9.23, §17.9.24, §17.3.1.12, §17.3.1.27,

**Related DR(s):** none

## Nature of the Defect:

Errors in examples: within w:ind, attributes w:left and w:right have been renamed to w:start and w:end, but examples are still using the former

## Solution Proposed by the Submitter:

Change "w:left" to "w:start", and "w:right" to "w:end" in these examples

## Schema Change(s) Needed:

## Editor's Response:

The exact changes are as follows:

Part 1, §11.3.11, "Numbering Definitions Part", pp. 55

```

<w:pPr>
 <w:tabs>
 <w:tab w:val="list" w:pos="720"/>
 </w:tabs>
 <w:ind w:startLeft="720" w:hanging="360"/>
</w:pPr>

```

Part 1, §11.3.12, “Style Definitions Part”, pp. 56

```

<w:pPr>
 <w:pStyle w:val="ListBullet"/>
 ...
 <w:ind w:startLeft="648"/>
</w:pPr>

```

Part 1, §17.3.1.12, “ind (Paragraph Indentation)”, pp. 226

```

<w:pPr>
 <w:ind w:startLeft="1440" w:endRight="1440" w:hanging="1080" />
</w:pPr>

```

Part 1, §17.3.1.27, “pStyle (Referenced Paragraph Style)”, pp. 253

[*Example:* Consider the following WordprocessingML fragment:

```

<w:pPr>
 <w:pStyle w:val="TestParagraphStyle" />
 <w:ind w:startLeft="1440" />
</w:pPr>

```

This paragraph specifies that it inherits all of the paragraph properties specified by the paragraph style with a styleId of TestParagraphStyle, which then has any indentation properties overridden with a startLeft indentation of 1440 twentieths of a point, and no indentation for any other value. *end example*]

Part 1, §17.7.8.1, “Numbering in Paragraph Styles”, pp. 744

```

<w:pPr>
 <w:tabs>
 <w:tab w:val="num" w:pos="720" />
 </w:tabs>
 <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>

```

Part 1, §17.9, “Numbering”, pp. 773

```

<w:pPr>
 <w:tabs>

```

```

<w:tab w:val="num" w:pos="720" />
</w:tabs>
<w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.1, “abstractNum (Abstract Numbering Definition)”, pp. 774

```

<w:pPr>
<w:tabs>
<w:tab w:val="num" w:pos="720" />
</w:tabs>
<w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.1, “abstractNum (Abstract Numbering Definition)”, pp. 775, attribute abstractNumId

```

<w:pPr>
<w:tabs>
<w:tab w:val="num" w:pos="720" />
</w:tabs>
<w:ind w:startLeft="720"/>
</w:pPr>
```

Part 1, §17.9.5, “legacy (Legacy Numbering Level Properties)”, pp. 780

```

<w:pPr>
<w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.6, “lvl (Numbering Level Override Definition)”, pp. 782–783

```

<w:pPr>
<w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>

<w:pPr>
<w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.9, “lvlOverride (Numbering Level Definition Override)”, pp. 790–791

```

<w:pPr>
<w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
...
<w:pPr>
```

```
<w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

```
<w:pPr>
 <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.9, “lvlOverride (Numbering Level Definition Override)”, pp. 791–792, attribute ilvl

```
<w:pPr>
 <w:ind w:startLeft="360" />
</w:pPr>
```

Part 1, §17.9.11, “lvlRestart (Restart Numbering Level Symbol)”, pp. 793–794

```
<w:pPr>
 <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
...
<w:pPr>
 <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
...
<w:pPr>
 <w:ind w:startLeft="1080" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.16, “num (Numbering Definition Instance)”, pp. 802

```
<w:pPr>
 <w:ind w:startLeft="360" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.18, “numFmt (Numbering Format)”, pp. 904

```
<w:pPr>
 <w:ind w:startLeft="1080" w:hanging="360" />
</w:pPr>
```

Part 1, §17.9.23, “pPr (Numbering Level Associated Paragraph Properties)”, pp. 810

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="num" w:pos="720" />
 </w:tabs>
 <w:ind w:startLeft="720" w:hanging="360" />
```

</w:pPr>

Part 1, §17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)”, pp. 812

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="num" w:pos="720" />
 </w:tabs>
 <w:ind w:startLeft="720" w:hanging="360" />
</w:pPr>
```

# 139. DR 09-0124 — SML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-055

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1, §12.3.7, §12.3.9, §12.3.23,

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: within s:sheet, attribute tabId is invalid

**Solution Proposed by the Submitter:**

Change "tabId" to "sheetId" in these examples

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §12.3.7, “Dialogsheet Part”, pp. 76

```
<sheets>
 ...
 <sheet name="Dialog1" tabsheetId="4" type="dialog" r:id="rId2"/>
</sheets>
```

Part 1, §12.3.9, “External Workbook References Part”, pp. 79

```
<sheets>
 <sheet name="Sheet1" tabsheetId="1" r:id="rId1"/>
 <sheet name="Sheet2" tabsheetId="2" r:id="rId2"/>
 <sheet name="Sheet3" tabsheetId="3" r:id="rId3"/>
</sheets>
```

Part 1, §12.3.23, “Workbook Part”, pp. 98

```
<sheets>
 <sheet name="January" tabsheetId="1" r:id="rId1"/>
 <sheet name="February" tabsheetId="2" r:id="rId2"/>
 <sheet name="March" tabsheetId="3" r:id="rId3"/>
</sheets>
```

## 140. DR 09-0125 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-056

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.3.2.26

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: within w:rFonts, attribute csTheme is invalid

**Solution Proposed by the Submitter:**

Change "csTheme" to "cstheme" in these examples

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.3.2.26, “[rFonts \(Run Fonts\)](#)”, pp. 317, attribute cs

If the csTtheme attribute is also specified, then this attribute shall be ignored and that value shall be used instead.

Part 1 §17.3.2.26, “[rFonts \(Run Fonts\)](#)”, pp. 318, attribute cstheme

[Example: Consider a run of Arabic text [that which](#) must be displayed using the majorBidi theme font. This requirement would be specified as follows in the resulting WordprocessingML:

```
<w:rPr>
 <w:rFonts w:cstheme="majorBidi" />
</w:rPr>
```

The csTtheme attribute specifies that the run must use the majorBidi theme font as defined in the document's themes part for all text in a complex script range. *end example*

# 141. DR 09-0126 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-057

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.7.5.1

**Related DR(s):** none

## **Nature of the Defect:**

Error in examples: w:rPrDefault is after w:pPrDefault inside w:docDefaults in the example, which is invalid

## **Solution Proposed by the Submitter:**

Swap order of w:rPrDefault and w:pPrDefault in this example

## **Schema Change(s) Needed:**

## **Editor's Response:**

The exact changes are as follows:

Part 1 §17.7.5.1, “docDefaults (Document Default Paragraph and Run Properties)”, pp. 716

```
<w:docDefaults>
 <w:rPrDefault>
 <w:rPr>
 <w:b/>
 </w:rPr>
 </w:rPrDefault>
 <w:pPrDefault>
 <w:pPr>
 <w:jc w:val="center"/>
 </w:pPr>
 </w:pPrDefault>
 <w:rPrDefault>
 <w:rPr>
 <w:b/>
 </w:rPr>
 </w:rPrDefault>
</w:docDefaults>
```

## 142. DR 09-0127 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-058

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.11.4

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: w:pos is after w:numFmt inside w:endnotePr in the example, which is invalid

### **Solution Proposed by the Submitter:**

Swap order of w:pos and w:numFmt in this example

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §17.11.4, “endnotePr (Document-Wide Endnote Properties)”, pp. 845

```
<w:endnotePr>
 <w:pos w:val="sectEnd"/>
 <w:numFmt w:val="lowerRoman" />
 <w:pos w:val="sectEnd"/>
</w:endnotePr>
```

## 143. DR 09-0128 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-059

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.12.9, §17.12.12, §17.18.16

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: w:name is after w:gallery inside w:category in the example, which is invalid

**Solution Proposed by the Submitter:**

Swap order of w:name and w:gallery in this example

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.12.9, “gallery (Gallery Associated With Entry)”, pp. 888

```
<w:category>
 <w:name w:val="Internal Memo Covers" />
 <w:gallery w:val="coverPg" />
 <w:name w:val="Internal Memo Covers" />
</w:category>
```

Part 1 §17.12.12, “name (Category Associated With Entry)”, pp. 891

```
<w:category>
 <w:name w:val="Internal Memo Covers" />
 <w:gallery w:val="coverPg" />
 <w:name w:val="Internal Memo Covers" />
</w:category>
```

Part 1 §17.18.16, “ST\_DocPartGallery (Entry Gallery Types)”, pp. 1523

```
<w:category>
 <w:name w:val="Internal Memo Covers" />
 <w:gallery w:val="coverPg" />
 <w:name w:val="Internal Memo Covers" />
</w:category>
```

## 144. DR 09-0129 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-060

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.13.4.2

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: within w:comment, attribute w:name is used, which is invalid

### **Solution Proposed by the Submitter:**

Change attribute w:name to w:author in this example

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1 §17.13.4.2, “comment (Comment Content)”, pp. 905, attribute initials

[Example: Consider a comment represented using the following WordprocessingML fragment:

```
<w:comment w:id="1" w:initials="KB" w:authorname="Krista Bendig">
...
</w:comment>
```

The initials attribute specifies that the initials of the author of the current comment are KB, which can be used as desired. *end example]*

# 145. DR 09-0130 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-061

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.15.2.17

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: within w:frame, w:frameLayout is used, which is invalid

**Solution Proposed by the Submitter:**

Change element w:frame to w:frameset in this example

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.15.2.17, “frameLayout (Frameset Layout)”, pp. 1244, attribute val

```
<w:frameset>
 <w:frameLayout w:val="cols" />
 ...
</w:frameset
```

## 146. DR 09-0131 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-062

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §19.5.90

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: within p:animClr, clrSpc attribute is used with invalid value "rgsb"

### **Solution Proposed by the Submitter:**

Change value "rgsb" to "rgb" in this example

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1 §19.5.90, “to (To)”, pp. 2964

```
<p:animClr clrSpc="rg$b">
...
</p:animClr>
```

## 147. DR 09-0132 — WML: Errors in examples

**Status:** Closed without action.

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-063

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.3.2.22, §17.3.2.26, §17.18.41

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: w:rPr appears directly within an w:pPr, which is invalid

**Solution Proposed by the Submitter:**

Change w:pPr to an w:r in these examples

**Schema Change(s) Needed:**

**Editor's Response:**

In §17.3.2.22, pp. 310, the list of valid parents for omath is rPr (§17.3.1.29); rPr (§17.3.1.30); rPr (§17.5.2.28); rPr (§17.9.25); rPr (§17.7.9.1); rPr (§17.7.5.4); rPr (§17.3.2.28); rPr (§17.5.2.27); rPr (§17.7.6.2); rPr (§17.3.2.27).

The first of these (§17.3.1.29) appears to allow a parent of pPr.

The examples in question are as follows:

Part 1 §17.3.2.22, “oMath (Office Open XML Math)”, pp. 310

```
<w:pPr>
 <w:rPr>
 <w:oMath />
 </w:rPr>
</w:pPr>
```

Part 1 §17.3.2.26, “rFonts (Run Fonts)”, pp. 321, attribute hint

```
<w:pPr>
 <w:rPr>
 <w:rFonts w:hint="eastAsia" />
 </w:rPr>
</w:pPr>
```

Part 1 §17.18.41, “ST\_Hint (Font Type Hint)”, pp. 1552

```
<w:pPr>
 <w:rPr>
 <w:rFonts w:hint="eastAsia" />
 </w:rPr>
</w:pPr>
```

**2009-04-23 Inigo Surguy:**

Interesting - the rPr directly inside pPr is for formatting the pilcrow itself! So, while it isn't a common case, this is actually correct for this example. My defect report is wrong - please leave unchanged.

## 148. DR 09-0133 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-064

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.6.1.11, §17.15.1.11, §17.15.1.13, §17.15.1.64

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: w:pgMar element is missing required attributes w:gutter and w:footer

**Solution Proposed by the Submitter:**

Add required attributes gutter and footer to this example

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.6.1.11, “pgMar (Page Margins)”, pp. 641

```
<w:sectPr>
 <w:pgMar w:header="720" w:bottom="1440" w:top="1440" w:right="1440"
 w:left="1440" w:footer="720" w:gutter="0" />
 ...
</w:sectPr>
```

Part 1 §17.15.1.11, “bookFoldPrinting (Book Fold Printing)”, pp. 1104

```
<w:pgMar w:header="0" w:top="1440" w:right="1440" w:bottom="1440" w:left="2160"
 w:footer="720" w:gutter="0" />
```

Part 1 §17.15.1.13, “bookFoldRevPrinting (Reverse Book Fold Printing)”, pp. 1108

```
<w:pgMar w:header="0" w:top="1440" w:right="1440" w:bottom="1440" w:left="2160"
 w:footer="720" w:gutter="0" />
```

Part 1 §17.15.1.64, “printTwoOnOne (Print Two Pages Per Sheet)”, pp. 1177

```
<w:pgMar w:header="0" w:top="2160" w:right="1440" w:bottom="1440" w:left="1440"
 w:footer="720" w:gutter="0" />
```

## 149. DR 09-0134 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-065

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.16.18, §17.16.18

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: w:fldChar element has attribute w:fldCharType with value "start", which is invalid.

### **Solution Proposed by the Submitter:**

Change "start" to "begin" in these examples

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1 §17.16.18, "fldChar (Complex Field Character)", pp. 1415

```
<w:body>
 <w:p>
 <w:r>
 <w:fldChar w:fldCharType="beginstart" />
 </w:r>
 ...
 </w:body>
```

Part 1 §17.16.18, “fldChar (Complex Field Character)”, pp. 1416, attribute dirty

```
<w:r>
 <w:fldChar w:fldCharType="beginstart" w:dirty="true"/>
</w:r>
```

Part 1 §17.16.18, “fldChar (Complex Field Character)”, pp. 1417, attribute fldLock

```
<w:r>
 <w:fldChar w:fldCharType="beginstart" w:fldLock="true"/>
</w:r>
```

# 150. DR 09-0135 — SML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** SML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-066

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §18.2.20, §18.2.27

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: sheet element has attribute "type", which is invalid

**Solution Proposed by the Submitter:**

Remove invalid attribute "type"

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §12.3.7, "Dialogsheet Part", pp. 76

```
<sheets>
...
<sheet name="Dialog1" tabId="4" type="dialog" r:id="rId2"/>
</sheets>
```

Part 1 §18.2.20, “sheets (Sheets)”, pp. 1733

```
<sheets>
<sheet name="Sheet1" sheetId="1" r:id="rId1"/>
<sheet name="Sheet2" sheetId="2" r:id="rId2"/>
<sheet name="Sheet5" sheetId="3" r:id="rId3"/>
<sheet name="Chart1" sheetId="4" type="chartsheet" r:id="rId4"/>
</sheets>
```

Part 1 §18.2.27, “workbook (Workbook)”, pp. 1739

```
<sheets>
<sheet name="Sheet1" sheetId="1" r:id="rId1"/>
<sheet name="Sheet2" sheetId="2" r:id="rId2"/>
<sheet name="Sheet5" sheetId="3" r:id="rId3"/>
<sheet name="Chart1" sheetId="4" type="chartsheet" r:id="rId4"/>
</sheets>
```

# 151. DR 09-0136 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-067

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.15.1.77

**Related DR(s):** none

## **Nature of the Defect:**

Error in examples: w:customXml has attribute w:namespaceuri, which is invalid

## **Solution Proposed by the Submitter:**

Change "w:namespaceuri" to "w:namespaceUri"

## **Schema Change(s) Needed:**

## **Editor's Response:**

The exact changes are as follows:

Part 1 §17.15.1.77, “saveXmlDataOnly (Only Save Custom XML Markup)”, pp. 1194

```
<w:customXml w:element="root" w:namespaceuri="urn:example">
 <w:r>
 <w:t>Hello world</w:t>
 </w:r>
</w:customXml>
```

## 152. DR 09-0137 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-068

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.11.6

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: example contains invalid element w:endfootnoteref

**Solution Proposed by the Submitter:**

Change "w:endfootnoteref" to "w:endnoteRef"

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.11.6, “endnoteRef (Endnote Reference Mark)”, pp. 848

```
<w:r>
 <w:rPr>
 <w:rStyle w:val="EndnoteReference" />
 </w:rPr>
 <w:endFootnoteRef />
</w:r>
```

## 153. DR 09-0138 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-069

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §11.3.11

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: example contains w:tab element with w:val attribute with invalid value "list"

**Solution Proposed by the Submitter:**

Change "list" to "num"

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §11.3.11, “Numbering Definitions Part”, pp. 55

```
<w:pPr>
 <w:tabs>
 <w:tab w:val="numList" w:pos="720"/>
 </w:tabs>
 <w:ind w:left="720" w:hanging="360"/>
</w:pPr>
```

## 154. DR 09-0139 — WML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-070

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §17.4.65

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: example contains w:tblW element with w:type attribute with invalid value "fixed"

**Solution Proposed by the Submitter:**

Change value "fixed" to one of the allowed values for this attribute

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1 §17.4.65, "tblW (Preferred Table Width Exception)", pp. 493

```
<w:tblPrEx>
 <w:tblW w:type="autofixed" w:w="1440"/>
</w:tblPrEx>
```

# 155. DR 09-0140 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-071

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §19.5.9

**Related DR(s):** none

## **Nature of the Defect:**

Error in examples: example contains p:cMediaNode element with vol attribute with invalid value "11000"

## **Solution Proposed by the Submitter:**

Change value "11000" to a percentage - e.g., "50%"

## **Schema Change(s) Needed:**

## **Editor's Response:**

The exact changes are as follows:

Part 1, §19.5.9, “audio (Audio)”, pp. 2882

```
<p:cMediaNode vol="50%11000">...
 <p:tgtEl>
 <p:rndTgt r:embed="rId2" />
 </p:tgtEl>
</p:cMediaNode>
```

## 156. DR 09-0141 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-072

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §19.5.62

**Related DR(s):** none

### **Nature of the Defect:**

Error in examples: example contains p:rCtr element with x and y attributes with invalid values  
x="457200" y="274638"

### **Solution Proposed by the Submitter:**

Change x and y values to percentages

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §19.5.62, “rCtr (Rotation Center)”, pp. 2935

```
<p:animMotion origin="layout" path="M 0 0 L 0.25 0.33333 E"
 pathEditMode="relative" rAng="0" ptsTypes="">
 ...
 <p:rCtr x="56.7%457200" y="83.4%274638" />
</p:animMotion>
```

## 157. DR 09-0142 — PML: Errors in examples

**Status:** Closed; will be incorporated in COR1

**Subject:** PML: Errors in examples

**Qualifier:** Editorial defect

**Submitter:** Inigo Surguy (BSI)

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-073

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-02-27

**Deadline for Response from Editor:** 2009-04-27

**IS 29500 Reference(s):** Part 1 §19.5.88

**Related DR(s):** none

**Nature of the Defect:**

Error in examples: example contains p:Ctn element with attribute decel with invalid value "100000"

**Solution Proposed by the Submitter:**

Change decel value to percentage

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §19.5.88, “to (To)”, pp. 2962

```
<p:cBhvr>
 <p:cTn id="9" dur="200" decel="10..5%0000" autoRev="1" fill="hold">
 <p:stCondLst>
 ...
 </p:stCondLst>
 ...
 </p:cTn>
</p:cBhvr>
```

# 158. DR 09-0143 — SML, Formulas: TIMEVALUE, return value and terminology

**Status:** Last Call

**Subject:** SML, Formulas: TIMEVALUE, return value and terminology

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-24

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §18.17.7.324 (pps. 2626, 2627)

**Related DR(s):** none

## Nature of the Defect:

The term *serial value* is not currently defined and requires proper definition, being a decimal fraction of a 24-hour day (if that is what it is). The return value is incorrectly specified – it should define the value range as for the TIME function (§18.17.7.323).

## Solution Proposed by the Submitter:

Revise the text describing the return value:

**Return Type and Value:** number – The serial value of the date and/or time represented by the string *date-time-string*, as a value greater than or equal to 0 and less than or equal to 1.

Add a definition of *serial value* to §12.1.

**Schema Change(s) Needed:** No**Editor's Response:**

The term *serial value* and its date component are defined in Part 1, §18.17.4.1, “Date Conversion for Serial Values”, pp. 2293, and the time component is defined in Part 1, §18.17.4.2, “Time Conversion for Serial Values”, pp. 2294.

The exact changes are as follows:

Part 1, §18.17.7.324, “TIMEVALUE”, (pp. 2627)

**Description:** Computes the serial value of the ~~date and/or~~ time represented by the string *date-time-string*.

**Arguments:**

Name	Type	Description
<i>date-time-string</i>	text	The date and/or time whose <a href="#">time component</a> serial value is to be computed. <i>date-time-string</i> can have any date and/or time format. Any date information in <i>date-time-string</i> shall be ignored.

**Return Type and Value:** number – The serial value of the ~~date and/or~~ time represented by the string *date-time-string*, [as a value greater than or equal to 0 and less than or equal to 1](#).

For consistency, the following change will also be made:

Part 1, §18.17.7.76, “DATEVALUE”, (pp. 2396–2397)

**Arguments:**

Name	Type	Description
<i>date-time-string</i>	text	The date and/or time whose <a href="#">date component</a> serial value is to be computed. ... Any time information in <i>date-time-string</i> shall be ignored. ...

# 159. DR 09-0144 — SML, Formulas: Various functions, iterative search technique

**Status:** [Further Consideration Required](#) Open

**Subject:** Reference to implementation-specific "iterative search technique" in normative text

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-25

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §18.17.7.28 (pp. 2333), §18.17.7.37 (pp. 2347), §18.17.7.121 (pp. 2438), §18.17.7.132 (pp. 2447), §18.17.7.173 (pp. 2487), §18.17.7.230 (pp. 2534), §18.17.7.232 (pp. 2535)

**Related DR(s):** none

**Nature of the Defect:**

Whether the function uses an "iterative search technique" or not is implementation-specific.

In §18.17.7.173, the return value specified in the same paragraph is inconsistent with the return value specified in identical circumstances for other functions. If a value is not available, for whatever reason, according to §18.17.3 the correct return value is #N/A, not #NUM, which signifies a value outside the value domain.

**Solution Proposed by the Submitter:**

Revise text as follows:

In §18.17.7.28:

**Description:** Computes the inverse of the cumulative distribution function for a specified beta distribution. Given a value for *probability*, BETAINV is used to seek for the value *x* such that  $\text{BETADIST}(x, \alpha, \beta, A, B) = \text{probability}$ . Thus, precision of BETAINV depends on precision of BETADIST. ~~BETAINV uses an iterative search technique.~~

In §18.17.7.37, §18.17.7.121, §18.17.7.132, §18.17.7.230, §18.17.7.232:

- ~~An implementation uses an iterative search technique, and the search has not converged after some implementation-defined number of iterations. The implementation determines that a return value cannot be computed,~~ #N/A is returned

In §18.17.7.173:

However, if ~~an implementation uses an iterative search technique, and the calculation has not converged after an implementation-defined number of iterations. The implementation determines that a return value cannot be computed,~~ #NUM! #N/A is returned.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 160. DR 09-0145 — SML, Formulas: Various functions, duplicate mathematical expressions

**Status:** Last Call

**Subject:** SML, Formulas: Various functions, duplicate mathematical expressions

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-26

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §18.17.7.63 (pp. 2382), §18.17.7.299 (pp. 2605), §18.17.7.300 (pp. 2606), §18.17.7.301 (pp. 2607), §18.17.7.302 (pp. 2608), §18.17.7.338 (pp. 2636), §18.17.7.339 (pp. 2637), §18.17.7.340 (pp. 2638), §18.17.7.341 (pp. 2639), §18.17.7.356 (pp. 2663)

**Related DR(s):** none

**Nature of the Defect:**

A number of mathematical expressions appear to have been duplicated as a result of some automated replacement process during preparation of the final text.

**Solution Proposed by the Submitter:**

In §18.17.7.63:

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{array-1})$

In §18.17.7.299, §18.17.7.300, §18.17.7.301, §18.17.7.302, §18.17.7.338, §18.17.7.339, §18.17.7.340, §18.17.7.341:

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

In §18.17.7.356:

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{array})$

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §18.17.7.63, "COVAR", pp. 2382

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{array-1})$

Part 1, §18.17.7.299, "STDEV", pp. 2605

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.300, "STDEVA", pp. 2606

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.301, "STDEVP", pp. 2607

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.302, "STDEVPA", pp. 2608

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.338, "VAR", pp. 2636

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.339, "VARA", pp. 2637

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.340, "VARP", pp. 2638

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.341, "VARPA", pp. 2639

- $\bar{x}$  = the sample mean  $\text{AVERAGE}(\text{argument-1}, \text{argument-1}, \dots, \text{argument-n})$

Part 1, §18.17.7.356, “ZTEST”, pp. 2663

- $\bar{x}$  = the sample mean `AVERAGE(array)`

# 161. DR 09-0146 — SML, Formulas: MATCH, inconsistent use of return value #NUM!

**Status:** [Further Consideration Required](#) [Open](#)

**Subject:** SML, Formulas: MATCH, inconsistent use of return value #NUM!

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §18.17.7.204 (pp. 2510)

**Related DR(s):** none

## Nature of the Defect:

In §18.17.3 it is clearly stated that the return value #NUM! is to be used when the return value is out of domain/range, whereas the return value #N/A is to be used if a return value is not available. This rule is not consistently applied, as in the case of the MATCH function, in which case the return value when no match is found should logically be #N/A.

## Solution Proposed by the Submitter:

In §18.17.7.204:

- No match is found, **#NUM!** [#N/A](#) is returned.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 162. DR 09-0147 — Shared MLS: incorrect attribute value format

**Status:** Last Call

**Subject:** Shared MLS: incorrect attribute value format

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-28

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.5.2.2 (pp. 4262)

**Related DR(s):** none

### **Nature of the Defect:**

The formatting of two attribute values in the bulleted list in the example contained in the description of the ‘uri’ attribute is inconsistent.

### **Solution Proposed by the Submitter:**

Revise as follows:

The uri attribute specifies the target namespace of each XML schema reference:

- <http://www.example.com/schema1>
- <http://www.example.com/schema2>

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §22.5.2.2, “schemaRef (Associated XML Schema)”, pp. 4262, attribute uri

Attributes	Description
uri (Target Namespace of Associated XML Schema)	<p>...</p> <p>The uri attribute specifies the target namespace of each XML schema reference:</p> <ul style="list-style-type: none"><li>• <a href="http://www.example.com/schema1">http://www.example.com/schema1</a></li><li>• <a href="http://www.example.com/schema2">http://www.example.com/schema2</a></li></ul> <p>...</p>

# 163. DR 09-0148 — Shared MLS: Inter-word space missing

**Status:** Last Call

**Subject:** Shared MLS: Inter-word space missing

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-29

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.3 (pp. 4074), §22.1.2.18 (pp. 4094), §22.1.2.105 (pp. 4202)

**Related DR(s):** none

**Nature of the Defect:**

Inter-word space character missing.

**Solution Proposed by the Submitter:**

Insert space where required (NOTE - space underlined in blue):

In §22.1.2.3:

This element specifies the alignment property on the box object. It is utilized only when the box is designated as an operator emulator. When \_1 or true, this operator emulator serves as an alignment point; that is, designated alignment points in other equations can be aligned with it.

In §22.1.2.18 (NOTE – incorrect style of attribute value also revised):

This element represents the (custom) column gap spacing information; the default value is  $\emptyset$  (which corresponds to 1 em). This value is interpreted differently depending on the value of cGpRule (\$xx). cGp is not used unless the value of cGpRule is 3 or 4. When cGpRule is omitted, the default spacing between matrix columns is 1 em (a val attribute value of 0).

In §22.1.2.105:

This element specifies the superscript object sSup, which consists of a base e and a reduced-size scr placed above and to the right, as in  $x^n$ . [Example: The XML that specifies this object is:

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §22.1.2.3, “aln (Alignment)”, pp. 4074

This element specifies the alignment property on the box object. It is utilized only when the box is designated as an operator emulator. When  $_1$  or true, this operator emulator serves as an alignment point; that is, designated alignment points in other equations can be aligned with it.

Part 1, §22.1.2.18, “cGp (Matrix Column Gap)”, pp. 4094

This element represents the (custom) column gap spacing information; the default value is  $\emptyset$  (which corresponds to 1 em). This value is interpreted differently depending on the value of cGpRule (\$xx). cGp is not used unless the value of cGpRule is 3 or 4. When cGpRule is omitted, the default spacing between matrix columns is 1 em (a val attribute value of 0).

Part 1, §22.1.2.105, “sSup (Superscript Object)”, pp. 4202

This element specifies the superscript object sSup, which consists of a base e and a reduced-size scr placed above and to the right, as in  $x^n$ . ...

# 164. DR 09-0149 — Shared MLs: Bad page break in Parent Elements table

**Status:** Last Call

**Subject:** Shared MLs: Bad page break in Parent Elements table

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-30

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.5 (pp. 4078)

**Related DR(s):** none

**Nature of the Defect:**

Bad page break in Parent Elements table.

**Solution Proposed by the Submitter:**

Ensure that this table is not allowed to break across a page division at the next reprint/revision.

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §22.1.2.5, “argPr (Argument Properties)”, pp. 4078

In the next reprint or revision, no page breaks will be allowed within this table (and the editor will try to inhibit them for any given row of any table, as appropriate).

# 165. DR 09-0150 — Shared MLs: Attribute value in incorrect style

**Status:** Last Call

**Subject:** Shared MLs: Attribute value in incorrect style

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-31

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.19 (pp. 4095) and many others

**Related DR(s):** none

## **Nature of the Defect:**

Attribute value in wrong font and/or in single quotation marks, which is inconsistent with the style used generally for presentation of attribute values.

## **Solution Proposed by the Submitter:**

Replace '0' (8 occurrences in Part 1) and '0' (3 occurrences in Part 1) with 0.

Replace '1' (approx. 20 occurrences) with 1.

**Schema Change(s) Needed:** No

## **Editor's Response:**

The exact changes are as follows:

Part 1, §18.3.1.2, "autoFilter (AutoFilter Settings)", pp. 1758

[Example: ... The filter is being applied to the range B3:E8, and the criteria is being applied to values in the column whose ~~colId='1'~~ colId is 1 (zero based column numbering, from left to right). ...

Part 1, §18.3.1.3, “brk (Break)”, pp. 1759, attribute man

Attributes	Description
man (Manual Page Break)	Manual Break flag. <del>'1'</del> means the break is a manually inserted break. ...

Part 1, §18.3.1.10, “cfRule (Conditional Formatting Rule)”, pp. 1765–1766, various attributes

Attributes	Description
aboveAverage (Above Or Below Average)	Indicates whether the rule is an "above average" rule. <del>'1'</del> indicates 'above average'. This attribute is ignored if type is not equal to aboveAverage. ...
bottom (Bottom N)	Indicates whether a "top/bottom n" rule is a "bottom n" rule. <del>'1'</del> indicates 'bottom'. This attribute is ignored if type is not equal to top10. ...
equalAverage (Equal Average)	Flag indicating whether the 'aboveAverage' and 'belowAverage' criteria is inclusive of the average itself, or exclusive of that value. <del>'1'</del> indicates to include the average value in the criteria. This attribute is ignored if type is not equal to aboveAverage. ...
priority (Priority)	The priority of this conditional formatting rule. This value is used to determine which format should be evaluated and rendered. Lower numeric values are higher priority than higher numeric values, where <del>'1'</del> is the highest priority. ...
stopIfTrue (Stop If True)	If this flag is <del>'1'</del> , no rules with lower priority shall be applied over this rule, when this rule evaluates to true. ...

Part 1, §18.3.1.11, “cfvo (Conditional Format Value Object)”, pp. 1768, attribute gte

Attributes	Description
gte (Greater Than Or Equal)	For icon sets, determines whether this threshold value uses the greater than or equal to operator. <del>'0'</del> indicates 'greater than' is used instead of 'greater than or equal to'. ...

Part 1, §18.3.1.32, “dataValidation (Data Validation)”, pp. 1791, attribute allowBlank

Attributes	Description
------------	-------------

Attributes	Description
allowBlank (Allow Blank) ...	A boolean value indicating whether the data validation allows the use of empty or blank entries. <span style="color:red">\textcolor{red}{\underline{1}}</span> means empty entries are OK and do not violate the validation constraints.

Part 1, §18.3.1.40, “f (Formula)”, pp. 1807

Attributes	Description
r2 (Input Cell 2)	Second input cell for data table when <a href="#">dt2D</a> is <span style="color:red">\textcolor{red}{\underline{1}}</span> . Only applies to the data tables array function "TABLE()". Written on master cell of data table formula only. ...

Part 1, §18.3.1.41, “firstFooter (First Page Footer)”, pp. 1808

First page footer content. Only used when [headerFooter@differentFirst](#) is \textcolor{red}{\underline{1}}.

Part 1, §18.3.1.42, “firstHeader (First Page Header)”, pp. 1808

First page header content. Only used when [headerFooter@differentFirst](#) is \textcolor{red}{\underline{1}}.

Part 1, §18.3.1.49, “iconSet (Icon Set)”, pp. 1813, attribute reverse

Attributes	Description
reverse (Reverse Icons)	If <span style="color:red">\textcolor{red}{\underline{1}}</span> , reverses the default order of the icons in this icon set. ...

Part 1, §18.3.1.73, “row (Row)”, pp. 1848, various attributes

Attributes	Description
collapsed (Collapsed)	<span style="color:red">\textcolor{red}{\underline{1}}</span> if the rows 1 level of outlining deeper than the current row are in the collapsed outline state. It means that the rows which are 1 outline level deeper (numerically higher value) than the current row are currently hidden due to a collapsed outline state. ...
customFormat (Custom Format)	<span style="color:red">\textcolor{red}{\underline{1}}</span> if the row style should be applied. ....
customHeight (Custom Height)	<span style="color:red">\textcolor{red}{\underline{1}}</span> if the row height has been manually set. ...
hidden (Hidden)	<span style="color:red">\textcolor{red}{\underline{1}}</span> if the row is hidden, e.g., due to a collapsed outline or by manually selecting and hiding a row. ...

Attributes	Description
ph (Show Phonetic)	'1' if the row should show phonetic. ...
thickBot (Thick Bottom)	'1' if any cell in the row has a medium or thick bottom border, or if any cell in the row directly below the current row has a thick top border. ...

Part 1, §18.3.2.1, "colorFilter (Color Filter Criteria)", pp. 1888, attribute cellColor

Attributes	Description
cellColor (Filter By Cell Color)	Flag indicating whether or not to filter by the cell's fill color. '1' indicates to filter by cell fill. '0' indicates to filter by the cell's font color. ...

Part 1, §18.3.2.3, "customFilters (Custom Filters)", pp. 1889, attribute and

Attributes	Description
and (And)	Flag indicating whether the two criteria have an "and" relationship. '1' indicates "and", '0' indicates "or". ...

Part 1, §18.8.1, "alignment (Alignment)", pp. 1936, attribute indent

Attributes	Description
indent (Indent)	... <i>[Example:</i> For example, an indent value of '1' means that the text begins 3 space widths (of the normal style font) from the edge of the cell. <i>end example]</i> ...

Part 1, §22.1.2.19, "cGpRule (Matrix Column Gap Rule)", pp. 4095 and many others

This element specifies the type of gap (horizontal spacing) between columns of a matrix; the default is '0'. Horizontal spacing units can be ems or points (stored as twips).

Part 1, §22.1.2.22, "cSp (Minimum Matrix Column Width)", pp. 4099

... If this element is omitted, the default minimum column width is '0'. ... Therefore, a spacing of '1' point will be set by a cSp value of '20'. ...

Part 1, §M.2.8.3.2.2, "Metadata Behaviors", pp. 5225

The metadata type expresses operations on cells that allow the metadata to remain associated with the cell. Operations not listed or set to ~~'0'~~ would cause the metadata to no longer be associated with the cell.

Part 1, §M.2.9.3.4.5, "Row Items", pp. 5251–5252

Note that the first item has no r explicitly written. Since a default of ~~'0'~~ is specified in the schema, for any item whose r is missing, a default value of ~~'0'~~ is implied.

Note that the first instance of x has no attribute value v associated with it, so v's default value of ~~'0'~~ is implied.

... The first item value "Bikes" is expressed implicitly, because the value of r on the second i element is ~~'1'~~, indicating that the first item value from the previous row is reused again as the first item value for the current row. ...

Part 1, §M.2.9.3.4.7, "Column Items", pp. 5254

Note that the first item has no r explicitly written so the default value of ~~'0'~~ is implied.

...

Note that the first instance of x has no attribute value v associated with it, so v's default value of ~~'0'~~ is implied.

## 166. DR 09-0151 — Shared MLs: Incorrect abbreviation of ‘points’ to ‘pts.’

**Status:** Last Call

**Subject:** Shared MLs: Incorrect abbreviation of ‘points’ to ‘pts.’

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter’s Defect Number:** GB-32

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.22 (pp. 4100)

**Related DR(s):** none

**Nature of the Defect:**

The abbreviation ‘pts.’ should not include a full stop, unless at the end of a sentence.

**Solution Proposed by the Submitter:**

Revise text as agreed in Response 555 to UK Fast Track comment GB-0533:

*[Example:* The following XML specifies that there should never be fewer than 6 pts.<sub>–</sub> (120 twips) between adjacent column edges of the matrix:

**Schema Change(s) Needed:** No

**Editor’s Response:**

The exact changes are as follows:

Part 1, §22.1.2.22, “cSp (Minimum Matrix Column Width)”, pp. 4100

[Example: The following XML specifies that there should never be fewer than 6 pts<sub>red</sub> (120 twips) between adjacent column edges of the matrix:

# 167. DR 09-0152 — Shared MLs: Unneeded blank in math formula

**Status:** Last Call

**Subject:** Shared MLs: Unneeded blank in math formula

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-33

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.32 (pp. 4114), §22.1.2.37 (pp. 4122), §22.1.2.39 (pp. 4126)

**Related DR(s):** none

## Nature of the Defect:

Formula contains a blank element between  $\lim_{n \rightarrow \infty}$  and  $x_n$ , which is the result of an incomplete deletion when preparing the final text.

## Solution Proposed by the Submitter:

Change formula to remove blank element:

In §22.1.2.32, §22.1.2.37:

[Example: For example, the func  $\lim_{n \rightarrow \infty} x_n$  has fName  $\lim$  and e  $x_n$ :

In §22.1.2.39:

As an example, the func  $\lim_{n \rightarrow \infty} x_n$  has fName  $\lim$  and e  $x_n$ :

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §22.1.2.32, “e (Element (Argument))”, pp. 4114

[*Example:* For example, the func  $\lim_{n \rightarrow \infty} \underline{x_n} - \overline{x_n}$  has fName  $\lim$  and e  $x_n$ :

Part 1, §22.1.2.37, “fName (Function Name)”, pp. 4122

[*Example:* As an example, the func  $\lim_{n \rightarrow \infty} \underline{x_n} - \overline{x_n}$  has fName  $\lim$  and e  $x_n$ :

Part 1, §22.1.2.39, “func (Function Apply Object)”, pp. 4126

As an example, the func  $\lim_{n \rightarrow \infty} \underline{x_n} - \overline{x_n}$  has fName  $\lim$  and e  $x_n$ :

# 168. DR 09-0153 — Shared MLs: XML Ill-formed example of sepChr

**Status:** Last Call

**Subject:** Shared MLs: XML Ill-formed example of sepChr

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-074

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.95 (pp. 4193)

**Related DR(s):** none

**Nature of the Defect:**

In §22.1.2.95, the XML expression <m:sepChr val="&#0058;/> is not well-formed.

**Solution Proposed by the Submitter:**

Correct the XML in the example as follows:

[*Example:* Examples of d, each with a different sepChr, are:  $(a_1|a_2)(a_1:a_2)(a_1;a_2)$ . The following example describes a separator character if :.]

```
<m:dPr>
 <m:sepChr val=":"/>
</m:dPr>
```

*end example]*

**Schema Change(s) Needed:** No

**Editor's Response:**

The exact changes are as follows:

Part 1, §22.1.2.95, “sepChr (Delimiter Separator Character)”, pp. 4193

[*Example*: Examples of d, each with a different sepChr, are:  $(a_1|a_2)(a_1:a_2)(a_1;a_2)$ . The following example setsdescribes the [COLON \(:\) as the](#) separator character:if [::](#)]

```
<m:dPr>
 <m:sepChr val=":" />
</m:dPr>
```

*end example]*

# 169. DR 09-0154 — Shared MLs: placeholders that should be visible in matrix are not

**Status:** Last Call

**Subject:** Shared MLs: placeholders that should be visible in matrix are not

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-075

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-15

**Deadline for Response from Editor:** 2009-05-15

**IS 29500 Reference(s):** Part 1, §22.1.2.83 (pp. 4181)

**Related DR(s):** none

## **Nature of the Defect:**

The placeholders in the left-hand matrix are not visible in the final text. This may be because placeholders do not show visibly when printed to PDF.

## **Solution Proposed by the Submitter:**

Correct the PDF for this example, so that the placeholders are visible in the left-hand matrix.

**Schema Change(s) Needed:** No

## **Editor's Response:**

The placeholders were lost when the PDF was generated.

The exact changes are as follows:

Part 1, §22.1.2.83. “plcHide (Hide Placeholders (Matrix))”, pp. 4181

$$\begin{pmatrix} 1 & \square & \square \\ \square & 1 & \square \\ \square & \square & 1 \end{pmatrix} \begin{pmatrix} 1 & & \\ & 1 & \\ & & 1 \end{pmatrix}$$

# 170. DR 09-0155 — WML: Error in Example

**Status:** Last Call

**Subject:** WML: Error in Example

**Qualifier:** Editorial Defect

**Submitter:** Jirka Kosek, CNI (CZ)

**Contact Information:** e-mail: [jirka@kosek.cz](mailto:jirka@kosek.cz)

**Submitter's Defect Number:** 08-00073

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-25

**Deadline for Response from Editor:** 2009-05-25

**IS 29500 Reference(s):** Part 1, §17.15.1.54, pp. 1168

**Related DR(s):** none

**Nature of the Defect:**

The example shown talks about `<w:doNotValidateAgainstSchema/>` settings instead of `<w:ignoreMixedContent/>`

**Solution Proposed by the Submitter:**

Example should be corrected or removed completely.

**Schema Change(s) Needed:** none

**Editor's Response:**

The exact changes are as follows:

Part 1, §17.15.1.54, “ignoreMixedContent (Ignore Mixed Content When Validating Custom XML Markup)”, pp. 1168

[Example: Consider a WordprocessingML document which should not have its custom XML content validated even by applications which support this operation. This requirement is specified using the following WordprocessingML in the document settings:

```
<w:doNotValidateAgainstSchema w:val="true" />
```

The doNotValidateAgainstSchema element's val attribute has a value of true specifying that the custom XML markup in this document must not be validated. end example

[Example: Consider a WordprocessingML document that contains the following markup:

```
<w:customXml w:element="invoice" w:uri="http://www.example.com/invoice">
 <w:p>
 <w:r>
 <w:t>Invoice #:</w:t>
 </w:r>
 <w:customXml w:element="id" w:uri="http://www.example.com/invoice">
 <w:r>
 <w:t>012345</w:t>
 </w:r>
 </w:customXml>
 </w:p>
 <w:p>
 <w:r>
 <w:t>Invoice Date:</w:t>
 </w:r>
 <w:customXml w:element="date" w:uri="http://www.example.com/invoice">
 <w:r>
 <w:t>01/29/2009</w:t>
 </w:r>
 </w:customXml>
 </w:p>
</w:customXml>
```

If all the custom markup is extracted from the document, that markup would include all content in the document, i.e.:

```
<invoice xmlns="http://www.example.com/invoice">
 Invoice #:
 <id>012345</id>
 Invoice Date
 <date>01/29/2009</date>
</invoice>
```

However, if the ignoreMixedContent element is present with a val attribute value of true (or equivalent) then an application should ignore all text nodes in elements with mixed content, i.e.:

```
<invoice xmlns="http://www.example.com/invoice">
 <id>012345</id>
 <date>01/29/2009</date>
</invoice>
```

*[end example]*

# 171. DR 09-0156 — WML: XSLT Transformation error in Example

**Status:** [Further Consideration Required](#) [Open](#)

**Subject:** WML: WML: XSLT Transformation error in Example

**Qualifier:** Editorial Defect

**Submitter:** Jirka Kosek, CNI (CZ)

**Contact Information:** e-mail: [jirka@kosek.cz](mailto:jirka@kosek.cz)

**Submitter's Defect Number:** 08-00075

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-25

**Deadline for Response from Editor:** 2009-05-25

**IS 29500 Reference(s):** Part 1, §F, pp. 4940

**Related DR(s):** none

## Nature of the Defect:

The presented XSLT stylesheet has two errors.

- 1) It invalidly reports all customXml data as having more than one root element
- 2) It can correctly handle only documents which use `<w:ignoreMixedContent/>` settings (§17.15.1.54) set to true. But documents having mixed content inside custom XML can't be reproduced correctly.

## Solution Proposed by the Submitter:

The attached file (extract-custom-xml.xsl, whose contents are shown below) contains a corrected stylesheet with parameter that can be used to change extraction behavior based on `<w:ignoreMixedContent/>` settings.

The stylesheet presented in the standard should be replaced by the attached code. It should also be carefully studied if the stylesheet behavior is aligned with the behavior of current implementations.

```

<?xml version="1.0" encoding="UTF-8" ?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
 xmlns:w="http://schemas.openxmlformats.org/wordprocessingml/2006/main">

 <!-- This parameter should have the same value as
 ignoreMixedContent settings (see 17.15.1.54 in Part 1) -->
 <xsl:param name="ignoreMixedContent" select="false()" />

 <!-- Some document structure checks -->
 <xsl:template match="/">
 <xsl:if test="count(/w:customXml/ancestor-or-self::w:customXml[last()]) >
1">
 <xsl:message>Produced XML document will not be WF and will have more than
one root element.</xsl:message>
 </xsl:if>
 <!-- Process content of document -->
 <xsl:apply-templates/>
 </xsl:template>

 <!-- copy over custom XML elements -->
 <xsl:template match="w:customXml">
 <xsl:element name="{@w:element}" namespace="{@w:uri}">
 <!-- copy over attribute values -->
 <xsl:for-each select="w:customXmlPr/w:attr">
 <xsl:attribute name="{@w:name}" namespace="{@w:uri}">
 <xsl:value-of select="@w:val"/>
 </xsl:attribute>
 </xsl:for-each>
 <!-- process content -->
 <xsl:apply-templates/>
 </xsl:element>
 </xsl:template>

 <!-- copy over only text inside custom XML -->
 <xsl:template match="text()[ancestor::w:customXml[not(.//w:customXml)]]"
priority="10">
 <xsl:value-of select="."/>
 </xsl:template>

 <!-- warn about mixed content -->
 <xsl:template match="text()[ancestor::w:customXml]" priority="5">
 <xsl:choose>

```

```

<xsl:when test="$ignoreMixedContent">
 <xsl:message>Stripping "<xsl:value-of select='.'/>" from
output.</xsl:message>
 <xsl:message>This text is part of mixed content and would cause non-
valid result.</xsl:message>
</xsl:when>
<xsl:otherwise>
 <xsl:value-of select='.'/>
</xsl:otherwise>
</xsl:choose>
</xsl:template>

<!-- warn about text which is not tagged -->
<xsl:template match="text()">
 <xsl:message>Stripping "<xsl:value-of select='.'/>" from
output.</xsl:message>
 <xsl:message>This text is not enclosed by root element and would cause non-
WF result.</xsl:message>
</xsl:template>

<!-- do not pick up deleted content -->
<xsl:template match="w:del|w:moveFrom"/>
</xsl:stylesheet>

```

**Schema Change(s) Needed:** none

**Editor's Response:**

2009-04-22 Caroline Arms:

Shawn, do you think it would be useful to supply an example reason why doNotValidateAgainstSchema might be set to advise against validation? This complicating factor has been introduced into the appendix by your suggested text.

I would probably change "An application can employ any desired method" to "An application can employ any suitable method."

## 172. DR 09-0157 — WML: restriction on ordering of run properties

**Status:** [Further Consideration Required](#)[Open](#)

**Subject:** WML: restriction on ordering of run properties

**Qualifier:** Technical Defect

**Submitter:** Jirka Kosek, CNI (CZ)

**Contact Information:** e-mail: [jirka@kosek.cz](mailto:jirka@kosek.cz)

**Submitter's Defect Number:** 08-00076

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-25

**Deadline for Response from Editor:** 2009-05-25

**IS 29500 Reference(s):** Part 1, §17.3.2.28, pp. 325

**Related DR(s):** none

### **Nature of the Defect:**

Schema defines run properties as xs:sequence which means that properties has to be specified in a specific order. This adds unnecessary complexity to OOXML producers. It would be better to allow run properties to appear in any order.

### **Solution Proposed by the Submitter:**

Definition of EG\_RPrContent and EG\_RPrBase types in the schema should be changed so they are not using xs:sequence but xs:all instead.

**Schema Change(s) Needed:** none

### **Editor's Response:**

# 173. DR 09-0158 — WML: Error in unit definition for ST\_UniversalMeasure

**Status:** Last Call

**Subject:** WML: Error in unit definition for ST\_UniversalMeasure

**Qualifier:** Editorial Defect

**Submitter:** Jirka Kosek, CNI (CZ)

**Contact Information:** e-mail: [jirka@kosek.cz](mailto:jirka@kosek.cz)

**Submitter's Defect Number:** 08-00077

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-25

**Deadline for Response from Editor:** 2009-05-25

**IS 29500 Reference(s):** Part 1, §22.9.2.15, pp. 4332

**Related DR(s):** none

## **Nature of the Defect:**

There are typos in the last two rows of the table (in the second column). The sole letter "p" is used instead of proper "pc" and "pi" unit measure.

## **Solution Proposed by the Submitter:**

Change "1p" to "1pc" and "1pi", respectively.

**Schema Change(s) Needed:** none

## **Editor's Response:**

The exact changes are as follows:

Part 1, §22.9.2.15, "ST\_UniversalMeasure (Universal Measurement)", pp. 4332

Unit Identifier	Definition
cm	As defined in ISO 31.
mm	As defined in ISO 31.
in	<u>1_in</u> = 2.54_cm (informative)
pt	<u>1_pt</u> = 1/72_in (informative)
pc	<u>1_pc</u> = 12_pt (informative)
pi	<u>1_pi</u> = 12_pt (informative)

# 174. DR 09-0159 — General: Unintended incompatibilities between Transitional schema and Ecma-376

**Status:** [Further Consideration Required](#) Open

**Subject:** General: Unintended incompatibilities between Transitional schema and Ecma-376

**Qualifier:** Technical defect

**Submitter:** Mr. Inigo Surguy

**Contact Information:** [inigo.surguy@gmail.com](mailto:inigo.surguy@gmail.com)

**Submitter's Defect Number:** GB-076

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-03-31

**Deadline for Response from Editor:** 2009-05-31

**IS 29500 Reference(s):**

**Related DR(s):** none

**Nature of the Defect:**

As a result of changes made at the BRM, a number of existing Ecma-376 documents were unintentionally made invalid against the IS29500 transitional schema. It was strongly expressed as an opinion at the BRM by many countries that the transitional schema should accurately reflect the existing Ecma-376 documents.

However, at the BRM, the ST\_OnOff type was changed from supporting 0,1,On,Off,True,False to supporting only 0,1,True,False (i.e. the xs:boolean type). Although this fits with the detail of the amendments made at the BRM, it is against the spirit of the desired changes for many countries, and we believe that due to time limitations at the BRM, this change was made without sufficient examination of the consequences, was made in error by the BRM (in which error the UK played a part), and should be fixed.

**Solution Proposed by the Submitter:**

Change the ST\_OnOff type to support 0,1,On,Off,True and False in the Transitional schemas only.

**Schema Change(s) Needed:** shared-commonSimpleTypes.xsd within the Transitional schemas only.

**Editor's Response:**

**2009-03-24 Prague meeting:**

There were concerns that resolving this would overturn a vote of the BRM. Various members spoke for/against doing that. It was decided to cover this on an up-coming teleconference.

# 175. DR 09-0160 — SML and Shared ML: Lack of Specialized Media Types

**Status:** Open

**Subject:** SML and Shared ML: Lack of Specialized Media Types

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00078

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §12.3.6 (pp. 74), "Custom XML Mappings Part"

**Related DR(s):** none

## **Nature of the Defect:**

Since OOXML has so many specialized media types (i.e., ones ending with "+xml"), I do not understand why this part does not have specialized media types. This part is always of the namespace  
["http://schemas.openxmlformats.org/spreadsheetml/2006/main"](http://schemas.openxmlformats.org/spreadsheetml/2006/main)

The same question applies to two other parts.

### 15.2.1 Additional Characteristics Part

application/xml

<http://schemas.openxmlformats.org/officeDocument2006/additionalCharacteristics>

### 15.2.3 Bibliography Part

application/xml

<http://schemas.openxmlformats.org/officeDocument/2006/bibliography>

Note: One could argue that this is not a defect but merely a peculiar design choice.

**Solution Proposed by the Submitter:**

Use a specialized media type and register it at IANA. Or, state the reason that a specialized media type is not needed.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 176. DR 09-0161 — Shared ML: Digital Signature Origin Part Media Type

**Status:** Open

**Subject:** Shared ML: Digital Signature Origin Part Media Type

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00079

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §15.2.7 (pp. 148), "Digital Signature Origin Part"

**Related DR(s):** none

## **Nature of the Defect:**

The MIME body of the media type

"application/vnd.openxmlformats-package.digital-signature-origin"

is always empty. Thus, this media type does look strange to me.

Should we register this anyway?

## **Solution Proposed by the Submitter:**

**Schema Change(s) Needed:** No

## **Editor's Response:**

# 177. DR 09-0162 — Shared ML: Printer Settings Part Media Types

**Status:** Open

**Subject:** Shared ML: Printer Settings Part Media Types

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00080

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §15.2.15 (pp. 161), "Printer Settings Part"

**Related DR(s):** none

## **Nature of the Defect:**

application/vnd.openxmlformats-officedocument.spreadsheetml.printerSettings (in SpreadsheetML documents)

application/vnd.openxmlformats-officedocument.wordprocessingml.printerSettings (in WordprocessingML documents).

These media types are very strange, since they do not provide any information about the MIME body.

"An instance of this part type contains information about the initialization and environment of a printer or a display device.

The layout of this information is application-defined."

## **Solution Proposed by the Submitter:**

Register a media type for DEVMODE and another for the print record of MAC OS.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 178. DR 09-0163 — VML: Drawing Part Media Type

**Status:** Open

**Subject:** VML: Drawing Part Media Type

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00081

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 4, §8.1 (pp. 13), "VML Drawing Part"

**Related DR(s):** none

**Nature of the Defect:**

application/vnd.openxmlformats-officedocument.vmlDrawing

This media type should have ended with "+xml" so that generic XML tools can handle VML Drawing parts.

**Solution Proposed by the Submitter:**

Use application/vnd.openxmlformats-officedocument.vmlDrawing+xml and register it at IANA, instead.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 179. DR 09-0164 — WML: Alternative Format Import Part Media Type

**Status:** Open

**Subject:** WML: Alternative Format Import Part Media Type

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00082

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §11.3.1 (pp. 32), "Alternative Format Import Part"

**Related DR(s):** none

**Nature of the Defect:**

application/vnd.openxmlformats-officedocument.wordprocessingml.document

There are no clear definitions of this media type. Is the MIME body a WML package? Ecma 1st edition or 29500?

**Solution Proposed by the Submitter:**

Define the content of this media type and register the media type at IANA. Alternatively, one could register a single media type for all OPC packages.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 180. DR 09-0165 — SML and PML: Lack of Media Types

**Status:** Open

**Subject:** SML and PML: Lack of Media Types

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00083

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** None

**Related DR(s):** none

**Nature of the Defect:**

No media types are provided for PML and SML.

**Solution Proposed by the Submitter:**

Since application/vnd.openxmlformats-officedocument.wordprocessingml.document is already available for WML, define media types for PML and SML and register them at IANA.

**Schema Change(s) Needed:**

**Editor's Response:**

# 181. DR 09-0166 — SML: Custom Property Part Media Type

**Status:** Open

**Subject:** SML: Custom Property Part Media Type

**Qualifier:** Request for Clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00084

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §12.3.5 (pp. 73), "Custom Property Part"

**Related DR(s):** none

## **Nature of the Defect:**

The media type "application/vnd.openxmlformats-officedocument.spreadsheetml.customProperty" is very strange, since it does not provide any information about the MIME body.

"This part supports the storage of user-defined data."

## **Solution Proposed by the Submitter:**

Drop this media type, since application/xml is already allowed for Custom Property Parts.

**Schema Change(s) Needed:** No

## **Editor's Response:**

## 182. DR 09-0167 — SML: Embedded Control Persistence Part Media Type

**Status:** Open

**Subject:** SML: Embedded Control Persistence Part Media Type

**Qualifier:** Technical Defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00085

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §12.2.9 (pp. 150), "Embedded Control Persistence Part"

**Related DR(s):** none

**Nature of the Defect:**

Little information about the permissible contents of the media type "application/vnd.ms-officeactivex+xml" is provided.

**Solution Proposed by the Submitter:**

Provide normative prose as well as a schema. Remember to register this media type at IANA.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 183. DR 09-0168 — OPC: No mechanism to distinguish ECMA-376:2006 from IS 29500

**Status:** Open

**Subject:** OPC: No mechanism to distinguish ECMA-376:2006 from IS 29500

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00086

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 2

**Related DR(s):** DR 08-0012 — Schemas: Supposedly incorrect schema namespace names

## **Nature of the Defect:**

There are no mechanisms for distinguishing OPC of ECMA-376:2006 and that of ISO/IEC 29500:2008.

Note that OPC of ECMA-376:2006 disallows non-ASCII part names, while that of ISO/IEC 29500:2008 allow non-ASCII part names.

## **Solution Proposed by the Submitter:**

Introduce an optional attribute or optional part.

**Schema Change(s) Needed:** No

## **Editor's Response:**

## 184. DR 09-0169 — Normative Reference to XML 1.1

**Status:** Open

**Subject:** Normative Reference to XML 1.1

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00087

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §3 (pp. 10), "Normative References"

**Related DR(s):** none

**Nature of the Defect:**

XML 1.1 is referenced. It is widely believed that XML 1.1 is dead.

**Solution Proposed by the Submitter:**

Reference the fourth edition of XML 1.0, instead.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 185. DR 09-0170 — Normative Reference to Namespaces in XML 1.1

**Status:** Open

**Subject:** Normative Reference to Namespaces in XML 1.1

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00088

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-13

**Deadline for Response from Editor:** 2009-06-13

**IS 29500 Reference(s):** Part 1, §3 (pp. 11), "Normative References"

**Related DR(s):** none

**Nature of the Defect:**

Namespaces in XML 1.1 is referenced. It is widely believed that Namespaces in XML 1.1 is dead.

**Solution Proposed by the Submitter:**

Reference Namespaces in XML 1.0 instead.

**Schema Change(s) Needed:** No

**Editor's Response:**

# 186. DR 09-0171 — WML and SML: Space-related errors in grammar productions

**Status:** Closed; will be incorporated in COR1

**Subject:** WML and SML: Space-related errors in grammar productions

**Qualifier:** Technical defect

**Submitter:** Editor

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** None

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-14

**Deadline for Response from Editor:** 2009-06-14

**IS 29500 Reference(s):**

Part 1: §17.16.1, “Syntax”, pp. 1303, Part 1: §18.17.2.1, “Constants”, pp. 2276, Part 1: §18.17.2.1, “Constants”, pp. 2277, Part 1: §18.17.2.3, “Cell References”, pp. 2281

**Related DR(s):** none

**Nature of the Defect:**

A number of terminals having the form “...” or ‘...’ in the productions double-quote, error-constant, double-quote, string-char and apostrophe erroneously contain leading and/or trailing spaces.

**Solution Proposed by the Submitter:**

Remove those leading and/or trailing spaces.

**Schema Change(s) Needed:** none

**Editor's Response:**

The exact changes are as follows:

Part 1: §17.16.1, “Syntax”, pp. 1303

```
double-quote=
'-' ; (* one double-quote character *)
```

Part 1: §18.17.2.1, “Constants”, pp. 2276

```
error-constant=
"#DIV/0!-" | "#N/A" | "#NAME?-" | "#NULL!-" |
"#NUM!-" | "#REF!-" | "#VALUE!-" ;
```

Part 1: §18.17.2.1, “Constants”, pp. 2277

```
double-quote=
'-' ; (* one double-quote character*)
```

```
string-char=
'""-' | (* consecutive double-quotes, with no space between them *) character -
double-quote ; (* any character except double-quote *)
```

Part 1: §18.17.2.3, “Cell References”, pp. 2281

```
apostrophe=
'-' ; (* one apostrophe character *)
```

# 187. DR 09-0172 — WML: Filename-to-IRI mapping

**Status:** Open

**Subject:** WML: Filename-to-IRI mapping

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 09-00089

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.16.5.27 (pp. 1362)

**Related DR(s):** none

## **Nature of the Defect:**

It needs to be specified how filenames which cannot be directly embedded in a syntactically valid IRI shall be represented by an IRI. For example, the ASCII space character is not allowed to occur in an IRI. The IRI in the example in the standard is syntactically wrong.

## **Solution Proposed by the Submitter:**

Specify that each ASCII character that does not belong to the set of reserved or unreserved characters as defined in RFC 3986 shall be percent-encoded by means of the mechanism defined in Step 2 in §3.1 of RFC 3987. Furthermore, specify that no other ASCII characters shall be percent-encoded. Delete the sentence “If field-argument contains white space, it shall be enclosed in double quotes.” Add an informative note that warns about the potential risk of security violations that could potentially result from bypassing, by means of percent-encoding, the validation of filenames against constraints on filenames. Also correct the example.

**Schema Change(s) Needed:** No

**Editor's Response:**

Look at other WML fields and at SML formulas, as some of these traffic in filenames.

# 188. DR 09-0173 — WML: shapeID attribute semantics missing

**Status:** Open

**Subject:** WML: shapeID attribute semantics missing

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00090

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.3.3.20, “objectEmbed (Embedded Object Properties)”, (pp. 367);  
Part 1, §17.3.3.21, “objectLink (Linked Object Properties)”, (pp. 369)

**Related DR(s):** none

**Nature of the Defect:**

The semantics of the value of the shapeID attribute need to be specified.

**Solution Proposed by the Submitter:**

Add the following text: “This shape ID reference is resolved by looking for a DrawingML object whose id attribute matches the value specified within this attribute. If no such shape exists, then the object shall be rendered inline in the document content at the current run content location.”

**Schema Change(s) Needed:** No

**Editor's Response:**

## 189. DR 09-0174 — WML: Header cell identifier resolution

**Status:** Open

**Subject:** WML: Header cell identifier resolution

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00091

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part x, §17.4.18, “header (Header Cell Reference)” (pp. 429)

**Related DR(s):** none

**Nature of the Defect:**

It needs to be specified how the value of the header cell identifier shall be resolved.

**Solution Proposed by the Submitter:**

Clarify that this header cell identifier shall be resolved by searching the values of the id attributes of the header cell tc elements of that particular table.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 190. DR 09-0175 — WML: Imprecise forward reference

**Status:** Closed; will be incorporated in COR1

**Subject:** WML: Imprecise forward reference

**Qualifier:** Editorial defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00092

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.3.3.20, “objectEmbed (Embedded Object Properties)” (pp. 366);  
Part 1, §17.3.3.21, “objectLink (Linked Object Properties)” (pp. 368)

**Related DR(s):** none

### Nature of the Defect:

The correct precise clause number for referencing the normative specification of “the field switches defined by the LINK field” is §17.16.5.32 rather than §17.16.

### Solution Proposed by the Submitter:

Change “§17.16” to “§17.16.5.32”, both in the normative text and in the explanation of the example.

**Schema Change(s) Needed:** No

### Editor's Response:

The exact changes are as follows:

Part 1, §17.3.3.20, “objectEmbed (Embedded Object Properties)” (pp. 366)

<u>Attributes</u>	<u>Description</u>
fieldCodes (Field Switches)	<p>This element specifies the WordprocessingML field switches which shall be stored with an embedded object, using the set of field switches defined by the LINK field, as specified in §17.16.<a href="#">5.32</a>. This element shall specify the exact field switches for the field which represents the object.</p> <p>...</p> <p>[<i>Example</i>:</p> <pre>&lt;w:objectEmbed ... fieldCodes="\f 0"/&gt;</pre> <p>This embedded object specifies additional LINK field code values of \f 0, which specifies that the embedded object must retain its source formatting (as defined in §17.16.<a href="#">5.32</a>).</p> <p><i>end example</i>]</p> <p>...</p>

Part 1, §17.3.3.21, “objectLink (Linked Object Properties)” (pp. 368)

<u>Attributes</u>	<u>Description</u>
fieldCodes (Field Switches)	<p>This element specifies the WordprocessingML field switches which shall be stored with an embedded object, using the set of field switches defined by the LINK field, as specified in §17.16.<a href="#">5.32</a>. This element shall specify the exact field switches for the field which represents the object.</p> <p>...</p> <p>[<i>Example</i>:</p> <pre>&lt;w:objectEmbed ... fieldCodes="\f 0"/&gt;</pre> <p>This embedded object specifies additional LINK field code values of \f 0, which specifies that the embedded object must retain its source formatting (as defined in §17.16.<a href="#">5.32</a>).</p> <p><i>end example</i>]</p> <p>...</p>

# 191. DR 09-0176 — General: ST\_String instance value set and length constraints

**Status:** Open

**Subject:** General: ST\_String instance value set and length constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 14.001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part 1, §22.9.2.13, “ST\_String (String)” (pp. 4329)

**Related DR(s):** [DR 08-0013](#) — Shared MLs, Shared Simple Types: ST\_String allowed characters and max length

## Nature of the Defect:

Many clauses of the standard describe instances of ST\_String with language like “The possible values for this attribute are defined by the ST\_String simple type (§22.9.2.13).” However, the referenced clause §22.9.2.13 fails to specify any set of possible values precisely, because that clause does not specify whether or not there are restrictions on string length, nor does it specify anything regarding character sets and encodings.

That issue was brought up in DR 08-0013. However, as pointed out correctly in the Editor's response to that DR, the problem unfortunately cannot be resolved in a centralized manner by modifying the specification of ST\_String, because that simple type is used in a too broad variety of contexts.

At the 2009-01-28 Okinawa meeting “[i]t was agreed that this is not an issue with the type itself, but that specific instances certainly might have constraints” and the submission of defect reports regarding

specific instances of the type was invited. (See the document “IS 29500:2008 Defect Report Log” dated 2009-02-09.)

The following 13 defect report items provide examples of references to the ST\_String simple type that clearly need to be amended with more precise statements about the set of allowed values. However, the problem is bigger than just these examples.

**Solution Proposed by the Submitter:**

Amend *all* clauses of the standard that reference ST\_String by adding language that clearly specifies the set of allowed values, either by stating that the string may contain any number of arbitrary Unicode characters, or by specifying precise constraints. Furthermore, unless in particular the ASCII quotation mark character is excluded from all attribute values of type ST\_String, amend the specification of the ST\_String simple type in §22.9.2.13 with a precise specification of an escape mechanism by means of which this character can be encoded for inclusion in attribute values.

**Schema Change(s) Needed:** No

**Editor’s Response:**

## 192. DR 09-0177 — WML: Embedded control name length and content constraints

**Status:** Open

**Subject:** WML: Embedded control name length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00094

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part 1, §17.3.3.3, “control (Embedded Control)” (pp. 350), attribute name

**Related DR(s):** none

### Nature of the Defect:

It needs to be precisely specified whether the “unique name for embedded controls” can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such a name. (Only some specific set of printable ASCII characters? Any ASCII characters including; e.g., the NUL character? Arbitrary Unicode characters?)

### Solution Proposed by the Submitter:

none

**Schema Change(s) Needed:** No

**Editor's Response:**

# 193. DR 09-0178 — WML: Syntax for, and handling of, fieldCodes values

**Status:** Open

**Subject:** WML: Syntax for, and handling of, fieldCodes values

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00095

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.3.3.20, “objectEmbed (Embedded Object Properties)”, (pp. 366);  
Part 1, §17.3.3.21, “objectLink (Linked Object Properties)”, (pp. 368)

**Related DR(s):** none

## Nature of the Defect:

There is an apparent contradiction here: The first paragraph specifies: “This element specifies the WordprocessingML field switches which shall be stored with an embedded object, using the set of field switches defined by the LINK field, as specified in §17.16. This element shall specify the exact field switches for the field which represents the object.” The last paragraph specifies, “The possible values for this attribute are defined by the ST\_String simple type (§22.9.2.13).” However, there are many possible values of the ST\_Simple type that are not of the form described in the first paragraph.

## Solution Proposed by the Submitter:

Specify the precise syntax for valid values of the fieldCodes attribute, and specify how invalid values shall be treated.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 194. DR 09-0179 — WML: progID length and content constraints

**Status:** Open

**Subject:** WML: progID length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00096

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.3.3.20, “objectEmbed (Embedded Object Properties)”, (pp. 366);  
Part 1, §17.3.3.21, “objectLink (Linked Object Properties)”, (pp. 369)

**Related DR(s):** none

### Nature of the Defect:

It needs to be precisely specified whether the value of progID can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such a progID. (Only alphanumeric characters? Or are characters allowed that may have a special meaning on some operating systems when searching for a program with a given name, and which may therefore cause security bugs unless implementations are written carefully to escape such characters?)

### Solution Proposed by the Submitter:

Specify this. Also, include an informative note about potential security implications of handling progID carelessly.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 195. DR 09-0180 — WML: Table cell id length and content constraints

**Status:** Open

**Subject:** WML: Table cell id length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00097

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part 1, §17.4.66, “tc (Table Cell)” (pp. 466)

**Related DR(s):** none

### **Nature of the Defect:**

It needs to be precisely specified whether the value of id (Table Cell Identifier) can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such an id. (Only some specific set of printable ASCII characters? Any ASCII characters including; e.g., the NUL character? Arbitrary Unicode characters?)

### **Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

## 196. DR 09-0181 — WML: Handling of invalid name values

**Status:** Open

**Subject:** WML: Handling of invalid name values

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00098

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part 1, §17.5.1.1, “attr (Custom XML Attribute)” (pp. 531); Part 1, §17.5.1.2, “attr (Smart Tag Property)” (pp. 533)

**Related DR(s):** none

**Nature of the Defect:**

It needs to be clarified how values of the name attribute that are not valid XML attribute names shall be handled. Or is a document non-conforming if it contains an attr element with a name attribute that is not a valid XML attribute name?

**Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

# 197. DR 09-0182 — WML: Handling of invalid uri values

**Status:** Open

**Subject:** WML: Handling of invalid uri values

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00099

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

## IS 29500 Reference(s):

Part 1, §17.5.1.1, “attr (Custom XML Attribute)” (pp. 532)

Part 1, §17.5.1.2, “attr (Smart Tag Property)” (pp. 533)

Part 1, §17.5.1.3, “customXml (Inline-Level Custom XML Element)” (pp. 536)

Part 1, §17.5.1.4, “customXml (Cell-Level Custom XML Element)” (pp. 538)

Part 1, §17.5.1.5, “customXml (Row-Level Custom XML Element)” (pp. 541)

Part 1, §17.5.1.6, “customXml (Block-Level Custom XML Element)” (pp. 543)

Part 1, §17.5.1.9, “smartTag (Inline-Level Smart Tag)” (pp. 548)

## Related DR(s):

### Nature of the Defect:

It needs to be clarified how values of the uri attribute that are not valid URIs shall be handled. Or is a document non-conforming if it contains an uri attribute the value of which is not a valid URI?

**Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

# 198. DR 09-0183 — WML: Handling of invalid customXML element name values

**Status:** Open

**Subject:** WML: Handling of invalid customXML element name values

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00100, 08-00101

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

## IS 29500 Reference(s):

Part 1, §17.5.1.3, “customXml (Inline-Level Custom XML Element)” (pp. 536)

Part 1, §17.5.1.4, “customXml (Cell-Level Custom XML Element)” (pp. 538)

Part 1, §17.5.1.5, “customXml (Row-Level Custom XML Element)” (pp. 540-541)

Part 1, §17.5.1.6, “customXml (Block-Level Custom XML Element)” (pp. 543)

Part 1, §17.5.1.9, “smartTag (Inline-Level Smart Tag)” (pp. 548)

## Related DR(s):

### Nature of the Defect:

It needs to be clarified how values of the name attribute that are not valid XML element names shall be handled. Or is a document non-conforming if it contains a customXML (or smartTag) element with an element attribute that is not a valid XML element name?

### Solution Proposed by the Submitter:

none

**Schema Change(s) Needed:** No

**Editor's Response:**

## 199. DR 09-0184 — WML: Alias val length and content constraints

**Status:** Open

**Subject:** WML: Alias val length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00102

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

IS 29500 Reference(s): Part 1, §17.5.2.1, “alias (Friendly Name)” (pp. 551)

**Related DR(s):** none

### **Nature of the Defect:**

It needs to be precisely specified whether the value of the val attribute can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such a “friendly name”. (Only a specific set of printable ASCII characters? Any ASCII characters including; e.g., the NUL character? Arbitrary Unicode characters?)

### **Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

# 200. DR 09-0185 — WML: Programmatic Tag val length and content constraints

**Status:** Open

**Subject:** WML: Programmatic Tag val length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00103

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):** Part 1, §17.5.2.42, “tag (Programmatic Tag)” (pp. 606), attribute val

**Related DR(s):** none

## **Nature of the Defect:**

It needs to be precisely specified whether the value of the val attribute can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such a “programmatic tag”. (Only a specific set of printable ASCII characters? Any ASCII characters including; e.g., the NUL character? Arbitrary Unicode characters?)

## **Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

# 201. DR 09-0186 — WML: Style Definition styleId length and content constraints

**Status:** Open

**Subject:** WML: Style Definition styleId length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00104

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):**

Part 1, §17.7.4.17, “style (Style Definition)” (pp. 710)

**Related DR(s):** none

**Nature of the Defect:**

It needs to be precisely specified whether the value of the styleId attribute can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters in such a “style id”. (Only a specific set of printable ASCII characters? Any ASCII characters including; e.g., the NUL character? Arbitrary Unicode characters?)

**Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

## 202. DR 09-0187 — WML: Font Properties name length and content constraints

**Status:** Open

**Subject:** WML: Font Properties name length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00105

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

### IS 29500 Reference(s):

Part 1, §17.8.3.10, “font (Properties for a Single Font)” (pp. 764)

**Related DR(s):** [DR 09-0044](#) — WML, Fonts: Support for commas in font family/subfamily/full names; [DR 09-0050](#) — SML, Worksheets: comma delimiter between font name and type

### Nature of the Defect:

It needs to be precisely specified whether the value of the name attribute can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters are in such a font name. (Some subset of the set of ASCII characters? From §17.8.3.1 it appears that font names should not be allowed to contain comma characters.)

### Solution Proposed by the Submitter:

none

**Schema Change(s) Needed:** No

**Editor's Response:**

## 203. DR 09-0188 — WML: Paragraph Style's Associated Numbering Level val length and content constraints

**Status:** Open

**Subject:** WML: Paragraph Style's Associated Numbering Level val length and content constraints

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00106

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):**

Part 1, §17.9.24, “pStyle (Paragraph Style's Associated Numbering Level)” (pp. 813)

**Related DR(s):** none

**Nature of the Defect:**

It needs to be precisely specified whether the value of the val attribute can be of arbitrary length, or otherwise what the maximum length is. Also it needs to be clarified what are the permissible characters are in such a name of a paragraph style. (Some subset of the set of ASCII characters? Arbitrary Unicode characters?)

**Solution Proposed by the Submitter:**

none

**Schema Change(s) Needed:** No

**Editor's Response:**

## 204. DR 09-0189 — WML: Font Character Set reference to non-existent attribute

**Status:** Open

**Subject:** WML: Font Character Set reference to non-existent attribute

**Qualifier:** Technical defect

**Submitter:** Ms. Ruth Schneider, SNV (CH)

**Contact Information:** [ruth.schneider@snv.ch](mailto:ruth.schneider@snv.ch)

**Submitter's Defect Number:** 08-00107

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):**

Part 1, §17.8.3.2, "charset (Character Set Supported By Font)" (pp. 752)

**Related DR(s):** none

**Nature of the Defect:**

The normative text [for the attribute characterSet] references a val attribute, which is not defined

**Solution Proposed by the Submitter:**

Delete or clarify the reference to the val attribute.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 205. DR 09-0190 — WML: Error in examples

**Status:** ~~Closed; will be incorporated in COR1~~ [Last Call](#)

**Subject:** WML: Error in examples

**Qualifier:** Editorial defect

**Submitter:** Rick Jelliffe

**Contact Information:** [rjelliffe@allette.com.au](mailto:rjelliffe@allette.com.au)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-17

**Deadline for Response from Editor:** 2009-06-17

**IS 29500 Reference(s):**

Part 1, §11.3.12, “Style Definitions Part” (pp. 55); Part 1, §11.6, “Master Documents and Subdocuments” (pp. 60)

**Related DR(s):** none

**Nature of the Defect:**

There are two occurrences of an example with `xmlns:wx` where clearly `xmlns:w` is intended.

**Solution Proposed by the Submitter:**

Correct these.

**Schema Change(s) Needed:** No

**Editor's Response:**

[\*\*2009-05-08 MURATA, Makoto:\*\*](#)

[`xmlns:wx="..."` in Part 1, §11.3.12, “Style Definitions Part” \(pp. 55\) should be deleted. Replacing `xmlns:wx` by `xmlns:w` is an error \(a doubly-defined prefix\).](#)

The exact changes are:

Part 1, §11.3.12, “Style Definitions Part” (pp. 55)

```
<w:styles xmlns:wxml="..." xmlns:w="..." ... xml:space="preserve">
...
</w:styles>
```

Part 1, §11.6, “Master Documents and Subdocuments” (pp. )

```
<w:document xmlns:r="..." xmlns:wxml="..." ...>
...
</w:document>
```

## 206. DR 09-0191 — Custom XML Schema: Allowed attribute values

**Status:** Open

**Subject:** Custom XML Schema: Allowed attribute values

**Qualifier:** Request for clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00108

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-04-24

**Deadline for Response from Editor:** 2009-06-24

**IS 29500 Reference(s):** Part 1, §23.2.1, “schema (Custom XML Schema Reference)”, pp. 4342

**Related DR(s):** none

### **Nature of the Defect:**

It is not clear what is allowed as the value of the attributes schemaLocation and manifestLocation.

### **Solution Proposed by the Submitter:**

Allow any IRIs and IRI references but disallow fragment identifiers. Revise the XSD and RNG schemas (for both conformance class) by replacing xsd:string with xsd:anyURI.

There are some issues about characters (most notably the space character). See

<http://blog.jclark.com/search?updated-min=2008-01-01T00%3A00%3A00%2B07%3A00&updated-max=2009-01-01T00%3A00%3A00%2B07%3A00&max-results=6>

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 207. DR 09-0192 — BRM Resolution not implemented (Transitional Migration Features)

**Status:** Last Call

**Subject:** BRM Resolution not implemented (Transitional Migration Features)

**Qualifier:** Editorial defect

**Submitter:** Jesper Lund Stockholm (DS)

**Contact Information:** [jesper.stockholm@ciber.dk](mailto:jesper.stockholm@ciber.dk)

**Submitter's Defect Number:** DK-09-0001

**Supporting Document(s):** BRM document "CA\_Conformance\_Class\_Proposal\_Draft4.doc"

**Date Circulated by Secretariat:** 2009-05-01

**Deadline for Response from Editor:** 2009-07-01

**IS 29500 Reference(s):** Part 4, §1

**Related DR(s):** none

### Nature of the Defect:

Resolution 10 at the Ballot Resolution Meeting in Geneva in February 2008 accepted the Canadian proposal "CA\_Conformance\_Class\_Proposal\_Draft4.doc". The Canadian proposal extended the original Response 92 and Response 992 from the Disposition of Comments. Specifically, the Canadian proposal modified Response 92. The proposal stated:

*A new annex in part 4 will be created as follows:*

Annex A. Selected Transitional Migration Features (normative)

*The features described in this Annex shall only be used by documents of conformance class WML Transitional, SML Transitional or PML Transitional. These features are sometimes needed for high-quality migration of existing binary documents to DIS 29500.*

*The intent of this Annex is to enable a transitional period during which existing binary documents being migrated to DIS 29500 can make use of legacy features to preserve their fidelity, while noting that new documents should not use*

*them. The Conformance clause states that WML Strict, SML Strict and PML Strict documents shall not use any of the features defined in this Annex.*

*This annex is normative for the current edition of the Standard, but not guaranteed to be part of the Standard in future revisions. The intent is to enable the future DIS 29500 maintenance group to choose, at a later date, to remove this set of features from a revised version of DIS 29500.*

This text was not included in the text of IS29500:2008-4.

**Solution Proposed by the Submitter:**

Add the specified text to the Scope clause (Part 4, §1).

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 4, §1, "Scope", pp. 1

...

The features described in this Part shall only be used by documents of conformance class WML Transitional (§2.1), SML Transitional (§2.1), or PML Transitional (§2.1). These features are sometimes needed for high-quality migration of existing binary documents to ISO/IEC 29500.

The intent of this Part is to enable a transitional period during which existing binary documents being migrated to ISO/IEC 29500 can make use of legacy features to preserve their fidelity, while noting that new documents should not use them. Part 1, §2.4, "Document Conformance", states that WML Strict, SML Strict and PML Strict documents shall not use any of the features defined in Part 4.

This Part is normative for the current edition of ISO/IEC 29500, but is not guaranteed to be included in future revisions of that Standard. The intent is to enable the group responsible for maintenance of ISO/IEC 29500 to choose, at a later date, to remove this set of features from a revised version of that Standard.

## 208. DR 09-0193 — WML: Move hMerge from strict to transitional

**Status:** Open

**Subject:** WML: Move hMerge from strict to transitional

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00109

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1, §17.4.22, “hMerge (Horizontally Merged Cell)”, pp. 435

**Related DR(s):** none

### **Nature of the Defect:**

The text says that hMerge is for compatibility. Therefore, it should be in Part 4, not Part 1.

### **Solution Proposed by the Submitter:**

Move the hMerge element from Part 1 to Part 4.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 209. DR 09-0194 — WML: Use of terminology "id" and "unique identifier"

**Status:** Open

**Subject:** WML: Use of terminology "id" and "unique identifier"

**Qualifier:** Technical defect

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00110

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1, §17.9.16, “num (Numbering Definition Instance)”, pp. 802

**Related DR(s):** none

### **Nature of the Defect:**

The term "id" and "unique id" are used outside their common meanings in SGML and XML and are consequently confusing. Furthermore, the capitalized version ID is sometimes used, which is definitely incorrect.

numId (Numbering Definition Instance ID)

Specifies a unique ID which any numbered paragraph which wishes to inherit these numbering properties shall reference using the numPr element (17.3.1.19).

Yet in the schema, we find it is not an ID at all.

```
2979 <xsd:complexType name="CT_Num">
2980 <xsd:sequence>
2981 <xsd:element name="abstractNumId" type="CT_DecimalNumber"
 minOccurs="1"/>
2982 <xsd:element name="lvlOverride" type="CT_NumLvl" minOccurs="0"
 maxOccurs="9"/>
2983 </xsd:sequence>
2984 <xsd:attribute name="numId" type="ST_DecimalNumber" use="required"/>
2985 </xsd:complexType>
```

**Solution Proposed by the Submitter:**

In every clause where there is reference to an "id" or "unique identifier" etc. which is a number in the schema, a clearer term must be used. (For example, "numerical identifier".) If the number is an index, then the term "index" should be used.)

Review all uses of capitalized "ID" in the document and replace it with the correct term if the identifier is not derived from xs:NMTOKEN. In particular, this means that no numbers may be referred to as IDs.

This applies to, for example, CT\_Num, CT\_NumPr, CT\_NumLvl

**Schema Change(s) Needed:****Editor's Response:**

## 210. DR 09-0195 — WML: numbering definition instance description

**Status:** Open

**Subject:** WML: numbering definition instance description

**Qualifier:** Request for clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00111

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1, §17.3.1.19, “numPr (Numbering Definition Instance Reference)”, pp. 240

**Related DR(s):** none

### **Nature of the Defect:**

§17.3.1.19 numPr (Numbering Definition Instance Reference)

This element specifies that the current paragraph references a numbering definition instance in the current document. The paragraph does not reference anything. The numPr element is the reference.

Also, what does "in the current document" mean? Does this relate to subdocuments or external links or what?

### **Solution Proposed by the Submitter:**

Replace with something like "This element specifies that the current paragraph uses a particular Numbering Definition Instance."

### **Schema Change(s) Needed:**

### **Editor's Response:**

# 211. DR 09-0196 — General: Conventions for element long names

**Status:** Open

**Subject:** General: Conventions for element long names

**Qualifier:** Request for clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00112

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1

**Related DR(s):** none

## **Nature of the Defect:**

Throughout Part 1, element names are followed by more formal names, in parentheses. For example,

§17.9.3 ilvl (Numbering Level Reference)

This element specifies the numbering level of the numbering definition instance which shall be applied to the parent paragraph.

However, in the general text, these names are used lower case. Sometimes in italic. This reduces the text to gobbledegook. Moreover, translation to the Japanese language becomes difficult. Better practice in this situation is to follow, for example, the W3C XML Schemas approach where defined terms are more clearly marked out typographically and to use hyperlinks.

## **Solution Proposed by the Submitter:**

Element formal names should either be capitalized in normal text, since they are proper names, or they should be all italicized or in some special font weight variation, such as a demi-bold. For example:

### §17.9.3 ilvl (Numbering Level Reference)

This element specifies the numbering level of the Numbering Definition Instance which shall be applied to the parent paragraph.

Note that in the following clause, the name is currently italicized:

#### §17.3.1.19 numPr (Numbering Definition Instance Reference)

This element specifies that the current paragraph references a *<i>numbering definition instance</i>* in the current document.

Indeed, all these phrases should be hyperlinks in the PDF.

This editorial change can be automated by

1. extracting all the parenthetical phrases
2. sorting longest first
3. finding instances of the phrase in paragraphs and lists, and markup up the reference.

#### **Schema Change(s) Needed:**

#### **Editor's Response:**

## 212. DR 09-0197 — General: dotted line rendering problem

**Status:** Open

**Subject:** General: dotted line rendering problem

**Qualifier:** Request for clarification

**Submitter:** Mr. Makoto Murata (JP)

**Contact Information:** [eb2m-mrt@asahi-net.or.jp](mailto:eb2m-mrt@asahi-net.or.jp)

**Submitter's Defect Number:** 08-00113

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1, §17.4.17, “gridSpan (Grid Columns Spanned by Current Table Cell)”, pp. 428

**Related DR(s):** none

### **Nature of the Defect:**

The text on top of pp. 428 says “(see the grid lines represented using dotted lines in the example above)”. However, there are no dotted lines in the PDF.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 213. DR 09-0198 — saveInvalidXml, clarification of text

**Status:** Last Call

**Subject:** saveInvalidXml, clarification of text

**Qualifier:** Editorial defect

**Submitter:** Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-23

**Deadline for Response from Editor:** 2009-07-23

**IS 29500 Reference(s):** Part 1: §17.15.1.74, “saveInvalidXml (Allow Saving Document As XML File When Custom XML Markup Is Invalid)”, pp. 999

**Related DR(s):** none

**Nature of the Defect:**

The text, “This element specifies that this document should be capable of being saved into a format consisting of a single XML file (not defined by ISO/IEC 29500) when its contents are invalid based XML schema validation of the custom XML markup contained in the document.” doesn’t quite read correctly.

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

[The exact changes are:](#)

[Part 1: §17.15.1.74, “saveInvalidXml \(Allow Saving Document As XML File When Custom XML Markup Is Invalid\)”, pp. 999](#)

This element specifies that this document should be capable of being saved into a format consisting of a single XML file (not defined by ISO/IEC 29500) even when its contents are invalid based XML schema validation of the custom XML markup contained in the document.

# 214. DR 09-0199 — WML: ST\_BrClear, description vs. intended behavior

**Status:** Open

**Subject:** WML: ST\_BrClear, description vs. intended behavior

**Qualifier:** Technical defect

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00114

**Supporting Document(s):** See the PDFs in WG4 N 0048, "DR 09-0199 support files.zip"

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1: §17.18.3, "ST\_BrClear (Line Break Text Wrapping Restart Location)", pp. 1508

**Related DR(s):** none

**Nature of the Defect:**

The current description does not match the intended behavior (as deduced from experimenting with MS Office 2007, and from the behavior of corresponding properties in the CSS standard (<http://www.w3.org/TR/CSS2/visuren.html#flow-control> ), in cases where there are floating objects both on the left and on the right of the line.

I assume that this is because of an erroneous recursive reference to the `all` value in the description of `left` and `right`.

The following links demonstrate the behavior of CSS in cases where images exist in both sides (MS Office 2007 does the same):

- [http://amit.freeshell.org/ecmarep\\_18\\_19/cright.html](http://amit.freeshell.org/ecmarep_18_19/cright.html)
- [http://amit.freeshell.org/ecmarep\\_18\\_19/cleft.html](http://amit.freeshell.org/ecmarep_18_19/cleft.html)

The supplied PDFs demonstrate the behavior that literal interpretation of the standard text seems to imply.

**Solution Proposed by the Submitter:**

In the description of `left`, replace "treat this as a break of type `a11`" with "advance the text to the next available line that does not have a floating object on the left" (2 places). Corresponding modifications should be applied to the `right` enumeration value as well.

**Schema Change(s) Needed:**

**Editor's Response:**

## 215. DR 09-0200 — WML: mirrorMargins

**Status:** Open

**Subject:** WML: mirrorMargins

**Qualifier:** Technical defect

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00115

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1: §17.15.1.57, "mirrorMargins (Mirror Page Margins)", pp. 1170

**Related DR(s):** none

**Nature of the Defect:**

The first sentence is non-informative, probably due to a typo.

**Solution Proposed by the Submitter:**

Replace "swapped on facing pages" with "swapped on even numbered pages".

**Schema Change(s) Needed:**

**Editor's Response:**

# 216. DR 09-0201 — WML: error in ST\_Jc example

**Status:** Last Call

**Subject:** WML: error in ST\_Jc example

**Qualifier:** Editorial defect

**Submitter:** SII - Standards Institution of Israel

**Contact Information:**

**Submitter's Defect Number:** 08-00116

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-04

**Deadline for Response from Editor:** 2009-07-04

**IS 29500 Reference(s):** Part 1: §17.18.44, "ST\_Jc (Horizontal Alignment Type)", pp. 1554

**Related DR(s):** none

**Nature of the Defect:**

Reference to right in the example is probably a remnant from an older version of the text.

**Solution Proposed by the Submitter:**

In the example, the current text says "attribute's value of right"; right should be replaced with end.

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are:

Part 1: §17.18.44, "ST\_Jc (Horizontal Alignment Type)", pp. 1554

[*Example:* ... The val attribute's value of ~~right~~end specifies that the content must be ~~right-~~aligned on the page for a left-to-right paragraph, and left-justified for a right-to-left paragraph. *end example*]

## 217. DR 09-0202 — WML: BRM Resolution 6

**Status:** Open [A9]

**Subject:** WML: BRM Resolution 6

**Qualifier:** Technical defect

**Submitter:** Editor

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** 08-00117

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-13

**Deadline for Response from Editor:** 2009-07-13

**IS 29500 Reference(s):** Part 1: §17.3.2.43, “w (Expanded/Compressed Text)”, pp. 342; Part 1: §17.18.95, “ST\_TextScale (Text Expansion/Compression Percentage)”, pp. 1668

**Related DR(s):** none

### **Nature of the Defect:**

This was identified during research associated with a previously submitted DR. As such, this DR is being submitted on behalf of WG4.

The implementation of the ballot resolution regarding percentages (aka BRM 6) failed to include certain clauses in WordprocessingML.

### **Solution Proposed by the Submitter:**

The following clauses should be updated to reflect the spirit of BRM 6:

- Part 1: §17.3.2.43, “w (Expanded/Compressed Text)”
- Part 1: §17.18.95, “ST\_TextScale (Text Expansion/Compression Percentage)”

### **Schema Change(s) Needed:**

### **Editor's Response:**

The exact changes are as follows:

Part 1, §17.3.2.43, “w (Expanded/Compressed Text)”, pp. 342–343

[Example: ...

```
<w:rPr>
 <w:w w:val="200%" />
</w:rPr>
```

This run explicitly declares that the w value is 200%, so the contents of this run appear at 200% of their normal character width by stretching the width of each character. *end example*]

...

Attributes	Description
val (Text Expansion/Compression Value)	<p>...</p> <p>[Example: ...</p> <pre>&lt;w:rPr&gt;   &lt;w:w w:val="50%" /&gt; &lt;/w:rPr&gt;</pre> <p>This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. <i>end example</i>]</p> <p>...</p>

Part 1, §17.18.95, “ST\_TextScale (Text Expansion/Compression Percentage)”, pp. 1668

[Example: ...

Consider a run of text which must be compressed to 200% when displaying each character within the contents of the run. This constraint is specified using the following WordprocessingML:

```
<w:rPr>
 <w:w w:val="50%" />
</w:rPr>
```

This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. *end example*]

This simple type's contents are a restriction of the W3C XML Schema integer datatype. [is a union of the following types:](#)

- [The ST\\_TextScalePercent simple type \(§xx\).](#)

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 600.~~

Part 1, §17.18.xx, “ST\_TextScalePercent (Text Expansion/Compression Percentage), new subclause

[This simple type specifies that the percentage by which the contents of a run shall be expanded or compressed with respect to its normal \(100%\) character width, with a minimum width of 1% and maximum width of 600%.](#)

[\[Example: Consider a run of text which must be compressed to 200% when displaying each character within the contents of the run. This constraint is specified using the following WordprocessingML:](#)

```
<w:rPr>
 <w:w w:val="50%" />
</w:rPr>
```

[This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. \*end example\*](#)

[This simple type also specifies the following restrictions:](#)

- [This simple type's contents shall match the following regular expression pattern:  \$0^\*\(600|\(\[0-5\]?\[0-9\]?\[0-9\]\)\)\%\$ .](#)

<a href="#">Referenced By</a>
<a href="#">ST_TextScale (§17.18.95)</a>

[\[Note: The W3C XML Schema definition of this simple type's content model \(ST\\_TextScalePercent\) is located in §Error! Reference source not found.. \*end note\*](#)

Part 1, §A.1, “WordprocessingML”, pp. 4347, lines 108–113

```

<xsd:simpleType name="ST_TextScale">
 <xsd:union memberTypes="ST_TextScalePercent"/>
 <xsd:restriction base="xsd:integer">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="600"/>
 </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_TextScalePercent">
 <xsd:pattern value="0*(600|([0-5]?[0-9]?[0-9]))%"/>
</xsd:simpleType>

```

Part 4, §9.10.xx, “Additional member types for the union in ST\_TextScale (Part 1, §17.18.95)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_TextScaleDecimal simple type (§NEW).

Part 4, §9.10.xx, ST\_TextScaleDecimal (Text Expansion/Compression Percentage), new subclause

This simple type specifies that the percentage by which the contents of a run shall be expanded or compressed with respect to its normal (100%) character width, with a minimum width of 1% and maximum width of 600%.

[Example: Consider a run of text which must be expanded to 300% when displaying each character within the contents of the run. This constraint is specified using the following WordprocessingML:

```

<w:rPr>
 <w:w w:val="300"/>
</w:rPr>

```

This run explicitly declares that the w value is 300, so the contents of this run appear at 300% of their normal character width by expanding the width of each character. end example]

This simple type's contents are a restriction of the W3C XML Schema integer datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 600.

#### Referenced By

ST\_TextScale (§17.18.95)

To Part 4, §A.1, “WordprocessingML”, pp. 813, lines 112–117

```
<xsd:simpleType name="ST_TextScale">
 <xsd:union memberTypes="ST_TextScalePercent ST_TextScaleDecimal"/>
 <xsd:restriction base="xsd:integer">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="600"/>
 </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_TextScalePercent">
 <xsd:pattern value="0*(600|([0-5]?[0-9]?[0-9]))%"/>
</xsd:simpleType>
<xsd:simpleType name="ST_TextScaleDecimal">
 <xsd:restriction base="xsd:integer">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="600"/>
 </xsd:restriction>
</xsd:simpleType>
```

# 218. DR 09-0203 — DML: BRM Resolution 6

**Status:** Open [A10]

**Subject:** DML: BRM Resolution 6

**Qualifier:** Technical defect

**Submitter:** Editor

**Contact Information:** Rex Jaeschke ([rex@RexJaeschke.com](mailto:rex@RexJaeschke.com))

**Submitter's Defect Number:** 08-00118

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-13

**Deadline for Response from Editor:** 2009-07-13

**IS 29500 Reference(s):** Part 1: §21.2.2.74, “gapDepth (Gap Depth)”, pp. 3795

**Related DR(s):** none

**Nature of the Defect:**

The implementation of the ballot resolution regarding percentages (aka BRM 6) failed to include certain DrawingML-related clauses.

**Solution Proposed by the Submitter:**

Update multiple DrawingML-clauses to reflect the true intention of BRM 6.

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are as follows:

Part 1, §21.2.2.74, “gapDepth (Gap Depth)”, pp. 3795

Attributes	Description
------------	-------------

Attributes	Description
val (Gap Size Value)	Specifies that the contents of this attribute contain a gap amount between 0% and 500%. The possible values for this attribute are defined by the ST_GapAmount simple type (\$xx).

Part 1, §21.2.2.75, “gapWidth (Gap Width)”, pp. 3796

Attributes	Description
val (Gap Size Value)	Specifies that the contents of this attribute contain a gap amount between 0% and 500%. The possible values for this attribute are defined by the ST_GapAmount simple type (\$xx).

Part 1, §21.2.3.16, “ST\_GapAmount (Gap Amount)”, pp. 3883

This simple type specifies that its contents contain ~~an integer a percentage~~ between 0% and 500%, ~~whose contents are a percentage~~.

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype, is a union of the following types:~~

- [ST\\_GapAmountPercent simple type \(\\$xx\)](#).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 500.~~

Part 1, §21.2.3.xx, “ST\_GapAmountPercent (Gap Amount Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 500%.](#)

[The simple type's contents shall match the following regular expression pattern:](#)

[0\\*\(\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-4\]\[0-9\]\[0-9\]\)|500\)%.](#)

<a href="#">Referenced By</a>
<a href="#">ST_GapAmount (§21.2.3.16)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4595, lines 264–272

```

<xsd:simpleType name="ST_GapAmount">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_GapAmountPercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_GapAmountPercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-4][0-9][0-9])|500)%"/>
</xsd:simpleType>
<xsd:complexType name="CT_GapAmount">
 <xsd:attribute name="val" type="ST_GapAmount" default="150%"/>
</xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_GapAmount (Part 1, §21.2.3.16)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_GapAmountUShort simple type (§xx).

Part 4, §13.1.xx.xx, “ST\_GapAmountUShort (Gap Amount UnsignedShort)”, new subclause

This simple type specifies that its contents contain a whole number between 0 and 500, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 500.

<u>Referenced By</u>
<u><a href="#">ST_GapAmount (Part 1, §21.2.3.16)</a></u>

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1067, lines 264–272

```

<xsd:simpleType name="ST_GapAmount">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_GapAmountPercent ST_GapAmountUShort"/>
</xsd:simpleType>

<xsd:simpleType name="ST_GapAmountPercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-4][0-9][0-9])|500)%"/>
</xsd:simpleType>

<xsd:simpleType name="ST_GapAmountUShort">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="500"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_GapAmount">
 <xsd:attribute name="val" type="ST_GapAmount" default="150%"/>
</xsd:complexType>

```

Part 1, §21.2.2.136, “perspective (Perspective)”, pp. 3827

Attributes	Description
val (Perspective Value)	Specifies the contents of this attribute contain <u>an integer a percentage</u> between 0% and 100%.  The possible values for this attribute are defined by the ST_Perspective simple type (§xx).

Part 1, §21.2.3.34, “ST\_Perspective (Perspective)”, pp. 3892

This simple type specifies that its contents contain an integer a percentage between 0% and 100%, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedByte datatype, is a union of the following types:

- ST\_PerspectivePercent simple type (§xx).

This simple type also specifies the following restrictions:

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 240.~~

Part 1, §21.2.3.xx, “ST\_PerspectivePercent (Perspective Percentage)”, new subclause

This simple type specifies that its contents contain a percentage between 0% and 240%.

The simple type's contents shall match the following regular expression pattern:

0\* (([0-9])|([1-9][0-9])|(1[0-9][0-9])|(2[0-3][0-9])|240)%.

<u>Referenced By</u>
<a href="#">ST Perspective (§21.2.3.34)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4594, lines 225–233

```

<xsd:simpleType name="ST_Perspective">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="240"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_PerspectivePercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_PerspectivePercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|(1[0-9][0-9])|(2[0-3][0-9])|240)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_Perspective">
 <xsd:attribute name="val" type="ST_Perspective" default="30%"/>
</xsd:complexType>
```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_Perspective (Part 1, §21.2.3.34)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_GapPerspectiveUByte simple type (§xx).

Part 4, §13.1.xx.xx, “ST\_PerspectiveUByte (Perspective UnsignedByte)”, new subclause

This simple type specifies that its contents contain a whole number between 0 and 240, whose contents are a percentage.

[This simple type's contents are a restriction of the W3C XML Schema unsignedByte datatype.](#)

[This simple type also specifies the following restrictions:](#)

- [This simple type has a minimum value of greater than or equal to 0.](#)
- [This simple type has a maximum value of less than or equal to 240.](#)

<a href="#">Referenced By</a>
<a href="#">ST_Perspective (Part 1, §21.2.3.34)</a>

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1066, lines 225–233

```

<xsd:simpleType name="ST_Perspective">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="240"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_PerspectivePercent ST_PerspectiveUByte"/>
</xsd:simpleType>

<xsd:simpleType name="ST_PerspectivePercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|(1[0-9][0-9])|(2|[0-3][0-
 9])|240)%"/>
</xsd:simpleType>

<xsd:simpleType name="ST_PerspectiveUByte">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="240"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_Perspective">
 <xsd:attribute name="val" type="ST_Perspective" default="30%"/>
</xsd:complexType>
```

Part 1, §21.2.2.164, “secondPieSize (Second Pie Size)”, pp. 3839

Attributes	Description
------------	-------------

Attributes	Description
val (Second Pie Size Value)	<p>Specifies the contents of this attribute contain <del>an integer</del> <a href="#">a percentage</a> between 5% and 200%.</p> <p>The possible values for this attribute are defined by the ST_SecondPieSize simple type (\$xx).</p>

Part 1, §21.2.3.41, “ST\_SecondPieSize (Second Pie Size)”, pp. 3896

This simple type specifies that its contents contain ~~an integer~~ [a percentage](#) between 5% and 200%, ~~whose contents consist of a percentage~~.

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype~~, [is a union of the following types](#):

- [ST\\_SecondPieSizePercent simple type \(\\$xx\)](#).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a maximum value of less than or equal to 200.~~
- ~~This simple type has a minimum value of greater than or equal to 5.~~

Part 1, §21.2.3.xx, “ST\_SecondPieSizePercent (Second Pie Size Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 5% and 200%.](#)

[The simple type's contents shall match the following regular expression pattern:](#)

[0\\* \(\[5-9\]\)|\(\[1-9\]\[0-9\]\)|\(1\[0-9\]\[0-9\]\)|200\)%.](#)

Referenced By
<a href="#">ST_SecondPieSize (§21.2.3.41)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4596–4597, lines 336–344

```

<xsd:simpleType name="ST_SecondPieSize">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="200"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_SecondPieSizePercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_SecondPieSizePercent">
 <xsd:pattern value="0*(([5-9])|([1-9][0-9])|(1[0-9][0-9])|200)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_SecondPieSize">
 <xsd:attribute name="val" type="ST_SecondPieSize" default="75%"/>
</xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_SecondPieSize (Part 1, §21.2.3.41)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_SecondPieSizeUShort simple type (\$NEW).

Part 4, §13.1.xx.xx, “ST\_SecondPieSizeUShort (Second Pie Size UnsignedShort)”, new subclause

This simple type specifies that its contents contain a whole number between 5 and 200, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 5.
- This simple type has a maximum value of less than or equal to 200.

#### Referenced By

[ST\\_SecondPieSize \(Part 1, §21.2.3.41\)](#)

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1068, lines 336–344

```

<xsd:simpleType name="ST_SecondPieSize">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="200"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_SecondPieSizePercent ST_SecondPieSizeUShort"/>
</xsd:simpleType>

<xsd:simpleType name="ST_SecondPieSizePercent">
 <xsd:pattern value="0*(([5-9])|([1-9][0-9])|(1[0-9][0-9])|200)%"/>
</xsd:simpleType>

<xsd:simpleType name="ST_SecondPieSizeUShort">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="5"/>
 <xsd:maxInclusive value="200"/>
 </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_SecondPieSize">
 <xsd:attribute name="val" type="ST_SecondPieSize" default="75%"/>
</xsd:complexType>

```

Part 1, §21.2.2.82, “holeSize (Hole Size)”, pp. 3799

Attributes	Description
val (Hole Size Value)	<p>Specifies that the contents of this attribute contain a hole size between 10% and 90% <b>that is measured as a percentage</b> of the size of the plot area.</p> <p>The possible values for this attribute are defined by the ST_HoleSize simple type (§xx).</p>

Part 1, §21.2.3.18, “ST\_HoleSize (Hole Size)”, pp. 3884

This simple type specifies that its contents contain a **percentage integer** between 10% and 90%, **whose contents are a percentage**.

This simple type's **contents are a restriction of the W3C XML Schema unsignedByte datatype**. **is a union of the following types:**

- [ST\\_HoleSizePercent simple type \(§NEW\)](#).

**This simple type also specifies the following restrictions:**

- **This simple type has a minimum value of greater than or equal to 10.**
- **This simple type has a maximum value of less than or equal to 90.**

Part 1, §21.2.3.xx, “ST\_HoleSizePercent (Hole Size Percentage)”, new subclause

This simple type specifies that its contents contain a percentage between 10% and 90%.

The simple type's contents shall match the following regular expression pattern: 0\*(([1-8][0-9])|90)%.

Referenced By
ST_HoleSize (§21.2.3.18)

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4596, lines 309–317

```

<xsd:simpleType name="ST_HoleSize">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="10"/>
 <xsd:maxInclusive value="90"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_HoleSizePercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HoleSizePercent">
 <xsd:pattern value="0*(([1-8][0-9])|90)%"/>
</xsd:simpleType>
<xsd:complexType name="CT_HoleSize">
 <xsd:attribute name="val" type="ST_HoleSize" default="10%"/>
</xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_HoleSize (Part 1, §21.2.3.18)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_HoleSizeUByte simple type (§xx).

Part 4, §13.1.xx.xx, “ST\_HoleSizeUByte (Hole Size UnsignedByte)”, new subclause

This simple type specifies that its contents contain a whole number between 10 and 90, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedByte datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 10.
- This simple type has a maximum value of less than or equal to 90.

Referenced By[ST\\_HoleSize \(Part 1, §21.2.3.18\)](#)

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1068, lines 309–317

```

<xsd:simpleType name="ST_HoleSize">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="10"/>
 <xsd:maxInclusive value="90"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_HoleSizePercent ST_HoleSizeUByte"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HoleSizePercent">
 <xsd:pattern value="0*(([1-8][0-9])|90)% "/>
</xsd:simpleType>

<xsd:simpleType name="ST_HoleSizeUByte">
 <xsd:restriction base="xsd:unsignedByte">
 <xsd:minInclusive value="10"/>
 <xsd:maxInclusive value="90"/>
 </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_HoleSize">
 <xsd:attribute name="val" type="ST_HoleSize" default="10%"/>
</xsd:complexType>

```

Part 1, §21.2.2.91, “LblOffset (Label Offset)”, pp. 3803

Attributes	Description
val (Label Offset Value)	Specifies the contents of this attribute contain a <del>percentage</del> <ins>integer</ins> between 0% and 1000%.  The possible values for this attribute are defined by the ST_LblOffset simple type (§xx).

Part 1, §21.2.3.23, “ST\_LblOffset (Label Offset)”, pp. 3886–3887

This simple type specifies that its contents contain a ~~percentage~~integer between 0% and 1000%, ~~whose contents are a percentage of the default value.~~

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype~~ is a union of the following types:

- [ST\\_LblOffsetPercent simple type \(§xx\).](#)

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 1000.

Part 1, §21.2.3, “ST\_LblOffsetPercent (Label Offset Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 1000%.](#)

The simple type’s contents shall match the following regular expression pattern:

[0\\*\(\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-9\]\[0-9\]\[0-9\]\)|1000\)%.](#)

<a href="#">Referenced By</a>
<a href="#">ST_LblOffset (§21.2.3.23)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4612, lines 1139–1147

```

<xsd:simpleType name="ST_LblOffset">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="1000"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_LblOffsetPercent"/>
</xsd:simpleType>

 <xsd:simpleType name="ST_LblOffsetPercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-9][0-9][0-9])|1000)%"/>
 </xsd:simpleType>
 <xsd:complexType name="CT_LblOffset">
 <xsd:attribute name="val" type="ST_LblOffset" default="100%"/>
 </xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_LblOffset (Part 1, §21.2.3.23)”, new subclause

[The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.](#)

- [The ST\\_LblOffsetUShort simple type \(§xx\).](#)

Part 4, §13.1.xx.xx, “ST\_LblOffsetUShort (Label Offset UnsignedShort)”, new subclause

This simple type specifies that its contents contain a whole number between 0 and 1000, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedShort datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 1000.

<u>Referenced By</u>
<a href="#">ST_LblOffset (Part 1, §21.2.3.23)</a>

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1083, lines 1139–1147

```

<xsd:simpleType name="ST_LblOffset">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="1000"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_LblOffsetPercent ST_LblOffsetUShort"/>
</xsd:simpleType>

<xsd:simpleType name="ST_LblOffsetPercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-9][0-9][0-9])|1000)%"/>
</xsd:simpleType>

<xsd:simpleType name="ST_LblOffsetUShort">
 <xsd:restriction base="xsd:unsignedShort">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="1000"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_LblOffset">
 <xsd:attribute name="val" type="ST_LblOffset" default="100%"/>
</xsd:complexType>

```

Part 1, §21.2.2.131, “overlap (Overlap)”, pp. 3820

Attributes	Description
------------	-------------

Attributes	Description
val (Overlap Value)	<p>Specifies the contents of this attribute contain an integer percentage between -100% and 100%.</p> <p>The possible values for this attribute are defined by the ST_Overlap simple type (§xx).</p>

Part 1, §21.2.3.31, “ST\_Overlap (Overlap)”, pp. 3891

This simple type specifies that its contents contain an integer percentage between -100% and 100%, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema byte datatype is a union of the following types:

- [ST\\_OverlapPercent simple type \(§xx\)](#).

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to -100.
- This simple type has a maximum value of less than or equal to 100.

Referenced By
overlap@val (§xx)

Part 1, §21.2.3.xx, “ST\_OverlapPercent (Overlap Percentage)”, new subclause

This simple type specifies that its contents contain a percentage between -100% and 100%.

The simple type's contents shall match the following regular expression pattern:

[\(-?0\\*\(\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|100\)\)%](#).

Referenced By
<a href="#">ST_Overlap (§21.2.3.31)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4595, lines 273–281

```

<xsd:simpleType name="ST_Overlap">
 <xsd:restriction base="xsd:byte">
 <xsd:minInclusive value="-100"/>
 <xsd:maxInclusive value="100"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_OverlapPercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_OverlapPercent">
 <xsd:pattern value="(-?0*(([0-9])|([1-9][0-9])|100))%">
</xsd:simpleType>

<xsd:complexType name="CT_Overlap">
 <xsd:attribute name="val" type="ST_Overlap" default="0%"/>
</xsd:complexType>

```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_Overlap (Part 1, §21.2.3.31)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_OverlapByte simple type (§xx).

Part 4, §13.1.xx.xx, “ST\_OverlapByte (Overlap Byte)”, new subclause

This simple type specifies that its contents contain a whole number between -100 and 100, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema byte datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to -100.
- This simple type has a maximum value of less than or equal to 100.

<u>Referenced By</u>
<u><a href="#">ST Overlap (Part 1, §21.2.3.31)</a></u>

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1067, lines 273–281

```

<xsd:simpleType name="ST_Overlap">
 <xsd:restriction base="xsd:byte">
 <xsd:minInclusive value="-100"/>
 <xsd:maxInclusive value="100"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_OverlapPercent ST_OverlapByte"/>
</xsd:simpleType>

<xsd:simpleType name="ST_OverlapPercent">
 <xsd:pattern value="(-?0*(([0-9])|([1-9][0-9])|100))%" />
</xsd:simpleType>

<xsd:simpleType name="ST_OverlapByte">
 <xsd:restriction base="xsd:byte">
 <xsd:minInclusive value="-100"/>
 <xsd:maxInclusive value="100"/>
 </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_Overlap">
 <xsd:attribute name="val" type="ST_Overlap" default="0%"/>
</xsd:complexType>

```

Part 1, §21.2.2.21, “bubbleScale (Bubble Scale)”, pp. 3767

This element specifies the scale factor for the bubble chart. This element can be a ~~n integer percentage~~ value from 0% to 300%, corresponding to ~~a percentage of~~ the default size.

Part 1, §21.2.3.5, “ST\_BubbleScale (Bubble Scale)”, pp. 3877–3878

This simple type specifies that its contents contain ~~a n integer percentage~~ between 0% and 300%.

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedInt datatype~~. is a union of the following types:

- ST\_BubbleScalePercent simple type (§xx).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 300.~~

Part 1, §21.2.3.xx, “ST\_BubbleScalePercent (Bubble Scale Percentage)”, new subclause

This simple type specifies that its contents contain a percentage between 0% and 300%.

The simple type's contents shall match the following regular expression pattern:

0\*(([0-9])|([1-9][0-9])|([1-2][0-9][0-9])|300)%.

<u>Referenced By</u>
<a href="#">ST_BubbleScale (\$21.2.3.5)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4595–4596, lines 282–290

```

<xsd:simpleType name="ST_BubbleScale">
 <xsd:restriction base="xsd:unsignedInt">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="300"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_BubbleScalePercent"/>
</xsd:simpleType>
<xsd:simpleType name="ST_BubbleScalePercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-2][0-9][0-9])|300)%"/>
</xsd:simpleType>
<xsd:complexType name="CT_BubbleScale">
 <xsd:attribute name="val" type="ST_BubbleScale" default="100%"/>
</xsd:complexType>
```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_BubbleScale (Part 1, §21.2.3.5)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- The ST\_BubbleScaleUInt simple type (\$xx).

Part 4, §13.1.xx.xx, “ST\_BubbleScaleUInt (Bubble Scale UnsignedInt)”, new subclause

This simple type specifies that its contents contain a whole number between 0 and 300, whose contents are a percentage.

This simple type's contents are a restriction of the W3C XML Schema unsignedInt datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 0.
- This simple type has a maximum value of less than or equal to 300.

<u>Referenced By</u>
----------------------

Referenced By[ST\\_BubbleScale \(Part 1, §21.2.3.5\)](#)

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1067, lines 282–290

```

<xsd:simpleType name="ST_BubbleScale">
 <xsd:restriction base="xsd:unsignedInt">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="300"/>
 </xsd:restriction>
 <xsd:union memberTypes="ST_BubbleScalePercent ST_BubbleScaleUInt"/>
</xsd:simpleType>
<xsd:simpleType name="ST_BubbleScalePercent">
 <xsd:pattern value="0*(([0-9])|([1-9][0-9])|([1-2][0-9][0-9])|300)%"/>
</xsd:simpleType>
<xsd:simpleType name="ST_BubbleScaleUInt">
 <xsd:restriction base="xsd:unsignedInt">
 <xsd:minInclusive value="0"/>
 <xsd:maxInclusive value="300"/>
 </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_BubbleScale">
 <xsd:attribute name="val" type="ST_BubbleScale" default="100%"/>
</xsd:complexType>

```

Part 1, §21.2.2.206, “thickness (Thickness)”, pp. 3861–3862

Attributes	Description
val (Integer Value)	<p>Specifies that the contents of this attribute contain <u>an integer number</u> <u>a percentage</u>.</p> <p>The contents of this number are interpreted based on the context of the parent XML element.</p> <p>The possible values for this attribute are defined by the <u>W3C XML Schema unsignedInt datatype</u> <u>ST_Thickness simple type (§xx)</u>.</p>

[Note: The W3C XML Schema definition of this element’s content model (CT UnsignedIntThickness) is located in §xx. end note]

Part 1, §21.2.3.xx, “ST\_Thickness (Thickness Percentage)”, new subclause

This simple type specifies that its contents contain a percentage.

This simple type is a union of the following types:

- [ST\\_ThicknessPercent simple type \(\\$xx\).](#)

Part 1, §21.2.3.xx, “ST\_ThicknessPercent (Thickness Percentage)”, new subclause

This simple type specifies that its contents contain a percentage.

The simple type's contents shall match the following regular expression pattern: ([0-9]+)%.

<a href="#">Referenced By</a>
<a href="#">ST_Thickness (\$xx)</a>

To Part 1, §A.5.1, “DrawingML - Charts”, pp. 4595, lines 245–252

```

<xsd:complexType name="CT_Surface">
 <xsd:sequence>
 <xsd:element name="thickness" type="CT_UnsignedIntThickness "
 minOccurs="0" maxOccurs="1"/>
 <xsd:element name="spPr" type="a:CT_ShapeProperties" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="pictureOptions" type="CT_PictureOptions" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="extLst" type="CT_ExtensionList" minOccurs="0"
 maxOccurs="1"/>
 </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="ST_Thickness">
 <xsd:union memberTypes="ST_ThicknessPercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_ThicknessPercent">
 <xsd:pattern value="([0-9]+)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_Thickness">
 <xsd:attribute name="val" type="ST_Thickness" use="required"/>
</xsd:complexType>
```

Part 4, §13.1.xx.xx, “Additional member types for union in ST\_Thickness (Part 1, §21.2.3.206)”, new subclause

The value space of the following additional member types can be used within the context of this simple type for a document of a transitional conformance class.

- [The W3C XML Schema unsignedInt datatype.](#)

To Part 4, §A.5.1, “DrawingML - Charts”, pp. 1066–1067, lines 245–252

```

<xsd:complexType name="CT_Surface">
 <xsd:sequence>
 <xsd:element name="thickness" type="CT_UnsignedIntThickness "
 minOccurs="0" maxOccurs="1"/>
 <xsd:element name="spPr" type="a:CT_ShapeProperties" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="pictureOptions" type="CT_PictureOptions" minOccurs="0"
 maxOccurs="1"/>
 <xsd:element name="extLst" type="CT_ExtensionList" minOccurs="0"
 maxOccurs="1"/>
 </xsd:sequence>
</xsd:complexType>

<xsd:simpleType name="ST_Thickness">
 <xsd:union memberTypes="ST_ThicknessPercent unsignedInt"/>
</xsd:simpleType>

<xsd:simpleType name="ST_ThicknessPercent">
 <xsd:pattern value="([0-9]+)%"/>
</xsd:simpleType>

<xsd:complexType name="CT_Thickness">
 <xsd:attribute name="val" type="ST_Thickness" use="required"/>
</xsd:complexType>
```

## 219. DR 09-0204 — WML: Custom markup

**Status:** Open

**Subject:** WML: Custom markup

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00119

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5, "Custom Markup", pp. 528

**Related DR(s):** none

**Nature of the Defect:**

The opening sentence begins "Within a WordprocessingML document, it is often necessary for specific documents to contain semantic information [...]"

This is nonsensical. What are the "specific documents" within a WordprocessingML document?

**Solution Proposed by the Submitter:**

Re-word so that it makes sense.

**Schema Change(s) Needed:**

**Editor's Response:**

## 220. DR 09-0205 — WML: Definition of “round tripping” missing

**Status:** Open

**Subject:** WML: Definition of “round tripping” missing

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter’s Defect Number:** 08-00120

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5, “Custom Markup”, pp. 528

**Related DR(s):** none

**Nature of the Defect:**

Para 2 begins "For these scenarios, multiple facilities are provided for the insertion and round-tripping of customer defined semantics within a WordprocessingML document."

The technical term "round-tripping" is never defined in the standard.

**Solution Proposed by the Submitter:**

Define this term in §4, “Terms and Definitions”.

**Schema Change(s) Needed:**

**Editor’s Response:**

## 221. DR 09-0206 — WML: Custom markup wording improvement

**Status:** Open

**Subject:** WML: Custom markup wording improvement

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00121

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5, "Custom Markup", pp. 528

**Related DR(s):** none

**Nature of the Defect:**

Para 2 begins "For these scenarios, multiple facilities are provided for the insertion and round-tripping of customer defined semantics within a WordprocessingML document."

This sentence redundantly anticipates the next, which is rather more precise.

**Solution Proposed by the Submitter:**

Merge the two sentences.

**Schema Change(s) Needed:**

**Editor's Response:**

## 222. DR 09-0207 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00122

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 528

**Related DR(s):** none

**Nature of the Defect:**

Para 3 begins, "The first example of customer-defined semantics that can be embedded in a WordprocessingML document are smart tags [...]"

This is a misuse of the word "example".

**Solution Proposed by the Submitter:**

Re-word.

**Schema Change(s) Needed:**

**Editor's Response:**

## 223. DR 09-0208 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00123

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

### **Nature of the Defect:**

Para begins, "The smart tag itself carries two required pieces of information, which together contain the customer semantics for this smart tag:"

How do the two pieces of information "contain" the "customer semantics". Maybe they name or identify them?

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 224. DR 09-0209 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00124

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

**Nature of the Defect:**

The first bullet on pp. 529 has, "The first of these is the namespace for this smart tag (contained in the uri attribute). This allows the smart tag to specify a URI which should identifies the namespace of this smart tag to a consumer."

What is the effect of omitting this attribute? Is the implied element conformant to XMLNames? Is it permitted for the attribute to be something other than a URI?

Also, correct, "which should identifies [sic]".

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

## 225. DR 09-0210 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00125

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

**Nature of the Defect:**

The first bullet on pp. 529 has, "It is intended to be used to specify a family of smart tags to which this one belongs."

The standard should not attempt to explain the purpose of XML Namespaces in normative text.

**Solution Proposed by the Submitter:**

Remove this sentence, or demote it to a note.

**Schema Change(s) Needed:**

**Editor's Response:**

## 226. DR 09-0211 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00126

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

### **Nature of the Defect:**

The second bullet on pp. 529 has, "This allows the smart tag to specify a name which identifies this type of smart tag within its namespace and again available to a consumer."

The standard should not attempt to explain the purpose of XML Element Type Names in normative text. Also, this sentence does not make sense.

### **Solution Proposed by the Submitter:**

Remove this sentence, or re-write it and demote it to a note.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 227. DR 09-0212 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00127

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 528

**Related DR(s):** none

### **Nature of the Defect:**

The w:element attribute is permitted by the schema (and by the normative text) to contain a string that does not constitute a valid XML Name. Thus, the standard permits custom tags implying tagged text that cannot be processed using conformant XML processors.

### **Solution Proposed by the Submitter:**

Reform the schema and normative text to limit the content of this attribute to become an NCName.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 228. DR 09-0213 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00128

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

**Nature of the Defect:**

The second bullet on pp. 529 has, "This allows the smart tag to specify [...]"

This implies optionality; normative text should be unambiguous.

**Solution Proposed by the Submitter:**

Re-word "the attribute content shall specify ...".

**Schema Change(s) Needed:**

**Editor's Response:**

## 229. DR 09-0214 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00129

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

**Nature of the Defect:**

The first para on pp. 529 following the bullets begins: "The next example of customer-defined semantics which can be embedded in a WordprocessingML document is custom XML markup."

This misuses the word "example".

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

## 230. DR 09-0215 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00130

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

### **Nature of the Defect:**

The first para on pp. 529 following the bullets has: "Custom XML markup allows the application of the XML elements defined in any schema syntax (XML Schema, NVDL, etc.) to be applied to the contents of a WordprocessingML document in one of two locations"

Change "two locations" to "two types of location"; and why only "one of" these? Can't a document contain multiple differing types of custom XML?

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 231. DR 09-0216 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00131

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 529

**Related DR(s):** none

### **Nature of the Defect:**

The second para on pp. 529 following the bullets has: "The distinction between custom XML markup and smart tags is that custom XML markup is based on a specified schema."

It is not clear how "a specified schema" is specified in this context. Can there only be one specified schema per document?

### **Solution Proposed by the Submitter:**

Point to normative text describing how one or more schemas are specified, or - if this does not exist - provide new text.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 232. DR 09-0217 — WML: Custom XML and Smart Tags

**Status:** Open

**Subject:** WML: Custom XML and Smart Tags

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00132

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1, "Custom XML and Smart Tags", pp. 530

**Related DR(s):** none

### **Nature of the Defect:**

The first normative para on pp. 530 begins: "Similar to the smart tag example above [...]"

The phrase "similar to" has no place in the normative text of a standard.

### **Solution Proposed by the Submitter:**

Remove this para and the following bullets and refer back to the smart tag descriptions.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 233. DR 09-0218 — WML: Custom XML Attribute

**Status:** Open

**Subject:** WML: Custom XML Attribute

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00133

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1.1, "attr (Custom XML Attribute)", pp. 531

**Related DR(s):** none

**Nature of the Defect:**

The first para has: "The attributes on this element shall be used to specify the contents of the custom XML attribute."

This is incomplete.

**Solution Proposed by the Submitter:**

Change "the contents" to "the Namespace URI, name, and content".

**Schema Change(s) Needed:**

**Editor's Response:**

## 234. DR 09-0219 — WML: Custom XML Attribute

**Status:** Open

**Subject:** WML: Custom XML Attribute

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00134

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1.1, “attr (Custom XML Attribute)”, pp. 531

**Related DR(s):** none

### **Nature of the Defect:**

The w:name attribute of w:attr is permitted by the schema (and by the normative text) to contain a string which does not constitute a conformant XML Name. Thus, the standard permits custom tags implying tagged text that cannot be processed using conformant XML processors

### **Solution Proposed by the Submitter:**

Reform the schema and normative text to limit the content of this attribute to become an NCName.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 235. DR 09-0220 — WML: Definition of “property bag” missing

**Status:** Open

**Subject:** WML: Definition of “property bag” missing

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00135

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1.1, “attr (Custom XML Attribute)”, pp. 531

**Related DR(s):** none

**Nature of the Defect:**

In the first example: "This property bag specifies [...]"

The term "property bag" is not defined in this Standard.

**Solution Proposed by the Submitter:**

Re-word or define this term.

**Schema Change(s) Needed:**

**Editor's Response:**

## 236. DR 09-0221 — WNL: Custom XML Attribute

**Status:** Open

**Subject:** WNL: Custom XML Attribute

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00136

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.1.1, “attr (Custom XML Attribute)”, pp. 531

**Related DR(s):** none

### **Nature of the Defect:**

The w:attr element may be repeated to declare duplicate Namespace/Name pairs for attributes on a single element. Thus, the standard describes documents that can imply tagged text that cannot be processed using conformant XML processors

### **Solution Proposed by the Submitter:**

Add normative text prohibiting this.

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 237. DR 09-0222 — WML: Bibliography Structured Document Tag

**Status:** Open

**Subject:** WML: Bibliography Structured Document Tag

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00137

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.2.2, "bibliography (Bibliography Structured Document Tag)", pp. 552

**Related DR(s):** none

### **Nature of the Defect:**

The first para states, of the bibliography element: "[t]his element specifies that the parent structured document tag shall be of type bibliography."

The parent shown in the example is the sdtPr element -- what does it mean that its "tag" is of "type bibliography"?

N.B. This query applies for many of the following clauses here.

### **Solution Proposed by the Submitter:**

None

### **Schema Change(s) Needed:**

### **Editor's Response:**

## 238. DR 09-0223 — WML: Structured Document Tags

**Status:** Open

**Subject:** WML: Structured Document Tags

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00138

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.2, "Structured Document Tags", pp. 549

**Related DR(s):** none

**Nature of the Defect:**

[A general comment about this subclause]

The schema permits the sdtPr element to contain any mixture of "typing" elements (bibliography, calendar, etc.) the normative text of the spec does not prohibit this.

How are such multiply typed structures to be processed?

**Solution Proposed by the Submitter:**

None

**Schema Change(s) Needed:**

**Editor's Response:**

## 239. DR 09-0224 — WML: Combo Box Structured Document Tag

**Status:** Open

**Subject:** WML: Combo Box Structured Document Tag

**Qualifier:** Request for clarification

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00139

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 1: §17.5.2.5, "comboBox (Combo Box Structured Document Tag)", pp. 554

**Related DR(s):** none

**Nature of the Defect:**

Has: "[...] choices which shall be displayed in a standard drop-down list format".

What is this "standard format"?

**Solution Proposed by the Submitter:**

Supply a definition or generalize.

**Schema Change(s) Needed:**

**Editor's Response:**

## 240. DR 09-0225 — Part 4 should normatively reference Part 1

**Status:** Open

**Subject:** Part 4 should normatively reference Part 1

**Qualifier:** Technical defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** 08-00140

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-22

**Deadline for Response from Editor:** 2009-07-22

**IS 29500 Reference(s):** Part 4: §3, “Normative References”, pp. 4

**Related DR(s):** none

**Nature of the Defect:**

Part 4 does not stand alone as an intelligible specification.

Interpretation of Part 4 relies on Part 1, yet Part 1 is not normatively referenced.

**Solution Proposed by the Submitter:**

Part 1 should be referenced, and an explanation given (in the introduction perhaps) of how this Part (4) forms a supplement to Part 1, and inherits its provisions (except where overridden).

**Schema Change(s) Needed:**

**Editor's Response:**

# 241. DR 09-0226 — PML: ST\_TransitionSideDirectionType

**Status:** Last Call

**Subject:** PML: ST\_TransitionSideDirectionType

**Qualifier:** Editorial defect

**Submitter:** Editor

**Contact Information:** [rex@RexJaeschke.com](mailto:rex@RexJaeschke.com)

**Submitter's Defect Number:** none

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-24

**Deadline for Response from Editor:** 2009-07-24

**IS 29500 Reference(s):** Part 1: §19.7.53, “ST\_TransitionSideDirectionType”, pp. 3004

**Related DR(s):** none

**Nature of the Defect:**

The word “Enum” is missing from the enumeration value r (Transition Slide Direction ( Right )).

**Solution Proposed by the Submitter:**

Make the row for the enumeration value r match the other rows in that table.

**Schema Change(s) Needed:**

**Editor's Response:**

The exact changes are:

Part 1: §19.7.53, “ST\_TransitionSideDirectionType (Transition Slide Direction Type)”, pp. 3004

Enumeration Value	Description
-------------------	-------------

Enumeration Value	Description
r (Transition Slide Direction <a href="#">Enum</a> ( Right ))	Specifies that the transition direction is right

## 242. DR 09-0227 — WML: Inconsistent use of ML style IDs in examples

**Status:** Open

**Subject:** WML: Inconsistent use of ML style IDs in examples

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-FC-001

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-26

**Deadline for Response from Editor:** 2009-07-26

**IS 29500 Reference(s):** Part 1, §17.3.1.27 (pp. 253) and 47 others

**Related DR(s):** DR-08-0014

### **Nature of the Defect:**

The standard contains 48 examples that contain the style ID "heading1", starting with a lower-case h, all in examples of the use of the element 'pStyle'. These include §22.9.2.13, the subject of DR-08-0014. There are seven examples that contain the style ID "Heading1", including five in examples of the use of the element 'style' and only two in examples of the use of the element 'pStyle'.

Existing implementations of Ecma-376 consistently use "Heading1" as the style ID for the style named "Heading 1", a built-in style in most implementations.

While it might be easier to change the two uses of "Heading1" to be consistent with the other 48 uses, existing implementations suggest that it is the two uses of "Heading1" that are most consistent with what implementers would expect, and it is the 48 uses of "heading1" that are inconsistent.

### **Solution Proposed by the Submitter:**

Revise the text of the 48 examples as follows:

```
<w:pPr>
 <w:pStyle w:val="hHeading1" />
</w:pPr>
```

**Schema Change(s) Needed:** No

**Editor's Response:**

## 243. DR 09-0228 — General: Inappropriate first paragraph in §7 of Parts 1, 2 and 4

**Status:** Open

**Subject:** General: Inappropriate first paragraph in §7 of Parts 1, 2 and 4

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-077

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-26

**Deadline for Response from Editor:** 2009-07-26

**IS 29500 Reference(s):** Part 1, §7 (pp. 16); Part 2, §7 (pp. 11); Part 4, §7 (pp. 12)

**Related DR(s):**

**Nature of the Defect:**

Ecma Response 395 to UK comment GB-0606 was accepted by the BRM (Resolution 35). Response 395 indicated that the first paragraph of DIS Part 5 §6 (became Part 3 §7 in the final text) would be revised, but in the final text this paragraph was entirely removed. However, the identical first paragraphs in the corresponding sections §7 of Parts 1, 2 and 4 remain in place. Although these three other instances of the same paragraph were not referred to in the original UK comment, the removal of this paragraph from what became Part 3 but not from the other Parts is inconsistent and leaves inappropriate wording in place.

**Solution Proposed by the Submitter:**

Remove the first paragraph of §7 in Parts 1, 2 and 4.

**Schema Change(s) Needed:** No

**Editor's Response:**

## 244. DR 09-0229 — Period missing at end of sentence

**Status:** Open

**Subject:** Period missing at end of sentence

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** francis@franciscave.com

**Submitter's Defect Number:** GB-078

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-26

**Deadline for Response from Editor:** 2009-07-26

**IS 29500 Reference(s):** Part 3, §10.1.3 (pp. 18)

**Related DR(s):**

**Nature of the Defect:**

The correction proposed in Ecma Response 399 (agreed by the BRM in Resolution 35) has not been made.

**Solution Proposed by the Submitter:**

Revise the text of paragraph 4 of Part 3, §10.1.3 as follows:

If a markup specification lacks such guidance, markup editors for markup documents governed by that markup specification should be conservative in their preservation behavior. Before preserving any ignored markup, markup editors should attempt to establish confidence that the preserved markup will be acceptable to, and interpretable with acceptable semantics by, all imaginable markup consumers that understand future versions of extensions. [Note: Such confidence could be established by deep understanding of the base specification. *end note*]

**Schema Change(s) Needed:** No

**Editor's Response:**

## 245. DR 09-0230 — Cross-reference to non-existent Example

**Status:** Open

**Subject:** Cross-reference to non-existent Example

**Qualifier:** Editorial defect

**Submitter:** Mr. Francis Cave (BSI)

**Contact Information:** [francis@franciscave.com](mailto:francis@franciscave.com)

**Submitter's Defect Number:** GB-079

**Supporting Document(s):** none

**Date Circulated by Secretariat:** 2009-05-26

**Deadline for Response from Editor:** 2009-07-26

**IS 29500 Reference(s):** Part 3, §10.2 (pp. 27)

**Related DR(s):**

**Nature of the Defect:**

The second Note contains a reference to Example 12-1, which is incorrect: it should be to Example 13-1. The DIS text was changed as a result of Ecma Response 406 (agreed by the BRM in Resolution 35), but this change did not take into account re-numbering as a result of other changes.

**Solution Proposed by the Submitter:**

Revise the Note as follows:

[*Note:* Example 12-1 illustrates how a markup preprocessor handles each of the two possible behaviors. *end note*]

**Schema Change(s) Needed:** No

**Editor's Response:**